PRAXIS DER SOFTWARENTWICKLUNG

SPECIFICATIONSBOOK

NEURAL NETWORK BASED IMAGE CLASSIFICATION SYSTEM ON HETEROGENEOUS PLATFORMS TEAM 2

from

Häring, Stangel, Drehwald, Guneshka, Dimitrov

Inhaltsverzeichnis

1	Preface	3
2	Goal	3
3	Product use	3
4	Acceptance criteria 4.1 Must	3 3
5	Functional Requirements Must	4
6	Functional Requirements Can	6
7	Productdata	7
8	Demarcation	7
9	Non-functional requirements	7
10	Test cases	9
11	System models 11.1 Scenarios 11.1.1 Scenario 1 11.1.2 Scenario 2 11.2 Usecases 11.2.1 Training page 11.2.2 Training page 11.3 GUI	12 12 12 12 12 12 12 12
12	Stage responsibilities	14

1 Preface

2 Goal

The goal is a software which performs image classification and is able to switch between deploy platforms and working modes. It also should have a GUI to control the software and to show the results.

3 Product use

Image classification

4 Acceptance criteria

4.1 Must

AC30 Different operating modes

The software has three modes. One mode for high perfomance, one for

low power consumption and one for high energy effiency.

AC50 Performance and power consumption prediction

The software can predict the performance with a certain powerconsump-

tion an also the powerconsumption for a certain performance.

MAC010: Image classification

MAC020: Running NN on heterogenous platforms, CPU and FPGA

MAC030 : Different operating modes

MAC040 : GUI for interacting with software MAC050 : Performance/power prediction

4.2 Can

KAC060: Training a nn for classification KAC070: Illustration of a topology of the nn

KAC080 : Object detection

KAC090: Choosing between different models

KAC100 : Creating new models

KAC110: Voting of multiple nn

KAC120: Using video for classification

KAC130 : Using camera for classification input

KAC140: Running NN on GPU

5 Functional Requirements Must

 ${
m MFR025}$: Dispatching the calculation process defined from the mode

MFR030 : Support CPU for calculation MFR031 : Support FPGA for calculation

MFR040 : Communication between Host-PC and platform

MFR041 : Send image for classification

MFR042 : Receive result

MFR050 : GUI

MFR060 : Showing results

MFR010 Use neural network for image classification

A neural network should be used in order to classify images based on what is shown on them. For each image a list of possible classes it could belong to along with degree of confidence should be given as output.

MFR011 Deploy pre-trained neural network with the corresponding layers

A pre-trained neural network should be deployed to with all the corresponding layers in order to fulfill MFR010.

MFR020 Have high performance operating mode

An option to perform calculations fast with low regard for power consumption.

MFR021 Have low power consumption operating mode

An option to perform calculations with low power consumption and low regard for speed.

MFR022 Have high energy efficiency operating mode

An option to perform calculations at an adequate balance between speed and power consumption.

MFR023 Calculator for power consumption

Calculations for the possible power consumption running the image classifications would result in based on the neural network, platform and operating mode used.

MFR024 Calculator for performance

Calculations for the possible performance running the image classifications would result in based on the neural network, platform and operating mode used.

FR070 Choosing image for classification

Testet with: Implements:

The GUI has a button with an on click event which opens a file explorer. The explorer filters the files so that only files of the format .jpg, .png, .bmp are listed. That also are the only valid formats.

FR080 Choosing platform/hardware

Testet with: Implements:

The GUI has a dropdown which lists the devices on which the classification can be done. The devices which can be theoretically be accessed but aren't connected to the host pc or the communication with them doesn't work are graved out.

FR090 Choosing mode

Testet with: Implements:

The GUI has dropdown which lists the modes (high performance mode, low power consumption mode and best energy efficiency mode). The power consumption in Watts and performance in FLOPs are also stated behind the mode names.

6 Functional Requirements Can

CFR012 Reading and parsing neural network configuration/weight file

Having the ability to import/export different (external) neural networks to use for the image classification.

FR100 Choosing between different models

Testet with: Implements:

The GUI has a button which opens the file explorer which filters for .txt files, there you choose the config file of the neural network with which you want to use. The program loads this config and parses it so it can be deployed. Possible models are GoogLeNet or AlexNet.

FR110 Train nn for classification of imageset (with transfer learning)

Testet with: Implements:

The user chooses a pretrained neural network and a new imageset and then can train the neural network on this new imageset with transfer learning.

KFR032 : Support GPU for calculation

KFR113: Backpropagation

KFR114: Choosing parameters like learning rate

KFR120 : Illustrating nn topology KFR130 : Object detection algorithm KFR131 : Showing detected object

KFR132: Choosing between detection and classification mode

7 Productdata

PD010 Images for classification

The user can choose images of the format .jpg, .png, .bmp. The images

are chosen by the user with the file explorer.

PD020 Config/weight file of pretrained model

It is a .cfg file. In the beginning are hyperparameters described with the format name = value. Then the layers are described in their order with

the following format

[kind of layer]

list of parameters in the format name = value

PD030 Labeled image set for classification training

The dataset is chosen by the user. The dataset is a directory with images

and the name of the image is the label.

PD040 Labeled set of images for object detection training

It is a .txt file and a directory with images. The images are labeled with their name. The bounding box for each image are described in the .txt file, in the format *imagename*, x,y,width,height. (X,Y) are the coordinates in pixel of the left bottom corner, the width and height are in pixel.

8 Demarcation

D010: No real time / no performance optimization

D020: No mobile support

D030 : No neural network size optimization D040 : No low-level (Assembler) optimization

9 Non-functional requirements

NF10

10 Test cases

T010 Use neural network for image classification

State: A image is given as an input.

Action: Calculations are performed on hand of the image and a neural network.

Reaction: A list of possible classes the given image could belong to along with degree of confidence for each class are given as output.

T011 Deploy pre-trained neural network with the corresponding layers

State: There is a neural network (already trained).

Action: Calculations are performed cased on a given image and the given neural network.

Reaction: A list of possible classes the given image could belong to along with degree of confidence for each class are given as output.

T012 Reading and parsing neural network configuration/weight file

T012.1 State: The user is on the page to select a neural network to use for the image classification.

Action: The user selects the option to import a neural network.

Reaction: The file explorer opens.

T012.2 State: The file explorer is open

Action: The user selects an neural network to import

Reaction: The file explorer closes and neural network is imported and selected for the classification calculations.

T020 Have high performance operating mode

State: The user is ready to start the calculations.

Action: The user chooses to perform the calculations in high performance operating mode.

Reaction: The calculations run considerably faster than in the other possible modes with the same conditions.

T021 Have low power consumption operating mode

State: The user is ready to start the calculations.

Action: The user chooses to perform the calculations in low power consumption operating mode.

Reaction: The calculations run with considerably lower power consumption than with the other possible modes in the same conditions.

T022 Have high energy efficiency operating mode

State: The user is ready to start the calculations.

Action: The user chooses to perform the calculations in high energy efficiency operating mode.

Reaction: The calculations run with regard to balance between power consumption and speed. 9

T070 Choosing image for classification

T070.1 State: The user is on the page for image classification.

Action: The user clicks on the button "Choose image".

Reaction: The file explorer opens with the filter for .png, .jpg, .bmp

T070.2 State: The file explorer is open

Action: The user selects an image with a valid format

Reaction: The file explorer closes and image is as preview shown

T080 Choosing platform/hardware

T080.1 State: The user is on the page for image classification

Action: The user chooses with the dropdown the desired platform Reaction: An internal flag is set to the desired platform and the drop-

down shows the chosen platform.

T090 Choosing mode

T090.1 State: The user is on the page for image classification

Action: The user chooses with the dropdown the desired mode

Reaction: An internal flag is set to the desired mode and the dropdown

shows the chosen mode

T100 Choosing between different models

T100.1 State: The user is on the page for image classification

Action: The user clicks on the button "Choose neural network"

Reaction: The file explorer opens

T100.2 State: The file explorer is open

Action: The user selects an config/weight file

Reaction: The file explorer closes and the software loads the input and

parses it. If it is loaded there is success message

T110 Train neural network for classification of imageset

T110.1 **State:** The user is on the page for training, has selected a neural network, a dataset for training, the kind of training, the learning rate and the desired precision.

Action: The user clicks on the button "Train"

Reaction: The software starts to train the selected network with the selected configuration and shows the progress in line graph.

T111 Saving a NN after training

T111.1 State: The user is on the page for training, has selected a neural network, a dataset for training, the kind of training, the learning rate and the desired precision.

The training finishes.

Action: No action required

Reaction: The software stores the trained network weights in a predifi-

ned format and with a usefull name in a fixed location.

T112 Choosing/Reading data set

T112.1 State: A folder containing images is provided by the user.

Action: No action required

The software is able to read all images matching the allowed formats and allows training and inferencing on these images.

T140 Creating new topology

T140.1 State:

Action: No action required 0

Reaction:

A folder containing images is provided by the user.

The software is able to read all images matching the allowed formats and allows training and inferencing on these images.

T150 Choosing between training and interference mode

T150.1 State:

Action: No action required

Reaction:

A folder containing images is provided by the user.

The software is able to read all images matching the allowed formats and allows training and inferencing on these images.

T160 Choosing video in format .avi

T160.1 State: The software is running.

Action: The user selects a .avi video file.

Reaction: The system stores the path to the selected video and is

available to process single images from this video.

T161 Apply classification for a certain amount of frames

T161.1 State: The software is running. A video source was choosen by the user.

All network details were provided by the user. Classification was choosen by the user.

Action: The user clicks on the button "start classification" Reaction: The system processes the video file imagewise

T170 Connect with camera

T170.1 State: The software is running

Action: The user connects a usb camera to the pc

Reaction: The system dynamically detects the camera and allows the user to select the camera as an image source

T171 Receive video stream from camera

T171.1 State: The software is running, a camera is connected to the host pc.

Action: The user chooses the camera as image source.

Reaction: The first camera image is provided as a preview, the continuous image stream is available for further processing.

T180 Detecting object

T180.1 **State:** The software is running, a network including all parameters and weights was provided. An image was provided. Detection mode was picked by the user

Action: The user clicks on the button "start detection"

Reaction: The network is run for inferencing and the network output is shown to the user.

T181 Drawing bounding box

T181.1 State: Inferencing was executed on an image given by the user, the choosen neural network predicted bounding boxes.

Action: No action required

Reaction: The original image, given by the user, is overlayed with the boxes predicted by the network, the updated image is presented to the user.

11 System models

11.1 Scenarios

11.1.1 Scenario 1

The user U1 wants to classificate the image of a cat. He goes on the classification page and he clicks on the dropdown and sees the three modes "low power consumption", "high performance"and "high energy efficiency", he can also see the predicted power consumption and performance. He chooses to classificate in the low power mode and runs the programm. The results are shown.

11.1.2 Scenario 2

The user U2 goes to the classification page and chooses the image of coala and the high power performance mode and CPU mode. The software states that it would take 86 watts with 166 GFLOPs. U2 decides he would rather use the high energy efficiency mode with 140 GFLOPs and 70 watts. He sets the other parameters and clicks on Start image classification. The result is that the image is a coala and shows this result.

11.2 Usecases

11.2.1 Training page

11.2.2 Training page

11.3 GUI




Abbildung 1: Usecase of the image classification page

Glossar

image a two dimensional matrix of red,green,glue (RGB) values that can be visualized as each cell represents a single pixel on the monitor. (ex.: a photo).

neural network a network or a circuit of neuron used for information processing inspired by the way biological neural systems process data.




Abbildung 2: Usecase of the trainingspage

12 Stage responsibilities

Requirements: Paul Stangel
Design: Johannes Häring
Implementation: Manuel Drehwald
Quality ins- Stefani Guneshka

urance:

Deployment: Dimitar Dimitrov




Abbildung 3: Main page of our software




Abbildung 4: Image classification page of our software




Abbildung 5: Object detection page of our software




Abbildung 6: Training page of our software




Abbildung 7: Page which shows the topology of a selected NN of our software