

--- Page 1 ---

--

MEY TS EX W A IO A

TERE SOURTN DAKOTA MNO AUALIOR ASSURA IN A HE

I -

FINAL TEST AND USPEAT IN WE IN I EXA H 70 A A D DATE I 22 FET

D I REIS IS ITOT ARK NO T 1E SOY AS O

I IS AS RON FT WAS A Z ZUTE ES

ME D EL A HE A 30 SEPIAL NO I Z T O S8 O A IS

1 I N IS CINENK WNIT AGAINST THE KNOMLEDAEM CHANGE ORDERS AND LIET TEST SHEETS

2 FAS CHENK FITTING MARKINGS AND TORQUE MARKINGS ON ROTATION BEARING BOLTS

3 I - CAMNEST ALL MUDRAULIA LINES I 13000 PS A 1N128 GRM SET FLOW I A ORN

A IS LUBRICATE ALL LNBE FITTINGS AND PINOT POINTS DER LNBE DATA CHART SET FLOW A B

5 YY INSTALL CAPS ON ALL GREASE FITTINGS

I I

G - T CHEGY ROTATION GEARBOX GREASE LEVEL PER LNBE DATA CHART WENT CORRECTHY F

A IN ESKRIDGE PLANETARY DRIVE ISLIP BREAK 3 A POINTS HOSONGO

SO IE ESKRIDGE PLANETARN BRAKE FILL WITH MOBIL A TED

MY - A MINCH GEARBOX GREASE LEVEL OER LNBE DATA CHART WENT CORRECTHY POSITION

ST MY 15 UBS I TN

8 CHENK DIGGER DRIVE GEARBOX GREASE LEVEL PER LUBE DATA CHART

A IS CHECK ALL CONTROL LEVERS FOR FREE AND UMRESTRICTE MOVEMENT

A IS CARRECT DIRECTION AND CORRECT DESAL

B TOR IT EEVER MUST OPERATE WITHOUT BINDING OR EXCESSIVE PLAY WITH ALL BOLTS PRO

10 CIFEK MOVEMENT AND TRAVEL OF ALL HRDRALULIC LINES ADIUST TO ELIMINATE CHAFIN

- I

ARRANGED NEAT AND ORDERTY

1 IT I REPAIR ALL LEAKS TIGHTER I DISASSEMBLE I INSPED AND REPAIR FITTINGS AS NECESSA

12 A A SET DERRICK RELIET VALVE AT 2T0D ES1 A 1ON GON SET PRESSURE I 2 R ES1

13 MY SET DIGGERMINCH RELLIET AT 2850 PS1 A TO OON SET PRESSURE 2 TS NO PS

- I

IN SET ALL TOOL CIRCUIT RELIEF VALVES AT 2250 ES1 A 68 G SET PRESSURE - S

1 IS MS SET DIGGER RELIET AT 28300 PA1 A 28 6ON SET PRESSURE 7 30 PS

18 I SMABRONIZE LIFT CVLINDER HOLDING VALVES AND FECORD LIFT CNLINDER PILOT PRESS

A SR EQUALIZE RETRACTES LIFT CNLINDER LENATHS - I NUMBER SHIMS ADDES A SO NOV ZO S

A T TIME TO LIFT 1587 SE 3 TIME FO SES

A TH TIME TO LOWER I 19858 SE 3 TIME OO 7T SES

B CHEAK SET SUREW ON CNLINDER ROD EVE

IT 3E SET HRDRAULIC BRD SEAMENCING FROM TOP CONTROLS AT 10 GPN BOOMS TO BE AT OD

FIBDERALASS BRD MUST EXTEND TIRST THEN STINGER STINGER MUST RETRANT FIRST AND T

A TIM TO EXTEND END SES TIME TO RETRANT END - SEC

A - MNTIME TO EXTEND BRID ESE TIME TO RETRANT BRD ESEO

I IH TOP CONTROL OVERRIDE CHENK THAT ALL LOWER CONTRO FUNCTIONS OPERATE WITH A

ENGAGE AND TOP CONTROL OVERRIDE IN THE LOWER CONTROL POSITION CHECK FOR ARY BO

IN ALL DIRECTIONS OTHER THAN THAT OF THE LOWER FUNCTION BEING OPERATED

I -

18 IT THE CHECK BOOM STOW TO DUMP BOOM DOWN THEN 1EU IS APPLIED

19 I ION CHENK ELESTRIA COLLECTOR RING VRUSH CLAMNS I MIRE SOREWS AND MOUNTINC E

20 I WET CHEAK DIGGER HASE CATRAN LIMSPECT MOSE I FITTING AND CATRAA I I

21 SO CNEAK STINGER EXTENSION 15 CVOLES FULL EXTEND AND RETRACT I NO INTERESTERENC

7 VIFTTAXI BASKET CAPACITY SUSPENDE I DRIFT MAY NOT EXCEED I INCH IN A 5 MINUTES

A A A TIME CHECK TO WEAR EXTEND PADS 1A4-12 FOR SEA CLEARANCE TIGNTMESS OF MOUN

C BS TIATE TO FETFACT 28535 SE WHTAY BRD - TIME ET SER
CAS A SETULS 11581 SE 951
A IY I INSPECT EXTENSION CNLINDER SEALS AND ROD
F EPINBT RER B
I OF 3
- S
- - -

--- Page 2 ---

LE -O EE A EE IS AN

23 I E I EST 10M ES STINGER THECK CNEAK THRUST CT TPP AT UNSPECT UNSPECT I5DE PER HO
I I

I TER STINGER MOLDING VALVE AT PATED LOAD

24 I A TOSTLIT - WE SS FULLY CNLINDER EXTENDED THRUST AT ODEG SEE CAPACITY CHARTS

A IF FULTY RETRASTED I SAD UBS

- I

C TEST LIFT CNLINDER HOLDING VALVES AT RALTED LOAD

25 A CNENK MRDRAULIC HRDRAULIC THIRD BRD EXTENSION THRUST 15 AT CRCLES 15DED FUL

A I TT CHENK RALLER ADIJUSTMENT

A A E TIME TO EXTEND I 19U-13 SE - 3 TIME AS SEN

A T TIME TO RETPANT TIME 74 SEN

28 S CHERK FIT OF ANSFERABLE SHEAVE HEAD ON THIRD SECTION AND ON STINGER PINS SHO

271 R AS W CHESK DIGGER DRIVE OPERATION

A I ISTNS DIGGER

A MY BH TEST DIGGER SHIFT SYSTEM BLEED AIR FROM SHIFT CNLINDER

- I -

C WHEY TRANSFER OF DIGGER HANGER

- -

1 GUIDE PIN ALIQMMENT

28 IY CHEPK IOS TORME AUGER AS STORAGE BOX LATCN SHIMS HINGES BRARKEL SPRING OPE

- I

A WE HRDRAULIC LIFT INSPECT TRAVEL OF CABLE

- I -

F LIFT MUST PULL 120N IBS

SET LIFT BRAKE AT 10D IBS

A YO MECHANICAL LIFT ICHECK CABLE AND MLIGHTING CLEARANCEL I

I NT IS RAVTRUM PELEASE ICHECK HASE ROUNTING AND ONLINDER IINKAGE I

- I

D A HRDRAULIC LATCH ICHECK IATCH MEHANISN AND VALVE OPERATION I I1

E MECHANISAL LATON ICHECK OPERATION OF LATCH AND PULL CABLE W

F CHENK FOR ANGER RETAINING PIN

G I Z IS CHENK TORQUE LIMITER OPERATION F WULL SPOOL TRAVEL REQUIRED WHEN AUGER
PRUNGER SHOULD EXTEND BELOW YOKE 31G

I NA AIR RELEASE IE-CHET MOSE ROUTING LINKAGE AND ONLINDER LEAKAGE

79 CHEAK POLE PLUMMER OPERATION CLEARANA OF TILT BRACKET HASES CLAW AOPEN AND

I I

WITTAGHT COMEPONENTS BOOM IS AT MORIZONTAL POSITION PRIOR TO OPERATION

AS HOLDING VALVE A

30 I SET H - NN P PILOT PRESSURE AT 200N PSL BOOM AT 15DE ELEVATION TES OPERATION WHI

- I I

WIRGEN UP STINGER EXTEND THIRDOUN SHOULD BE INOPERATIVE REVERSE OF THESE FUNCT

I I - -I

11 CHECK BOOM DOWN HOLD SETTING
31 CHECK MINCH BRAKE OPERATION
32 TEST TASTREINC LIME PRIOR TO BREAK-IN
41 CHECK WINCH MOUNTING PRIOR TO PULLING
4 FOT CHECK ALL MINCH ROPE ROLLERS AND SHEAVES FOR BINDING
--
11 PULL ON BARE DRUM WITH BOOM AT 15 DE WITH SUPPAR PRESSURE AT 1950 PSI
1 -
11 ES1 SUPPLY PRESSURE UBS ACTUAL PULL
EH RETUTMORE 11 MINIMUM 610N UBS FOR MORM DRIVEL
11 MINIMUM GADO IBS FOR PLANETARY DRIVE 3
1 -
F VOR08S RER A
11212924
2 OF 3

--

--- Page 3 ---

LEY -O EXE W A 30
33 41 SET ROTATION CONTROL RELIET VALVES TO PULL A 1950 US WITH BOOM AT 300N 1790 I
34 SHECK ANOFT BRAKE ROTATION SYSTEM
4 A ADJUST COUNTER BALANCE VALVES TO ROTATE AT 500G00 ES1
IS 1 CHECK FOR SMOOTH ROTATION
155 PHEEK MRDRAULIC SLIP ROTATION SUSTEM
4 IO TO ADJUST COUNTERBALAL VALVES TO ROTATE AT 500V ES1 7 LOC
35 1 -E A CHEPTY PULL RRATATE DERRICK 1 380DER ROTATION AXOD IN UBS TIME AT IN 32-100
COW AS ZO SEN
4 IV TH VERITY THAT ALL TOP A BOTTOM BEARING BOLTS ARE MARKED WITH VELLOWLIWM
INDICALTINA PROPER TORQUE PROCESS
3T OR 100 CHENK IBS PUSH ROTATION BOTH PINION DIRECTIONS BACKLASH AND RMAXIMUM
1 -
38 W A VIELENTRIC TEST FIBERALASS COMPONENTS DER SPECIFICATION A ANS1 AR0S COMPL
4 IO 1 FIBDERALASS THIRD SECTION 1 100 WAC 3 S
A - FIBERALASS JIB 1 1 500 WVAR
C - FIL TIBERALASS CT CONTROLS 1 100 WVAO
4 1 1 EIBERGLASS POLE PLUMMER TUBE 1 NOO WVAC
E 1 1 INSPECT VISUALLY ALL FIBERQLASS SURTACE 1 MOUNTING 1 ROLLERS FOR PROPER ASSEM
39 OR AEIT BASKET TO BOTH SIDES OF FIDERLASS BOOM ATTACH TOP CONTROLS TO BASKEL C
AN ALL BOOMS MUST BE FULLY EXTENDED THIS INCLUDES MANUAL ATH LIF PROVIDED 1 A EN
ALSO ANY IIB WITH BASKET MOUNTING CAPABILITIES MUST BE INSTALLED TO ENSURE CATRA
4 A IT 1 A CHECK AIR CNLINDER AND PRESSURE SWITCH OPERATION FOR THE FOLLOMING OPT
HOLD TEST LIGHT FOR ONE MINUTE
4 1 STOPLSTART
A - TWO SPEED THROTTLE
SOS 1 EMERGENAY POWER
AT IS VISUALLN INSPECT COMPLETE UNIT FOR APPEARANCE OF FASTENEFS 1 COVERS 1 INTERT
4 ZEPAIRS AND SHORTAGES AFFECTINA TEST MUST BE CARREST AND CLEARED
4 1 PAIRS DISCREPANCIE NOT AFFECTINA TEST ARE TO BE TAGGED AND ENTERED ON FORM 71
13 4 MOVE COMOLETED UNIT TO FINAL INSPECTIOR AND NOTE ARY SPECIAL INSTRUCTI
TY TRANSTER COMPLETED UNIT TO FINAL INSPECTIOR 1 NOTE ANY INSTRUCTIONS MILINGRSS
- AA

T EST INSPECTOR A Z I IS AN WST SU UPERVISE I I THE WE A
F UPNGR0GS RER A
3 OF 3

--- Page 4 ---

VEL MO EE WE A IO A
F I I I A I I I I A P P I E O I N N A E P P N O N A M
A ARK NO JK ST O TO IS SEIAL 1T NO - 7 44 A IS SO SS O
I 7O A SOM ED G GNENT IT A AND REST EPOAT EINAL CIHELIK EETET 115T
YO ALL MOAA CAPPER ON P FGET A
TOS ALL PNOR P UNSNUTS TOOUEOF PAOPEAL YA
I ALL C CONTA NOBS ANND DELALS IN ITALL A P AS P E A IN MA
WIEA EINAL ISPETION S SHEETS LET
PP ROUST I DENTIELL PLATE IN ALLET
HE IO WH OVEARS I ANGLE IS NOCATOF AND NSTALII VTION 1 D EUT I AS IN RALL ED P OP F A1
P LUT MANS ACCEPTAE
TO ALL EXPOSET NUNOET RODS REEOF P RAIUNT
IR A IS VEAIEY MY ALL TOT A BEATING BOLTS AFE MAAIKED N MITH MAY E IT A WT VNUT PEN
PIFE A APPLIC M TOHOUE BEAAN BOLTS AT F UET AL A IS MAAIK FR RON I NO
UP ITANOAFD OPEAATHL PCEDUIFE NNIA IF NOT A OF PLLUC A E I
ITEN IF PAFR NO A VESLAE P A SA YINISS P SAATS IN IS A INT A C IT IN ER D IAT E
P A IS A 15AI SS E A N IS I E D IN ST H IN PP NN E I IT
MTE IF P A NO D ES I A P I 10 A P O AS IS A D JATE F
ID F D IN EINMAL DATE YSPERTO A LESY IN I IT CTMP I S 1 IS TEP 'S S IS AS I FINAL IN ISPETL SP
--

F FNROST RER F
9828-1 A

--- Page 5 ---

I I I MY A - E A T A A -O W A T NO A A
A ASTER A A O TO RY OW 1 A 20 A AN A DIGGEL OW A DERRICKS TESTED RE REAMIRE THE TO T
ITEMS IN
1 IS DECAL A A8889 INSTALLED MEAR LOWER CONTROLS AS
7 T DENAL A 1 9213 3 MUST BE RER A IR 1 13A I
3 A PLATE MUST INDICATE ANS1 A RO31 R0TS 3
A I A F MMER STOP S AT LOWER CONTROL LOCATOR I I
A I CABELED A EMERGENC STOP IS WITH A RED ENGRAVED LABEL I 18BA8I 2 3
TOY MUST BE SEPARATE CONTROL I
A WILL STOP ALL HRDRAULIC FUNCTIONS OR SHUT OFF PTO AND ENQIME
I A WILL STOP OPERATION OF REMOTE CONTROLS
5 LOWER CONTRO WILL HAVE - EPPER CONTROL SELESTOR FOR USE WHEN A
AMOVADL PLATTORM IS ARDERED
G I A I PPE CONTROL SELECTOR WILL DISABLE DIGGER AND POLE CLAM WHEN
MY - - IH ALL UNITS WITH SHEAVE HEIGHTS OVER 50 AH MUST HAVE VASLUM
OREVENTION FOOT VALVES IN PRESSURE AND RETURN LINES
A AT THE UPPER CONTRO LOCATION EMERGENAY STOP CONTROL MUST NOT
IS PERTORM ANY OTHER FUNCTION
9 IL UPPER CONTROL BOOM FUNCTIONS REQUIRE AN UNLOCKING OR ENABLE
I A SEVICE BEFORE OPERATION
1 N TY IF IS OPPER VALIFARMIE CONTROLS IF PROPOSITION EQMIPPED 65 DEZAL IAFTER 81 8R2
I I

ENSOZR RER A

AOTAIL A

--- Page 6 ---

1E1 T WE A WE AN IO A

I A - A IO - E I A I A I A I

A I A A EE IS I A I A A I I IH I IMD I ST A I 1 A I AN

OP 1 IS IN AN PP I IR I A I A E ID IS MY I F I N A T N

THE CALLENTOR BLOOK PORTS ANDLOR OTHER PLUMBIN NOTES MUST BE CONNESTED
BY THE INSTALLER FOR PROPER OPERATION OF THE UNIT

ARK IF BE A A A D E A A CK SN S NO IT DO A A A

RETER TO THE DIAGRAM FOR RELIET ADIJUSTMENT AND PORT ICATIO IN

RETER TO UNIT MANUAL FOR DROPER PRESSURE SETTINA

THE INSTALLER MUST COMNEST THE FOLLOMINA PORTS

A E I I EF THE A EE A E CO IR I D I A

P UN I I ON I F A I A I P T SN N TT TOS E AS SIZE

P O A I A S IS HE UN F A I A E OT I M F FROM PUNF 314

PR I A E A SUR AE I LINNE TO ON RAIGT A IS 1AL IES 314

I A E STUAN I LINNE FHOM ON A IS AL VET TIRN

TI NAN AETUAN TO A TAS 'LLL F TEF 1Y PIG

A THEF A TO OLN A LEE IFVO

T8 COW P RESSUAT E DAAIN LINE THAT MUST 1Y MIA

GO D I REOTL MHY I SO I TANK

CR ILT TOF A F I ON AS E I A D E A

B DAK P SOM I IF D E AS IN A I P I AN N H IOS E A TE

AF IS H DAAN THAS IT I F 1 M14

F E F FLOW ETUAN 1 1IRS

IN HOOK DIAEL TO I TANKS

IT EQMIPPED WITH THE FOLLOWING OPTIONS PLUMBING CONNECTIO ARE MADE ON VALVES F

I I I

COLLECTOR BLOOK PORTS I OR PIGYY BACK PORTS LOCATED IN THE TOWER AREA I

IT I AAGET PIUMP PAESSUA LIME TO D DIGGEF A 314

NT NIOH THE VAIVE MLET ON I TOR A

A AUGEA LATOH ALT OF IHS IACN IS IS 1 1K

A I BGE A ST STHIET - ALT ON IHS INN IS 1 14 IN

- M

IH D I G G E A MWIN IS VAIVE O IEN A EVOND D 314 IN

F FNZRT 1 RER A

1 -1U1 1

--- Page 7 ---

S S

S VY M WE A A A IO A - S - - I S S S - S S

A S S

I ASSY TEAM DD

IT I A A F A D F A A I G K DATE - 44 - A 4

- A A A IE A AT A I MY A E N AN AE M

DX NO 8 NO A A ST IN LVE A BLON I ENENT ROEF A S

P IN

- S SENIAL NO DANN CAD IN A I I

I S

A 1EUTOT BLORK IUT YY A ZANNIC 320 I INT A E A 1 I
- ON SN I 4 LO 9 - I I 7 IN - ZE I 3N IN -
S S S A IS MINOH NODEL SETIAL NO NO GEAP A I ZUE EUI IO T PN 2 - SO X EE WE A A - F P AS I IN
I MINCT NOTOF A I I IN IF F I A F A LASI A ATH A SELTLL I
P S P IN N S
IN S SN
S A IG I
A ROTAT GEAT S F A E A ILT SO IT I I
PIN 4 I I A AS M OLT P IN IN
SN 3 SOT 2 84 S IN -
TATION NOTOR D NIOOET A
OIN IS 30 32 1 P IF 34 -F CARES S IOT
SN Z 123 - A D A 3 I HE SIN I 7 DO A IS SET I A ZN A A
S ROTATIC A BEAFING LIET ENINND
I SN PN 1LE TO ZIE SN T A A 3U A G 3 - SN PIN A AH H TY AR AS 1R A MS O TN IH IH I TS 4 N IF 238
S A BEAFINE - SACK MMTINDEL A AS
P P IN WN TO SON 4 LO0TK 20TK S - ST A 7 3E SN PN IO I O TH I PN SIN
A BR A C C CKLAST WKLAST X UPPEF OWVER IS ES A N IT AY - SN NNT ON PIN
P IIE I SIKE S
CLAW ON I PIN I
S A IS NOEL PEOLAL NO NIPN E IT IS I A I IF H SN
I SN PP I G G 1S A A A 1 E ELERTTLL A EET A RNO -
S A
S S IF IF EAN WE I I
S S - O POFT I I TO ENTU I I A TU IT IR IFR B ASS K - A RA AND I
S I IL IR RETURN PRESSURE IF IF 1 1 A 7 - A I 7F3 I H A 73 IA TH B A A A ION SISE HE OW
43 F PRESSURE IF 3 - S S 75 F5S AS EEN-
S I THROTTLE IF A AF AS A I I A A
AS REDUCED PRESSURE IF 5 IFT IFT
S AS DRAIN IF 1 G S I IS IE
IFT IF X MY IG 7 S
- -
I8 IF A A I D FLO
IFG IFF A - I I I
IF 1 NO ARO0 A S
IS - S S F ENZ88R RER D 9508-15 5
- A A I
S - IN - VANG A - S - I
- - - I
- - - - -

--- Page 8 ---

S S
A SO NO AS O OR A I W A IX IER
- A ON SO -N I S S A S S A NNO AS TO AS D S A A A AS N TO SO IS SO S A
A Z IN A NN A T NO NNO IS SO I S S TO NN I NO WAS IN A
A NON RO SON I SO ES IN A AS IT I AS IN
OU NO 5 S A SOO A A S I NON SO S NO A TO I
SO N SO
S A S AS IS X 3
IN A S NON
O A - M - TO A IF A I IN I IS IE O A FOT A ZU OT W - IS SON SO IN A SO AS IS A SO 3 S A S A S AS SO

A I A AS SO A A NON TO S A
I SO I I IT Z A I SO A TO S S SO SO KO IN S A A I SO A A S A A A SN IN - TO IS S I I E SN
A S NN A S IS SO A IS S SO A AS ES AS
I E A A
A AT ES NON A SON A A NN A
S SO SO BE SON A TO A A -
SON AS A A A S S 3 SO S SOR 3 A
SO SN N 8 SO SO S I A SO I NON S SO A A IS
S S SO O A ES A E 8 A FRI A
- S - ONE 3 S
I I S 3 A A AS A IS F
- S S B -E A
A I
IS E E I IS
1 A
S I - - A IS SO IN
A A IS
AN IE ES SL S I I IS A 1 A 7 IN
I A
S S 3 B
I -
- E ZO S OR S I S - S S S A S ON IS 19S 10 IN I T IIS IF AS AS HO BE OY WE O A I TO -N ON IS AE STO
T - S
- S
- S
S S S
--

--- Page 9 ---

A - - S S IS
IS A -S HE A A W A A - A I - S S
- I A - - - S S S A -
A I
- - D I G A E A D - A A I T X A ASSY TEAM AON - S
DIK NO 80 A I A A A IS E IN A A I MY A I PP AN A I DATE 3 Z4 I S
I - -
S S S
MARN BOOM
SN PN STEE 340 A IT IHE IF I IT - - A I I S S -
SN TO I M E IS S S I I
STINGES EXTENSION CNIND A - S ZS A - IN I
SN PIN ALFL- SA4 I IT 2IYR TO I - O - 23 - I - A 4U0 I I S S
YVDRALN 310 MEAN
S PIN HIL 495
- SN TTO - IM I8 - SO - I - P - IF - O I -
- F ILBETGL 15S 340 A 3ELTION I
SN I
- F A E GLAS - A IH AS SECTION IE A I T A
P I
S - SO I S S S
S S

I - I S
S F A E A 1 I MIB -
P IF
S S
I A S I - -
D 1 OGET A S
SIN -
LIET CNINDE A
PIN 7H 'T
SN A H 1S
IS -
SAOIK C LINOE A AS A
I PIN PIN
SN SN A - - -
- S NNT ON PIN A X I
SN 12A4 - A 332 AR 21 I 3 H
- CLAS CN PIN 4 IR M A A I TE S S I
IS A SIN A A I A IH I I
S MINOH GEAP 30X PIN IO - - S
MOVEL NO - - S S - IS I -
A SERLAL NO AN S I -
I IN - S S S I S -
- MINCT NOTOF PN
I - S S
PIN IT TH I
SN S
S S
S S S S S
S S
S S
S S S S S S
S S S S
- S S S S -
A S S
I I S I F FMZ8ZZ RER F DO ASSY REPOT I 13
---OS ---

--- Page 10 ---

A -
OR A N W A IE IE
- A A D TO IN SO
ON A S TO TO IS AS SO A
IN - I AN
Z A S I IS 3 A TO ON A INT Z A AO
A 9 NO S
NO A S S 9 A IS O A SO A A A S S IS A X NON SO MS O - SON S E A AN A I 2
TO A A A IS
- A - A IF I I H A HO A A SO AS A IS A A TO S SO I A S S S A T0 A A NN S S TO A A AS A AS -
-N ZN A SO - S IS 8 I
IS S
I IT A I ON IS AO IS A I I A
S - A SO A A SO ON

TO IS I IS 3
- S0 SS 3 SO IS
A A 7
SON SO TN
A A I IA
S S S A
II - -E S F 3 A S A 7 IS IS SO A A A S ES A IT A
O A A ES A O
S H SO A E I SO - -
SN A
IT RO 7 O NON S A 3 A 3 E I A B -
S - 3
3 A IS
I 1
7 SO A IS
T IT A
- -E A I TH - - AT B IS IS IN IS A -
A 7
- I 3F ES
S A
IS I
NO I I SO
IO SO A TT 3 S S MY Y N EN IL OS IS IT IO ES I IS FNE FF IS T NON I A T SO IR A I 1 I
TO I
ON TN NON
- SO
- S - - -
- -
I -
- - - S -
- - - - - - -