

High Availability Setup Guide

*** Draft ***

Revised: 02/14/06

Introduction

This document describes the extra steps needed to configure a pair of systems for redundant operation to provide highly available calling service. It does not replace the normal installation guide; it should be used with the normal instructions to make the manual changes needed for a high availability installation.

In an HA configuration, there are two servers:

- one Master Server (MS) running the full set of services.
- one Distributed Server (DS) running:
 - forking proxy (sipproxy)
 - authentication proxy (sipauthproxy)
 - registrar/redirect service (sipregistrar)

Hardware

Both servers should conform to the standard hardware guidelines in the installation guide. However, only the MS hosts a VXML service and stores the associated voicemail, so the DS does not need to budget disk for voicemail; it may have a /var partition that is correspondingly smaller.

Select Server Names and Addresses

Select the fully qualified host names and IP addresses for your sipX servers. In the examples below, "example.com" represents the local domain name; replace it with your actual domain name for your installation. The host names used here are:

- sipx1.example.com for the MS
- sipx2.example.com for the DS

The HA system as a whole has a name of its own – the SIP domain name. This is the name that is used as the right side of the SIP addresses (sip:[user@domain](#)). Typically, this will be the domain name of the organization (example.com), but it may be any unique name within that domain.

Installation

The recommended installation sequence is:

1. Install the Master Server
2. Configure DNS
3. Create TLS/SSL certificates
4. Install the Distributed Server
5. Modify Configurations

Each of these steps is detailed below.

Install Master Server

Install the Master Server software normally, using the names you chose above for the SIP domain name and the host name.

Configure DNS

In order to provide load sharing and failover, all SIP message routing to redundant services in an HA configuration uses DNS SRV records. The following SRV records are required:

domain

The domain record maps the SIP domain name to the proxy host names.

registrar

In an HA configuration, each proxy is configured to use a registry service name that is mapped first to the registrar instance on the same Server, and then falls back to the registrar instance on the other Server .

authproxy

The authorization proxy service is also addressed using a service name that prefers the local instance first, with a fallback to the redundant instance.

To generate all the DNS records needed for your installation, use the `sipx-dns` command on the Master Server; log in to the server, and execute:

```
sipx-dns sip-domain server-name/server-ip server-name/server-ip
```

substituting your names and IP addresses:

sip-domain

Is the domain that will be used as the domain part of your SIP addresses. Typically, this will be your top level domain name (example.com).

server-name/server-ip

This is the fully qualified name and IP address of each sipXpbx server in your domain, separated by a '/' character.

The output of the `sipx-dns` command is suitable for use in a zone file for the BIND nameserver (Linux `named`).

Example DNS Configuration

For the example HA configuration, the DNS records can be generated by:

```
sipx-dns example.com sipx1.example.com/10.1.1.50 sipx2.example.com/10.1.2.50
```

the output generated is:

```
////////////////////////////////////
; sipX Servers for SIP domain 'example.com'
////////////////////////////////////
sipx1.example.com.      IN      A      10.1.1.50
sipx2.example.com.      IN      A      10.1.2.50

; Allow either UDP or TCP at equal preference
example.com.            IN      NAPTR 2 0 "s" "SIP+D2T" "" _sip._tcp.example.com.
example.com.            IN      NAPTR 2 0 "s" "SIP+D2U" "" _sip._udp.example.com.
_sip._tcp.example.com.  IN      SRV    1 0 5060 sipx1.example.com.
_sip._tcp.example.com.  IN      SRV    1 0 5060 sipx2.example.com.
_sip._udp.example.com.  IN      SRV    1 0 5060 sipx1.example.com.
_sip._udp.example.com.  IN      SRV    1 0 5060 sipx2.example.com.

; sipx1.example.com routing for registry/redirect service
_sip._tcp.rr.sipx1.example.com.  IN      SRV    1 0 5070 sipx1.example.com.
_sip._tcp.rr.sipx1.example.com.  IN      SRV    2 100 5070 sipx2.example.com.

; sipx1.example.com routing for authorization service
_sip._tcp.ap.sipx1.example.com.  IN      SRV    1 0 5080 sipx1.example.com.
_sip._tcp.ap.sipx1.example.com.  IN      SRV    2 100 5080 sipx2.example.com.

; sipx2.example.com routing for registry/redirect service
_sip._tcp.rr.sipx2.example.com.  IN      SRV    1 0 5070 sipx2.example.com.
_sip._tcp.rr.sipx2.example.com.  IN      SRV    2 100 5070 sipx1.example.com.

; sipx2.example.com routing for authorization service
_sip._tcp.ap.sipx2.example.com.  IN      SRV    1 0 5080 sipx2.example.com.
_sip._tcp.ap.sipx2.example.com.  IN      SRV    2 100 5080 sipx1.example.com.

////////////////////////////////////
```

Create TLS/SSL Certificates

The synchronization of the replicated services in an HA configuration is secured by TLS, and requires that:

- the certificates for each system are signed by an authority trusted by each system.
- Each certificate contains a SubjectAltName entry with a DNS name for the host.

If you use the `gen-ssl-keys.sh` script to create self-signed certificates for your systems, these requirements are met for you.

Create and install the certificate for the Master Server by logging in to the Master Server, and execute:

```
mkdir $HOME/sslkeys
cd $HOME/sslkeys
/usr/bin/ssl-cert/gen-ssl-keys.sh
```

answer the questions, providing the name of your domain and the Master Server.

To create a compatible certificate for the Distributed Server, in that same directory execute:

```
/usr/bin/ssl-cert/gen-ssl-keys.sh --csr
```

answer the questions; the default answers should be correct for all but the full name of the server : provide the name of the Distributed Server. The above creates a key and a certificate request for the Distributed Server. The certificate request is the file named *dist-server.csr*, where *dist-server* is the name of the Distributed Server. To create the certificate for the Distributed Server, execute:

```
/usr/bin/ssl-cert/gen-ssl-keys.sh -sign dist-server.csr
```

The above will produce the files:

```
dist-server.key
dist-server.crt
caname.crt
```

where *caname* is the name you provided for the Certificate Authority. These three files will need to be copied to the Distributed Server when it is installed (see below).

Install the certificates and key for the Master Server by running the following as root in that directory:

```
/usr/bin/ssl-cert/install-cert.sh
```

Install the Distributed Server

Install the sipXpbx software on the Distributed Server normally. When you reach the step of generating the TLS/SSL certificate, rather than generating new certificates, copy the three files listed above to a directory on the Distributed Server and execute the following as root in that directory:

```
/usr/bin/ssl-cert/install-cert.sh
```

When the installation is finished, log in to the server to modify configurations.

Modify Configurations

There are N changes to be made to the configurations

1. Disable non-replicated services on the Distributed Server.
2. Configure the Master Server to manage the Distributed Server.
3. Configure registry synchronization on both servers.
4. Modify proxy routing for redundant services on both servers.

Disable non-replicated services on the Distributed Server

The Distributed Server runs only three services:

- registrar/redirect service (sipregistrar)
- forking proxy (sipproxy)
- authentication proxy (sipauthproxy)

To disable the other services, edit the file `/etc/sipxpbx/WatchDog.xml` on the Distributed Server (for safety, first make a backup copy of the file, e.g., `WatchDog.xml.bak`). Each process has an entry like this one for the publisher/status server:

```
<process name="SIPStatus"
  restart="enable" max_restarts="3" report="enable" max_reports="3">
  <failure_contact method="email">wgillett@localhost</failure_contact>
</process>
```

Remove the process elements (from '`<process>`' through '`</process>`' inclusive) for all processes except those with the names "KeepAlive", "SIPRegistrar", "SIPProxy", and "SIPAuthProxy", which conveniently appear at the top of `WatchDog.xml` in the order listed. Save the file, and then run the following command to check that the file is still valid:

```
sipx-validate-xml /etc/sipxpbx/WatchDog.xml
```

If no error message is printed, the file is valid.

Configure the Master Server to manage the Distributed Server

On the Master Server, edit the file `/etc/sipxpbx/topology.xml.in`, which should look like:

```
<?xml version="1.0" ?>

<!-- This file defines the "topology" file that resides on the
configuration server. This file acts as a registry/database for
replication targets and remove process management agents -->

<!DOCTYPE topology [
  <!ELEMENT topology (location+)>
  <!ELEMENT location (component+, replication_url, agent_url, sip_domain?)>
  <!ATTLIST location id CDATA #REQUIRED>
  <!ELEMENT component EMPTY>
  <!ATTLIST component id CDATA #REQUIRED>
  <!ATTLIST component type (media-server | config-server | comm-server)
#REQUIRED>
  <!ELEMENT replication_url (#PCDATA)>
  <!ELEMENT agent_url (#PCDATA)>
  <!ELEMENT sip_domain (#PCDATA)>
]>

<topology>
  <location id="Config Server, Media Server and Comm Server">
    <component id="MediaServer1" type="media-server" />
    <component id="CommServer1" type="comm-server" />
    <replication_url>
      https://${MY_FULL_HOSTNAME}:${CONFIG_SERVER_HTTPS_PORT}/cgi-
bin/replication/replication.cgi
    </replication_url>
    <agent_url>
      https://${MY_FULL_HOSTNAME}:${CONFIG_SERVER_HTTPS_PORT}/cgi-
bin/processmonitor/process.cgi
    </agent_url>
  </location>

  <!-- REMOVE THIS LINE TO ADD DISTRIBUTED SERVER
  <location id="Distributed Comm Server">
    <component id="CommServer2" type="comm-server" />
    <replication_url>
      https://DISTRIBUTED_HOSTNAME:${CONFIG_SERVER_HTTPS_PORT}/cgi-
bin/replication/replication.cgi
    </replication_url>
    <agent_url>
      https://DISTRIBUTED_HOSTNAME:${CONFIG_SERVER_HTTPS_PORT}/cgi-
bin/processmonitor/process.cgi
    </agent_url>
  </location>
  REMOVE THIS LINE TO ADD DISTRIBUTED SERVER -->
</topology>
```

(some lines above are wrapped in this document but not in the original file)

The default file shown instructs the configuration server to replicate configuration information only to itself. To configure replication to the Distributed server, delete the two lines:

```
<!-- REMOVE THIS LINE TO ADD DISTRIBUTED SERVER
and
```

REMOVE THIS LINE TO ADD DISTRIBUTED SERVER -->

and change each instance of 'DISTRIBUTED_HOSTNAME' to the full name of your Distributed Server.

Configure registry synchronization on both servers

On both the Master and Distributed Servers, edit the file /etc/sipxpbx/registrar-config.in ; at the bottom of the file, you will find a block of lines:

```
# See HaSetup.pdf for how to use the following
#SIP_REGISTRAR_XMLRPC_PORT : 5077
#SIP_REGISTRAR_NAME : ${MY_FULL_HOSTNAME}
#SIP_REGISTRAR_SYNC_WITH : MASTER_HOSTNAME, DISTRIBUTED_HOSTNAME
```

For each of the last three of these lines, delete the leading '#' character (so that they begin 'SIP_REGISTRAR_').

Replace MASTER_HOSTNAME and DISTRIBUTED_HOSTNAME with the fully qualified host names of your Master and Distributed Servers.

Modify proxy routing for redundant services on both servers

On both the Master and Distributed Servers, edit the file /etc/sipxpbx/config.defs

Find the line:

```
REGISTRAR_SERVER_SIP_SRV_OR_HOSTPORT=${MY_FULL_HOSTNAME}
```

and add 'rr.' after the '=' to make it:

```
REGISTRAR_SERVER_SIP_SRV_OR_HOSTPORT=rr.${MY_FULL_HOSTNAME}
```

Find the line:

```
AUTH_PROXY_SERVER_SIP_SRV_OR_HOSTPORT=${MY_FULL_HOSTNAME}
```

and add 'ap.' after the '=' to make it:

```
AUTH_PROXY_SERVER_SIP_SRV_OR_HOSTPORT=ap.${MY_FULL_HOSTNAME}
```

Your HA configuration is complete. You can now proceed to configuring your systems.