

RWorksheet_Camarista#3b

John Lyxton Camarista

2024-10-02

```
# a. Write the codes.
dataFrame <- data.frame(
  Respondents = 1:20,
  Sex = c(2, 2, 1, 2, 2, 2, 2, 1, 2, 1, 2, 2, 1, 2, 1, 2, 1, 2),
  FathersOccupation = c(1, 3, 3, 3, 1, 2, 2, 3, 1, 3, 1, 3, 1, 2, 2, 3, 1, 3, 2, 1),
  PersonsAtHome = c(5, 7, 3, 8, 9, 6, 7, 8, 4, 6, 8, 5, 6, 9, 1, 6, 11, 7, 7, 6),
  SiblingsAtSchool = c(6, 4, 3, 1, 8, 5, 5, 2, 2, 3, 1, 2, 2, 1, 1, 6, 5, 1, 2, 2),
  TypesOfHouses = c(1, 3, 1, 3, 3, 2, 1, 3, 3, 2, 3, 2, 1, 3, 2, 3, 1, 3, 3, 2))
dataFrame
```

1. Create a data frame using the table below.

##	Respondents	Sex	FathersOccupation	PersonsAtHome	SiblingsAtSchool
## 1	1	2	1	5	6
## 2	2	2	3	7	4
## 3	3	1	3	3	3
## 4	4	2	3	8	1
## 5	5	2	1	9	8
## 6	6	2	2	6	5
## 7	7	2	2	7	5
## 8	8	1	3	8	2
## 9	9	2	1	4	2
## 10	10	1	3	6	3
## 11	11	2	1	8	1
## 12	12	1	3	5	2
## 13	13	2	1	6	2
## 14	14	2	2	9	1
## 15	15	1	2	1	1
## 16	16	2	3	6	6
## 17	17	1	1	11	5
## 18	18	2	3	7	1
## 19	19	1	2	7	2
## 20	20	2	1	6	2
##	TypesOfHouses				
## 1	1				
## 2	3				
## 3	1				
## 4	3				
## 5	3				

```
## 6          2
## 7          1
## 8          3
## 9          3
## 10         2
## 11         3
## 12         2
## 13         1
## 14         3
## 15         2
## 16         3
## 17         1
## 18         3
## 19         3
## 20         2
```

```
#b. Describe the data. Get the structure or the summary of the data
str(dataFrame)
```

```
## 'data.frame':    20 obs. of  6 variables:
## $ Respondents    : int  1 2 3 4 5 6 7 8 9 10 ...
## $ Sex            : num  2 2 1 2 2 2 2 1 2 1 ...
## $ FathersOccupation: num  1 3 3 3 1 2 2 3 1 3 ...
## $ PersonsAtHome   : num  5 7 3 8 9 6 7 8 4 6 ...
## $ SiblingsAtSchool : num  6 4 3 1 8 5 5 2 2 3 ...
## $ TypesOfHouses   : num  1 3 1 3 3 2 1 3 3 2 ...
```

```
summary(dataFrame)
```

```
## Respondents      Sex      FathersOccupation PersonsAtHome
## Min.   : 1.00    Min.   :1.00    Min.   :1.00    Min.   : 1.00
## 1st Qu.: 5.75    1st Qu.:1.00    1st Qu.:1.00    1st Qu.: 5.75
## Median :10.50    Median :2.00    Median :2.00    Median : 6.50
## Mean   :10.50    Mean   :1.65    Mean   :2.05    Mean   : 6.45
## 3rd Qu.:15.25    3rd Qu.:2.00    3rd Qu.:3.00    3rd Qu.: 8.00
## Max.   :20.00    Max.   :2.00    Max.   :3.00    Max.   :11.00
## SiblingsAtSchool TypesOfHouses
## Min.   :1.00    Min.   :1.00
## 1st Qu.:1.75    1st Qu.:1.75
## Median :2.00    Median :2.50
## Mean   :3.10    Mean   :2.25
## 3rd Qu.:5.00    3rd Qu.:3.00
## Max.   :8.00    Max.   :3.00
```

- the data frame has 20 rows and 6 columns.
 - There are 20 respondents
 - In sex, 1 is for male and 2 is for female
 - In father's occupation, 1 is for farmer, 2 for driver, and 3 for others
 - The Person's at home shows how many people living in the respondent's house
 - Siblings at schools shows how many siblings of the respondents are still attending school
 - In types of house, 1 is for wood, 2 is for semi-concrete and 3 for concrete

```
#c. Is the mean number of siblings attending is 5?
meanSiblings <- mean(dataFrame$SiblingsAtSchool)
```

```
print(paste(meanSiblings, "is the mean of Sibling attending school"))
```

```
## [1] "3.1 is the mean of Sibling attending school"
```

```
#d. Extract the 1st two rows and then all the columns using the subsetting functions.
#Write the codes and its output.
```

```
subset(dataFrame[1:2, ])
```

```
## Respondents Sex FathersOccupation PersonsAtHome SiblingsAtSchool
## 1          1  2              1              5              6
## 2          2  2              3              7              4
## TypesOfHouses
## 1          1
## 2          3
```

```
#e. Extract 3rd and 5th row with 2nd and 4th column. Write the codes and its result.
dataFrame[c(3, 5), c(2, 4)]
```

```
## Sex PersonsAtHome
## 3  1              3
## 5  2              9
```

```
#f. Select the variable types of houses then store the vector that results as types_houses.
#Write the codes.
```

```
types_houses <- dataFrame$TypesOfHouses
types_houses
```

```
## [1] 1 3 1 3 3 2 1 3 3 2 3 2 1 3 2 3 1 3 3 2
```

```
#g. Select only all Males respondent that their father occupation was farmer.
#Write the codes and its output.
```

```
male_farmer <- dataFrame[dataFrame$Sex == 1 & dataFrame$FathersOccupation == 1, ]
male_farmer
```

```
## Respondents Sex FathersOccupation PersonsAtHome SiblingsAtSchool
## 17          17  1              1              11              5
## TypesOfHouses
## 17          1
```

```
#h. Select only all females respondent that have greater than or equal to 5 number of siblings attending.
#Write the codes and its outputs.
```

```
female_siblings <- dataFrame[dataFrame$Sex == 2 & dataFrame$SiblingsAtSchool >= 5, ]
female_siblings
```

```
## Respondents Sex FathersOccupation PersonsAtHome SiblingsAtSchool
## 1          1  2              1              5              6
## 5          5  2              1              9              8
```

```
## 6          6  2          2          6          5
## 7          7  2          2          7          5
## 16         16  2          3          6          6
##      TypesOfHouses
## 1          1
## 5          3
## 6          2
## 7          1
## 16         3
```

2. Write a R program to create an empty data frame. Using the following codes:

```
df = data.frame(Ints=integer(),
Doubles=double(), Characters=character(),
Logicals=logical(),
Factors=factor(),
stringsAsFactors=FALSE)

print("Structure of the empty dataframe:")
```

```
## [1] "Structure of the empty dataframe:"
```

```
print(str(df))
```

```
## 'data.frame':    0 obs. of  5 variables:
## $ Ints      : int
## $ Doubles   : num
## $ Characters: chr
## $ Logicals  : logi
## $ Factors   : Factor w/ 0 levels:
## NULL
```

- The structure of the empty data frame shows no data but has predefined columns with their respective data types.

#a. Import the csv file into the R environment. Write the codes.

```
HouseholdData <- read.csv("E:/Github/Data Science Worksheets/DataScience_Worksheets_Camarista/Worksheet1/
HouseholdData")
```

3. Create a .csv file of this. Save it as HouseholdData.csv

```
##      Respondents      sex Fathers.Occupation Persons.at.Home Siblings.at.School
## 1          1      Male          1          5          2
## 2          2  Female          2          7          3
## 3          3  Female          3          3          0
## 4          4      Male          3          8          5
## 5          5      Male          1          6          2
## 6          6  Female          2          4          3
```

```
## 7      7 Female      2      4      1
## 8      8  Male      3      2      2
## 9      9 Female     1     11      6
## 10     10  Male      3      6      2
##      Types.of.Houses
## 1      Wood
## 2      Concrete
## 3      Concrete
## 4      Wood
## 5      Semi-Concrete
## 6      Semi-Concrete
## 7      Wood
## 8      Semi-Concrete
## 9      Semi-Concrete
## 10     Concrete
```

*#b. Convert the Sex into factor using factor() function and change it into integer.
#[Legend: Male = 1 and Female = 2]. Write the R codes and its output.*

```
HouseholdData$sex <- factor(HouseholdData$sex, levels = c(1, 2), labels = c("Male", "Female"))
HouseholdData
```

```
##      Respondents  sex Fathers.Occupation Persons.at.Home Siblings.at.School
## 1      1 <NA>      1      5      2
## 2      2 <NA>      2      7      3
## 3      3 <NA>      3      3      0
## 4      4 <NA>      3      8      5
## 5      5 <NA>      1      6      2
## 6      6 <NA>      2      4      3
## 7      7 <NA>      2      4      1
## 8      8 <NA>      3      2      2
## 9      9 <NA>      1     11      6
## 10     10 <NA>      3      6      2
##      Types.of.Houses
## 1      Wood
## 2      Concrete
## 3      Concrete
## 4      Wood
## 5      Semi-Concrete
## 6      Semi-Concrete
## 7      Wood
## 8      Semi-Concrete
## 9      Semi-Concrete
## 10     Concrete
```