

Chapter 1

Software Installation/Getting Started

1.1 Introduction

This chapter describes how to download and set up METplus. METplus has been developed and tested on the Debian Linux operating system.

1.2 Supported architectures

METplus was developed on Debian Linux and is supported on this platform.

1.3 Programming/scripting languages

METplus is written in Python 2.7. METplus is intended to be a tool for the modeling community to use and adapt. As users make upgrades and improvements to the tools, they are encouraged to offer those upgrades to the broader community by offering feedback to the developers or coordinating for a GitHub pull. For more information on contributing code to METplus, please contact `met_help@ucar.edu`.

1.4 Pre-requisites

The following software is required to run METplus:

- Python 2.7

- R version 3.2.5 ¹
- nco (netCDF operators)
- MET version 6.1 or above
- Basic familiarity with MET
- GitHub account (if you plan on contributing code to METplus)

1.5 METplus directory structure

Once you have cloned the METplus from the GitHub repository at <https://github.com/NCAR/METplus> to a location on your host, change directories to the METplus directory. You should have the following directory structure:

```
METplus
  doc
  internal_tests
  parm
  src
  ush
  README.md
```

The top-level METplus directory consists of a README.md file and several subdirectories.

The doc/ directory contains documentation for users (PDF) and Doxygen files that are used to create the developer documentation. The Doxygen documentation can be created and viewed via web browser if the developer has Doxygen installed on the host.

The internal_tests/ directory contains unit test scripts that are only relevant to METplus developers and contributors.

The parm/ directory contains all the configuration files for MET and METplus.

The src/ directory contains Doxygen executables to generate documentation for developers.

The ush/ directory contains the source code for each of the wrappers in METplus.

The ush/ directory contains the Python wrappers to the MET tools.

¹R version 3.2.5 is required when the tcmpr_plotter_wrapper.py wraps the plot_tcmpr.R script. Please refer to Chapter 21 Plotting and Graphics Support for more information about plot_tcmpr.R.

1.6 Getting the METplus source code


The METplus source code is available for download from a public GitHub repository. You can retrieve the source code through your web browser or the command line.

1.6.1 Get the source code via your Web Browser

1.6.1.1 Source code only:

If you wish to retrieve only the source code, then the following steps will illustrate how to quickly access the METplus source code and relevant documentation:

- On your local host (or wherever you wish to install the METplus code) create a directory where you want the code to reside
- Open the browser of your choice and navigate to <https://github.com/NCAR/METplus>. You will see something like the following:



[Pull requests](#)
[Issues](#)
[Marketplace](#)
[Explore](#)

[NCAR / METplus](#)

[Unwatch](#)
17

[Star](#)
17

[Fork](#)
5

[Code](#)
[Issues 55](#)
[Pull requests 0](#)
[Projects 0](#)
[Wiki](#)
[Insights](#)
[Settings](#)


Python scripting infrastructure for MET tools.

Edit

[Manage topics](#)

1,037 commits
14 branches
13 releases
7 contributors

Branch: master
New pull request
Create new file
Upload files
Find file
Clone or download


CPKalb Update grid2grid_hwt_env.conf
Latest commit a724bbc 2 hours ago

doc	Merge branch 'develop' of https://github.com/NCAR/METplus into develop	8 months ago
internal_tests	Updated to reflect changes in the conf file.	5 months ago
parm	Update grid2grid_hwt_env.conf	2 hours ago
sorc	Change name from Alpha-produtil to Beta-METplus.	11 months ago
ush	Accidentally committed GitHub Issue #92 changes to master branch. Rev...	2 months ago
.gitignore	Initial commit	2 years ago
.travis.yml	try ./ since we don't know how directory is structured in the travis ...	6 months ago
README.md	Updated top-level README .	a year ago

README.md

METplus Repository README File {#METplus_README}

Welcome to the documentation for the Model Evaluation Tools Plus (METplus).

This is the METplus repository Top level README.md

Basic DOCUMENTATION - getting started

ALL Documentation specific to this repository can be found in the doc/ directory.

The ORIGINAL setup text documentation in a markdown file is found here.

- doc/README_install.md — installation, configuration, running
- doc/README_terms_of_use.md — legal Terms Of Use

METplus is a Python scripting infrastructure around the MET verification tools (and eventually METViewer, a tool used for plotting MET output verification statistics).

This infrastructure utilizes the NCEP produtil package. A Platform-independent weather and ocean forecasting utility package. Developed at the National Oceanic and Atmospheric Administration (NOAA).

Website Documentation

Users can generate an entire METplus documentation website, if they have Doxygen version 1.8.9.1 or later installed.

```
cd METplus/sorc
make doc
In your browser, open the page METplus/doc/html/index.html
```

Terms of Use

@ref METplus_TermsOfUse


Install/Configure/Run Guide

@ref METplus_install_guide

Produtil Guide

@ref METplus_produtil

- You should be directed to the 'master' branch, verify this by looking at the button labelled 'Branch' in the upper left corner of your window, directly beneath the solid blue horizontal line.
- Click on the green "Clone or download" button near the top right of the page.
- A box appears with "Clone with HTTPS" label
- Click on the blue text: "Download Zip" :




- Your browser should prompt you on what to do with this file. Save it to the directory you created above
- cd to the directory where you saved the code. You should see the file METplus-master.zip
- Uncompress the file:
 - Linux/Unix:
 - unzip METplus-master.zip
 - You should now have a METplus-master directory
 - * If you downloaded the code via the command line, you will get a METplus directory rather than METplus-master.
 - * GitHub appends the '-master' to the name to emphasize that is is from the master branch
 - * To avoid clutter and confusion, you can now remove the METplus-master.zip (optional)

1.6.1.2 Source code, additional documentation, and sample data

If you are a new METplus user and would like to experiment with the use cases, you will want to follow these instructions to retrieve the source code, additional documentation and sample data that accompanies the use cases:

- On your local host (or wherever you wish to install the METplus code) create a directory where you want the code to reside
- Open the browser of your choice and navigate to <https://github.com/NCAR/METplus>. You will see something like the following:



[Pull requests](#)
[Issues](#)
[Marketplace](#)
[Explore](#)

[NCAR / METplus](#)

[Unwatch](#) 17
 [Star](#) 17
 [Fork](#) 5

[Code](#)
[Issues 55](#)
[Pull requests 0](#)
[Projects 0](#)
[Wiki](#)
[Insights](#)
[Settings](#)


Python scripting infrastructure for MET tools.
 [Edit](#)

[Manage topics](#)


1,037 commits
 14 branches
 13 releases
 7 contributors

Branch: master
 [New pull request](#)

[Create new file](#)
[Upload files](#)
[Find file](#)
[Clone or download](#)


 Update grid2grid_hwt_env.conf
 Latest commit a724bbc 2 hours ago

doc	Merge branch 'develop' of https://github.com/NCAR/METplus into develop	8 months ago
internal_tests	Updated to reflect changes in the conf file.	5 months ago
parm	Update grid2grid_hwt_env.conf	2 hours ago
sorc	Change name from Alpha-produtil to Beta-METplus.	11 months ago
ush	Accidentally committed GitHub Issue #92 changes to master branch. Rev...	2 months ago
.gitignore	Initial commit	2 years ago
.travis.yml	try ./ since we don't know how directory is structured in the travis ...	6 months ago
README.md	Updated top-level README .	a year ago

README.md
 

METplus Repository README File {#METplus_README}

Welcome to the documentation for the Model Evaluation Tools Plus (METplus).

This is the METplus repository Top level README.md

Basic DOCUMENTATION - getting started

ALL Documentation specific to this repository can be found in the doc/ directory.

The ORIGINAL setup text documentation in a markdown file is found here.

- doc/README_install.md — installation, configuration, running
- doc/README_terms_of_use.md — legal Terms Of Use

METplus is a Python scripting infrastructure around the MET verification tools (and eventually METViewer, a tool used for plotting MET output verification statistics).

This infrastructure utilizes the NCEP produtil package. A Platform-independent weather and ocean forecasting utility package. Developed at the National Oceanic and Atmospheric Administration (NOAA).

Website Documentation

Users can generate an entire METplus documentation website, if they have Doxygen version 1.8.9.1 or later installed.

```
cd METplus/sorc
make doc
In your browser, open the page METplus/doc/html/index.html
```

Terms of Use

@ref METplus_TermsOfUse


Install/Configure/Run Guide

@ref METplus_install_guide


Produtil Guide

@ref METplus_produtil

- Click on the 'releases' link, highlighted by a red circle in the diagram below:



- You will be redirected to another screen. The latest available release appears at the top of the screen:



- Click on the 'Source code' link (either the *zip* or *tar.gz*) and when prompted, save it to the directory you created.

- Uncompress the source code (on Linux/Unix: *gunzip* for zip file or *tar xvfz* for the tar.gz file)
- Create a directory for the sample data directory
- Click on the *sample_data.tar.gz* link and when prompted, save the file to the directory you created above

1.6.2 Get the source code via Command line

- On your local host (or wherever you wish to install the METplus code) create a directory where you want the code to reside
- cd to the directory you just created.
- On the command line, enter the following:
 - *git clone https://github.com/NCAR/METplus*
 - The source code should appear under the METplus directory
- To update your copy, cd to your METplus install directory: */path/to/METplus* and enter *git pull* at the command line

1.7 Set up your environment

Environment variables need to be set to allow the METplus application to be run from any directory and for locating the necessary Python modules. There is an option to set the `JLOGFILE` environment variable, which indicates where JLOGS will be saved. JLOGS provide information pertinent to the configuration-file framework. If this environment is unset, then output from the configuration framework will be directed to stdout (your display).

Add the following information to your `.cshrc` (C shell) or `.bashrc` (Bash shell):

.cshrc:

- Open your `.cshrc` file and do the following:
- To your `PATH`, add: *full-path-to-METplus/ush*
- To your `PYTHONPATH`, add: *full-path-to-METplus/ush:full-path-to-METplus/parm*
- Optional: add `JLOGFILE` variable and set to *full-path-to-save-jlog-files*
- Close your `.cshrc` file and run `source ~/.cshrc`

- *e.g.*

```
set path = (other_path_entries ~/METplus/ush
setenv PYTHONPATH ~/METplus/ush:~/METplus/parm:$PYTHONPATH
# optional
setenv JLOGFILE ~/jlog_out
```

.bashrc:

- Open your .bashrc file and do the following:
- To your PATH, add : *full-path-to-METplus*/ush
- To your PYTHONPATH, add *full-path-to-METplus*/parm
- Optional: add a JLOGFILE environment variable and set it to the directory where you want the logs to reside
- Close your .bashrc file and run `source ~/.bashrc`

- *e.g.*

```
export PATH=~/METplus/ush:$PATH
export PYTHONPATH="~/METplus/ush:~/METplus/parm:$PYTHONPATH"
#optional
export JLOGFILE=~/
```

1.8 Set up METplus Configuration files

There are four METplus configuration files that must be defined prior to running METplus. These configuration files reside in the `METplus_INSTALL_DIRECTORY/METplus/parm/metplus_config`

The following configuration files are automatically loaded during a METplus run and do not need to be invoked on the command line.

- `metplus_data.conf`
 - data-relevant settings:
 - * filename templates
 - * regular expressions for input or output filenames
 - * directories where input data are located
- `metplus_logging.conf`
 - set logging levels for METplus and MET output
 - turn on/off logging to stdout (screen) or log files

- `metplus_runtime.conf`
 - runtime-related settings:
 - * location of METplus master `metplus.conf` file (the 'master' conf file that is a collection of all the final METplus configuration files)
- `metplus_system.conf`
 - system-related settings:
 - * location of METplus source code
 - * location of MET source and build
 - * location of other non-MET executables/binaries
 - * location of METplus parm directory

They must be fully defined by replacing all variables with */path/to's* with valid path names, or have those variables defined in a down-stream config file. If configuring METplus in a common location for multiple users, it is recommended that these four configuration files are fully defined. Individual users have the option to make customizations by over-riding any of these values in their own configuration files.

1.9 Running METplus

Running METplus involves invoking the Python script `master_metplus.py` from any directory followed by a list of configuration files (file path relative to the `path_to_METplus_install_dir/METplus/parm` directory).

Example: Using a default configuration

```
>master_metplus.py
```

Does nothing, a usage message appears, indicating that other config files are required to perform useful tasks.

Example: Using a use-case configuration

```
>master_metplus.py -c use_cases/feature_relative/feature_relative.conf \
```

Runs METplus using the defaults set in the three config files found in `parm/metplus_config`. Any variables defined in these three config files can be over-ridden in the `parm/use_cases/feature_relative/feature_relative.conf` file. METplus will run using the values specified in the `feature_relative.conf` file.

Example: Using example configuration to perform specific evaluation (e.g. Model 1 vs. Obs1, Model 1 vs Obs 2, Model 2 vs. Obs 1, etc.)

```
>master_metplus.py -c use_cases/feature_relative/feature_relative.conf \
-c use_cases/feature_relative/example/series_by_lead_all_fhrs.conf
```

This runs METplus using the defaults set in the three config files found in `parm/metplus_config`, where variables can be over-ridden by `parm/use_cases/feature_relative/feature_relative.conf` or in `parm/use_cases/feature_relative/example/series_by_lead_all_fhrs.conf`. The order in which conf files are called is important. Variables that are defined in intermediate conf files will be over-ridden by the same variables set in the conf file following it, or the last conf file.