

## ✓ Reshaping Data

### ✓ About the data

In this notebook, we will use daily temperature data from the National Centers for Environmental Information (NCEI) API. We will use the Global Historical Climatology Network - Daily (GHCND) data set; see the documentation [here](#).

This data was collected for New York City for October 2018, using the Boonton 1 station (GHCNDUSC00280907). It contains:



- the daily minimum temperature ( TMIN )
- the daily maximum temperature ( TMAX )
- the daily temperature at time of observation ( TOBS )

*Note: The NCEI is part of the National Oceanic and Atmospheric Administration (NOAA) and, as you can see from the URL for the API, this resource was created when the NCEI was called the NCDC. Should the URL for this resource change in the future, you can search for the NCEI weather API to find the updated one.*

### ✓ Setup

We need to import pandas and read in the long-format data to get started:

```
1 import pandas as pd
2 long_df = pd.read_csv(
3     'data/long_data.csv',
4     usecols=['date', 'datatype', 'value']
5 ).rename(
6     columns={
7         'value' : 'temp_C'
8     }
9 ).assign(
10     date=lambda x: pd.to_datetime(x.date),
11     temp_F=lambda x: (x.temp_C * 9/5) + 32
12 )
13 long_df.head()
14
```

	datatype	date	temp_C	temp_F	
0	TMAX	2018-10-01	21.1	69.98	
1	TMIN	2018-10-01	8.9	48.02	
2	TOBS	2018-10-01	13.9	57.02	
3	TMAX	2018-10-02	23.9	75.02	
4	TMIN	2018-10-02	13.9	57.02	

Next steps:  [View recommended plots](#)

### ✓ Transposing

Transposing swaps the rows and the columns. We use the T attribute to do so:

```
1 long_df.head().T
```

	0	1	2	3	4
<b>datatype</b>	TMAX	TMIN	TOBS	TMAX	TMIN
<b>date</b>	2018-10-01 00:00:00	2018-10-01 00:00:00	2018-10-01 00:00:00	2018-10-02 00:00:00	2018-10-02 00:00:00
<b>temp_C</b>	21.1	8.9	13.9	23.9	13.9
<b>temp_F</b>	69.98	48.02	57.02	75.02	57.02

---

Next steps: [View recommended plots](#)

## ✓ Pivoting

Going from long to wide format.

`pivot()`

We can restructure our data by picking a column to go in the index ( `index` ), a column whose unique values will become column names ( `columns` ), and the values to place in those columns ( `values` ). The `pivot()` method can be used when we don't need to perform any aggregation in addition to our restructuring (when our index is unique); if this is not the case, we need the `pivot_table()` method which we will cover in future modules.

```
1 pivoted_df = long_df.pivot(
2 index='date', columns='datatype', values='temp_C'
3 )
4 pivoted_df.head()
```

<b>datatype</b>	TMAX	TMIN	TOBS
<b>date</b>			
<b>2018-10-01</b>	21.1	8.9	13.9
<b>2018-10-02</b>	23.9	13.9	17.2
<b>2018-10-03</b>	25.0	15.6	16.1
<b>2018-10-04</b>	22.8	11.7	11.7
<b>2018-10-05</b>	23.3	11.7	18.9

---

Next steps: [View recommended plots](#)

Note there is also the `pd.pivot()` function which yields equivalent results:

```
1 pd.pivot(data=long_df, index='date', columns='datatype', values='temp_C').head()
```

<b>datatype</b>	TMAX	TMIN	TOBS
<b>date</b>			
<b>2018-10-01</b>	21.1	8.9	13.9
<b>2018-10-02</b>	23.9	13.9	17.2
<b>2018-10-03</b>	25.0	15.6	16.1
<b>2018-10-04</b>	22.8	11.7	11.7
<b>2018-10-05</b>	23.3	11.7	18.9

Now that the data is pivoted, we have wide-format data that we can grab summary statistics with:

```
1 pivoted_df.describe()
```

datatype	TMAX	TMIN	TOBS
count	31.000000	31.000000	31.000000
mean	16.829032	7.561290	10.022581
std	5.714962	6.513252	6.596550
min	7.800000	-1.100000	-1.100000
25%	12.750000	2.500000	5.550000
50%	16.100000	6.700000	8.300000
75%	21.950000	13.600000	16.100000
max	26.700000	17.800000	21.700000



We can also provide multiple values to pivot on, which will result in a hierarchical index:

```
1 pivoted_df = long_df.pivot(
2   index='date', columns='datatype', values=['temp_C', 'temp_F']
3 )
4 pivoted_df.head()
```

datatype	temp_C			temp_F		
	TMAX	TMIN	TOBS	TMAX	TMIN	TOBS
date						
2018-10-01	21.1	8.9	13.9	69.98	48.02	57.02
2018-10-02	23.9	13.9	17.2	75.02	57.02	62.96
2018-10-03	25.0	15.6	16.1	77.00	60.08	60.98
2018-10-04	22.8	11.7	11.7	73.04	53.06	53.06
2018-10-05	23.3	11.7	18.9	73.94	53.06	66.02



Next steps: [View recommended plots](#)

With the hierarchical index, if we want to select TMIN in Fahrenheit, we will first need to select 'temp\_F' and then 'TMIN':

```
1 pivoted_df['temp_F']['TMIN'].head()
```

```
date
2018-10-01    48.02
2018-10-02    57.02
2018-10-03    60.08
2018-10-04    53.06
2018-10-05    53.06
Name: TMIN, dtype: float64
```

*unstack()*

We have been working with a single index throughout this chapter; however, we can create an index from any number of columns with `set_index()`. This gives us a MultiIndex where the outermost level corresponds to the first element in the list provided to `set_index()`:

```
1 multi_index_df = long_df.set_index(['date', 'datatype'])
2 multi_index_df.index
```



```
( '2018-10-17', 'TMIN' ),
( '2018-10-17', 'TOBS' ),
( '2018-10-18', 'TMAX' ),
( '2018-10-18', 'TMIN' ),
( '2018-10-18', 'TOBS' ),
( '2018-10-19', 'TMAX' ),
( '2018-10-19', 'TMIN' ),
( '2018-10-19', 'TOBS' ),
( '2018-10-20', 'TMAX' ),
( '2018-10-20', 'TMIN' ),
( '2018-10-20', 'TOBS' ),
( '2018-10-21', 'TMAX' ),
( '2018-10-21', 'TMIN' ),
( '2018-10-21', 'TOBS' ),
( '2018-10-22', 'TMAX' ),
( '2018-10-22', 'TMIN' ),
( '2018-10-22', 'TOBS' ),
( '2018-10-23', 'TMAX' ),
( '2018-10-23', 'TMIN' ),
( '2018-10-23', 'TOBS' ),
( '2018-10-24', 'TMAX' ),
( '2018-10-24', 'TMIN' ),
( '2018-10-24', 'TOBS' ),
( '2018-10-25', 'TMAX' ),
( '2018-10-25', 'TMIN' ),
( '2018-10-25', 'TOBS' ),
( '2018-10-26', 'TMAX' ),
( '2018-10-26', 'TMIN' ),
( '2018-10-26', 'TOBS' ),
( '2018-10-27', 'TMAX' ),
( '2018-10-27', 'TMIN' ),
( '2018-10-27', 'TOBS' ),
( '2018-10-28', 'TMAX' ),
( '2018-10-28', 'TMIN' ),
( '2018-10-28', 'TOBS' ),
( '2018-10-29', 'TMAX' ),
( '2018-10-29', 'TMIN' ),
( '2018-10-29', 'TOBS' ),
( '2018-10-30', 'TMAX' ),
( '2018-10-30', 'TMIN' ),
( '2018-10-30', 'TOBS' ),
( '2018-10-31', 'TMAX' ),
( '2018-10-31', 'TMIN' ),
( '2018-10-31', 'TOBS' )],
names=['date', 'datatype'])
```

Notice there are now 2 index sections of the dataframe:

```
1 multi_index_df.head()
```

		temp_C	temp_F
date	datatype		
2018-10-01	TMAX	21.1	69.98
	TMIN	8.9	48.02
	TOBS	13.9	57.02
2018-10-02	TMAX	23.9	75.02
	TMIN	13.9	57.02

Next steps: [View recommended plots](#)

With the MultiIndex, we can no longer use `pivot()`. We must now use `unstack()`, which by default moves the innermost index onto the columns:

```
1 unstacked_df = multi_index_df.unstack()
2 unstacked_df.head()
```

	temp_C			temp_F			
datatype	TMAX	TMIN	TOBS	TMAX	TMIN	TOBS	
date							
2018-10-01	21.1	8.9	13.9	69.98	48.02	57.02	
2018-10-02	23.9	13.9	17.2	75.02	57.02	62.96	
2018-10-03	25.0	15.6	16.1	77.00	60.08	60.98	
2018-10-04	22.8	11.7	11.7	73.04	53.06	53.06	
2018-10-05	23.3	11.7	18.9	73.94	53.06	66.02	

Next steps: [View recommended plots](#)

The `unstack()` method also provides the `fill_value` parameter, which let's us fill-in any NaN values that might arise from this restructuring of the data. Consider the case that we have data for the average temperature on October 1, 2018, but no other date:

1

```
1 extra_data = long_df.append(
2   [{'datatype': 'TAVG', 'date': '2018-10-01', 'temp_C': 10, 'temp_F': 50}]
3 ).set_index(['date', 'datatype']).sort_index()
4
5 extra_data.head(8)
```

```
<ipython-input-18-2fd676795dfa>:1: FutureWarning: The frame.append method is deprecated
extra_data = long_df.append(
<ipython-input-18-2fd676795dfa>:3: FutureWarning: Inferring datetime64[ns] from data cor
).set_index(['date', 'datatype']).sort_index()
```

		temp_C	temp_F	
date	datatype			
2018-10-01	TAVG	10.0	50.00	
	TMAX	21.1	69.98	
	TMIN	8.9	48.02	
	TOBS	13.9	57.02	
2018-10-02	TMAX	23.9	75.02	
	TMIN	13.9	57.02	
	TOBS	17.2	62.96	
2018-10-03	TMAX	25.0	77.00	

Next steps: [View recommended plots](#)

If we use `unstack()` in this case, we will have NaN for the TAVG columns every day but October 1, 2018:

```
1 extra_data.unstack().head()
```

	temp_C				temp_F				
datatype	TAVG	TMAX	TMIN	TOBS	TAVG	TMAX	TMIN	TOBS	
date									
2018-10-01	10.0	21.1	8.9	13.9	50.0	69.98	48.02	57.02	
2018-10-02	NaN	23.9	13.9	17.2	NaN	75.02	57.02	62.96	
2018-10-03	NaN	25.0	15.6	16.1	NaN	77.00	60.08	60.98	
2018-10-04	NaN	22.8	11.7	11.7	NaN	73.04	53.06	53.06	
2018-10-05	NaN	23.3	11.7	18.9	NaN	73.94	53.06	66.02	

o address this, we can pass in an appropriate `fill_value` . However, we are restricted to passing in a value for this, not a strategy (like we saw with `fillna()` ), so while -40 is definitely not be the best value, we can use it to illustrate how this works, since this is the temperature at which Fahrenheit and Celsius are equal:

```
1 extra_data.unstack(fill_value=-40).head()
2
```

datatype	temp_C				temp_F			
	TAVG	TMAX	TMIN	TOBS	TAVG	TMAX	TMIN	TOBS
date								
2018-10-01	10.0	21.1	8.9	13.9	50.0	69.98	48.02	57.02
2018-10-02	-40.0	23.9	13.9	17.2	-40.0	75.02	57.02	62.96
2018-10-03	-40.0	25.0	15.6	16.1	-40.0	77.00	60.08	60.98
2018-10-04	-40.0	22.8	11.7	11.7	-40.0	73.04	53.06	53.06
2018-10-05	-40.0	23.3	11.7	18.9	-40.0	73.94	53.06	66.02

## ▼ Melting

Going from wide to long format.

## ▼ Setup

```
1 wide_df = pd.read_csv('/content/data/wide_data.csv')
2 wide_df.head()
```

	date	TMAX	TMIN	TOBS
0	2018-10-01	21.1	8.9	13.9
1	2018-10-02	23.9	13.9	17.2
2	2018-10-03	25.0	15.6	16.1
3	2018-10-04	22.8	11.7	11.7
4	2018-10-05	23.3	11.7	18.9

Next steps: [View recommended plots](#)

`melt()`

In order to go from wide format to long format, we use the `melt()` method. We have to specify:

- which column contains the unique identifier for each row ( `date` , here) to `id_vars`
- the column(s) that contain the values ( `TMAX` , `TMIN` , and `TOBS` , here) to `value_vars`

Optionally, we can also provide:-

- `value_name` : what to call the column that will contain all the values once melted
- `var_name` : what to call the column that will contain the names of the variables being measured

```
1 melted_df = wide_df.melt(
2   id_vars='date',
3   value_vars=['TMAX', 'TMIN', 'TOBS'],
4   value_name='temp_C',
5   var_name='measurement'
6 )
7 melted_df.head()
```

	date	measurement	temp_C
0	2018-10-01	TMAX	21.1
1	2018-10-02	TMAX	23.9
2	2018-10-03	TMAX	25.0
3	2018-10-04	TMAX	22.8
4	2018-10-05	TMAX	23.3

Next steps: [View recommended plots](#)

Just as we also had `pd.pivot()` there is a `pd.melt()` :

```
1 pd.melt(
2     wide_df,
3     id_vars='date',
4     value_vars=['TMAX', 'TMIN', 'TOBS'],
5     value_name='temp_C',
6     var_name='measurement'
7 ).head()
8
```

	date	measurement	temp_C
0	2018-10-01	TMAX	21.1
1	2018-10-02	TMAX	23.9
2	2018-10-03	TMAX	25.0
3	2018-10-04	TMAX	22.8
4	2018-10-05	TMAX	23.3

`stack()`

Another option is `stack()` which will pivot the columns of the dataframe into the innermost level of a MultiIndex . To illustrate this, let's set our index to be the date column:

```
1 wide_df.set_index('date', inplace=True)
2 wide_df.head()
```

	TMAX	TMIN	TOBS
date			
2018-10-01	21.1	8.9	13.9
2018-10-02	23.9	13.9	17.2
2018-10-03	25.0	15.6	16.1
2018-10-04	22.8	11.7	11.7
2018-10-05	23.3	11.7	18.9

Next steps: [View recommended plots](#)



By running `stack()` now, we will create a second level in our index which will contain the column names of our dataframe ( TMAX , TMIN , TOBS ). This will leave us with a Series containing the values:

```
1 stacked_series = wide_df.stack()
2 stacked_series.head()
```

```
date
2018-10-01  TMAX    21.1
             TMIN     8.9
             TOBS    13.9
2018-10-02  TMAX    23.9
             TMIN    13.9
             TMIN    13.9
dtype: float64
```

We can use the `to_frame()` method on our Series object to turn it into a DataFrame . Since the series doesn't have a name at the moment, we will pass in the name as an argument:

```
1 stacked_df = stacked_series.to_frame('values')
2 stacked_df.head()
```

		values	
date			
2018-10-01	TMAX	21.1	
	TMIN	8.9	
	TOBS	13.9	
2018-10-02	TMAX	23.9	
	TMIN	13.9	

Next steps:

 [View recommended plots](#)

Once again, we have a MultiIndex:

```
1 stacked_df.index
('2018-10-13', 'TMAX'),
('2018-10-13', 'TMIN'),
('2018-10-13', 'TOBS'),
('2018-10-14', 'TMAX'),
('2018-10-14', 'TMIN'),
('2018-10-14', 'TOBS'),
('2018-10-15', 'TMAX'),
('2018-10-15', 'TMIN'),
('2018-10-15', 'TOBS'),
('2018-10-16', 'TMAX'),
('2018-10-16', 'TMIN'),
('2018-10-16', 'TOBS'),
('2018-10-17', 'TMAX'),
('2018-10-17', 'TMIN'),
('2018-10-17', 'TOBS'),
('2018-10-18', 'TMAX'),
```



```
( '2018-10-30', 'TMIN' ),  
( '2018-10-30', 'TOBS' ),  
( '2018-10-31', 'TMAX' ),  
( '2018-10-31', 'TMIN' ),  
( '2018-10-31', 'TOBS' )],  
names=['date', None])
```

Unfortunately, we don't have a name for the datatype level:

```
1 stacked_df.index.names  
  
FrozenList(['date', None])
```

We can use `rename()` to address this though:

+ Code

+ Text

```
1 stacked_df.index.rename(['date', 'datatype'], inplace=True)  
2 stacked_df.index.names  
  
FrozenList(['date', 'datatype'])
```