RDTII Rocky

Setup note: the installs, in order, for a computer that has nothing on it

Team: Rocky has a home run

6 October 2026

Before you start

This note installs what the tool needs, in order, and stops when the tool opens. You do not need to be a programmer: every command below is copied and pasted whole into one window. Allow 30 minutes and 2 GB of disk, plus 20 minutes and 9 GB if you want the free local AI engine (Section 5), which is optional.

The one window you need.

- **Windows**: press the Start button, type `PowerShell`, open *Windows PowerShell*.
- **Mac**: press `Cmd`+`Space`, type `Terminal`, press Enter.

Where a program may already be on the computer, a *check* line comes first. If the window answers with a version number, skip the install and go on. If it says *not found* or *not recognized*, run the install lines under it. Whether everything works is not checked here: once the tool is open, the **Check** button on each stage page and the health dots along the top say what is missing.

1 Get the project onto the computer

Download the project as a ZIP from the repository page on GitHub (green **Code** button → **Download ZIP**) and unzip it to your Desktop. GitHub names the unzipped folder after the branch or tag it came from, `rdtii-rocky-next-main` or `rdtii-rocky-next-final-submission`: rename it to `rdtii-rocky-next` (right-click the folder, *Rename*). It holds folders named `interface`, `stages` and `submission`.

Point the window at that folder; every later command assumes you are inside it.

Windows:

```
cd $HOME\Desktop\rdtii-rocky-next
```

Mac:

```
cd ~/Desktop/rdtii-rocky-next
```

If `git` is already installed, `git clone https://github.com/JohnChen-kmg/rdtii-rocky-next` followed by `cd rdtii-rocky-next` and `git checkout final-submission` does the same, without the rename.

2 Python

The tool is written in Python, 3.12 or newer. Check:

Windows:

```
python --version
```

Mac:

```
python3 --version
```

If *not found*, if the Microsoft Store opens, or if the number is below 3.12, install: open https://www.python.org/downloads/ and download the latest version.

- **Windows**: in the installer, tick **"Add python.exe to PATH"** on the first screen before pressing Install; that tick is what makes the command above work.
- **Mac**: open the downloaded `.pkg` and accept every default.

Close the window, open a new one, go back to the project folder (Section 1) and check again.

3 The packages of the three stages

Four commands, run once, inside the project folder. The first gives the project its own package area (a folder called `.venv`, so nothing is installed into the computer at large). The second installs the packages of all three stages from one list; allow 5 minutes, it ends with `Successfully installed`. The third installs the extraction stage, which is part of the project itself. The fourth downloads the browser engine (about 150 MB) that the scraping stage uses on portals built with JavaScript.

Windows:

```
python -m venv .venv
.venv\Scripts\pip install -r requirements-demo.txt
.venv\Scripts\pip install -e stages/p2-extract
.venv\Scripts\python -m playwright install chromium
```

Mac:

```
python3 -m venv .venv
.venv/bin/pip install -r requirements-demo.txt
.venv/bin/pip install -e stages/p2-extract
.venv/bin/python -m playwright install chromium
```

4 Tesseract — only for scanned documents

Lao PDR's laws are 96% scans, so Stage 2 reads them with OCR. Check:

```
tesseract --version
```

If *not found*, install:

Windows:

```
winget install UB-Mannheim.TesseractOCR
```

Mac (needs Homebrew; if `brew` is not found, install it from `https://brew.sh` first):

```
brew install tesseract
```

Close the window and open a new one, then check again. The language packs (English, Lao, Chinese, Portuguese) are already inside the project — nothing to download.

5 The free local engine (optional)

Mapping uses an AI engine. **Engine A** is hosted (Claude) and needs a key you pay for; you type it into the tool, on the Mapping page under **Engine API keys**, and it is held in memory only. **Engine B** runs on your own computer and is free. Everything else in the tool works without either: an engine is needed only to start a *new* mapping run. For Engine B, check:

```
ollama --version
```

If *not found*, install Ollama from https://ollama.com (a normal installer for Windows and Mac), then download the model the tool declares, about 9 GB:

```
ollama pull qwen2.5:14b
```

6 Start the tool

There is nothing to configure: no file to edit, no `.env`, no environment variable.

- **Windows**: double-click `Start-RDTII-Rocky.cmd` in the project folder.
- **Mac**: double-click `Start-RDTII-Rocky.command`.

The pages open in a window of their own, using the Edge or Chrome already on your machine; closing that window stops the tool.

A **Mac** may need one extra step, once: if the double-click opens the file as text, or says it cannot be executed, the unzip has dropped its permission to run. Give it back from the window, inside the project folder, then double-click again:

```
chmod +x Start-RDTII-Rocky.command
```

If the double-click does nothing, start it from the window instead and open http://127.0.0.1:8765/ in your browser; the message in the window says what is wrong.

Windows:

```
.venv\Scripts\python interface/app.py
```

Mac:

```
.venv/bin/python interface/app.py
```

From here the tool checks itself. The health dots along the top of the Overview show **Stages**, **Tesseract**, **Chromium**, **Ollama** and **Key** (grey for Ollama if you skipped Section 5, and for Key until you type one, which is correct), and the **Check** button on each stage page names anything still missing. Then carry on with the README's *Verify* section.

Questions: John (Jiaxiang) Chen, jiaxiangchen.kmg@gmail.com. The tool is Apache 2.0 licensed; this note covers the release tagged `final-submission`. The longer `SETUP_GUIDE.pdf` beside it explains what each package is for, what a working setup looks like and what to do when something is not found.