User Commands from Chat Transcripts

Source: chat_transcripts/*.jsonl. Only messages typed by the user are included. Automatic follow-up prompts injected by the tool are omitted.

0f7df47d-6db6-43da-9a87-b9d9fbf3e66c.jsonl

2 commands

1. Monday, Oct 19, 2026, 3:21 PM (UTC-5)

   Create a src/data_explorer_agents/{ui,backend,ai,database}/ and for each, create a FastAPI app in a app.py.

   Make each run in a separate port.

   Have a dummy request flow, follow the following mermaid diagram.

   Prove it works once done.

2. Monday, Oct 19, 2026, 3:30 PM (UTC-5)

   put this verification logic in docs/runbooks/HOW_TO_VERIFY_SERVERS.md and then put the app logic in docs/runbooks/HOW_THE_APP_SERVERS_WORK.md, this should have a table with the app name and the port number, and then reference the run book for how to verify the server.

   Once done, git add commit and push.

7b1c8c1a-43ba-4077-b9ee-97546bf67bea.jsonl

1 commands

1. Monday, Oct 26, 2026, 3:32 PM (UTC-5)

   Review all my chat sessions for this repo in Cursor. Get each of the transcripts. Put in chat_transcripts/. Each should be a separate .jsonl file.

b6181304-3875-4ec3-9721-073c2ef01cc8.jsonl

7 commands

1. Monday, Oct 26, 2026, 3:13 PM (UTC-5)

   in @src/ :

   - For the UI app.py, we write HTML and JS code as raw text. That's dumb. Write the index.html and JS code to run this.
   - Add OpenAPI docs for the API endpoints for each.

2. Monday, Oct 26, 2026, 3:18 PM (UTC-5)

   Add a single config.yaml in src/data_explorer_agents with ai, backend, database, and ui sections, and for each, define the host, port, and database URL. Then add a

src/data_explorer_agents/utils/config.py that reads the config YAML, and have callers import that.

3. Monday, Oct 26, 2026, 3:25 PM (UTC-5)
   How is the _path, which is first passed in @src/data_explorer_agents/ui/app.py , used? Define the call trace, as this seems overly complicated.

4. Monday, Oct 26, 2026, 3:25 PM (UTC-5)
   git add commit (but don't push) the latest changes. Then continue:

   How is the _path, which is first passed in @src/data_explorer_agents/ui/app.py , used? Define the call trace, as this seems overly complicated.

5. Monday, Oct 26, 2026, 3:28 PM (UTC-5)
   This is bad design. Propose how to resolve this for clean code.

6. Monday, Oct 26, 2026, 3:31 PM (UTC-5)
   LGTM. Implement this.

7. Monday, Oct 26, 2026, 3:31 PM (UTC-5)
   LGTM. Implement this. Then summarize for me. Don't commit yet, I'll review.

da526b2d-7205-41bc-ba5b-7cf42980f57d.jsonl

6 commands

1. Monday, Oct 19, 2026, 3:17 PM (UTC-5)
   install the latest langchain and then in src/data_explorer_agents/ create an agents.py file.

2. Monday, Oct 19, 2026, 3:43 PM (UTC-5)
   In the @src/data_explorer_agents/agents.py , implement simple stub nodes and then a graph in LangGraph for the logic defined in @agents.py (43-52) . Then import that into the ai app server. Then run it (see @docs/runbooks/HOW_TO_VERIFY_SERVERS.md).

3. Monday, Oct 19, 2026, 3:53 PM (UTC-5)
   let's create a simple mcp server in the db API, and then let's have the AI agent call that (via a tool call). Let's make the return a simple pass-through.

4. Monday, Oct 19, 2026, 4:02 PM (UTC-5)
   let's put all prompts in a prompts.py.

5. Monday, Oct 19, 2026, 4:04 PM (UTC-5)
   git add commit and push all the latest stuff. Shut down the servers that are running.

6. Monday, Oct 19, 2026, 4:06 PM (UTC-5)
   Now in docs/runbooks/ create a HOW_APP_WORKS.md, with mermaid diagrams for how the high-level flow works and then how the AI agent graph works.