

Package ‘chartist’

February 22, 2017

Title chartist.js in R

Version 0.0.0.9000

Description Implements chartist.js in R.

Depends R (>= 3.3.2)

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Imports htmlwidgets,
magrittr,
htmltools

RoxygenNote 5.0.1

R topics documented:

add_ist	2
anim_ist	3
baropt_ist	4
chartist-shiny	5
chart_ist	5
danim_ist	6
ganim_ist	6
gauge_ist	7
hover_ist	7
label_ist	8
lanim_ist	8
lineopt_ist	9
loop_ist	10
name_ist	11
opt_ist	11
peak_ist	12
pieopt_ist	13
ratio_ist	14
resp_ist	15
sanim_ist	16
scatter_ist	16
thresh_ist	17
xaxis_ist	17

xtitle_ist 18

yaxis_ist 19

ytitle_ist 20

Index 21

add_ist	<i>Add Series</i>
---------	-------------------

Description

Add series(s) to chart

Usage

add_ist(p, values, name, ...)

Arguments

- p a chartist object.
- values values to plot on y axis.
- name name the serie, see details (optional).
- ... Additional parameter.

Details

Naming the serie (name) is useful if you want to apply different options ([opt_ist](#)) for each serie later on. If no name is specified then the assigns one; type + i where i is the serie index and starts from 1. Names can be retrieved using [name_ist](#). See examples.

See Also

[name_ist](#), [opt_ist](#)

Examples

```
# basic example
mtcars[1:10,] %>%
  chart_ist(x = mpg) %>%
  add_ist(dis) %>%
  add_ist(hp)

# option applies to both "dis" and "hp"
mtcars[1:10,] %>%
  chart_ist(x = mpg) %>%
  add_ist(dis) %>%
  add_ist(hp) %>%
  opt_ist(showArea = TRUE)

# use names to apply different option to each serie
mtcars[1:10,] %>%
  chart_ist(x = mpg) %>%
  add_ist(dis, name = "dis") %>%
```

```

add_ist(hp, name = "hp") %>%
opt_ist(name = "hp", showArea = TRUE, showPoint = FALSE) %>%
opt_ist(name = "disp", lineSmoothing = "step")

# if you haven't assigned names you can retrieve generated ones with name_ist
# See details for generated names logic
mtcars[1:10,] %>%
  chart_ist(x = mpg) %>%
  add_ist(disp, name = "disp") %>%
  add_ist(hp, name = "hp") %>%
  name_ist()

```

anim_ist

*Animate chart***Description**

Animate chart.

Usage

```
anim_ist(p, type, anim, begin, dur, from, to, easing, ...)
```

Arguments

p	a chartist object.
type	chart element type to animate (i.e.: line, or grid).
anim	animation (i.e.: opacity).
begin	begin index.
dur	duration of animation in ms.
from	start of animation.
to	end of animation.
easing	apply easing.
...	any other param to pass to anim.

Examples

```

mtcars %>%
  chart_ist(wt) %>%
  add_ist(disp) %>%
  add_ist(hp) %>%
  anim_ist(type = c("line", "point"),
    anim = "opacity",
    begin = 0,
    from = 0,
    to = 1,
    dur = 2000)

```

baropt_ist	<i>Bar options</i>
------------	--------------------

Description

Pass options to bar type.

Usage

```
baropt_ist(p, fullWidth = TRUE, centerBars = FALSE, stackBars = FALSE,
  distributeSeries = FALSE, seriesBarDistance, width, height, low, high,
  chartPadding, ...)
```

Arguments

p	a chartist object.
fullWidth	When set to true, the last grid line on the x-axis is not drawn and the chart elements will expand to the full available width of the chart. For the last label to be drawn correctly you might need to add chart padding or offset the last label with a draw event handler.
centerBars	set to TRUE to draw bars on the grid lines, FALSE to draw on grid lines.
stackBars	whether to stack bars, default to FALSE.
distributeSeries	distributed serie along x axis only works for 1 serie, defaults to FALSE.
seriesBarDistance	distance in pixels between bar groups.
width	set fixed width in pixels or percent (i.e.: 300px, 70%).
height	set fixed height in pixels or percent (i.e.: 300px, 70%).
low	lower bound of value.
high	higher bound of value.
chartPadding	padding around chart div.
...	additional options.

Examples

```
mtcars$models <- rownames(mtcars)

mtcars[1:10,] %>%
  chart_ist(x = models, type = "bar") %>%
  add_ist(cyl) %>%
  add_ist(carb) %>%
  add_ist(gear) %>%
  baropt_ist(stackBars = TRUE)

mtcars[1:10,] %>%
  chart_ist(x = models, type = "bar") %>%
  add_ist(cyl) %>%
  add_ist(carb) %>%
  add_ist(gear) %>%
  baropt_ist(seriesBarDistance = 10, centerBars = TRUE)
```

chartist-shiny

*Shiny bindings for chartist***Description**

Output and render functions for using chartist within Shiny applications and interactive Rmd documents.

Usage

```
chartistOutput(outputId, width = "100%", height = "400px")
```

```
renderChartist(expr, env = parent.frame(), quoted = FALSE)
```

Arguments

outputId	output variable to read from
width, height	Must be a valid CSS unit (like '100%', '400px', 'auto') or a number, which will be coerced to a string and have 'px' appended.
expr	An expression that generates a chartist
env	The environment in which to evaluate expr.
quoted	Is expr a quoted expression (with quote())? This is useful if you want to save an expression in a variable.

chart_ist

*Initiate a chartist visualisation***Description**

Initiate a chartist chart.

Usage

```
chart_ist(data, x, type = "line", width = NULL, height = NULL,
  elementId = NULL)
```

Arguments

data	data.frame containing data to plot.
x	Must be passed for line and bar (type).
type	type of charts, defaults to line, may also be bar or pie.
width, height	Must be a valid CSS unit (like '100%', '400px', 'auto') or a number, which will be coerced to a string and have 'px' appended, defaults to NULL.
elementId	Use specific element id.

Examples

```
mtcars %>%
  chart_ist(cyl) %>%
  add_ist(hp)
```

danim_ist	<i>Animate donut chart</i>
-----------	----------------------------

Description

Out of the box animation for donut chart.

Usage

```
danim_ist(p)
```

Arguments

p a chartist object.

Examples

```
mtcars[1:5,] %>%  
  chart_ist(x = hp, type = "pie") %>%  
  add_ist(dis) %>%  
  pieopt_ist(donut = TRUE, showLabel = TRUE) %>%  
  danim_ist()
```

ganim_ist	<i>Animate grid</i>
-----------	---------------------

Description

Out of the box animation for the chart grid.

Usage

```
ganim_ist(p)
```

Arguments

p a chartist object.

Examples

```
mtcars %>%  
  chart_ist(wt) %>%  
  add_ist(dis) %>%  
  add_ist(hp) %>%  
  ganim_ist()
```

gauge_ist	<i>Make a gauge from a pie</i>
-----------	--------------------------------

Description

Helper function to easily make a gauge chart from a pie

Usage

```
gauge_ist(p, ...)
```

Arguments

p	a chartist object
...	additional parameters to pass to opt_ist

Examples

```
mtcars[1:5,] %>%  
  chart_ist(type = "pie") %>%  
  add_ist(dis) %>%  
  gauge_ist()
```

hover_ist	<i>Add hover tooltip</i>
-----------	--------------------------

Description

Add hover tooltip

Usage

```
hover_ist(p, prefix = "", suffix = "")
```

Arguments

p	a chartist object.
prefix	add prefix to label.
suffix	add suffix to label.

Details

The tooltip displays series name which is passed in [add_ist](#)

Examples

```
mtcars %>%
  chart_ist(displ) %>%
  add_ist(values = hp, name = "Your Tooltip") %>%
  hover_ist(prefix = "US$")

mtcars %>%
  chart_ist(displ) %>%
  add_ist(values = hp, name = "Your <span style='color:blue;'>Tooltip</span>") %>%
  hover_ist()
```

label_ist

*Add point label***Description**

Add data point labels to line type chart.

Usage

```
label_ist(p, position = "middle")
```

Arguments

p a chartist object.

position position of label, defaults to middle.

Examples

```
mtcars %>%
  chart_ist(displ) %>%
  add_ist(hp) %>%
  label_ist()
```

lanim_ist

*Line and area chart animation***Description**

Out of the box animation for line and/or area chart.

Usage

```
lanim_ist(p, type = c("line", "area"))
```

Arguments

p a chartist object.

type chart element type to animate (i.e.: line, or grid).

Examples

```
mtcars %>%
  chart_ist(wt) %>%
  add_ist(displ, name = "displ") %>%
  add_ist(hp, name = "hp") %>%
  opt_ist(showPoint = FALSE) %>%
  lineopt_ist(name = "hp", showArea = TRUE) %>%
  lanim_ist()
```

lineopt_ist

Line options

Description

Pass options to line type.

Usage

```
lineopt_ist(p, name, fillHoles = FALSE, showPoint = TRUE,
  showArea = FALSE, showLine = TRUE, areaBase = 0,
  lineSmoothing = "simple", fullWidth = TRUE, distributeSeries = FALSE,
  width, height, low, high, chartPadding, ...)
```

Arguments

p	a chartist object.
name	name the serie, see details (optional).
fillHoles	whether to fill missing data, defaults to FALSE.
showPoint	whether to show points, defaults to TRUE.
showArea	turn line chart into area chart, defaults to FALSE.
showLine	set FALSE to hide line.
areaBase	base for the chart, defaults to 0.
lineSmoothing	defaults to simple, can take an integer, step, none or an htmlwidgets javascript function (class JS_EVAL).
fullWidth	When set to true, the last grid line on the x-axis is not drawn and the chart elements will expand to the full available width of the chart. For the last label to be drawn correctly you might need to add chart padding or offset the last label with a draw event handler.
distributeSeries	distributed serie along x axis only works for 1 serie, defaults to FALSE.
width	set fixed width in pixels or percent (i.e.: 300px, 70%).
height	set fixed height in pixels or percent (i.e.: 300px, 70%).
low	lower bound of value.
high	higher bound of value.
chartPadding	padding around chart div.
...	additional options.

Examples

```
mtcars %>%
  chart_ist(x = mpg, type = "line") %>%
  add_ist(displ) %>%
  lineopt_ist(showArea = TRUE, showLine = FALSE, showPoint = FALSE)

mtcars %>%
  chart_ist(x = mpg, type = "line") %>%
  add_ist(displ) %>%
  lineopt_ist(lineSmoothing = "step", showLine = TRUE, showPoint = FALSE)

mtcars %>%
  chart_ist(x = mpg, type = "line") %>%
  add_ist(displ, name = "displ") %>%
  add_ist(hp, name = "hp") %>%
  lineopt_ist(name = "displ", lineSmoothing = "none") %>%
  lineopt_ist(name = "hp", showArea = TRUE, showPoint = FALSE)

mtcars %>%
  chart_ist(qsec) %>%
  add_ist(mpg) %>%
  lineopt_ist(lineSmoothing = htmlwidgets::JS("
    Chartist.Interpolation.cardinal({tension: 0.2})"))
```

loop_ist

Loop animation

Description

Loop animation

Usage

```
loop_ist(p, ms = 5000)
```

Arguments

p	a chartist object.
ms	Milliseconds for loop, defaults to 500.

Examples

```
mtcars %>%
  chart_ist(qsec) %>%
  add_ist(hp) %>%
  lanim_ist() %>%
  loop(6000)
```

name_ist	<i>Get assigned name</i>
----------	--------------------------

Description

Get the generated series name.

Usage

```
name_ist(p)
```

Arguments

p a chartist object

Examples

```
# default names
mtcars[1:20,] %>%
  chart_ist(x = qsec) %>%
  add_ist(dis) %>%
  add_ist(hp) %>%
  name_ist()

#assigned names
mtcars[1:20,] %>%
  chart_ist(x = qsec) %>%
  add_ist(dis, name = "SERIE1") %>%
  add_ist(hp, name = "hp") %>%
  name_ist()
```

opt_ist	<i>Configure options for chartist visualisation</i>
---------	---

Description

Pass any option to any chart here. Also see options specific to your chart type, [pieopt_ist](#), [baropt_ist](#) or [lineopt_ist](#)

Usage

```
opt_ist(p, name, width, height, low, high, chartPadding, ...)
```

Arguments

p	a chartist object.
name	name the serie, see details (optional).
width	set fixed width in pixels or percent (i.e.: 300px, 70%).
height	set fixed height in pixels or percent (i.e.: 300px, 70%).
low	lower bound of value.
high	higher bound of value.
chartPadding	padding around chart div.
...	additional options.

See Also

[baropt_ist](#), [pieopt_ist](#), [lineopt_ist](#)

Examples

```
mtcars$models <- row.names(mtcars)

mtcars[1:10,] %>%
  chart_ist(x = models) %>%
  add_ist(wt) %>%
  add_ist(drat) %>%
  opt_ist(chartPadding = 10, width = 700, height = 200)

mtcars[1:10,] %>%
  chart_ist(x = qsec) %>%
  add_ist(displ, name = "DISP") %>%
  add_ist(hp, name = "HP") %>%
  opt_ist(name = "DISP", lineSmoothing = "step") %>%
  opt_ist(name = "HP",
    showArea = TRUE,
    showLine = FALSE,
    showPoint = FALSE)
```

peak_ist

Turn bar chart into peak chart

Description

Turn bar chart into peak chart

Usage

```
peak_ist(p, size = 15)
```

Arguments

p	a chartist object.
size	point size.

Examples

```
mtcars %>%
  chart_ist(qsec, type = "bar") %>%
  add_ist(hp) %>%
  peak_ist()
```

pieopt_ist	<i>Pie and donut options</i>
------------	------------------------------

Description

Pass options to pie type.

Usage

```
pieopt_ist(p, percent = FALSE, donut = FALSE, showLabel = FALSE,
  startAngle, total, donutWidth, labelDirection, labelOffset, width, height,
  low, high, chartPadding, ...)
```

Arguments

p	a chartist object.
percent	convert to percent.
donut	set to TRUE for donut chart, defaults to FALSE.
showLabel	set to FALSE to hide labels.
startAngle	start angle of the pie chart in degrees.
total	By specifying a total value, the sum of the values in the series must be this total.
donutWidth	donut width.
labelDirection	label direction takes neutral, explode or implode.
labelOffset	numeric to offset labels.
width	set fixed width in pixels or percent (i.e.: 300px, 70%).
height	set fixed height in pixels or percent (i.e.: 300px, 70%).
low	lower bound of value.
high	higher bound of value.
chartPadding	padding around chart div.
...	additional options.

See Also

[gauge_ist](#)

Examples

```
mtcars$models <- rownames(mtcars)

mtcars[1:5,] %>%
  chart_ist(type = "pie") %>%
  add_ist(dis) %>%
  pieopt_ist(startAngle = 270,
             donut = TRUE,
             donutWidth = 50,
             showLabel = FALSE)

mtcars[1:5,] %>%
  chart_ist(x = models, type = "pie") %>%
  add_ist(dis) %>%
  pieopt_ist(labelDirection = "explode",
             labelOffset = 100,
             chartPadding = 50)

mtcars[1:5,] %>%
  chart_ist(type = "pie") %>%
  add_ist(dis) %>%
  pieopt_ist(percent = TRUE)
```

ratio_ist	<i>Select aspect ratio</i>
-----------	----------------------------

Description

Change aspect ratio of chart.

Usage

```
ratio_ist(p, ratio)
```

Arguments

p	a chartist object.
ratio	ratio of chart, see details and examples.

Details

Valid values for ratio:

- square or 1
- minor-second or 15:16
- major-second or 8:9
- minor-third or 5:6
- major-third or 4:5
- perfect-fourth or 3:4
- perfect-fifth or 2:3

- minor-sixth or 5:8
- golden-section or 1:1.618
- major-sixth or 3:5
- minor-seventh or 9:16
- major-seventh or 8:15
- octave or 1:2
- major-tenth or 2:5
- major-eleventh or 3:8
- major-twelfth or 1:3
- double-octave or 1:4

Examples

```
mtcars$models <- row.names(mtcars)

mtcars %>%
  chart_ist(x = models) %>%
  add_ist(displ) %>%
  ratio_ist(ratio = "square")
```

resp_ist

Configure responsive options for chartist visualisation

Description

Configure responsive options for chartist visualisation

Usage

```
resp_ist(p, query, width, height, low, high, chartPadding, ...)
```

Arguments

p	a chartist object.
query	responsive query.
width	set fixed width in pixels or percent (i.e.: 300px, 70%).
height	set fixed height in pixels or percent (i.e.: 300px, 70%).
low	lower bound of value.
high	higher bound of value.
chartPadding	padding around chart div.
...	additional options.

Examples

```
mtcars$models <- row.names(mtcars)

mtcars %>%
  chart_ist(models) %>%
  add_ist(qsec) %>%
  resp_ist(query = "screen and (max-width: 640px)", low = 15,
    chartPadding = 50) %>%
  resp_ist(query = "screen and (min-width: 641px) and (max-width: 1024px)",
    chartPadding = 0)
```

sanim_ist

*Scatter animation***Description**

Out of the box animation for scatter plot.

Usage

```
sanim_ist(p)
```

Arguments

p a chartist object.

Examples

```
mtcars %>%
  chart_ist(wt) %>%
  add_ist(dis) %>%
  add_ist(hp) %>%
  scatter_ist() %>%
  sanim_ist()
```

scatter_ist

*Make a scatter plot from a line chart***Description**

Helper function to easily turn a line chart into a scatter plot

Usage

```
scatter_ist(p, ...)
```

Arguments

p a chartist object
 ... additional parameters to pass to [opt_ist](#).

Examples

```
mtcars$models <- rownames(mtcars)
mtcars[1:20,] %>%
  chart_ist(x = models) %>%
  add_ist(displ) %>%
  scatter_ist()
```

thresh_ist	<i>Add threshold</i>
------------	----------------------

Description

Add threshold

Usage

```
thresh_ist(p, threshold)
```

Arguments

p	a chartist object.
threshold	threshold, defaults to mean of first series passed with add_ist .

Examples

```
mtcars %>%
  chart_ist(displ) %>%
  add_ist(hp) %>%
  thresh_ist()

mtcars %>%
  chart_ist(displ) %>%
  add_ist(hp) %>%
  thresh_ist(220)
```

xaxis_ist	<i>Tweak X axis</i>
-----------	---------------------

Description

Tweak the x axis for chartist visualisation.

Usage

```
xaxis_ist(p, showLabel = TRUE, showGrid = TRUE, suffix = "",
  prefix = "", position, offset, labelOffset, scaleMinSpace, ...)
```

Arguments

<code>p</code>	a chartist object.
<code>showLabel</code>	set to FALSE to hide labels.
<code>showGrid</code>	set to FALSE to hide the grid.
<code>suffix</code>	add suffix to label.
<code>prefix</code>	add prefix to label.
<code>position</code>	positon of axis.
<code>offset</code>	offset axis.
<code>labelOffset</code>	offset labels, takes integer, vector or list (i.e.: <code>1, c(1,2), list(x = 1, y = 2)</code>).
<code>scaleMinSpace</code>	minimum height in pixel of scale.
<code>...</code>	additional options.

Examples

```
mtcars$models <- row.names(mtcars)

mtcars[1:20,] %>%
  chart_ist(x = models, type = "bar") %>%
  add_ist(displ) %>%
  xaxis_ist(showLabel = FALSE, showGrid = FALSE)

mtcars[1:10,] %>%
  chart_ist(x = mpg, type = "bar") %>%
  add_ist(displ) %>%
  xaxis_ist(suffix = "MPG", scaleMinSpace = 100)
```

`xtitle_ist`*Add x axis title*

Description

Add x axis title

Usage

```
xtitle_ist(p, title = "", textAnchor = "middle", flipTitle = FALSE,
  offsetx = 0, offsety = 0)
```

Arguments

<code>p</code>	a chartist object.
<code>title</code>	axis title.
<code>textAnchor</code>	title position, defaults to middle.
<code>flipTitle</code>	set to TRUE to flip title on x axis.
<code>offsetx</code>	offset x alignment of title.
<code>offsety</code>	offsety y alignment of title.

Examples

```
mtcars %>%
  chart_ist(displ) %>%
  add_ist(values = hp) %>%
  xtitle_ist(title = "HP", offsety = 30)
```

yaxis_ist	<i>Tweak Y axis</i>
-----------	---------------------

Description

Tweak the y axis for chartist visualisation.

Usage

```
yaxis_ist(p, showLabel = TRUE, showGrid = TRUE, suffix = "",
  prefix = "", position, offset, labelOffset, scaleMinSpace, ...)
```

Arguments

p	a chartist object.
showLabel	set to FALSE to hide labels.
showGrid	set to FALSE to hide the grid.
suffix	add suffix to label.
prefix	add prefix to label.
position	positon of axis.
offset	offset axis.
labelOffset	offset labels, takes integer, vector or list (i.e.: 1, c(1,2), list(x = 1, y = 2)).
scaleMinSpace	minimum height in pixel of scale.
...	additional options.

Examples

```
mtcars$models <- row.names(mtcars)

mtcars[1:5,] %>%
  chart_ist(x = models, type = "bar") %>%
  add_ist(displ) %>%
  yaxis_ist(suffix = " $")

mtcars[1:10,] %>%
  chart_ist(x = mpg, type = "bar") %>%
  add_ist(displ) %>%
  yaxis_ist(offset = 200, labelOffset = list(x = -50, y = 0))
```

ytitle_ist	<i>Add y axis title</i>
------------	-------------------------

Description

Add y axis title

Usage

```
ytitle_ist(p, title = "", flipTitle = FALSE, offsetx = 0, offsety = 0)
```

Arguments

p	a chartist object.
title	axis title.
flipTitle	set to TRUE to flip title on x axis.
offsetx	offset x alignment of title.
offsety	offsety y alignment of title.

Examples

```
mtcars %>%  
  chart_ist(displ) %>%  
  add_ist(values = hp) %>%  
  ytitle_ist(title = "displ", offsetx = 30)
```

Index

`add_ist`, [2](#), [7](#), [17](#)
`anim_ist`, [3](#)

`baropt_ist`, [4](#), [11](#), [12](#)

`chart_ist`, [5](#)
`chartist-shiny`, [5](#)
`chartistOutput` (`chartist-shiny`), [5](#)

`danim_ist`, [6](#)

`ganim_ist`, [6](#)
`gauge_ist`, [7](#), [13](#)

`hover_ist`, [7](#)

`label_ist`, [8](#)
`lanim_ist`, [8](#)
`lineopt_ist`, [9](#), [11](#), [12](#)
`loop_ist`, [10](#)

`name_ist`, [2](#), [11](#)

`opt_ist`, [2](#), [7](#), [11](#), [16](#)

`peak_ist`, [12](#)
`pieopt_ist`, [11](#), [12](#), [13](#)

`ratio_ist`, [14](#)
`renderChartist` (`chartist-shiny`), [5](#)
`resp_ist`, [15](#)

`sanim_ist`, [16](#)
`scatter_ist`, [16](#)

`thresh_ist`, [17](#)

`xaxis_ist`, [17](#)
`xtitle_ist`, [18](#)

`yaxis_ist`, [19](#)
`ytitle_ist`, [20](#)