


Machine learning workflow management in R




Will Landau


Workflows have interconnected steps.



When you change something...



...the downstream steps are no longer valid.



Do you rerun everything from scratch?

- Not if you deal with long runtimes!



<https://openclipart.org/detail/275842/sisyphus-overcoming-silhouette>

Do you pick and choose what to update?

- Messy.
- Prone to human error.
- Not reproducible.



<https://openclipart.org/detail/216179/messy-desk>

When do we face these issues?

- Long computation!
 - Clinical trial modeling and simulation
 - Subgroup identification
 - Bayesian data analysis
 - Graph-based multiple comparison procedures
 - Bayesian networks in genomics
 - PK/PD modeling (e.g. [mrgsolve](#))
 - **Deep learning**
 - ...


Solution: pipeline tools



Scale up the
work you need.



Skip the
work you don't.



See evidence of
reproducibility.

- Tons exist already: github.com/pditommaso/awesome-pipeline.
- Most are language-agnostic or designed for Python or the shell.

What makes drake different?



- Aggressively designed for R.
 - Think **functions**, not script files.
 - Think **variables**, not output files.
 - Think **data frames**, not Makefiles.
- Major improvements in late 2018 and early 2019:
 - A **domain-specific language** for workflows.
 - Massive improvements in speed and memory usage.
 - Special **functions and checks** to safeguard reproducibility.

Example: a deep learning workflow

- Goal: predict customers who cancel their subscriptions with a telecom company.
- Data: **IBM Watson Telco Customer Churn dataset**.
- Workflow principles generalize to other industries.



<https://openclipart.org/detail/90739/newplus>, <https://github.com/rstudio/keras>

File structure

```
make.R  
R/  
├─ packages.R  
├─ functions.R  
└─ plan.R  
data/  
└─ customer_churn.csv
```

packages.R

```
library(drake)  
library(keras)  
library(recipes)  
library(rsample)  
library(tidyverse)  
library(yardstick)
```

functions.R

```
prepare_recipe <- function(data) {  
  # ...  
}  
  
define_model <- function(rec, units1, units2, act1, act2, act3) {  
  # ...  
}  
  
train_model <- function(data, rec, units1, units2, act1, act2, act3) {  
  # ...  
}  
  
confusion_matrix <- function(data, rec, serialized_model) {  
  # ...  
}  
  
compare_models <- function(...) {  
  # ...  
}
```

plan.R


```
activations <- c("relu", "sigmoid")

plan <- drake_plan(
  data = read_csv(file_in("data/customer_churn.csv"), col_types = cols()) %>%
    initial_split(prop = 0.3),
  rec = prepare_recipe(data),
  model = target(
    train_model(data, rec, act1 = act),
    transform = map(act = !!activations)
  ),
  conf = target(
    confusion_matrix(data, rec, model),
    transform = map(model, .id = act)
  ),
  metrics = target(
    compare_models(conf),
    transform = combine(conf)
  )
)
```

Data frame of workflow steps

```
plan
## # A tibble: 7 x 2
##   target      command
##   <chr>      <expr>
## 1 data      read_csv(file_in("data/customer_churn.csv"), col_types = c
## 2 rec       prepare_recipe(data)
## 3 model_relu train_model(data, rec, act1 = "relu")
## 4 model_sigmo... train_model(data, rec, act1 = "sigmoid")
## 5 conf_relu  confusion_matrix(data, rec, model_relu)
## 6 conf_sigmoid confusion_matrix(data, rec, model_sigmoid)
## 7 metrics   compare_models(conf_relu, conf_sigmoid)
```

The workflow




Run the project in make.R.

```
source("R/packages.R")  
source("R/functions.R")  
source("R/plan.R")  
  
make(plan)  
## target data  
## target rec  
## target model_relu  
## target model_sigmoid  
## target conf_relu  
## target conf_sigmoid  
## target metrics
```

Compare models.

```
readd(metrics) # See also loadd()
```




Try another activation function.

```
activations <- c("relu", "sigmoid", "softmax")

plan <- drake_plan(
  data = read_csv(file_in("data/customer_churn.csv"), col_types = cols()) %>%
    initial_split(prop = 0.3),
  rec = prepare_recipe(data),
  model = target(
    train_model(data, rec, act1 = act),
    transform = map(act = !!activations)
  ),
  conf = target(
    confusion_matrix(data, rec, model),
    transform = map(model, .id = act)
  ),
  metrics = target(
    compare_models(conf),
    transform = combine(conf)
  )
)
```

vis_drake_graph()




Refresh the results in make.R.

```
source("R/packages.R")  
source("R/functions.R")  
source("R/plan.R") # modified
```

```
make(plan)  
## target model_softmax  
## target conf_softmax  
## target metrics
```

Compare models.

```
readd(metrics)
```



Evidence of reproducibility

```
source("R/packages.R")
source("R/functions.R")
source("R/plan.R")

make(plan)
## All targets are already up to date.
```

- See also `outdated()`.

History and provenance

```
history <- drake_history()
```

```
history
```

```
## # A tibble: 10 x 9
```

##	target	time	hash	exists	command	runtime	latest	prop	act.
##	<chr>	<chr>	<chr>	<lgl>	<chr>	<dbl>	<lgl>	<dbl>	<ch
## 1	conf_r...	2019-06-...	e82b0...	TRUE	confusion_ma...	1.58	TRUE	NA	<NA>
## 2	conf_s...	2019-06-...	e735c...	TRUE	confusion_ma...	1.86	TRUE	NA	<NA>
## 3	conf_s...	2019-06-...	562f7...	TRUE	confusion_ma...	2.49	TRUE	NA	<NA>
## 4	data	2019-06-...	ca84b...	TRUE	"read_csv(fi...	0.0860	TRUE	0.3	<NA>
## 5	metrics	2019-06-...	4ddc4...	TRUE	compare_mode...	0.0230	FALSE	NA	<NA>
## 6	metrics	2019-06-...	1a16a...	TRUE	compare_mode...	0.02	TRUE	NA	<NA>
## 7	model_...	2019-06-...	1b810...	TRUE	"train_model...	13.5	TRUE	NA	rel
## 8	model_...	2019-06-...	4163b...	TRUE	"train_model...	6.02	TRUE	NA	sig
## 9	model_...	2019-06-...	23402...	TRUE	"train_model...	6.97	TRUE	NA	sof
## 10	rec	2019-06-...	7abeb...	TRUE	prepare_reci...	0.164	TRUE	NA	<NA>

High-performance computing

```
# template file with configuration
drake_hpc_template_file("slurm_clustermq.tmpl")

# Use SLURM resource manager with the template.
options(
  clustermq.scheduler = "slurm",
  clustermq.template = "slurm_clustermq.tmpl"
)

# make() is the basically the same.
make(plan, jobs = 2, parallelism = "clustermq")
```

High-performance computing

Resources

- Get **drake**:

```
install.packages("drake")
```

- Workshop materials:

```
remotes::install_github("wlandau/learndrake")
```

- Example code from these slides:

```
drake::drake_example("customer-churn-simple")
```

Links

- Development repository: <https://github.com/ropensci/drake>
- Full user manual <https://ropenscilabs.github.io/drake-manual>
- Reference website: <https://ropensci.github.io/drake>
- Code examples: <https://github.com/wlandau/drake-examples>
- Discuss at rOpenSci.org: <https://discuss.ropensci.org>

rOpenSci use cases

- Use **drake**? Share your use case at <https://ropensci.org/usecases>.



Thanks



- Edgar Ruiz
- example code



- Matt Dancho
- blog post

Thanks



- Maëlle Salmon
- Ben Marwick
- Julia Lowndes
- Peter Slaughter
- Jenny Bryan
- Rich FitzJohn
- Stefanie Butland

- Jarad Niemi
- Kirill Müller
- Henrik Bengtsson
- Michael Schubert
- Kendon Bell
- Miles McBain
- Patrick Schratz
- Alex Axthelm
- Jasper Clarkberg
- Tiernan Martin
- Ben Listyg
- TJ Mahr
- Ben Bond-Lamberty
- Tim Mastny
- Bill Denney
- Amanda Dobbyn
- Daniel Falster
- Rainer Krug
- Brianna McHorse
- Chan-Yub Park