OPEN STANDARD PROTOCOL · CCRFC SERIES

Cognitive Commons Framework

Creative Commons, but for AI chat data flow. Fast, portable, user-sovereign privacy.

Apache 2.0 Specification & Reference Implementation

THE STATUS QUO

Cloud AI Has a Broken Privacy Bargain

Binary Choice

Accept extractive terms, or abandon cloud AI completely.

Invisible Training

Chat logs quietly feed model weights and targeted ad profiles.

False Deletion

User deletion buttons rarely purge underlying downstream training pipelines.



MATHEMATICAL REALITY

You Cannot Un-Ring the Bell



Raw Data Can Be Deleted

GDPR and right-to-erasure requests can delete server logs, databases, and stored chat history.



Model Weights Cannot

Once ingested into matrix weights via gradient descent, un-training is mathematically impossible. Prevention at the wire is the only true defense.

THE ANTIDOTE

A Sovereign Privacy Architecture

5 Handling Tiers

Standardized license labels from freely open to zero transmission.

Wire-Level Flags

Flags precede payload. Servers halt before reading unhonored data.

Portable Profile

Define your terms once. Carry them seamlessly across all providers.

STANDARD VOCABULARY

The 5 CCF Handling Tiers

UF

Use Freely

Open domain training and public commons.

SO

Service Only

Improve system; strictly exclude advertising.

CO

Conversation

Active session memory; expire at chat close.

NK

No Keep

Seen to route; zero retention; audited discard.

NT

No Transmit

Never leaves hardware; local inference only.

USER CONFIGURATION MATRIX

Assign Tiers by Content Class

Content Category	UF (Free)	SO (Service)	CO (Session)	NK (Route)	NT (Local)
Public General Knowledge	✓	—	—	—	—
Personal Tasks & Summaries	—	—	✓	—	—
Credentials & Identifiers	—	—	—	✓	—
Financials & Deep Medical	—	—	—	—	🔒

SAFETY BY CONSTRUCTION

Firewall Stance: Conflict Resolution

Default-Deny

Unclassified streams instantly lock down to the most private tier.

Downward Fallback

Conflicting profile rules resolve automatically to maximum protection.

PROTOCOL MECHANICS

The Sealed Envelope Handshake

STEP 01

Flag Transmission

Client header signals handling tier before payload enters socket.

STEP 02

Pre-Read Evaluation

Server evaluates capability without buffering or caching body.

STEP 03

Halt or Ingest

Unhandled flags trigger immediate zero-read connection drop.

ACCOUNTABILITY

Auditable Proof Without Content Exposure

The Event Is Logged

Receipt records flag verification, protocol status code, and timestamp.

Status: 202 Hold

The Payload Is Never Kept

Absence in storage is the checkable promise:
proof of accounting, not proof of non-use.

NETWORK PROPAGATION

First-Contact Bootstrap & Class Discovery

Null Header Detection

When an uninitialized user arrives, the server serves the clean CCF setup grid.

Local Profile Minting

The profile is saved in user-held storage, immediately portable to any subsequent engine.

Evolving Content Classes

Providers can propose novel classes. When adopted in user profiles, they spread organically across the ecosystem.

USER FRICTION

Setup Once, Protected Everywhere

1x


Profile creation

0

Repeated opt-out forms

100%

User-held sovereignty



The Commons Is Live

Explore the RFC specifications, test the reference server, and take your privacy back.

github.com/JohnHenryUS/ccf · github.com/JohnHenryUS/ccf-srs

Image Sources



https://images.stockcake.com/public/d/2/f/d2f1d59c-de47-4b61-9f63-8d58dbe43336_large/cyber-security-lock-stockcake.jpg

Source: stockcake.com