


Symmetric Cipher Model

- There are two requirements for secure use of conventional encryption (symmetric):
- 1. A strong encryption algorithm
- 2. Sender and receiver must have obtained copies of the secret key in a secure fashion and must keep the key secure





© 2020 Pearson Education, Inc., Hoboken, NJ. All rights reserved

4



5







Type of Attack	Known to Cryptanalyst		
Ciphertext Only	Encryption algorithm Ciphertext		
Known Plaintext	Encryption algorithm Ciphertext One or more plaintext-ciphertext pairs formed with the secret key	Table 2	
Chosen Plaintext	Encryption algorithm Ciphertext Plaintext message chosen by cryptanalyst, together with its corresponding ciphertext generated with the secret key	Table 3. Types of Attacks on Encrypted Messages	
Chosen Ciphertext	Encryption algorithm Ciphertext Ciphertext chosen by cryptanalyst, together with its corresponding decrypted plaintext generated with the secret key		
Chosen Text	Encryption algorithm Ciphertext Plaintext message chosen by cryptanalyst, together with its corresponding ciphertext generated with the secret key Ciphertext chosen by cryptanalyst, together with its corresponding decrypted plaintext generated with the secret key		

Encryption Scheme Security

- Unconditionally secure
 - No matter how much time an opponent has, it is impossible for him or her to decrypt the ciphertext simply because the required information is not there
- Computationally secure
 - The cost of breaking the cipher exceeds the value of the encrypted information
 - The time required to break the cipher exceeds the useful lifetime of the information





Strong Encryption

- The term strong encryption refers to encryption schemes that make it impractically difficult for unauthorized persons or systems to gain access to plaintext that has been encrypted
- Properties that make an encryption algorithm strong are:
 - Appropriate choice of cryptographic algorithm
 - Use of sufficiently long key lengths
 - Appropriate choice of protocols
 - A well-engineered implementation
 - Absence of deliberately introduced hidden flaws

© 2020 Pearson Education, Inc., Hoboken, NJ. All rights reserved.

11

Substitution Technique

- Is one in which the letters of plaintext are replaced by other letters or by numbers or symbols
- If the plaintext is viewed as a sequence of bits, then substitution involves replacing plaintext bit patterns with ciphertext bit patterns



2020 Pearson Education, Inc., Hoboken, NJ, All rights reserved



Caesar Cipher Algorithm Can define transformation as: a b c d e f q h i j k l m n o p q r s t u v w x y z D E F G H I J k L M N o P Q R S T U V W X Y Z A B C Mathematically give each letter a number a b c d e f y h i j k l m n p q r s t v v x y z A B C Mathematically give each letter a number a b c d e f y h i j k l m n p q r s t v v x y z b l s p q r s t v v x y z c E (3, p) = (p + 3) mod (26) Algorithm can be expressed as: c = E(3, p) = (p + 3) mod (26) A shift may be of any amount, so that the general Caesar algorithm is: C = E(k, p) = (p + k) mod 26 Where k takes on a value in the range 1 to 25; the decryption algorithm is simply: p = D(k, C) = (C - k) mod 26

14

Figure 3.3

Figure 5.

Figure

Sample of Compressed Text

Figure 3.4 Sample of Compressed Text

120 Payreon Education Inc. Hobokan N I All rights reserved


16

Monoalphabetic Cipher

- Permutation
 - Of a finite set of elements S is an ordered sequence of all the elements of S, with each element appearing exactly once
- If the "cipher" line can be any permutation of the 26 alphabetic characters, then there are 26! or greater than 4 x 10²⁶ possible keys
 - This is 10 orders of magnitude greater than the key space for DES
 - Approach is referred to as a monoalphabetic substitution cipher because a single cipher alphabet is used per message


2020 Pearson Education, Inc., Hoboken, NJ. All rights reserved.

17



Monoalphabetic Ciphers

- Easy to break because they reflect the frequency data of the original alphabet
- Digram (or Bigram)
 - Two-letter combination
 - Most common is th
- Trigram
- Three-letter combination
- Most frequent is the



Payreon Education Inc. Hoboken N I All rights reserved

19

Digram frequency to break a cipher

- Digram (or Bigram) analysis
 - Two-letter combination
 - Most common is th (ZW is most likely TH)

UZQSOVUOHXMOPVGPOZPEVSGZWSZOPFPESXUDBMETSXAIZ
ta e e te a that e e a a
VUEPHZHMDZSHZOWSFPAPPDTSVPQUZWYMXUZUHSX
e t ta t ha e ee a e th t a
EPYEPOPDZSZUFPOMBZWPFUPZHMDJUDTMOHMQ
e e e tat e the t

© 2020 Pearson Education, Inc., Hoboken, NJ. All rights reserved

20

Playfair Cipher

- Best-known multiple-letter encryption cipher
- Treats digrams in the plaintext as single units and translates these units into ciphertext digrams
- Based on the use of a 5 x 5 matrix of letters constructed using a keyword
- Invented by British scientist Sir Charles Wheatstone in 1854
- Used as the standard field system by the British Army in World War I and the U.S. Army and other Allied forces during World War II

20 Pearson Education, Inc., Hoboken, NJ, All rights reserved

Playfair Key Matrix

- Fill in letters of keyword (minus duplicates) from left to right and from top to bottom, then fill in the remainder of the matrix with the remaining letters in alphabetic order
- Using the keyword MONARCHY:

M	0	N	A	R
C	Н	Y	В	D
C E	F	G	I/J	K
L	Р	Q W	I/J S X	Т
U	V	W	×	Z

© 2020 Pearson Education, Inc., Hoboken, NJ. All rights reserved


22

Playfair Cipher

- Plaintext is encrypted two letters at a time, according to the following rules:
- Repeating plaintext letters that are in the same pair are separated with a filler letter, such as x, so that balloon would be treated as balk lo on.
- Two plaintext letters that fall in the same row of the matrix are each replaced by the letter to the right, with the first element of the row circularly following the last. For example, ar is encrypted as RM
- Two plaintext letters that fall in the same column are each replaced by the letter beneath, with the top element of the column circularly following the last. For example, mu is encrypted as CM.
- Otherwise, each plaintext letter in a pair is replaced by the letter that lies in its own row and the column occupied by the other plaintext letter. Thus, hs becomes BP and ea becomes IM (or JM, as the encipherer wishes).

© 2020 Pearson Education, Inc., Hoboken, NJ. All rights reserved

23



Polyalphabetic Ciphers

- Polyalphabetic substitution cipher
 - Improves on the simple monoalphabetic technique by using different monoalphabetic substitutions as one proceeds through the plaintext message

All these techniques have the following features in common:

- A set of related monoalphabetic substitution rules is used
- A key determines which particular rule is chosen for a given transformation

Pearson Education Inc. Hoboken, N.I. All rights received

25

Vigenère Cipher

- Best known and one of the simplest polyalphabetic substitution ciphers
- In this scheme the set of related monoalphabetic substitution rules consists of the 26 Caesar ciphers with shifts of o through 25
- Each cipher is denoted by a key letter which is the ciphertext letter that substitutes for the plaintext letter a

© 2020 Pearson Education, Inc., Hoboken, NJ. All rights reserved.

26

Example of Vigenère Cipher

- To encrypt a message, a key is needed that is as long as the message
- · Usually, the key is a repeating keyword
- For example, if the keyword is deceptive, the message "we are discovered save yourself" is encrypted as:

key: deceptivedeceptive plaintext: wearediscoveredsaveyourself ciphertext: ZICVTWQNGRZGVTWAVZHCQYGLMGJ

020 Pearson Education, Inc., Hoboken, NJ. All rights reserved

Vigenère Autokey System


- A keyword is concatenated with the plaintext itself to provide a running key
- Example:

key: deceptivewearediscoveredsav plaintext: wearediscoveredsaveyourself ciphertext: ZICVTWQNGKZEIIGASXSTSLVWWLA

- Even this scheme is vulnerable to cryptanalysis
 - Because the key and the plaintext share the same frequency distribution of letters, a statistical technique can be applied

Decree Education by Hababas NJ All dabte second

28



29

One-Time Pad

- Improvement to Vernam cipher proposed by an Army Signal Corp officer, Joseph Mauborgne
- Use a random key that is as long as the message so that the key need not be repeated
- Key is used to encrypt and decrypt a single message and then is discarded
- Each new message requires a new key of the same length as the new message
- Scheme is unbreakable
- Produces random output that bears no statistical relationship to the plaintext
- Because the ciphertext contains no information whatsoever about the plaintext, there is simply no way to break the code



2020 Pearson Education, Inc., Hoboken, NJ. All rights reserved

Difficulties

- The one-time pad offers complete security but, in practice, has two fundamental difficulties:
- There is the practical problem of making large quantities of random keys
 Any heavily used system might require millions of random characters on a regular basis
- Mammoth key distribution problem
- For every message to be sent, a key of equal length is needed by both sender and receiver
- Because of these difficulties, the one-time pad is of limited
 - Useful primarily for low-bandwidth channels requiring very high security
- The one-time pad is the only cryptosystem that exhibits $\ensuremath{\textit{perfect}}$ secrecy (see Appendix F)

31

Rail Fence Cipher

- Simplest transposition cipher
- Plaintext is written down as a sequence of diagonals and then read off as a sequence of rows
- To encipher the message "meet me after the toga party" with a rail fence of depth 2, we would

mematrhtgpry etefeteoaat Encrypted message is: MEMATRHTGPRYETEFETEOAAT

32

Row Transposition Cipher


- Is a more complex transposition
- Write the message in a rectangle, row by row, and read the message off, column by column, but permute the order of the columns
 - The order of the columns then becomes the key to the algorithm

Key: 4312567 Plaintext: attackp ostpone


duntilt w o a mx y z

Ciphertext:

TTNAAPTMTSUOAODWCOIXKNLYPETZ







Present an overview of the main concepts of symmetric cryptography Explain the difference between cryptanalysis and brute-force attack Understand the operation of a monoalphabetic substitution cipher