Ch – 2 Application Layer (Cont.)

Class 4




```
GET /home?pageId=c5789534 HTTP/1.1
Host: www.buildvsbreak.com
User-Agent: Mozilla/5.0
Accept: text/html,application/xhtml+xml,application/xml;
Accept-Language: en;q=0.5
Accept-Encoding: gzip, deflate
DNT: 1
Connection: keep-alive
```



Recap





Application Layer: Overview

- Principles of network applications
- Web and HTTP
- E-mail, SMTP, IMAP
- The Domain Name System DNS

- P2P applications
- video streaming and content distribution networks
- socket programming with UDP and TCP

Peer-to-peer (P2P) architecture

- *no* always-on server
- arbitrary end systems directly communicate
- peers request service from other peers, provide service in return to other peers
  - *self scalability* – new peers bring new service capacity, and new service demands
- peers are intermittently connected and change IP addresses
  - complex management
- examples: P2P file sharing (BitTorrent), streaming (KanKan), VoIP (Skype)



File distribution: client-server vs P2P

Q: how much time to distribute file (size *F*) from one server to *N peers*?

- peer upload/download capacity is limited resource



File distribution time: client-server

- *server transmission:* must sequentially send (upload) N file copies:
  - time to send one copy: F/u_s
  - time to send N copies: NF/u_s



- *client:* each client must download file copy
  - d_{min} = min client download rate
  - min client download time: F/d_{min}

time to distribute F to N clients using client-server approach

$$D_{c\text{-}s} \geq max\{NF/u_s, F/d_{min}\}$$

increases linearly in N

File distribution time: P2P

- *server transmission:* must upload at least one copy:
  - time to send one copy: F/u_s
- *client:* each client must download file copy
  - min client download time: F/d_{min}
- *clients:* as aggregate must download *NF* bits
  - max upload rate (limiting max download rate) is $u_s + \Sigma u_i$



time to distribute F to N clients using P2P approach	$D_{P2P} \geq max\{F/u_s,F/d_{min},NF/(u_s + \Sigma u_i)\}$

increases linearly in *N* …

… but so does this, as each peer brings service capacity

Client-server vs. P2P: example

client upload rate = u, F/u = 1 hour, $u_s = 10u$, $d_{min} \geq u_s$



P2P file distribution: BitTorrent

- file divided into 256Kb chunks
- peers in torrent send/receive file chunks

tracker: tracks peers participating in torrent

torrent: group of peers exchanging chunks of a file



Alice arrives …
… obtains list
of peers from tracker
… and begins exchanging
file chunks with peers in torrent

P2P file distribution: BitTorrent



- peer joining torrent:
  - has no chunks, but will accumulate them over time from other peers
  - registers with tracker to get list of peers, connects to subset of peers ("neighbors")
- while downloading, peer uploads chunks to other peers
- peer may change peers with whom it exchanges chunks
- *churn:* peers may come and go
- once peer has entire file, it may (selfishly) leave or (altruistically) remain in torrent

BitTorrent: requesting, sending file chunks

Requesting chunks:

- at any given time, different peers have different subsets of file chunks
- periodically, Alice asks each peer for list of chunks that they have
- Alice requests missing chunks from peers, rarest first

Sending chunks: tit-for-tat

- Alice sends chunks to those four peers currently sending her chunks *at highest rate*
  - other peers are choked by Alice (do not receive chunks from her)
  - re-evaluate top 4 every10 secs
- every 30 secs: randomly select another peer, starts sending chunks
  - "optimistically unchoke" this peer
  - newly chosen peer may join top 4

BitTorrent: tit-for-tat

(1) Alice “optimistically unchokes” Bob

(2) Alice becomes one of Bob’s top-four providers; Bob reciprocates

(3) Bob becomes one of Alice’s top-four providers



higher upload rate: find better trading partners, get file faster !

Application layer: overview

- Principles of network applications
- Web and HTTP
- E-mail, SMTP, IMAP
- The Domain Name System DNS
- P2P applications
- video streaming and content distribution networks
- socket programming with UDP and TCP

Video Streaming and CDNs: context

- stream video traffic: major consumer of Internet bandwidth
  - Netflix, YouTube, Amazon Prime: 80% of residential ISP traffic (2020)

- video: sequence of images displayed at constant rat e.g., 24 images/sec

- Digital image: array of pixels
  - Each pixel represented by bits

Streaming stored video

simple scenario:



Main challenges:

- server-to-client bandwidth will *vary* over time, with changing network congestion levels (in house, in access network, in network core, at video server)
- packet loss and delay due to congestion will delay playout, or result in poor video quality

Streaming stored video



streaming: at this time, client playing out early part of video, while server still sending later part of video

Streaming stored video: challenges

- continuous playout constraint: once client playout begins, playback must match original timing
  - … but network delays are variable (jitter), so will need client-side buffer to match playout requirements



- other challenges:
  - client interactivity: pause, fast-forward, rewind, jump through video
  - video packets may be lost, retransmitted

Streaming stored video: playout buffering



- *client-side buffering and playout delay:* compensate for network-added delay, delay jitter

Streaming multimedia: DASH

- *DASH: D*ynamic, *A*daptive *S*treaming over *H*TTP
- *server:*
  - divides video file into multiple chunks
  - each chunk stored, encoded at different rates
  - *manifest file:* provides URLs for different chunks



- *client:*
  - periodically measures server-to-client bandwidth
  - consulting manifest, requests one chunk at a time
    - chooses maximum coding rate sustainable given current bandwidth
    - can choose different coding rates at different points in time (depending on available bandwidth at time)

Streaming multimedia: DASH

- *"intelligence"* at client: client determines
  - *when* to request chunk (so that buffer starvation, or overflow does not occur)
  - *what encoding rate* to request (higher quality when more bandwidth available)



  - *where* to request chunk (can request from URL server that is "close" to client or has high available bandwidth)

Streaming video = encoding + DASH + playout buffering

Content distribution networks (CDNs)

- *challenge:* how to stream content (selected from millions of videos) to hundreds of thousands of *simultaneous* users?

- option 1: single, large "mega-server"
  - single point of failure
  - point of network congestion
  - long path to distant clients
  - multiple copies of video sent over outgoing link

....quite simply: this solution *doesn't scale*

Content distribution networks (CDNs)

- *challenge:* how to stream content (selected from millions of videos) to hundreds of thousands of *simultaneous* users?
- option 2: store/serve multiple copies of videos at multiple geographically distributed sites *(CDN)*
  - *enter deep:* push CDN servers deep into many access networks
    - close to users
    - Akamai: 240,000 servers deployed in more than 120 countries (2015)
  - *bring home:* smaller number (10's) of larger clusters in IXP near (but not within) access networks
    - used by Limelight

Google CDN Facts

- 19 ‘mega data centers’: 100,000 servers each
- 90 clusters in IXP: 100s of servers
- 100s ‘enter-deep’: 10s of server per rack

YouTube retrieval example:

- Video -> bring-home cache
- Surrounding webpage: enter-deep cache
- Advertisement: data centers

Content distribution networks (CDNs)

- CDN: stores copies of content at CDN nodes
  - e.g. Netflix stores copies of MadMen
- subscriber requests content from CDN
  - directed to nearby copy, retrieves content
  - may choose different copy if network path congested



CDN content access: a closer look

Bob (client) requests video http://netcinema.com/6Y7B23V

- video stored in CDN at http://KingCDN.com/NetC6y&B23V



Case study: Netflix



Application Layer: Overview

- Principles of network applications
- Web and HTTP
- E-mail, SMTP, IMAP
- The Domain Name System DNS
- P2P applications
- video streaming and content distribution networks
- socket programming with UDP and TCP

Socket programming

goal: learn how to build client/server applications that communicate using sockets

socket: door between application process and end-end-transport protocol



Socket programming

Two socket types for two transport services:

- *UDP:* unreliable datagram
- *TCP:* reliable, byte stream-oriented

Application Example:

1. client reads a line of characters (data) from its keyboard and sends data to server
2. server receives the data and converts characters to uppercase
3. server sends modified data to client
4. client receives modified data and displays line on its screen

Socket programming with UDP

UDP: no "connection" between client & server

- no handshaking before sending data
- sender explicitly attaches IP destination address and port # to each packet
- receiver extracts sender IP address and port# from received packet

UDP: transmitted data may be lost or received out-of-order

Application viewpoint:

- UDP provides *unreliable* transfer of groups of bytes ("datagrams") between client and server

Client/server socket interaction: UDP



server (running on serverIP)

create socket, port= x:
serverSocket =
socket(AF_INET,SOCK_DGRAM)

read datagram from
serverSocket

write reply to
serverSocket
specifying
client address,
port number

client

create socket:
clientSocket =
socket(AF_INET,SOCK_DGRAM)

Create datagram with server IP and
port=x; send datagram via
clientSocket

read datagram from
clientSocket

close
clientSocket

Example app: UDP client

Python UDPClient

include Python's socket library → `from socket import *`

```
serverName = 'hostname'
serverPort = 12000
```

create UDP socket for server →

```
clientSocket = socket(AF_INET,
                      SOCK_DGRAM)
```

get user keyboard input → `message = raw_input('Input lowercase sentence:')`

attach server name, port to message; send into socket →

```
clientSocket.sendto(message.encode(),
                    (serverName, serverPort))
```

read reply characters from socket into string →

```
modifiedMessage, serverAddress =
                    clientSocket.recvfrom(2048)
```

print out received string and close socket →

```
print modifiedMessage.decode()
clientSocket.close()
```

Example app: UDP server

Python UDPServer

create UDP socket →
bind socket to local port number 12000 →
loop forever →
Read from UDP socket into message, getting client's address (client IP and port) →
send upper case string back to this client →

```
from socket import *
serverPort = 12000
serverSocket = socket(AF_INET, SOCK_DGRAM)
serverSocket.bind(('', serverPort))
print ("The server is ready to receive")
while True:
    message, clientAddress = serverSocket.recvfrom(2048)
    modifiedMessage = message.decode().upper()
    serverSocket.sendto(modifiedMessage.encode(),
                        clientAddress)
```

Socket programming with TCP

Client must contact server

- server process must first be running
- server must have created socket (door) that welcomes client's contact

Client contacts server by:

- Creating TCP socket, specifying IP address, port number of server process
- *when client creates socket:* client TCP establishes connection to server TCP

- when contacted by client, *server TCP creates new socket* for server process to communicate with that particular client
  - allows server to talk with multiple clients
  - source port numbers used to distinguish clients (more in Chap 3)

Application viewpoint

TCP provides reliable, in-order byte-stream transfer ("pipe") between client and server

Client/server socket interaction: TCP



Example app: TCP client

Python TCPClient

create TCP socket for server, remote port 12000

No need to attach server name, port

```
from socket import *
serverName = ’servername’
serverPort = 12000
clientSocket = socket(AF_INET, SOCK_STREAM)
clientSocket.connect((serverName,serverPort))
sentence = raw_input(‘Input lowercase sentence:’)
clientSocket.send(sentence.encode())
modifiedSentence = clientSocket.recv(1024)
print (‘From Server:’, modifiedSentence.decode())
clientSocket.close()
```

Example app: TCP server

Python TCPServer

create TCP welcoming socket

server begins listening for incoming TCP requests

loop forever

server waits on accept() for incoming requests, new socket created on return

read bytes from socket (but not address as in UDP)

close connection to this client (but *not* welcoming socket)

```
from socket import *
serverPort = 12000
serverSocket = socket(AF_INET,SOCK_STREAM)
serverSocket.bind((‘’,serverPort))
serverSocket.listen(1)
print ‘The server is ready to receive’
while True:
    connectionSocket, addr = serverSocket.accept()

    sentence = connectionSocket.recv(1024).decode()
    capitalizedSentence = sentence.upper()
    connectionSocket.send(capitalizedSentence.
                                   encode())
    connectionSocket.close()
```

Chapter 2: Summary

our study of network application layer is now complete!

- application architectures
  - client-server
  - P2P
- application service requirements:
  - reliability, bandwidth, delay
- Internet transport service model
  - connection-oriented, reliable: TCP
  - unreliable, datagrams: UDP
- specific protocols:
  - HTTP
  - SMTP, IMAP
  - DNS
  - P2P: BitTorrent
- video streaming, CDNs
- socket programming:
  TCP, UDP sockets

Chapter 2: Summary

Most importantly: learned about *protocols*!

- typical request/reply message exchange:
  - client requests info or service
  - server responds with data, status code
- message formats:
  - *headers*: fields giving info about data
  - *data:* info(payload) being communicated

important themes:

- centralized vs. decentralized
- stateless vs. stateful
- scalability
- reliable vs. unreliable message transfer
- “complexity at network edge”

Ch – 3 Transport Layer

Transport layer: overview

Our goal:

- understand principles behind transport layer services:
  - multiplexing, demultiplexing
  - reliable data transfer
  - flow control
  - congestion control
- learn about Internet transport layer protocols:
  - UDP: connectionless transport
  - TCP: connection-oriented reliable transport
  - TCP congestion control

Transport layer: roadmap

- Transport-layer services
- Multiplexing and demultiplexing
- Connectionless transport: UDP
- Principles of reliable data transfer
- Connection-oriented transport: TCP
- Principles of congestion control
- TCP congestion control
- Evolution of transport-layer functionality

Transport services and protocols

- provide *logical communication* between application processes running on different hosts
- transport protocols actions in end systems:
  - sender: breaks application messages into *segments*, passes to network layer
  - receiver: reassembles segments into messages, passes to application layer
- two transport protocols available to Internet applications
  - TCP, UDP



Transport vs. network layer services and protocols

household analogy:

12 kids in Ann's house sending letters to 12 kids in Bill's house:

- hosts = houses
- processes = kids
- app messages = letters in envelopes

Transport vs. network layer services and protocols

- network layer: logical communication between *hosts*
- transport layer*:* logical communication between *processes*
  - relies on, enhances, network layer services

household analogy:

12 kids in Ann's house sending letters to 12 kids in Bill's house:

- hosts = houses
- processes = kids
- app messages = letters in envelopes

Transport Layer Actions

Sender:

- is passed an application-layer message
- determines segment header fields values
- creates segment
- passes segment to IP



Transport Layer Actions



Receiver:

- receives segment from IP
- checks header values
- extracts application-layer message
- demultiplexes message up to application via socket

Two principal Internet transport protocols

- **TCP:** Transmission Control Protocol
  - reliable, in-order delivery
  - congestion control
  - flow control
  - connection setup
- **UDP:** User Datagram Protocol
  - unreliable, unordered delivery
  - no-frills extension of "best-effort" IP
- services not available:
  - delay guarantees
  - bandwidth guarantees



Chapter 3: roadmap

- Transport-layer services
- Multiplexing and demultiplexing
- Connectionless transport: UDP
- Principles of reliable data transfer
- Connection-oriented transport: TCP
- Principles of congestion control
- TCP congestion control
- Evolution of transport-layer functionality


HTTP server
client
application
NETFLIX
transport
network
link
physical
APACHE
HTTP SERVER
HTTP msg
transport
network
link
physical
application
transport
network
link
physical


HTTP server
client
application
NETFLIX
transport
network
link
physical
APACHE
HTTP SERVER
HTTP msg
H_t HTTP msg
network
link
physical
application
transport
network
link
physical


HTTP server
client
application
NETFLIX
transport
network
link
physical
APACHE
HTTP SERVER
HTTP msg
H_t HTTP msg
$H_n H_t$ HTTP msg
link
physical
application
transport
network
link
physical


HTTP server
client
application
NETFLIX
transport
network
link
physical
APACHE
HTTP SERVER
transport
network
link
physical
application
transport
network
link
physical
H n H t HTTP msg


HTTP server
client1
client2
application
transport
network
link
physical
P-client1
P-client2
NETFLIX

Multiplexing/demultiplexing

multiplexing at sender:

handle data from multiple sockets, add transport header (later used for demultiplexing)

demultiplexing at receiver:

use header info to deliver received segments to correct socket



How demultiplexing works

- host receives IP datagrams
  - each datagram has source IP address, destination IP address
  - each datagram carries one transport-layer segment
  - each segment has source, destination port number
- host uses *IP addresses & port numbers* to direct segment to appropriate socket



TCP/UDP segment format

Connectionless demultiplexing

Recall:

- when creating socket, must specify *host-local* port #:

```
DatagramSocket mySocket1
 = new DatagramSocket(12534);
```

- when creating datagram to send into UDP socket, must specify
  - destination IP address
  - destination port #

when receiving host receives *UDP* segment:

- checks destination port # in segment
- directs UDP segment to socket with that port #

IP/UDP datagrams with *same dest. port #,* but different source IP addresses and/or source port numbers will be directed to *same socket* at receiving host

Connectionless demultiplexing: an example



Connection-oriented demultiplexing

- TCP socket identified by 4-tuple:
  - source IP address
  - source port number
  - dest IP address
  - dest port number
- demux: receiver uses *all four values (4-tuple)* to direct segment to appropriate socket

- server may support many simultaneous TCP sockets:
  - each socket identified by its own 4-tuple
  - each socket associated with a different connecting client

Connection-oriented demultiplexing: example



Three segments, all destined to IP address: B,
dest port: 80 are demultiplexed to *different* sockets

Summary

- Multiplexing, demultiplexing: based on segment, datagram header field values
- **UDP:** demultiplexing using destination port number (only)
- **TCP:** demultiplexing using 4-tuple: source and destination IP addresses, and port numbers
- Multiplexing/demultiplexing happen at *all* layers

Chapter 3: roadmap

- Transport-layer services
- Multiplexing and demultiplexing
- Connectionless transport: UDP
- Principles of reliable data transfer
- Connection-oriented transport: TCP
- Principles of congestion control
- TCP congestion control
- Evolution of transport-layer functionality

UDP: User Datagram Protocol

- "no frills," "bare bones" Internet transport protocol
- "best effort" service, UDP segments may be:
  - lost
  - delivered out-of-order to app
- *connectionless:*
  - no handshaking between UDP sender, receiver
  - each UDP segment handled independently of others

Why is there a UDP?

- no connection establishment (which can add RTT delay)
- simple: no connection state at sender, receiver
- small header size
- no congestion control
  - UDP can blast away as fast as desired!
  - can function in the face of congestion

UDP: User Datagram Protocol

- UDP use:
  - streaming multimedia apps (loss tolerant, rate sensitive)
  - DNS
  - SNMP
  - HTTP/3
- if reliable transfer needed over UDP (e.g., HTTP/3):
  - add needed reliability at application layer
  - add congestion control at application layer

UDP: User Datagram Protocol [RFC 768]

```
                                                  INTERNET STANDARD
RFC  768                                                  J. Postel
                                                                ISI
                                                     28 August 1980



                         User Datagram Protocol
                         ----------------------

Introduction
------------

This User Datagram  Protocol  (UDP)  is  defined  to  make  available  a
datagram   mode  of  packet-switched   computer   communication  in  the
environment  of  an  interconnected  set  of  computer  networks.   This
protocol  assumes  that the Internet  Protocol  (IP)  [1] is used as the
underlying protocol.

This protocol  provides  a procedure  for application  programs  to send
messages  to other programs  with a minimum  of protocol mechanism.  The
protocol  is transaction oriented, and delivery and duplicate protection
are not guaranteed.  Applications requiring ordered reliable delivery of
streams of data should use the Transmission Control Protocol (TCP) [2].

Format
------


                  0      7 8     15 16    23 24    31
                 +--------+--------+--------+--------+
                 |     Source      |   Destination   |
                 |      Port       |      Port       |
                 +--------+--------+--------+--------+
                 |                 |                 |
                 |     Length      |    Checksum     |
                 +--------+--------+--------+--------+
                 |
                 |          data octets ...
                 +---------------- ...
```

UDP: Transport Layer Actions



UDP: Transport Layer Actions



UDP sender actions:

- is passed an application-layer message
- determines UDP segment header fields values
- creates UDP segment
- passes segment to IP





UDP: Transport Layer Actions



UDP receiver actions:

- receives segment from IP
- checks UDP checksum header value
- extracts application-layer message
- demultiplexes message up to application via socket



UDP segment header



UDP segment format

UDP checksum

Goal: detect errors (*i.e.,* flipped bits) in transmitted segment

	1st number	2nd number	sum
Transmitted:	5	6	11
Received:	4	6	11

receiver-computed checksum $\neq$ sender-computed checksum (as received)

Internet checksum

Goal: detect errors (*i.e.,* flipped bits) in transmitted segment

sender:

- treat contents of UDP segment (including UDP header fields and IP addresses) as sequence of 16-bit integers
- checksum: addition (one's complement sum) of segment content
- checksum value put into UDP checksum field

receiver:

- compute checksum of received segment
- check if computed checksum equals checksum field value:
  - not equal - error detected
  - equal - no error detected. *But maybe errors nonetheless?* More later ….

Internet checksum: an example

example: add two 16-bit integers

	1 1 1 0 0 1 1 0 0 1 1 0 0 1 1 0
	1 1 0 1 0 1 0 1 0 1 0 1 0 1 0 1
wraparound	1 1 0 1 1 1 0 1 1 1 0 1 1 1 0 1 1
sum	1 0 1 1 1 0 1 1 1 0 1 1 1 1 0 0
checksum	0 1 0 0 0 1 0 0 0 1 0 0 0 0 1 1

Note: when adding numbers, a carryout from the most significant bit needs to be added to the result

* Check out the online interactive exercises for more examples: http://gaia.cs.umass.edu/kurose_ross/interactive/

Internet checksum: weak protection!

example: add two 16-bit integers

		1	1	1	0	0	1	1	0	0	1	1	0	0	1	1	0
		1	1	0	1	0	1	0	1	0	1	0	1	0	1	0	1
wraparound	1	1	0	1	1	1	0	1	1	1	0	1	1	1	0	1	1
sum		1	0	1	1	1	0	1	1	1	0	1	1	1	1	0	0
checksum		0	1	0	0	0	1	0	0	0	1	0	0	0	0	1	1

0 1
1 0

Even though numbers have changed (bit flips), *no* change in checksum!

Summary: UDP

- "no frills" protocol:
  - segments may be lost, delivered out of order
  - best effort service: "send and hope for the best"
- UDP has its plusses:
  - no setup/handshaking needed (no RTT incurred)
  - can function when network service is compromised
  - helps with reliability (checksum)
- build additional functionality on top of UDP in application layer (e.g., HTTP/3)