Probabilistic programming with Edward

John Reid

Biostatistics Unit, School of Clinical Medicine, Cambridge University

April 25, 2017

George E.P. Box (1919 - 2013)




An iterative process for science:

- **1.** Build a model of the science
- 2. Infer the model given data
- **3.** Criticize the model given data

G. E. P. Box and Hunter, 1962; G. E. P. Box and Hunter, 1965; G. E. P. Box and Hill, 1967; George E. P. Box, 1976; George E. P. Box, 1980

Box's Loop



Edward is a library designed around this loop. (George E. P. Box, 1976; George E. P. Box, 1980; David M. Blei, 2014)

Edward is a probabilistic programming language, designed for fast experimentation and research (Tran et al., 2017).

Modelling

- ► Composable Turing-complete language of random variables.
- ► Examples: Graphical models, neural networks, probabilistic programs.
- Many data types, tensor vectorization, broadcasting, 3rd party support.

Inference

- ► Composable language for hybrids, message passing, data subsampling.
- Examples: Black box VI, Hamiltonian MC, stochastic gradient MCMC, generative adversarial networks.
- ► Infrastructure to develop your own algorithms.

Criticism

► Examples: Scoring rules, hypothesis tests, predictive checks.

Built on TensorFlow (features distributed computing, GPUs, autodiff).

```
# DATA
x_{data} = np.array([0, 1, 0, 0, 0, 0, 0, 0, 0, 1])
# MODEL
p = Beta(a=1.0, b=1.0)
x = Bernoulli(p=tf.ones(10) * p)
# VARIATIONAL DISTRIBUTION
qp_a = tf.nn.softplus(tf.Variable(tf.random_normal([])))
qp_b = tf.nn.softplus(tf.Variable(tf.random_normal([])))
qp = Beta(a=qp_a, b=qp_b)
# INFERENCE
inference = ed.KLqp(\{p: qp\}, data=\{x: x_data\})
inference.run(n_iter=500)
# CRITICISM
x_post = ed.copy(x, \{p : qp\})
def T(xs, zs):
  return tf.reduce_mean(xs[x_post])
ed.ppc(T, data={x_post: x_data})
```

- [1] G. E. P. Box and William G. Hunter. "A Useful Method for Model-Building". In: *Technometrics* 4.3 (1962), pp. 301–318. JSTOR: 1266570.
- [2] G. E. P. Box and William G. Hunter. "The Experimental Study of Physical Mechanisms". In: *Technometrics* 7.1 (1965), pp. 23–42. JSTOR: 1266125.
- [3] G. E. P. Box and W. J. Hill. "Discrimination among Mechanistic Models". In: *Technometrics* 9.1 (1967), pp. 57–71. JSTOR:1266318.
- [4] George E. P. Box. "Science and Statistics". In: *Journal of the American Statistical Association* 71.356 (1976), pp. 791–799. JSTOR: 2286841.
- [5] George E. P. Box. "Sampling and Bayes' Inference in Scientific Modelling and Robustness". In: Journal of the Royal Statistical Society. Series A (General) 143.4 (1980), pp. 383–430. JSTOR: 2982063.
- [6] David M. Blei. "Build, Compute, Critique, Repeat: Data Analysis with Latent Variable Models". In: Annual Review of Statistics and Its Application 1.1 (2014), pp. 203–232.
- [7] Dustin Tran et al. "Deep Probabilistic Programming". In: (Jan. 13, 2017). arXiv: 1701.03757 [cs, stat].