BeagleBone AI System Reference Manual (SRM)

(BB AI Image)

THIS DOCUMENT

Supply comments and errors via https://github.com/beagleboard/beaglebone-ai/issues.

All information in this document is subject to change without notice.

For an up to date version of this document refer to:

https://github.com/beagleboard/beaglebone-ai/wiki/System-Reference-Manual

BeagleBone AI Design

REGULATORY AND COMPLIANCE INFORMATION

WARNINGS, RESTRICTIONS, AND DISCLAIMERS

WARRANTY

Table of Contents (insert here)

1.0 Introduction

Built on the proven BeagleBoard.org® open source Linux approach, BeagleBone® AI fills the gap between small SBCs and more powerful industrial computers. Based on the Texas Instruments AM5729, developers have access to the powerful SoC with the ease of BeagleBone® Black header and mechanical compatibility. BeagleBone® AI makes it easy to explore how artificial intelligence (AI) can be used in every-day life via TI C66x digital-signal-processor (DSP) cores and embedded-vision-engine (EVE) cores supported through an optimized TIDL machine learning OpenCL API with pre-installed tools. Focused on everyday automation in industrial, commercial and home applications.

2.0 Change History

2.1 Document Change History

2.2 Board changes

2.2.1 Rev A0

Initial prototype revision. Not taken to production.

2.2.2 Rev A1

Second round prototype.

- Fixed size of mounting holes.
- Added LED for WiFi status.
- Added microHDMI.
- Changed eMMC voltage from 3.3V to 1.8V to support HS200.
- Changed eMMC from 4GB to 16GB.
- Changed serial debug header from 6-pin 100mil pitch to 3-pin 1.5mm pitch.
- Switched expansion header from UART4 to UART5. The UART4 pins were used for the microHDMI.

2.2.3 Rev A1a

Pilot run.

- Added pull-down resistor on serial debug header RX line.

2.2.4 Rev A2

Proposed changes.

- Moved microSD card cage closer to microHDMI to fit cases better.
- Connected AM5729 ball AB10 to to P9.13 to provide a GPIO.
- HDMI hot-plug detection fixes planned (TBD).

3.0 Connecting Up Your BeagleBone AI

3.1 What's In the Box

3.2 Main Connection Scenarios

3.3 Tethered to a PC

3.4 Standalone w/Display and Keyboard/Mouse

4.0 BeagleBone AI Overview

4.1 BeagleBone Compatibility (Do we want this?)

4.2 BeagleBone AI Features

Main Processor Features

- Dual 1.5GHz ARM® Cortex®-A15 with out-of-order speculative issue 3-way superscalar execution pipeline for the fastest execution of existing 32-bit code
- 2 466x Floating-Point VLIW DSP supported by OpenCL
- 4 Embedded Vision Engines (EVEs) supported by TIDL machine learning library
- 2x Dual-Core Programmable Real-Time Unit (PRU) subsystems (4 PRUs total) for ultra low-latency control and software generated peripherals
- 2x Dual ARM® Cortex®-M4 co-processors for real-time control
- IVA-HD subsystem with support for 4K @ 15fps H.264 encode/decode and other codecs @ 1080p60
- Vivante® GC320 2D graphics accelerator
- Dual-Core PowerVR® SGX544™ 3D GPU

Communications

- BeagleBone Black header and mechanical compatibility
- 16-bit LCD interfaces
- 4+ UARTs
- 2 I2C ports
- 2 SPI ports
- Lots of PRU I/O pins

Memory

- 1GB RAM
- 16GB on-board eMMC flash

Connectors

- USB Type-C connector for power and SuperSpeed dual-role controller
- Gigabit Ethernet
- 802.11ac 2.4/5GHz WiFi

Out of Box Software

- Zero-download out of box software environment

4.3 Board Component Locations

5.0 BeagleBone AI High Level Specification

Block Diagram

Processor

DSP

EVEs

PRUs

Graphics Accelerator

Memory

Power

Connectivity

6.0 Detailed Hardware Design

This section provides a detailed description of the Hardware design. This can be useful for interfacing, writing drivers, or using it to help modify specifics of your own design.

Figure ? below is the high level block diagram of the board.

(Block Diagram Picture)

Figure ?. BeagleBone AI Block Diagram

6.1 Power Section

Figure ? is the high level block diagram of the power section of the board.

(Block Diagram for Power)

6.1.1 TPS6590377 PMIC

(Info from Datasheet)

(Block Diagram from Datasheet)

6.1.2 USB-C Power

Figure 23 below shows how the USB-C power input is connected to the **TPS6590377**.

(Schematic screenshoot)

6.1.3 Power Button

6.1.4

7.0 Connectors

7.1 Expansion Connectors

The expansion interface on the board is comprised of two 46 pin connectors. All signals on the expansion headers are **3.3V** unless otherwise indicated.

NOTE: Do not connect 5V logic level signals to these pins or the board will be damaged.

NOTE: DO NOT APPLY VOLTAGE TO ANY I/O PIN WHEN POWER IS NOT SUPPLIED TO THE BOARD. IT WILL DAMAGE THE PROCESSOR AND VOID THE WARRANTY.

NO PINS ARE TO BE DRIVEN UNTIL AFTER THE SYS_RESET LINE GOES HIGH.

Figure ? shows the location of the expansion connectors.

Insert Figure Here

The location and spacing of the expansion headers are the same as on the BeagleBone Black.

7.1.1 Connector P8

Table ? shows the pinout of the **P8** expansion header. Other signals can be connected to this connector based on setting the pin mux on the processor, but this is the default settings on power up. The SW is responsible for setting the default function of each pin. There are some signals that have not been listed here. Refer to the processor documentation for more information on these pins and detailed descriptions of all of the pins listed. In some cases there may not be enough signals to complete a group of signals that may be required to implement a total interface.

The **PROC** column is the pin number on the processor.

The **PIN** column is the pin number on the expansion header.

The **MODE** columns are the mode setting for each pin. Setting each mode to align with the mode column will give that function on that pin.

NOTE: DO NOT APPLY VOLTAGE TO ANY I/O PIN WHEN POWER IS NOT SUPPLIED TO THE BOARD. IT WILL DAMAGE THE PROCESSOR AND VOID THE WARRANTY.

NO PINS ARE TO BE DRIVEN UNTIL AFTER THE SYS_RESET LINE GOES HIGH.

Table ? Expansion Header P8 Pinout

PIN	PROC	NAME	MODE0	MODE1	MODE2	MODE3	MODE4
1		GND					
2		GND					
3	AB8	AB8_MMC3_DATA6	mmc3_dat6	spi4_d0	uart10_ctsn		vin2b_de1
4	AB5	AB5_MMC3_DATA7	mmc3_dat7	spi4_cs0	uart10_rtsn		vin2b_clk1
5	AC9	AC9_MMC3_DATA2	mmc3_dat2	spi3_cs0	uart5_ctsn		vin2b_d3
6	AC3	AC3_MMC3_DATA3	mmc3_dat3	spi3_cs1	uart5_rtsn		vin2b_d2
7	G14	G14_TIMER11	mcasp1_axr14	mcasp7_aclkx	mcasp7_aclkr		
8	F14	F14_TIMER12	mcasp1_axr15	mcasp7_fsx	mcasp7_fsr		
9	E17	E17_TIMER14	xref_clk1	mcasp2_axr9	mcasp1_axr5	mcasp2_ahclkx	mcasp6_ahclkx
10	A13	A13_TIMER10	mcasp1_axr13	mcasp7_axr1			
11	AH4	AH4_GPIO3_11	vin1a_d7			vout3_d0	vout3_d16
12	AG6	AG6_GPIO3_10	vin1a_d6			vout3_d1	vout3_d17
13	D3	D3_EHRPWM2B	vin2a_d10			mdio_mclk	vout2_d13
14	D5	D5_GPIO4_13	vin2a_d12			rgmii1_txc	vout2_d11

PIN	PROC	NAME	MODE0	MODE1	MODE2	MODE3	MODE4
15	D1	GPIO4_3	vin2a_d2				vout2_d21
	A3		vin2a_d19		vin2b_d4	rgmii1_rxctl	vout2_d4
16	B4	B4_GPIO4_29	vin2a_d21		vin2b_d2	rgmii1_rxd2	vout2_d2
17	A7	A7_GPIO8_18	vout1_d18		emu4	vin4a_d2	vin3a_d2
18	F5	F5_GPIO4_9	vin2a_d8				vout2_d15
19	E6	E6_EHRPWM2A	vin2a_d9				vout2_d14
20	AC4	AC4_MMC3_CMD	mmc3_cmd	spi3_sclk			vin2b_d6
21	AD4	AD4_MMC3_CLK	mmc3_clk				vin2b_d7
22	AD6	AD6_MMC3_DATA5	mmc3_dat5	spi4_d1	uart10_txd		vin2b_d0
23	AC8	AC8_MMC3_DATA4	mmc3_dat4	spi4_sclk	uart10_rxd		vin2b_d1
24	AC6	AC6_MMC3_DATA1	mmc3_dat1	spi3_d0	uart5_txd		vin2b_d4
25	AC7	AC7_MMC3_DATA0	mmc3_dat0	spi3_d1	uart5_rxd		vin2b_d5
26	B3	B3_GPIO4_28	vin2a_d20		vin2b_d3	rgmii1_rxd3	vout2_d3
27	E11	LCD_VSYNC	vout1_vsync			vin4a_vsync0	vin3a_vsync0
	A8		vout1_d19		emu15	vin4a_d3	vin3a_d3
28	D11	LCD_CLK	vout1_clk			vin4a_fld0	vin3a_fld0
	C9		vout1_d20		emu16	vin4a_d4	vin3a_d4
29	C11	LCD_HSYNC	vout1_hsync			vin4a_hsync0	vin3a_hsync0
	A9		vout1_d21		emu17	vin4a_d5	vin3a_d5
30	B10	LCD_DE	vout1_de			vin4a_de0	vin3a_de0
	B9		vout1_d22		emu18	vin4a_d6	vin3a_d6
31	C8	LCD_DATA14	vout1_d14		emu13	vin4a_d14	vin3a_d14
	G16		mcasp4_axr0		spi3_d0	uart8_ctsn	uart4_rxd
32	C7	LCD_DATA15	vout1_d15		emu14	vin4a_d15	vin3a_d15
	D17		mcasp4_axr1		spi3_cs0	uart8_rtsn	uart4_txd
33	C6	LCD_DATA13	vout1_d13		emu12	vin4a_d13	vin3a_d13
	AF9		vin1a_fld0	vin1b_vsync1			vout3_clk
34	D8	LCD_DATA11	vout1_d11		emu10	vin4a_d11	vin3a_d11
	G6		vin2a_vsync0			vin2b_vsync1	vout2_vsync
35	A5	LCD_DATA12	vout1_d12		emu11	vin4a_d12	vin3a_d12
	AD9		vin1a_de0	vin1b_hsync1		vout3_d17	vout3_de
36	D7	LCD_DATA10	vout1_d10		emu3	vin4a_d10	vin3a_d10
	F2		vin2a_d0				vout2_d23
37	E8	LCD_DATA8	vout1_d8		uart6_rxd	vin4a_d8	vin3a_d8
	A21		mcasp4_fsx	mcasp4_fsr	spi3_d1	uart8_txd	i2c4_scl
38	D9	LCD_DATA9	vout1_d9		uart6_txd	vin4a_d9	vin3a_d9
	C18		mcasp4_aclkx	mcasp4_aclkr	spi3_sclk	uart8_rxd	i2c4_sda
39	F8	F8_LCD_DATA6	vout1_d6		emu8	vin4a_d22	vin3a_d22
40	E7	E7_LCD_DATA7	vout1_d7		emu9	vin4a_d23	vin3a_d23
41	E9	E9_LCD_DATA4	vout1_d4		emu6	vin4a_d20	vin3a_d20
42	F9	F9_LCD_DATA5	vout1_d5		emu7	vin4a_d21	vin3a_d21
43	F10	F10_LCD_DATA2	vout1_d2		emu2	vin4a_d18	vin3a_d18
44	G11	G11_LCD_DATA3	vout1_d3		emu5	vin4a_d19	vin3a_d19
45	F11	LCD_DATA0	vout1_d0		uart5_rxd	vin4a_d16	vin3a_d16
	B7		vout1_d16		uart7_rxd	vin4a_d0	vin3a_d0
46	G10	LCD_DATA1	vout1_d1		uart5_txd	vin4a_d17	vin3a_d17
	A10		vout1_d23		emu19	vin4a_d7	vin3a_d7

PIN	PROC	MODE5	MODE6	MODE7	MODE8	MODE9	MODE10
1							
2							

PIN	PROC	MODE5	MODE6	MODE7	MODE8	MODE9	MODE10
3	AB8					vin5a_hsync0	ehrpwm3_tripzone_input
4	AB5					vin5a_vsync0	eCAP3_in_PWM3_out
5	AC9					vin5a_d3	eQEP3_index
6	AC3					vin5a_d2	eQEP3_strobe
7	G14			vin6a_d9			timer11
8	F14			vin6a_d8			timer12
9	E17			vin6a_clk0			timer14
10	A13			vin6a_d10			timer10
11	AH4						eQEP2B_in
12	AG6						eQEP2A_in
13	D3					kbd_col7	ehrpwm2B
14	D5				mii1_rxclk	kbd_col8	eCAP2_in_PWM2_out
15	D1	emu12			uart10_rxd	kbd_row6	eCAP1_in_PWM1_out
	A3		vin3a_d11		mii1_txer		ehrpwm3_tripzone_input
16	B4	vin3a_fld0	vin3a_d13		mii1_col		
17	A7	obs11	obs27				pr2_edio_data_in2
18	F5	emu18			mii1_rxd3	kbd_col5	eQEP2_strobe
19	E6	emu19			mii1_rxd0	kbd_col6	ehrpwm2A
20	AC4					vin5a_d6	eCAP2_in_PWM2_out
21	AD4					vin5a_d7	ehrpwm2_tripzone_input
22	AD6					vin5a_d0	ehrpwm3B
23	AC8					vin5a_d1	ehrpwm3A
24	AC6					vin5a_d4	eQEP3B_in
25	AC7					vin5a_d5	eQEP3A_in
26	B3	vin3a_de0	vin3a_d12		mii1_rxer		eCAP3_in_PWM3_out
27	E11				spi3_sclk		
	A8	obs12	obs28				pr2_edio_data_in3
28	D11				spi3_cs0		
	C9	obs13	obs29				pr2_edio_data_in4
29	C11				spi3_d0		
	A9	obs14	obs30				pr2_edio_data_in5
30	B10				spi3_d1		
	B9	obs15	obs31				pr2_edio_data_in6
31	C8	obs9	obs25				pr2_uart0_txd
	G16		vout2_d18		vin4a_d18	vin5a_d13	
32	C7	obs10	obs26				pr2_ecap0_ecap_capin_apwm_o
	D17		vout2_d19		vin4a_d19	vin5a_d12	
33	C6	obs8	obs24				pr2_uart0_rxd
	AF9	uart7_txd		timer15	spi3_d1	kbd_row1	eQEP1B_in
34	D8	obs6	obs22	obs_dmarq2			pr2_uart0_cts_n
	G6	emu9		uart9_txd	spi4_d1	kbd_row3	ehrpwm1A
35	A5	obs7	obs23				pr2_uart0_rts_n
	AD9	uart7_rxd		timer16	spi3_sclk	kbd_row0	eQEP1A_in
36	D7	obs5	obs21	obs_irq2			pr2_edio_sof
	F2	emu10		uart9_ctsn	spi4_d0	kbd_row4	ehrpwm1B
37	E8						pr2_edc_sync1_out
	A21		vout2_d17		vin4a_d17	vin5a_d14	
38	D9						pr2_edio_latch_in
	C18		vout2_d16		vin4a_d16	vin5a_d15	
39	F8	obs4	obs20				pr2_edc_latch1_in
40	E7						pr2_edc_sync0_out
41	E9	obs2	obs18				pr1_ecap0_ecap_capin_apwm_o

PIN	PROC	MODE5	MODE6	MODE7	MODE8	MODE9	MODE10
42	F9	obs3	obs19				pr2_edc_latch0_in
43	F10	obs0	obs16	obs_irq1			pr1_uart0_rxd
44	G11	obs1	obs17	obs_dmarq1			pr1_uart0_txd
45	F11				spi3_cs2		pr1_uart0_cts_n
	B7						pr2_edio_data_in0
46	G10						pr1_uart0_rts_n
	A10				spi3_cs3		pr2_edio_data_in7

PIN	PROC	MODE11	MODE12	MODE13	MODE14
1					
2					
3	AB8	pr2_mii1_rxd1	pr2_pru0_gpi10	pr2_pru0_gpo10	gpio1_24
4	AB5	pr2_mii1_rxd0	pr2_pru0_gpi11	pr2_pru0_gpo11	gpio1_25
5	AC9	pr2_mii_mr1_clk	pr2_pru0_gpi6	pr2_pru0_gpo6	gpio7_1
6	AC3	pr2_mii1_rxdv	pr2_pru0_gpi7	pr2_pru0_gpo7	gpio7_2
7	G14	pr2_mii0_rxdv	pr2_pru1_gpi16	pr2_pru1_gpo16	gpio6_5
8	F14	pr2_mii0_rxd3	pr2_pru0_gpi20	pr2_pru0_gpo20	gpio6_6
9	E17	pr2_mii1_crs	pr2_pru1_gpi6	pr2_pru1_gpo6	gpio6_18
10	A13	pr2_mii_mr0_clk	pr2_pru1_gpi15	pr2_pru1_gpo15	gpio6_4
11	AH4		pr1_pru0_gpi4	pr1_pru0_gpo4	gpio3_11
12	AG6		pr1_pru0_gpi3	pr1_pru0_gpo3	gpio3_10
13	D3	pr1_mdio_mdclk	pr1_pru1_gpi7	pr1_pru1_gpo7	gpio4_11
14	D5	pr1_mii1_txd1	pr1_pru1_gpi9	pr1_pru1_gpo9	gpio4_13
15	D1	pr1_ecap0_ecap_capin_apwm_o	pr1_edio_data_in7	pr1_edio_data_out7	gpio4_3
	A3	pr1_mii1_rxd0	pr1_pru1_gpi16	pr1_pru1_gpo16	gpio4_27
16	B4	pr1_mii1_rxlink	pr1_pru1_gpi18	pr1_pru1_gpo18	gpio4_29
17	A7	pr2_edio_data_out2	pr2_pru0_gpi15	pr2_pru0_gpo15	gpio8_18
18	F5	pr1_mii1_txd3	pr1_pru1_gpi5	pr1_pru1_gpo5	gpio4_9
19	E6	pr1_mii1_txd2	pr1_pru1_gpi6	pr1_pru1_gpo6	gpio4_10
20	AC4	pr2_mii1_txd2	pr2_pru0_gpi3	pr2_pru0_gpo3	gpio6_30
21	AD4	pr2_mii1_txd3	pr2_pru0_gpi2	pr2_pru0_gpo2	gpio6_29
22	AD6	pr2_mii1_rxd2	pr2_pru0_gpi9	pr2_pru0_gpo9	gpio1_23
23	AC8	pr2_mii1_rxd3	pr2_pru0_gpi8	pr2_pru0_gpo8	gpio1_22
24	AC6	pr2_mii1_txd0	pr2_pru0_gpi5	pr2_pru0_gpo5	gpio7_0
25	AC7	pr2_mii1_txd1	pr2_pru0_gpi4	pr2_pru0_gpo4	gpio6_31
26	B3	pr1_mii1_rxer	pr1_pru1_gpi17	pr1_pru1_gpo17	gpio4_28
27	E11		pr2_pru1_gpi17	pr2_pru1_gpo17	gpio4_23
	A8	pr2_edio_data_out3	pr2_pru0_gpi16	pr2_pru0_gpo16	gpio8_19
28	D11				gpio4_19
	C9	pr2_edio_data_out4	pr2_pru0_gpi17	pr2_pru0_gpo17	gpio8_20
29	C11				gpio4_22
	A9	pr2_edio_data_out5	pr2_pru0_gpi18	pr2_pru0_gpo18	gpio8_21
30	B10				gpio4_20
	B9	pr2_edio_data_out6	pr2_pru0_gpi19	pr2_pru0_gpo19	gpio8_22
31	C8		pr2_pru0_gpi11	pr2_pru0_gpo11	gpio8_14
	G16				
32	C7		pr2_pru0_gpi12	pr2_pru0_gpo12	gpio8_15
	D17		pr2_pru1_gpi0	pr2_pru1_gpo0	
33	C6		pr2_pru0_gpi10	pr2_pru0_gpo10	gpio8_13
	AF9				gpio3_1
34	D8		pr2_pru0_gpi8	pr2_pru0_gpo8	gpio8_11

PIN	PROC	MODE11	MODE12	MODE13	MODE14
	G6	pr1_uart0_rts_n	pr1_edio_data_in4	pr1_edio_data_out4	gpio4_0
35	A5		pr2_pru0_gpi9	pr2_pru0_gpo9	gpio8_12
	AD9				gpio3_0
36	D7		pr2_pru0_gpi7	pr2_pru0_gpo7	gpio8_10
	F2	pr1_uart0_rxd	pr1_edio_data_in5	pr1_edio_data_out5	gpio4_1
37	E8		pr2_pru0_gpi5	pr2_pru0_gpo5	gpio8_8
	A21				
38	D9		pr2_pru0_gpi6	pr2_pru0_gpo6	gpio8_9
	C18				
39	F8		pr2_pru0_gpi3	pr2_pru0_gpo3	gpio8_6
40	E7		pr2_pru0_gpi4	pr2_pru0_gpo4	gpio8_7
41	E9		pr2_pru0_gpi1	pr2_pru0_gpo1	gpio8_4
42	F9		pr2_pru0_gpi2	pr2_pru0_gpo2	gpio8_5
43	F10		pr2_pru1_gpi20	pr2_pru1_gpo20	gpio8_2
44	G11		pr2_pru0_gpi0	pr2_pru0_gpo0	gpio8_3
45	F11		pr2_pru1_gpi18	pr2_pru1_gpo18	gpio8_0
	B7	pr2_edio_data_out0	pr2_pru0_gpi13	pr2_pru0_gpo13	gpio8_16
46	G10		pr2_pru1_gpi19	pr2_pru1_gpo19	gpio8_1
	A10	pr2_edio_data_out7	pr2_pru0_gpi20	pr2_pru0_gpo20	gpio8_23

PIN	PROC
1	
2	
3	AB8
4	AB5
5	AC9
6	AC3
7	G14
8	F14
9	E17
10	A13
11	AH4
12	AG6
13	D3
14	D5
15	D1
	A3
16	B4
17	A7
18	F5
19	E6
20	AC4
21	AD4
22	AD6
23	AC8
24	AC6
25	AC7
26	B3
27	E11
	A8
28	D11

PIN	PROC
	C9
29	C11
	A9
30	B10
	B9
31	C8
	G16
32	C7
	D17
33	C6
	AF9
34	D8
	G6
35	A5
	AD9
36	D7
	F2
37	E8
	A21
38	D9
	C18
39	F8
40	E7
41	E9
42	F9
43	F10
44	G11
45	F11
	B7
46	G10
	A10

Notes regarding the resistors on muxed pins.

7.1.2 Connector P9

Table ? lists the signals on connector **P9**. Other signals can be connected to this connector based on setting the pin mux on the processor, but this is the default settings on power up.

There are some signals that have not been listed here. Refer to the processor documentation for more information on these pins and detailed descriptions of all of the pins listed. In some cases there may not be enough signals to complete a group of signals that may be required to implement a total interface.

The **PROC** column is the pin number on the processor.

The **PIN** column is the pin number on the expansion header.

The **MODE** columns are the mode setting for each pin. Setting each mode to align with the mode column will give that function on that pin.

NOTES:

In the table are the following notations:

PWR_BUT is a 5V level as pulled up internally by the TPS6590377. It is activated by pulling the signal to GND.

(Actually, on BeagleBone AI, I believe PWR_BUT is pulled to 3.3V, but activation is still done by pulling the signal to GND. Also, a quick grounding of PWR_BUT will trigger a system event where shutdown can occur, but there is no hardware power-off function like on BeagleBone Black via this signal. It does, however, act as a hardware power-on.)

NOTE: DO NOT APPLY VOLTAGE TO ANY I/O PIN WHEN POWER IS NOT SUPPLIED TO THE BOARD. IT WILL DAMAGE THE PROCESSOR AND VOID THE WARRANTY.

NO PINS ARE TO BE DRIVEN UNTIL AFTER THE SYS_RESET LINE GOES HIGH.

(On BeagleBone Black, SYS_RESET was a bi-directional signal, but it is only an output from BeagleBone AI to capes on BeagleBone AI.)

Table ?. Expansion Header P9 Pinout

(Please update the table to look reasonable on both web pages and in PDF.)

PIN	PROC	NAME	MODE0	MODE1	MODE2	MODE3	MODE4	MODE5	MODE6	MODE7	MODE8	MODE9	MODE10	MODE11	MODE12	MODE13	MODE14
1		GND															
2		GND															
3	AB8	AB8_MMC3_DAT6	MMC3_dat6	gpmc_a16	uart10_ctsn	vin2b_de1						vin5a_hsync0	shrpwm3_tripzone_in	pr2_pru1_gpi10	pr2_pru0_gpo10	gpio1_12	gpio4_24
4	AB5	AB5_MMC3_DAT7	MMC3_dat7	gpmc_a17	uart10_rtsn	vin2b_clk1						vin5a_vsync0	eCAP3_in_PWM3_out	pr2_pru1_gpi11	pr2_pru0_gpo11	gpio1_13	gpio4_25
4	AC9	AC9_MMC3_DAT2	MMC3_dat2	gpmc_a12	uart5_ctsn	vin2b_d3						vin5a_d3	eQEP3_index	pr2_mii_mrxclk	pr2_pru0_gpi6	gpio1_6	gpio3_7
6	AC3	AC3_MMC3_DAT3	MMC3_dat3	gpmc_a13	uart5_rtsn	vin2b_d2						vin5a_d2	eQEP3_strobe	pr2_mii_mrxdv	pr2_pru0_gpi7	gpio1_7	gpio3_2
7	G14	G14_TIMER5	mcasp1_axr1	mcasp7_aclkr					vin6a_d9				timer11	pr2_mii0_txd2	pr2_pru1_gpi16	gpio1_16	gpio6_5
8	F14	F14_TIMER6	mcasp1_axr0	mcasp7_fsr					vin6a_d8				timer12	pr2_mii0_txd3	pr2_pru1_gpi17	gpio1_17	gpio6_6
9	E17	E17_TIMER4	mcasp1_aclkx	mcasp2_axr9	mcasp1_axr5	mcasp2_aclkx	ahclkx		vin6a_clk0				timer14	pr2_mii1_txd2	pr2_pru1_gpi18	gpio1_18	gpio6_18
10	A13	A13_TIMER7	mcasp1_fsx	mcasp7_axr1					vin6a_d10				timer10	pr2_mii_mrxclk	pr2_pru1_gpi15	gpio1_15	gpio6_4
11	AH4	AH4_GPIO3_11	GPIO3_11			vout3_d0	vout3_d16						eQEP2B_in		pr1_pru0_gpi4	pr1_pru0_gpo4	gpio3_11
12	AG6	AG6_GPIO3_10	GPIO3_10			vout3_d1	vout3_d17						eQEP2A_in		pr1_pru0_gpi3	pr1_pru0_gpo3	gpio3_10
13	D3	D3_EHRPWM2B	EHRPWM2B			mdio_mclk	vout2_d13					kbd_col7	ehrpwm2B	pr1_mdio_mdclk	pr1_pru1_gpi7	pr1_pru1_gpo7	gpio4_11
14	D5	D5_GPIO4_13	GPIO4_13			rgmii1_txc	vout2_d11				mii1_rxdv	kbd_col6	eCAP2_in_PWM2_out	pr1_mii1_txd1	pr1_pru1_gpi9	pr1_pru1_gpo9	gpio4_13
15	D1	GPIO4_14	vin2a_d2				vout2_d21	emu12			uart10_rxd	kbd_row6	eCAP1_in_PWM1_out	pr1_edio_data_in6	pr1_edio_data_out6	pr1_edio_sel_out6	gpio4_30
	A3		vin2a_d19		vin2b_d4	rgmii1_rxc	vout2_d4		vin3a_d11		mii1_txer		ehrpwm3_tripzone_in	pr1_mii1_txd0	pr1_pru1_gpi16	pr1_pru1_gpo16	gpio4_27
16	B4	B4_GPIO4_29	vin2a_d21		vin2b_d2	rgmii1_rxd2	vout2_d2	n3a_fld0	in3a_d13		mii1_col			pr1_mii1_rxlink	pr1_pru1_gpi8	pr1_pru1_gpo8	gpio4_29
17	A7	A7_GPIO4_18	vout1_d18	emu4	vin4a_d2	n3a_d2	obs11	obs27					pr2_edio_data_in2	pr2_edio_data_out2	pr2_pru0_gpi5	pr2_pru0_gpo5	gpio4_18
18	F5	F5_GPIO4_9	vin2a_d8			vout2_d15	emu18				mii1_rxdv	kbd_col3	eQEP2_strobe	pr1_mii1_txd3	pr1_pru1_gpi5	pr1_pru1_gpo5	gpio4_9
19	E6	E6_EHRPWM2A	EHRPWM2A			vout2_d14	emu19				mii1_rxdv	kbd_col8	ehrpwm2A	pr1_mii1_txd2	pr1_pru1_gpi6	pr1_pru1_gpo6	gpio4_10
20	AC4	AC4_MMC3_SPI3_sclk	MMC3_spi3_sclk			vin2b_d6						vin5a_d6	eCAP2_in_PWM2_out	pr2_pru1_gpi14	pr2_pru0_gpo14	pr2_pru0_gpo14	gpio6_30
21	AD4	AD4_MMC3_CLK	MMC3_clk			vin2b_d7						vin5a_d7	ehrpwm2_tripzone_in	pr2_pru1_gpi13	pr2_pru0_gpo13	pr2_pru0_gpo13	gpio6_29
22	AD6	AD6_MMC3_DAT5	MMC3_dat5	gpmc_a15	uart10_txd	vin2b_d0						vin5a_d4	ehrpwm3B	pr2_mii1_txd2	pr2_pru0_gpi9	pr2_pru0_gpo9	gpio6_19
23	AC8	AC8_MMC3_DAT4	MMC3_dat4	gpmc_a14	uart10_rxd	vin2b_d1						vin5a_d5	ehrpwm3A	pr2_mii1_txd3	pr2_pru0_gpi8	pr2_pru0_gpo8	gpio6_22
24	AC6	AC6_MMC3_DAT1	MMC3_dat1	gpmc_a11	uart5_txd	vin2b_d4						vin5a_d0	eQEP3B_in	pr2_mii1_txd0	pr2_pru0_gpi5	pr2_pru0_gpo5	gpio6_7
25	AC7	AC7_MMC3_DAT0	MMC3_dat0	gpmc_a10	uart5_rxd	vin2b_d5						vin5a_d1	eQEP3A_in	pr2_mii1_txd1	pr2_pru0_gpi4	pr2_pru0_gpo4	gpio6_31
26	B3	B3_GPIO4_28	vout1_d20	vin2b_d3	rgmii1_rxc	vout2_d3	n3a_d10	obs12			mii1_rxer		eCAP3_in_PWM3_out	pr1_mii1_txd4	pr1_pru1_gpi17	pr1_pru1_gpo17	gpio4_28
27	E11	LCD_VSYNC	vout1_vsync		vin4a_vsync0	vin3a_vsync0					spi3_sclk			pr2_pru1_gpi17	pr2_pru1_gpo17		gpio4_23
	A8		vout1_d19	emu15	vin4a_d3	n3a_d3	obs12	obs28					pr2_edio_data_in3	pr2_edio_data_out3	pr2_pru0_gpi10	pr2_pru0_gpo10	gpio6_16
28	D11	LCD_CLK	vout1_clk		vin4a_fld0	vin3a_fld0					spi3_cs0						gpio4_19
	C9		vout1_d20	emu16	vin4a_d4	n3a_d4	obs13	obs29					pr2_edio_data_in4	pr2_edio_data_out4	pr2_pru0_gpi7	pr2_pru0_gpo7	gpio6_20
29	C11	LCD_HSYNC	vout1_hsync		vin4a_hsync0	vin3a_hsync0					spi3_d0						gpio4_22
	A9		vout1_d21	emu17	vin4a_d5	n3a_d5	obs14	obs30					pr2_edio_data_in5	pr2_edio_data_out5	pr2_pru0_gpi8	pr2_pru0_gpo8	gpio6_21
30	B10	LCD_DE	vout1_de		vin4a_de0	vin3a_de0					spi3_d1						gpio4_20
	B9		vout1_d22	emu18	vin4a_d6	n3a_d6	obs15	obs31					pr2_edio_data_in6	pr2_edio_data_out6	pr2_pru0_gpi9	pr2_pru0_gpo9	gpio6_22
31	C8	LCD_DATA14	vout1_d14	emu13	vin4a_d14	n3a_d14	obs9	obs25					pr2_uart0_txd	pr2_pru0_gpi1	pr2_pru0_gpo1		gpio6_14
	G16		mcasp4_axr0	spi3_d0	uart8_ctsn	uart4_rxd		vout2_d18			vin4a_d18	n5a_d13					
32	C7	LCD_DATA15	vout1_d15	emu14	vin4a_d15	n3a_d15	obs10	obs26					pr2_ecap0_ecap_in_	pr2_pru0_gpi2	pr2_pru0_gpo2		gpio6_15
	D17		mcasp4_axr1	spi3_cs0	uart8_rtsn	uart4_txd		vout2_d19			vin4a_d19	n5a_d12		pr2_pru1_gpi1	pr2_pru1_gpo0		
33	C6	LCD_DATA13	vout1_d13	emu12	vin4a_d13	n3a_d13	obs8	obs24					pr2_uart0_rxd	pr2_pru0_gpi0	pr2_pru0_gpo0		gpio6_13

PIN	PROC	NAME	MODE0	MODE1	MODE2	MODE3	MODE4	MODE5	MODE6	MODE7	MODE8	MODE9	MODE10	MODE11	MODE12	MODE13	MODE14
	AF9		vin1a_fld1	mcasp4_axr1	vin1b_vsync1		vout3_d11	uart7_txd		timer15	spi3_d1	kbd_row0	eQEP1B_in				gpio3_1
34	D8	LCD_DATA11	ATA11	mcasp4_fsx	emu10	vin4a_d11	vin3a_d11	obs6	obs22	obs_dmarq2			pr2_uart0_cts_n		pr2_pru0_pru_r30_15	pr2_pru0_pru_r31_15	gpio3_11
	G6		vin2a_vsync0			vin2b_vsync1	vout2_vsync	emu9		uart9_txd	spi4_d1	kbd_row3	ehrpwm1A	mcasp1_axr0	pr1_uart0_rts_n	pr1_edio_data_out4	gpio4_0
35	A5	LCD_DATA12	ATA12	mcasp4_axr2	emu11	vin4a_d12	vin3a_d12	obs7	obs23				pr2_uart0_rts_n		pr2_pru0_pru_r30_9	pr2_pru0_pru_r31_9	gpio3_12
	AD9		vin1a_de1	vin1b_hsync1		vout3_d17	vout3_de	uart7_rxd		timer16	spi3_sck	kbd_row1	eQEP1A_in				gpio3_0
36	D7	LCD_DATA10	ATA10	mcasp4_axr1	emu3	vin4a_d10	vin3a_d10	obs5	obs21	obs_irq2			pr2_edio_sof		pr2_pru0_pru_r30_7	pr2_pru0_pru_r31_7	gpio3_10
	F2		vin2a_d0			vout2_d23	emu10			uart9_rxd	spi4_d0	kbd_row4	ehrpwm1B	mcasp1_axr1	pr1_edio_data_out5	pr1_edio_data_in5	gpio4_1
37	E8	LCD_DATA13	ATA13	mcasp4_axr3	uart6_rxd	vin4a_d13	vin3a_d13						pr2_edc_sync1_out		pr2_pru0_pru_r30_5	pr2_pru0_pru_r31_5	gpio3_13
	A21		mcasp4_fsx	mcasp4_axr0	spi3_d1	uart8_txd	i2c4_scl		vout2_d17		vin4a_d17	vin5a_d14					
38	D9	LCD_DATA9	ATA9	mcasp4_aclkx	uart6_txd	vin4a_d9	vin3a_d9						pr2_edio_latch_in		pr2_pru0_pru_r30_6	pr2_pru0_pru_r31_6	gpio3_9
	C18		mcasp4_aclkx	mcasp4_axr0	spi3_clk	uart8_rxd	i2c4_sda		vout2_d16		vin4a_d16	vin5a_d15					
39	F8	F8_LCD_DATA6	vout1_DATA6		emu8	vin4a_d22	vin3a_d22	obs4	obs20				pr2_edc_latch1_in		pr2_pru0_pru_r30_3	pr2_pru0_pru_r31_3	gpio3_6
40	E7	E7_LCD_DATA7	vout1_DATA7		emu9	vin4a_d23	vin3a_d23						pr2_edc_sync0_out		pr2_pru0_pru_r30_4	pr2_pru0_pru_r31_4	gpio3_7
41	E9	E9_LCD_DATA4	vout1_DATA4		emu6	vin4a_d20	vin3a_d20	obs2	obs18				pr1_ecap0_ecap_cap		pr2_pru0_pru_r30_1	pr2_pru0_pru_r31_1	gpio3_4
42	F9	F9_LCD_DATA5	vout1_DATA5		emu7	vin4a_d21	vin3a_d21	obs3	obs19				pr2_edc_latch0_in		pr2_pru0_pru_r30_2	pr2_pru0_pru_r31_2	gpio3_5
43	F10	F10_LCD_DATA2	vout1_DATA2		emu2	vin4a_d18	vin3a_d18	obs0	obs16	obs_irq1			pr1_uart0_rxd		pr2_pru1_pru_r30_10	pr2_pru1_pru_r31_10	gpio3_2
44	G11	G11_LCD_DATA3	vout1_DATA3		emu5	vin4a_d19	vin3a_d19	obs1	obs17	obs_dmarq1			pr1_uart0_txd		pr2_pru0_pru_r30_0	pr2_pru0_pru_r31_0	gpio3_3
45	F11	LCD_DATA0	vout1_d0	uart5_rxd	vin4a_d16	vin3a_d16					spi3_cs2		pr1_uart0_cts_n		pr2_pru1_pru_r30_8	pr2_pru1_pru_r31_8	gpio3_0
	B7		vout1_d16	uart7_rxd	vin4a_d0	vin3a_d0							pr2_edio_data_out0	pr2_edio_data_in0	pr2_pru0_pru_r30_16	pr2_pru0_pru_r31_16	gpio3_16
46	G10	LCD_DATA1	vout1_d1	uart5_txd	vin4a_d17	vin3a_d17							pr1_uart0_rts_n		pr2_pru1_pru_r30_9	pr2_pru1_pru_r31_9	gpio3_1
	A10		vout1_d23	emu19	vin4a_d7	vin3a_d7					spi3_cs3		pr2_edio_data_out7	pr2_edio_data_in7	pr2_pru0_pru_r30_20	pr2_pru0_pru_r31_20	gpio3_23

8.0 Cape Board Support

9.0 BeagleBone AI Mechanical

10.0 Pictures

BeagleBone AI Back of Board Image


BeagleBone AI REV A1
beagleboard.org
AM57X
U4
U2
U37
J41



11.0 Support Information