

## Problem 1

### MEME Implementation

Write a program, `learn_motif.py`, that takes as input a set of DNA sequences and an integer width  $W$  and learns an OOPS model for a motif of width  $W$ .

```

1: function OOPS_EXHAUSTIVE(input_seqs,  $W$ ,  $\pi_{init}$ )
2:    $bestProb = -\infty$ 
3:   for  $W$ -mer in input_seqs do
4:      $pwm \leftarrow get\_init\_pwm(W\text{-mer})$ 
5:      $Z, prob \leftarrow E\_step\_get\_Z(pwm, sequences)$ 
6:     if  $prob > bestProb$  then
7:        $best\_Z, best\_prob \leftarrow Z, prob$ 
8:        $best\_pwm \leftarrow M\_step\_get\_pwm(Z, sequences)$ 
9:     end if
10:     $pwm, Z \leftarrow best\_pwm, best\_Z$ 
11:  end for
12:  while not Converged do
13:     $Z \leftarrow E\_step\_get\_Z(pwm, sequences)$ 
14:     $pwm' \leftarrow M\_step\_get\_pwm(Z, sequences)$ 
15:     $Converged \leftarrow |pwm' - pwm| < tol$ 
16:     $pwm \leftarrow pwm'$ 
17:  end while
18:  Write  $pwm, Z_{i,max}, \dots$ 
19: end function

```

Algorithm 1: Exhaustive Start OOPS Algorithm

## Problem 2

### Motif Discovery

We suppose the input sequences in the file `hw1_hidden.txt` come from the promoter regions of 100 yeast genes that are differentially expressed in a stress response experiment. We would like to use motif finding to learn more about a candidate regulator (transcription factor) of this expression response. Using our program from part I, we find the best OOPS motif of width 8:

ch	BG	Pos1	Pos2	Pos3	Pos4	Pos5	Pos6	Pos7	Pos8
C	0.256	0.010	0.094	0.019	0.010	0.010	0.019	0.595	0.797
A	0.241	0.240	0.010	0.022	0.970	0.856	0.020	0.251	0.010
G	0.250	0.029	0.886	0.948	0.011	0.020	0.922	0.020	0.020
T	0.252	0.721	0.010	0.011	0.010	0.114	0.040	0.135	0.174

Hidden Motif PWM

### Problem 3

#### Sequence Logo

Express the PWM as a sequence Logo.



### Problem 4

#### Transcription Factor Search

To find a candidate match for our transcription factor, we go to JASPAR, "an open-access database of curated, non-redundant transcription factor (TF) binding profiles." By following the instructions on the alignment page, we see that the top hit, MA0304.1 (GCR1) is a very close match:



Others in the top 5 include MA0377.1 (SFL1), MA0305.1 (GCR2), MA0323.1 (IXR1), and MA0418.1 (YAP6), but they aren't nearly as close. The maximum possible score is two times the length of the two sequences, and the top hit was over 15, compared with 13 for second place.

There are slight differences. As the Jasper description is "Finalized", it doesn't need to use pseudo counts, and thus the informational content is marginally higher at every location.

Using the [www.yeastgenome.org](http://www.yeastgenome.org) website, we find GCR1 is a "transcriptional activator of genes involved in glycolysis." From Wikipedia, glycolysis is the metabolic pathway that breaks down glucose into pyruvate, releasing the free energy needed to create the universal fuel ATP. GCR1 is known to regulate 86 genes.

## Problem 5

### PWM Parameters

We are given the following motif solution, using no pseudocounts:

C	A	T	G	T	G	A	A
C	A	G	C	A	G	G	G
A	C	C	T	C	T	T	C
C	A	G	A	C	A	T	G
A	C	C	T	A	T	C	G
G	C	G	G	C	A	G	T
G	T	G	T	A	G	T	T
C	C	A	G	G	A	A	G
A	T	G	A	C	C	G	G
G	G	A	T	A	G	T	A

	i=1	i=2	i=3	i=4	Background
A	0.1	0.5	0.1	0.1	0.325
C	0.6	0.1	0.1	0.3	0.175
G	0.2	0.1	0.7	0.2	0.325
T	0.1	0.3	0.1	0.4	0.175

A) Extend existing solution to  $W = 5$

	i=1	i=2	i=3	i=4	i=5	Background
A	0.100	0.500	0.100	0.100	0.400	0.300
C	0.600	0.100	0.100	0.300	0.200	0.167
G	0.200	0.100	0.700	0.200	0.300	0.333
T	0.100	0.300	0.100	0.400	0.100	0.200

B) Compare Log Likelihoods

$\log_{10} P(X W = 4)$	-42.73
$\log_{10} P(X W = 5)$	-42.57
$\log_{10} P(X W = 5) - \log_{10} P(X W = 4)$	0.168

## C) Discussion

Extending the width will always give a likelihood which is greater than or equal to the shorter solution.

To see why, we can first look at the case in which  $W \ll L$ , so background probabilities are unchanged by the single extension. Then the probability of each character in each sequence will be unchanged, except for the terms in the  $w + 1$  motifs position. In the  $W_0$  case, the background probabilities  $p_{bg_c}$ , are used, and in the  $W_0 + 1$  case, the probabilities used are the Dirichlet parameters,  $p_{D_c}$ , calculated just for this position. The Dirichlet distribution was been shown to be a maximum likelihood estimator. Thus

$$\prod_{c \in seq_{W_0+1}} p_{D_c} \geq \prod_{c \in seq_{W_0+1}} p_{bg_c}$$

because it's greater than or equal for *all* distributions. Therefore

$$\frac{P(X|W = W_0 + 1)}{P(X|W = W_0)} = \prod_{c \in seq_{W_0+1}} \frac{p_{D_c}}{p_{bg_c}} \geq 1$$

For the case in which the background changes, we note that the new background probabilities,  $p_{bg'_c}$  are again MLE estimators of all non-motif characters for the case in which the  $W_0 + 1$  characters *are excluded*. So their ratio is again greater than one:

$$\prod_{c \notin motif_{W_0+1}} \frac{p_{bg'_c}}{p_{bg_c}} \geq 1$$

To complete the argument, we note when two terms that are each  $\geq 1$  are multiplied, their product is as well. This implies that while maximizing likelihood is able to find the best motif solution for a given width, it is not able to choose the *best* width.

## Listing 1: Problem 5 Code

```

import numpy as np
import itertools

ch_to_n = {el:i for i,el in enumerate('ACGT')}

def get_pwm(seqs,z1,W):
    Nc = {el:0 for el in 'ACGT'}
    for seq in seqs:
        for ch in seq:
            Nc[ch] += 1

    pwm = np.zeros((4,W+1))
    for i, seq in enumerate(seqs):
        for j in range(W):
            pwm[ch_to_n[seq[j + z1[i]]],j+1] += 1

    for ch in ch_to_n:
        pwm[ch_to_n[ch],0] = Nc[ch] - sum(pwm[ch_to_n[ch],1:W+1])

    pwm = pwm/pwm.sum(axis=0)
    return (pwm)

def get_log_prob(seqs,pwm,z1,W):
    log_pwm = np.log10(pwm)
    prob = 0
    L = len(seqs[0])
    for i,seq in enumerate(seqs):
        motif_pos = range(W)
        non_motif_range = itertools.chain(range(z1[i]),range(z1[i]+W,L))
        for j in non_motif_range:
            prob += log_pwm[ch_to_n[seq[j]],0]
        for j in motif_pos:
            prob += log_pwm[ch_to_n[seq[j+z1[i]]],j+1]
    return prob

seqs = [
    'CATGTGAA',
    'CAGCAGGG',
    'ACCTCTTC',
    'CAGACATG',
    'ACCTATCG',
    'GCGGCAGT',
    'GTGTAGTT',
    'CCAGGAAG',
    'ATGACCGG',
    'GGATAGTA']

```

```
z1 = [1,3,1,0,2,1,0,1,2,3]

print (get_pwm(seqs,z1,4))
pwm = get_pwm(seqs,z1,5)
for i, ch in enumerate('ACGT'):
    print ('_&_'.join(
        [ch]
        + [" {:.3f} ".format(el) for el in pwm[i,1:]]
        + [" {:.3f} ".format(pwm[i,0])]))
p4 = get_log_prob(seqs, get_pwm(seqs,z1,4), z1, 4)
p5 = get_log_prob(seqs, get_pwm(seqs,z1,5), z1, 5)
print("The log likelihood for W=4 solution is {:.2f} ".format(p4))
print("The log likelihood for W=5 solution is {:.2f} ".format(p5))
print("The difference is {:.3f} ".format(p5-p4))
```