

```
from typing import Union, Dict, Optional, Any, List, Tuple
```

```
# --- Spark Imports ---
```

```
from pyspark.sql import DataFrame, SparkSession
```

```
import pyspark.sql.functions as F
```

```
from pyspark.sql.types import (
```

```
    StructType,
```

```
    StructField,
```

```
    StringType,
```

```
    LongType,
```

```
    NumericType
```

```
)
```

```
# --- DQX Imports ---
```

```
from databricks.labs.dqx.profiler.profiler import DQProfiler
```

```
from databricks.labs.dqx.profiler.generator import DQGenerator
```

```
from databricks.labs.dqx.metrics_observer import DQMetricsObserver
```

```
from databricks.labs.dqx.config import (
```

```
    InputConfig,
```

```
    WorkspaceFileChecksStorageConfig,
```

```
    LLMModelConfig
```

```
)
```

```
from databricks.labs.dqx.engine import DQEngine
```

```
from databricks.sdk import WorkspaceClient
```

```
# --- Local Config ---
```

```
from dqx_config import (
```

```
    init_logging,
```

```
    get_rules_path,
```

```
    extrayendo_summary_stats,
```

```
    create_dataframe
```

```
)
```

```
logger = init_logging("dqx_quality")
```

```

#
=====

# CLASE DQXProfiling

#
=====

class DQXProfiling:
    """
    Capa central de profiling y generación de reglas de calidad (DQX).
    Diseñada para ejecución one-shot, alineada con DQX y Catalyst-friendly.
    """

    def __init__(self, workspace_client: Optional[WorkspaceClient] = None) -> None:
        self.ws = workspace_client or WorkspaceClient()
        self.profiler = DQProfiler(self.ws)
        self.generator = DQGenerator(self.ws)
        self.engine = DQEngine(self.ws)
        logger.info("DQXProfiling inicializado correctamente.")

    def profile_table(
        self,
        table_name: str,
        columns: Optional[List[str]] = None,
        options: Optional[Dict[str, Any]] = None,
        quality_check_filename: Optional[str] = None,
        save_path: Optional[str] = None,
    ):
        logger.info(f"Profiling tabla: {table_name}")

        stats, profiles = self.profiler.profile_table(
            input_config=InputConfig(location=table_name),
            columns=columns,
            options=options,
        )

```

```
return self._finalize_profiling(  
    identifier=table_name,  
    stats=stats,  
    profiles=profiles,  
    quality_check_filename=quality_check_filename,  
    save_path=save_path,  
)
```

```
def profile_dataframe(  
    self,  
    df: Any,  
    columns: Optional[List[str]] = None,  
    options: Optional[Dict[str, Any]] = None,  
    quality_check_filename: Optional[str] = None,  
    save_path: Optional[str] = None,  
):  
    logger.info("Profiling DataFrame en memoria")
```

```
    stats, profiles = self.profiler.profile(  
        df,  
        columns=columns,  
        options=options,  
    )
```

```
return self._finalize_profiling(  
    identifier="dataframe_memory",  
    stats=stats,  
    profiles=profiles,  
    quality_check_filename=quality_check_filename,  
    save_path=save_path,  
)
```

```
def _finalize_profiling(  
    self,
```

```

    identifier: str,
    stats: Dict[str, Any],
    profiles: Any,
    quality_check_filename: Optional[str],
    save_path: Optional[str],
):
    rules = self.generator.generate_dq_rules(profiles)

    final_path = get_rules_path(
        identifier,
        identifier,
        quality_check_filename,
        save_path,
    )

    self.engine.save_checks(
        rules,
        WorkspaceFileChecksStorageConfig(final_path),
    )

    logger.info(f"Reglas de profiling guardadas en: {final_path}")
    return self._summary_stats_to_df(stats)

def _summary_stats_to_df(self, summary_stats: Dict[str, Any]):
    try:
        columns_data = summary_stats.get("columns", summary_stats)
        rows = extrayendo_summary_stats(columns_data)

    schema = StructType([
        StructField("columna", StringType(), True),
        StructField("total", LongType(), True),
        StructField("nulos", LongType(), True),
        StructField("cardinalidad", LongType(), True),
        StructField("min", StringType(), True),

```

```

StructField("max", StringType(), True),
StructField("media", StringType(), True),
StructField("desviacion_estandar", StringType(), True),
])

```

```

extra_cols = [
F.when(F.col("total") > 0,
F.round((F.col("nulos") / F.col("total")) * 100, 2))
.otherwise(F.lit(0.0)).alias("porcentaje_nulos")
]

```

```

return create_dataframe(schema, rows, extra_cols)

```

```

except Exception as e:
raise e

```

```

def generate_rules_from_prompt(
self,
user_prompt: str,
input_data: Union[str, Any],
model_name: str = "databricks/databricks-claude-sonnet-4-5",
options: Optional[Dict[str, Any]] = None,
quality_check_filename: Optional[str] = None,
save_path: Optional[str] = None,
) -> None:
target_name = input_data if isinstance(input_data, str) else "dataframe_memory"
logger.info(f"IA Rules Generation | Target={target_name} | Model={model_name}")

try:
llm_config = LLMModelConfig(model_name=model_name)
ai_generator = DQGenerator(self.ws, llm_model_config=llm_config)

if isinstance(input_data, str):
checks = ai_generator.generate_dq_rules_ai_assisted(

```

```

user_input=user_prompt,
input_config=InputConfig(location=input_data),
)
else:
stats, _ = self.profiler.profile(
input_data,
options=options,
)
checks = ai_generator.generate_dq_rules_ai_assisted(
user_input=user_prompt,
summary_stats=stats,
)

final_path = get_rules_path(
target_name,
target_name if isinstance(input_data, str) else None,
quality_check_filename,
save_path,
)

self.engine.save_checks(checks, WorkspaceFileChecksStorageConfig(final_path))
logger.info(f"Reglas IA guardadas en: {final_path}")

except Exception as e:
logger.error(f"Error generando reglas con IA: {e}")
raise e

```

```

#
=====

# CLASE DQXQuality (Optimized Split + VARIANT)
#
=====

class DQXQuality:

def __init__(self, observer_name: str = "dq_monitoring_observer") -> None:

```

```
self.ws = WorkspaceClient()
self.observer = DQMetricsObserver(name=observer_name)
self.engine = DQEngine(self.ws, observer=self.observer)
logger.info(f"DQXQuality (DQX Native) inicializado.")
```

```
def apply_checks_table(
    self,
    table_name: str,
    quality_check_filename: Optional[str] = None,
    rules_path: Optional[str] = None
) -> Tuple[DataFrame, DataFrame, DataFrame]:

    spark = SparkSession.builder.getOrCreate()
    logger.info(f"Applying checks on Table: {table_name}")

    return self._execute_check_logic(
        spark.table(table_name),
        table_name,
        table_name,
        quality_check_filename,
        rules_path
    )
```

```
def apply_checks_dataframe(
    self,
    df: Any,
    quality_check_filename: Optional[str] = None,
    rules_path: Optional[str] = None
) -> Tuple[DataFrame, DataFrame, DataFrame]:

    logger.info(f"Applying checks on DataFrame en Memoria")

    return self._execute_check_logic(
        df,
        "dataframe_memory",
        "dataframe_memory",
        quality_check_filename,
```

```
rules_path
```

```
)
```

```
def _execute_check_logic(
```

```
self,
```

```
df_target: Any,
```

```
input_ref: Any,
```

```
dataset_name: str,
```

```
quality_check_filename: Optional[str],
```

```
rules_path: Optional[str]
```

```
) -> Tuple[DataFrame, DataFrame, DataFrame]:
```

```
try:
```

```
spark = SparkSession.builder.getOrCreate()
```

```
ref_for_path = input_ref if isinstance(input_ref, str) else dataset_name
```

```
final_rules_path = get_rules_path(
```

```
ref_for_path,
```

```
dataset_name,
```

```
quality_check_filename,
```

```
rules_path
```

```
)
```

```
dq_rules_raw = self.engine.load_checks(
```

```
WorkspaceFileChecksStorageConfig(final_rules_path)
```

```
)
```

```
# 1. EJECUCIÓN LAZY (DQX añade columnas _errors, _warnings)
```

```
df_enriched, observation = self.engine.apply_checks_by_metadata(
```

```
df_target,
```

```
dq_rules_raw
```

```
)
```

```
# Cacheamos porque bifurcaremos el DF en 3 caminos
```

```
df_enriched.cache()
```



```
# Trigger action
```

```
count_res = df_enriched.count()
```

```
logger.info(f"Checks procesados. Total filas: {count_res}")
```

```
# 2. SUMMARY (Control)
```

```
metrics_dict = observation.get
```

```
df_summary = self._build_summary_df(spark, metrics_dict, dataset_name)
```

```
# 3. SPLIT INTELIGENTE & TRANSFORMACIÓN
```

```
# Columnas técnicas de DQX a excluir de la data limpia y del payload VARIANT
```

```
# (Ya NO incluimos _dq_status ni _dq_validation_result aquí)
```

```
dqx_cols = ["_errors", "_warnings"]
```

```
# A) Datos Válidos: Filtramos donde array de errores está vacío
```

```
df_valid = df_enriched.filter(F.size(F.col("_errors")) == 0).drop(*dqx_cols)
```

```
# B) Datos Rechazados: Filtramos donde hay errores
```

```
df_failed_raw = df_enriched.filter(F.size(F.col("_errors")) > 0)
```

```
# Columnas de negocio = Todas - Metadatos DQX
```

```
business_cols = [c for c in df_enriched.columns if c not in dqx_cols]
```

```
# Transformación VARIANT (Solo para las filas que fallaron)
```

```
# DBR 15.3+ soporta parse_json para crear VARIANT nativo
```

```
df_rejected = df_failed_raw.select(
```

```
    F.parse_json(
```

```
        F.to_json(F.struct(*[F.col(c) for c in business_cols]))
```

```
    ).alias("row_values"),
```

```
    F.col("_errors"),
```

```
    F.col("_warnings"),
```

```
    F.current_timestamp().alias("fecha_auditoria")
```

```
)
```

```
return df_summary, df_valid, df_rejected
```

```
except Exception as e:
```

```
    logger.error(f"Error aplicando checks: {e}")
```

```
if 'df_enriched' in locals(): df_enriched.unpersist()
raise e
```

```
def _build_summary_df(self, spark: SparkSession, metrics: Dict, dataset_name: Optional[str] =
None):
```

```
rows = [(
int(metrics.get("input_row_count", 0)),
int(metrics.get("valid_row_count", 0)),
int(metrics.get("error_row_count", 0)),
int(metrics.get("warning_row_count", 0))
)]
```

```
schema = StructType([
StructField("total_filas", LongType(), True),
StructField("filas_validas", LongType(), True),
StructField("error_filas", LongType(), True),
StructField("advertencias_filas", LongType(), True)
])
```

```
extra_cols = [
F.current_timestamp().alias("fecha_actual"),
F.lit(dataset_name).alias("nombre_tabla"),
F.lit(-1).alias("pipeline_run_id")
]
```

```
return create_dataframe(schema, rows, extra_cols)
```