



LINEAR DATA STRUCTURES AND ALGORITHMS.

ASSIGNMENT 2: ALGORITHMS

BACKGROUND.

In this assignment we are going to implement **divide&conquer** and **greedy**-based algorithms for solving different problems.

Note: The exercises proposed in this assignment are related to the exercises seen in the lectures. Thus, we strongly recommend to download, get to understand, run and debug the code examples of the lectures before start attempting the exercises of the assignment.

ASSIGNMENT 2 – HINT 1

(Week 8)

Divide and Conquer: First set of exercises.

BACKGROUND.

The folder `/src` contains the following files:

- **(MyList.java, MyStaticList.java, MyNode.java, MyDynamicList.java):**
These classes stand for the package `MyList<T>` we have seen previously in the lectures of the Block II: Data Structures.
- **DivideAndConquerAlgorithms.java:** This class contains the proposed divide&Conquer functions you have to implement.
- **MyMain.java:** This class tests the functionality of the divide&Conquer functions.

The folder `/doc` contains the documentation of the project. In particular:

- **(MyList.html, MyStaticList.html, MyNode.html, MyDynamicList.html):**
Contains the description of the package `MyList<T>` classes.
- **DivideAndConquerAlgorithms.html:** Contains the description of the class `DivideAndConquerAlgorithms.java`.
- **MyMain.html:** Contains the description of the class `MyMain.java`.

EXERCISE.

Implement the following functions of the class `DivideAndConquerAlgorithms.java`.

1. `public int maxInt(MyList<Integer> m);`
The function returns the maximum item of `m` (-1 if `m` is empty).
2. `public boolean isReverse(MyList<Integer> m);`
The function returns whether `m` is sorted in decreasing order or not.
3. `public int getNumAppearances(MyList<Integer> m, int n);`
The function returns the amount of times that the integer `n` appears in `m`.
4. `public int power(int n, int m);`
The function returns `n^m`.
5. `public int lucas(int n);`

Mathematically, the Lucas series is defined as:

$$L_n := \begin{cases} 2 & \text{if } n = 0; \\ 1 & \text{if } n = 1; \\ L_{n-1} + L_{n-2} & \text{if } n > 1. \end{cases}$$

Thus, the Lucas series is as follows:

2, 1, 3, 4, 7, 11, 18, 29, 47, 76, 123

The function returns the n-th item of the lucas series.

Examples: $lucas(0) \rightarrow 2$, $lucas(4) \rightarrow 7$

6. `public void drawImage(int n);`

The function prints a pattern of a given length.

```
*  
**  
***  
...
```

Divide and Conquer: Second set of exercises.

BACKGROUND.

The folder `/src` contains the following files:

- **(MyList.java, MyStaticList.java, MyNode.java, MyDynamicList.java):**
These classes stand for the package `MyList<T>` we have seen previously in the lectures of the Block II: Data Structures.
- **DivideAndConquerAlgorithms.java:** This class contains the proposed divide&Conquer functions you have to implement.
- **MyMain.java:** This class tests the functionality of the divide&Conquer functions.

The folder `/doc` contains the documentation of the project. In particular:

- **(MyList.html, MyStaticList.html, MyNode.html, MyDynamicList.html):**
Contains the description of the package `MyList<T>` classes.
- **DivideAndConquerAlgorithms.html:** Contains the description of the class `DivideAndConquerAlgorithms.java`.
- **MyMain.html:** Contains the description of the class `MyMain.java`.

EXERCISE.

Implement the following functions of the class `DivideAndConquerAlgorithms.java`.

7. `public void recursiveDisplayElements(MyList<Integer> m);`
Given a `MyList`, this recursive algorithm displays its elements by screen (if any).
8. `public MyList<Integer> smallerMyList(MyList<Integer> m, int e);`
The function filters all elements of `MyList` being smaller than 'e'.
9. `public MyList<Integer> biggerEqualMyList(MyList<Integer> m, int e);`
The function filters all elements of `MyList` being bigger or equal than 'e'.
10. `public MyList<Integer> concatenate(MyList<Integer> m1,
MyList<Integer> m2);`
The function computes a new lists whose content is the concatenation of `m1` and `m2`.
11. `public MyList<Integer> quickSort(MyList<Integer> m);`
Given a concrete `MyList`, it computes a new sorted list using the method Quick Sort.