



Developer Migration Guide

CyberArk Self-Hosted v12.2 → v14.2

PLATFORM	Self-Hosted
REPORT DATE	May 10, 2026
FROM VERSION	<code>v12.2</code> (Build 8.2.5)
TO VERSION	<code>v14.2</code> (Build 8.3.6)
AUDIENCE	Engineers, integration owners, API consumers
DATA SOURCE	<code>exports/comparison_sh-v12.2_to_sh-v14.2_20260510.md</code>

At a Glance

The upgrade from v12.2 to v14.2 adds three new endpoints without removing or breaking existing ones. All 25 endpoints from v12.2 remain functional and compatible. The upgrade is low-risk for existing integrations.

Item	Count	Assessment
Breaking changes	0	No action required
New endpoints available	3	Optional adoption
Endpoints removed	0	Full compatibility
Core API compatibility	25/25	No deprecations
Overall migration effort	Low	Safe to upgrade

New Endpoints — Evaluate for Adoption

Three new endpoints are available in v14.2. Adoption is optional; existing code continues to work without changes.

1 AccountSecretVersions

Endpoint: `GET /api/Accounts/{AccountID}/Secret/Versions`

What it does: Retrieve the password change history for an account, including timestamps and version metadata. Useful for compliance audits, incident investigations, and tracking secret rotation.

When to adopt: If your organization needs to audit password history or implement rotation tracking without querying external systems.

PARAMETERS

- `AccountID` (required): The account ID
- `limit` (optional): Number of versions per page (default 50)
- `offset` (optional): Pagination offset (default 0)

EXAMPLE

```
# Retrieve password history for account 123
$response = Invoke-RestMethod `
  -Uri "https://vault/api/Accounts/123/Secret/Versions?limit=100" `
  -Headers @{ Authorization = "CyberArk $sessionToken" } `
  -Method Get

# Returns array of version objects with timestamps
$response | ForEach-Object {
  Write-Host "Version: ${_.VersionNumber} - Changed: ${_.ChangeTime}"
}
```

Reference: `versions/self-hosted/v14.2/endpoints/AccountSecretVersions.md`

2 AuthenticationMethodsConfiguration

Endpoint: `GET /api/AuthenticationMethodsConfiguration` .

`PUT /api/AuthenticationMethodsConfiguration`

What it does: Manage global authentication method settings (MFA requirements, session timeouts, allowed authentication types). Enables programmatic control over vault-wide authentication policies.

When to adopt: If you need to enforce authentication policies across your vault or integrate authentication configuration into your IAM workflows.

METHODS

- **GET:** Retrieve current authentication method configuration
- **PUT:** Update authentication method settings

EXAMPLE

```
# Get current authentication configuration
$currentConfig = Invoke-RestMethod `
  -Uri "https://vault/api/AuthenticationMethodsConfiguration" `
  -Headers @{ Authorization = "CyberArk $sessionToken" } `
  -Method Get

# Update to require MFA for all users
$newConfig = @{
  RequireMFA = $true
  SessionTimeout = 30
  AllowedMethods = @("LDAP", "SAML", "OTP")
}

$response = Invoke-RestMethod `
  -Uri "https://vault/api/AuthenticationMethodsConfiguration" `
  -Headers @{ Authorization = "CyberArk $sessionToken" } `
  -Method Put `
  -Body ($newConfig | ConvertTo-Json)
```

Reference: [versions/self-hosted/v14.2/endpoints/AuthenticationMethodsConfiguration.md](#)

3 PTAAAdministration

Endpoint: `GET /api/PTAAAdministration` · `PUT /api/PTAAAdministration`

What it does: Manage Privileged Threat Analytics settings (threat detection thresholds, alerting rules, policy enforcement). Enables programmatic tuning of PTA behavior without UI access.

When to adopt: If you run Privilege Threat Analytics and need to adjust detection policies or integrate PTA configuration into your security operations workflow.

METHODS

- **GET:** Retrieve current PTA configuration
- **PUT:** Update PTA detection thresholds and policies

EXAMPLE

```
# Get current PTA settings
$ptaConfig = Invoke-RestMethod `
  -Uri "https://vault/api/PTAAAdministration" `
  -Headers @{ Authorization = "CyberArk $sessionToken" } `
  -Method Get

# Adjust threat detection sensitivity
$ptaConfig.ThreatThreshold = "Medium"
$ptaConfig.AlertOnSuspiciousActivity = $true

$response = Invoke-RestMethod `
  -Uri "https://vault/api/PTAAAdministration" `
  -Headers @{ Authorization = "CyberArk $sessionToken" } `
  -Method Put `
  -Body ($ptaConfig | ConvertTo-Json)
```

Reference: [versions/self-hosted/v14.2/endpoints/PTAAAdministration.md](#)

Existing Endpoints — No Breaking Changes

All 25 endpoints from v12.2 remain fully compatible. No changes to paths, required parameters, response formats, or authentication methods.

Verified compatible endpoints:

AccountActions, AccountGroups, Accounts, Applications, Authentication, BulkUpload, DiscoveredAccounts, General, Groups, LDAPIntegration, LinkedAccounts, MonitorSessions, OnboardingRules, OPMCommands, Platforms, PTAAInstallation, Requests, Safes, Security, Server, SessionManagement, SSHKeys, SystemHealth, UsageExamples, Users

Action required: **NONE** — existing integrations do not need code changes.

Migration Checklist

PRE-UPGRADE ASSESSMENT

- ☐ Review the three new endpoints above
- ☐ Assess whether any new endpoints benefit your current workflows
- ☐ Confirm no code depends on endpoints listed as removed (there are none)
- ☐ Check for any custom auth token generation that might conflict

TESTING IN DEV

- ☐ Deploy v14.2 to DEV environment
- ☐ Run existing integration tests against all 25 common endpoints
- ☐ Test all results pass without code changes
- ☐ If adopting new endpoints, test them in isolation first
- ☐ Test new endpoints with your authentication method (session tokens, LDAP, SAML)

PRE-PRODUCTION

- ☐ Code review (if adopting new endpoints)
- ☐ Test against v14.2 in UAT with live data
- ☐ Run load tests to confirm performance is consistent
- ☐ Get sign-off from operations team before production deployment

UPGRADE EXECUTION

- ☐ Schedule maintenance window if required by your deployment
- ☐ Verify all custom scripts still execute without error
- ☐ Monitor API error logs for the first 24 hours
- ☐ Test critical workflows end-to-end
- ☐ Confirm all metrics and dashboards are still updating

POST-UPGRADE

- ☐ Collect baseline performance metrics (API latency, throughput, error rates)
- ☐ Document any workarounds or issues discovered
- ☐ Update internal API documentation to reference v14.2 endpoints
- ☐ Archive v12.2 endpoint docs for historical reference

Code Review Checklist

Areas to focus on when reviewing v14.2 code.

- ☐ **Auth flow:** Confirm session token generation still works (no breaking changes)
- ☐ **Error handling:** Test response codes for existing endpoints (should match v12.2)
- ☐ **Pagination:** Limit/offset parameters work the same for list endpoints
- ☐ **Date formats:** No changes to ISO 8601 formatting across endpoints
- ☐ **Null handling:** New optional fields shouldn't break existing parsing logic
- ☐ **Rate limiting:** Confirm rate limit headers are present and consistent

Related Resources

- **Full endpoint specifications:** [versions/self-hosted/v14.2/endpoints/](#)
- **Version changelog:** [versions/self-hosted/v14.2/changelog.md](#)
- **Raw comparison data:** [exports/comparison_sh-v12.2_to_sh-v14.2_20260510.md](#)
- **Manager summary:** [reports/manager/](#) (stakeholder-focused overview)
- **CyberArk official docs:** docs.cyberark.com/pam-self-hosted/14.2

Last Updated: May 10, 2026

Template Version: 1.0

Generated By: Compare-APIVersions.ps1 + Developer Report Generator