

SIAM YAMATO STEEL CO., LTD. MILL INSPECTION CERTIFICATE

In Accordance with DIN 50049 / EN 10204-3.1

Head office: 1 Siam Cement Road, Bangsue, Bangkok Thailand 10800 Tel: (662) 586-2783-4, 5865329-30 Fax: (662) 586 2687, 910-3123



This document issued in accordance with NSC-ONSC Accreditation requirement. NSC-ONSC accredited testing No.0293 for compliance with ISO/IEC 17025

NSC-TISI-TIS 17025 TESTING 0293 SYS's Quality management system is certified by MASCI (Certificate No. QMS 03173/777)

Revision

Page 1 of 1

:00

Date of Issue : 16/01/2021

Certificate No. : 42121010126

Reference No. : OCE2000661/1

Customer

Remark 1

Remark 2 Remark 3

Description of Goods

D/P No. 3425032846, 3425032847, 3425032848

: H.J. ASMUSS

: Hot Rolled Structural Steel

: CONFORMED TO AS/NZS 3679.1 : 2016 GRADE AS/NZS 3679.1-300

Standard: AS/NZS 3679.1-2016 AS/NZS 3679.1-300

Steelmaking and Manufacturing Process: EAF, Cast Analysis (L)

Location of sample and test piece : Comply with AS/NZS 3679.1 :2016

Type of Impact test piece : -

Tensile Test : Comply with AS 1391-2007

Impact Test : Comply with AS 1544.2-2003

Shape of Tensile test piece : Rectangular cross-section

Marking of the product : Marking and Information available on Sticker

Remark 5 .						Marking 0	n the pi	oduci			: Marking	y anu i	IIIOIIII	alion	avallat	ne on	Slicke									
Dimension & Length	Grade	Qty (Pcs.)	Heat No.	Yield Str. (MPa)	Mechanical Property (Test Piece Direction : L)						Chemical Composition (%)															
					Tancila Str	Elong.(%)		Charpy Impact (J) -			-	C	Si	Mn	Cu	AI	Р	s	Nb	V	Ni	Cr	Ti	Мо	CE ⁽¹⁾	⁽¹⁾ B
					(MPa)		Test	Test Test1	Test2	Test3	Avg.	_		x100			x1000	-		x1000					-	x10000
200 PFC 22.9KG/MX9.00M	AS/NZS 3679.1-300	27	AB3685	350	510	35.40	-	-	-	-	-	18	18	88	26	0	17	15	1	4	9	12	1	15	38	3
				375	520	33.27	-	-	-	-	-	18	18	88	26	0	17	15	1	4	9	12	1	15	38	3
200 PFC 22.9KG/MX9.00M	AS/NZS 3679.1-300	5	AB3687	365	500	35.06	-	-	-	-	-	14	18	110	26	0	14	20	1	2	8	11	1	16	37	3
230 PFC 25.1KG/MX12.00M	AS/NZS 3679.1-300	3	AB2574	375	520	32.42	-	-	-	-	-	15	17	115	21	2	18	23	0	22	8	15	1	18	40	5
230 PFC 25.1KG/MX12.00M	AS/NZS 3679.1-300	6	AB2575	345	500	32.27	-	-	-	-	-	15	17	118	22	2	13	24	2	21	8	11	1	16	40	5
				375	520	37.61	-	-	-	-	-	15	17	118	22	2	13	24	2	21	8	11	1	16	40	5
230 PFC 25.1KG/MX12.00M	AS/NZS 3679.1-300	1	BB0108	390	540	29.35	-	-	-	-	-	17	16	113	26	2	15	21	0	22	10	11	1	24	41	2
230 PFC 25.1KG/MX6.00M	AS/NZS 3679.1-300	2	BB0109	365	520	33.24	-	-	-	-	-	16	16	110	24	1	17	17	1	21	11	14	1	24	40	3
				390	530	35.66	-	-	-	-	-	16	16	110	24	1	17	17	1	21	11	14	1	24	40	3
230 PFC 25.1KG/MX6.00M	AS/NZS 3679.1-300	20	BB0110	340	500	34.51	-	-	-	-	-	16	18	106	24	2	17	17	1	6	12	14	1	22	39	4
				340	510	37.14	-	-	-	-	-	16	18	106	24	2	17	17	1	6	12	14	1	22	39	4
																										i
																										ĺ
																										i
																										i
																								i l		i
																										<u></u>

Checked By: Finished Goods Checking Operator

Remark : $CE^0 = Carbon equivalent$

- Carbon equivalent (CE) = C+ (Mn/6) + (Cr+Mo+V)/5 + (Ni+Cu)/15

We hereby certify that the material described herein has been tested and inspected in accordance with the requirements of the above specification.

Manufactured by Siam Yamato Steel Co.,Ltd.

-A Chemical composition of carbon (C), Phosphorus(P), manganese (Mn), Silicon (Si),sulphur (S), chromium (Cr), molybdenum (Mo), vanadium (V), nickel (Ni), copper (Cu),titanium (Ti), niobium (Nb), boron (B) test performed by NSC-ONSC accredited testing No. as above for compliance with ISO/IEC 17025

Mr. Panupong Sinpreechanon
Quality Promotion Department Manager

QP 206 (11-01/07/50)