ch3

2019년 7월 10일

1 Foundations for Analytics with Python (ch3)

1.1 Excel 파일 열기 (pandas)

```
In [1]: import pandas as pd
        data_frame = pd.read_excel('sales_2013.xlsx', sheet_name = 'january_2013')
        print(data_frame)
```

	Customer ID	Customer Name	Invoice Number	Sale Amount	Purchase Date
0	1234	John Smith	100-0002	1200	1/1/2013
1	2345	Mary Harrison	100-0003	1425	1/6/2013
2	3456	Lucy Gomez	100-0004	1390	1/11/2013
3	4567	Rupert Jones	100-0005	1257	1/18/2013
4	5678	Jenny Walters	100-0006	1725	1/24/2013
5	6789	Samantha Donaldson	100-0007	1995	1/31/2013

1.2 Excel 파일 필터링하기 (pandas)

```
In [3]: data_frame = \
        pd.read_excel('sales_2013.xlsx', sheet_name = 'january_2013', index_col=None)


        data_frame_value_meets_condition = \
        data_frame[(data_frame['Sale Amount'].astype(float) > 1400.0)]
        print(data_frame_value_meets_condition)
```

```
   Customer ID       Customer Name Invoice Number  Sale Amount Purchase Date
1         2345       Mary Harrison       100-0003         1425      1/6/2013
4         5678       Jenny Walters       100-0006         1725     1/24/2013
5         6789  Samantha Donaldson       100-0007         1995     1/31/2013
```

1.3 Excel 파일 필터링하기 (pandas) - 리스트 포함 여부 (.isin)

```
In [5]: data_frame = \
        pd.read_excel('sales_2013.xlsx', sheet_name = 'january_2013', index_col=None)

        important_dates = ['1/24/2013', '1/31/2013']
        data_frame_value_in_set = \
        data_frame[data_frame['Purchase Date'].isin(important_dates)]

        print(data_frame_value_in_set)
```

```
   Customer ID       Customer Name Invoice Number  Sale Amount Purchase Date
4         5678       Jenny Walters       100-0006         1725     1/24/2013
5         6789  Samantha Donaldson       100-0007         1995     1/31/2013
```

1.4 Excel 파일 필터링하기 (pandas) - 패턴 활용(.startswith)

```
In [7]: data_frame = \
        pd.read_excel('sales_2013.xlsx', sheet_name = 'january_2013', index_col=None)

        data_frame_value_matches_pattern = \
        data_frame[data_frame['Customer Name'].str.startswith('J')]

        print(data_frame_value_matches_pattern)
```

```
   Customer ID  Customer Name Invoice Number  Sale Amount Purchase Date
0         1234     John Smith       100-0002         1200      1/1/2013
4         5678  Jenny Walters       100-0006         1725     1/24/2013
```

1.5 특정 열 선택하기 (pandas) - 인덱스 값 사용(.iloc), 헤더 사용(.loc)

```
In [2]: data_frame = \
        pd.read_excel('sales_2013.xlsx', sheet_name = 'january_2013', index_col=None)

        data_frame_cloumn_by_index = data_frame.iloc[:, [1, 4]] # index = 1 or index = 4

        print(data_frame_cloumn_by_index)

        print('-'*20)

        data_frame_column_by_name = \
        data_frame.loc[:, ['Customer ID', 'Purchase Date']]

        print(data_frame_column_by_name)

        Customer Name Purchase Date
0          John Smith      1/1/2013
1       Mary Harrison      1/6/2013
2          Lucy Gomez     1/11/2013
3        Rupert Jones     1/18/2013
4       Jenny Walters     1/24/2013
5  Samantha Donaldson     1/31/2013
--------------------
   Customer ID Purchase Date
0         1234      1/1/2013
1         2345      1/6/2013
2         3456     1/11/2013
3         4567     1/18/2013
4         5678     1/24/2013
5         6789     1/31/2013
```

1.6 모든 워크시트에서 특정 행 필터링하기 (pandas)

```
In [3]: data_frame = \
        pd.read_excel('sales_2013.xlsx', sheet_name = None, index_col=None)
        row_output = []
```

```
        for worksheet_name, data in data_frame.items():
            row_output.append\
            (data[data['Sale Amount'].replace('$', '').replace(',','').astype(float) > 2000.0])
        filtered_rows = pd.concat(row_output, axis=0, ignore_index = True)

        print(filtered_rows)
```

	Customer ID	Customer Name	Invoice Number	Sale Amount	Purchase Date
0	7654	Roger Lipney	100-0010	2135	2/15/2013
1	6543	Rachel Paz	100-0017	2042	3/22/2013
2	4321	Susan Wallace	100-0019	2280	3/30/2013

1.7 모든 워크시트에서 특정 열 선택하기 (pandas)

```
In [4]: data_frame = \
        pd.read_excel('sales_2013.xlsx', sheet_name = None, index_col=None)
        column_output = []
        for worksheet_name, data in data_frame.items():
            column_output.append\
            (data.loc[:, ['Customer Name', 'Sale Amount']])

        selected_columns = pd.concat(column_output, axis=0, ignore_index = True)

        print(selected_columns)
```

	Customer Name	Sale Amount
0	John Smith	1200
1	Mary Harrison	1425
2	Lucy Gomez	1390
3	Rupert Jones	1257
4	Jenny Walters	1725
5	Samantha Donaldson	1995
6	Daniel Farber	1115
7	Laney Stone	1367
8	Roger Lipney	2135
9	Thomas Haines	1346

```
10          Anushka Vaz         1560
11       Harriet Cooper         1852
12           John Smith         1350
13            Tony Song         1167
14       Marry Harrison         1789
15           Rachel Paz         2042
16           Lucy Gomez         1511
17        Susan Wallace         2280
```

1.8 워크시트 집합에 걸쳐서 특정 행 필터링하기 (pandas)

```
In [17]: my_sheets = [0, 1]
         threshold = 1900.0

         data_frame = \
         pd.read_excel('sales_2013.xlsx', sheet_name =my_sheets, index_col=None)

         row_list = []
         for worksheet_name, data in data_frame.items():
             row_list.append\
             (data[data['Sale Amount'].replace('$', '').replace(',','').astype(float) > thresh
         filtered_rows = pd.concat(row_list, axis=0, ignore_index=True)

         print(filtered_rows)
```

```
   Customer ID       Customer Name Invoice Number  Sale Amount Purchase Date
0         6789  Samantha Donaldson       100-0007         1995     1/31/2013
1         7654        Roger Lipney       100-0010         2135     2/15/2013
```

1.9 파일에서 데이터 값의 합계 및 평균 계산하기 (pandas), 그래프로 표현하기 (matplotlib)

```
In [5]: import pandas as pd
        import matplotlib.pyplot as plt
        %matplotlib inline

        df = \
```

```
        pd.read_excel('sales_2013.xlsx', sheet_name = None, index_col=None)
        row_list = []
        for worksheet_name, data in df.items():
            row_list.append(data)
        data_frame = pd.concat(row_list, axis=0, ignore_index=True)


        print(data_frame.head())
        print('-'*20)
        print(data_frame.tail())
        print('-'*20)


        total_sales = \
        pd.DataFrame([float(str(value).strip('$').replace(',','')) \
                      for value in data_frame.loc[:, 'Sale Amount']]).sum()
        average_sales = \
        pd.DataFrame([float(str(value).strip('$').replace(',','')) \
                     for value in data_frame.loc[:, 'Sale Amount']]).mean()

        print('total sales: ', round(float(total_sales), 2))
        print('average sales: ', round(float(average_sales), 2))

        df2 = data_frame[['Customer Name', 'Sale Amount']]
        df2.boxplot()
        plt.show()
```

```
   Customer ID  Customer Name Invoice Number  Sale Amount Purchase Date
0         1234     John Smith       100-0002         1200      1/1/2013
1         2345  Mary Harrison       100-0003         1425      1/6/2013
2         3456     Lucy Gomez       100-0004         1390     1/11/2013
3         4567   Rupert Jones       100-0005         1257     1/18/2013
4         5678  Jenny Walters       100-0006         1725     1/24/2013
--------------------
    Customer ID   Customer Name Invoice Number  Sale Amount Purchase Date
13         8765       Tony Song       100-0015         1167      3/8/2013
```

```
14          2345  Marry Harrison       100-0016          1789      3/17/2013
15          6543      Rachel Paz       100-0017          2042      3/22/2013
16          3456      Lucy Gomez       100-0018          1511      3/28/2013
17          4321   Susan Wallace       100-0019          2280      3/30/2013
--------------------
total sales:  28506.0
average sales:  1583.67
```



jj2015@korea.ac.kr