



Diversey Suma · SKU 7010064

Suma Grill D9

Oven, grill & fryer cleaner — 2L

2L **pH >12** **Foam spray**
bottle sizehighly alkaline+ extension lance

Suma Grill D9 is a heavy-duty alkaline degreaser built for periodic deep cleaning where grease has really built up — ovens, grills, salamanders and fryers. It cuts through carbonised, baked-on soil that everyday cleaners won't touch. This guide covers how to use it safely on each type of equipment.

Before you start

- This is a strong alkaline product (pH over 12) — wear gloves and eye protection, and make sure the area is well ventilated.
- For professional/trade use only.
- Do not use on aluminium, copper, galvanised metal, wood or linoleum — it's suitable for stainless steel and similar kitchen surfaces.
- Store the sealed bottle away from extremes of temperature.
- Full safety information is in the product's Safety Data Sheet — ask us if you need a copy.

How to use it

Choose the method for what you're cleaning — the dilution and contact time are different for each.

●Oven & grill cleaning

- 1 Make sure the surface has cooled to below 80°C — it works best between 60–80°C.
- 2 Spray the product on neat, straight from the bottle (a foam trigger with an extension lance gives better reach and less mist).
- 3 Leave it to work for **5-30 minutes**, depending on how heavily soiled the surface is.
- 4 Loosen any remaining deposit with a scourer or brush.
- 5 Rinse thoroughly with clean, hot water and leave to air dry.

●Fryer cleaning

- 1 Drain the oil and close the valve.
- 2 Fill the fryer with water up to close to the normal oil level.
- 3 Add Suma Grill D9 at **1L per 10L of water (a 10% solution)**.
- 4 Turn the fryer on and bring it to a controlled boil for **15-30 minutes**.
- 5 Once cooled and drained, scrub any remaining residue from the walls and heating elements with a scourer or brush.
- 6 Rinse twice with clean, hot water and leave to air dry.

●Grill extractor cleaning

- 1
- Dismantle the extractor.
- 2
- Mix Suma Grill D9 at a minimum of 50ml per litre of hot water (a 5% solution) .
- 3
- Leave the parts to soak for 15-60 minutes .
- 4
- Rinse well with clean water and leave to air dry.

Product details

Appearance	Clear brown, viscous liquid
Odour	Surfactant
pH (neat)	Greater than 12
pH (in use)	Around 12
Relative density (20°C)	Approx. 1.12 g/cm³

Surface compatibility: safe for stainless steel and similar kitchen materials under normal use. Avoid aluminium, copper, galvanised metal, wood and linoleum, which are sensitive to strong alkalis.