

```
void main()
{
    int data, key, item, ch, chl;
    printf("\nEnter root node");
    scanf("%d", &data);
```

```

    struct node *new=(struct node*)malloc(sizeof(struct
node));
    new->data=data;
    new->lc=new->rc=NULL;
    root=new;

    BuildTree(root);

    printf("\n1. INSERTION \n2.DELETION\n3.SEARCHING
\n4.DISPLAY\n5.EXIT");

    do
    {
        printf("\n\nEnter the choice :\t");
        scanf("%d",&ch);
        switch(ch)
        {
            case 1: printf("Enter node to insert \t");
                    scanf("%d",&item);
                    printf("Enter parent node\t");
                    scanf("%d",&key);
                    Insert(item,key);
                    break;

            case 2: printf("Enter the node to be deleted
\t");
                    scanf("%d",&key);
                    Delete(root,key);
                    break;

            case 3: flag=0;
                    printf("Enter the value to be searched
\t");
                    scanf("%d",&key);
                    Search(root,key);
                    if(flag==1)
                        printf("\nNode found ");
                    else
                        printf("\nNode not found");
                    break;

            case 4: printf("1.INORDER\t2.PREORDER
\t3.POSTORDER\nEnter the choice :\t");
                    scanf("%d",&ch1);
                    switch(ch1)
                    {
                        case 1: Inorder(root); break;
                        case 2: Preorder(root); break;
                        case 3: Postorder(root); break;
                    }
                    break;

            case 5: break;
        }
    }
    while(ch!=5);

```