Corridor Attention: A Fixture for the References Page

Anonymous Author(s)

Abstract

A fixture whose only job is its page layout: two pages of body text, and a reference list that opens the third page under the running head.

Keywords

fixtures, page layout

ACM Reference Format:
Anonymous Author(s). 2026. Corridor Attention: A Fixture for the References Page. In *Proceedings of The Fixture Conference (FIXTURE '26)*. ACM, New York, NY, USA, 3 pages. https://doi.org/10.1145/nnnnnnn.nnnnnnn

1 Introduction

Long-context sequence models spend most of their compute on attention, and the share grows with the length of the input. A routing scheme that bounds the number of keys each query may read changes that growth from quadratic to linear, at the price of a scorer that has to decide which keys are worth reading. This paragraph stands in for the prose of a real submission: it is long enough to fill a column with ordinary text, and it says nothing a reviewer of layout would need to read closely. Prior work bounds the interaction pattern [1].

Long-context sequence models spend most of their compute on attention, and the share grows with the length of the input. A routing scheme that bounds the number of keys each query may read changes that growth from quadratic to linear, at the price of a scorer that has to decide which keys are worth reading. This paragraph stands in for the prose of a real submission: it is long enough to fill a column with ordinary text, and it says nothing a reviewer of layout would need to read closely.

Long-context sequence models spend most of their compute on attention, and the share grows with the length of the input. A routing scheme that bounds the number of keys each query may read changes that growth from quadratic to linear, at the price of a scorer that has to decide which keys are worth reading. This paragraph stands in for the prose of a real submission: it is long enough to fill a column with ordinary text, and it says nothing a reviewer of layout would need to read closely.

2 Method

Long-context sequence models spend most of their compute on attention, and the share grows with the length of the input. A routing scheme that bounds the number of keys each query may read changes that growth from quadratic to linear, at the price of a scorer that has to decide which keys are worth reading. This paragraph stands in for the prose of a real submission: it is long enough to fill a column with ordinary text, and it says nothing a reviewer of layout would need to read closely.

FIXTURE '26, Springfield, USA
2026. ACM ISBN 978-x-xxxx-xxxx-x/YYYY/MM
https://doi.org/10.1145/nnnnnnn.nnnnnnn

Long-context sequence models spend most of their compute on attention, and the share grows with the length of the input. A routing scheme that bounds the number of keys each query may read changes that growth from quadratic to linear, at the price of a scorer that has to decide which keys are worth reading. This paragraph stands in for the prose of a real submission: it is long enough to fill a column with ordinary text, and it says nothing a reviewer of layout would need to read closely.

Long-context sequence models spend most of their compute on attention, and the share grows with the length of the input. A routing scheme that bounds the number of keys each query may read changes that growth from quadratic to linear, at the price of a scorer that has to decide which keys are worth reading. This paragraph stands in for the prose of a real submission: it is long enough to fill a column with ordinary text, and it says nothing a reviewer of layout would need to read closely.

Long-context sequence models spend most of their compute on attention, and the share grows with the length of the input. A routing scheme that bounds the number of keys each query may read changes that growth from quadratic to linear, at the price of a scorer that has to decide which keys are worth reading. This paragraph stands in for the prose of a real submission: it is long enough to fill a column with ordinary text, and it says nothing a reviewer of layout would need to read closely.

3 Experiments

Long-context sequence models spend most of their compute on attention, and the share grows with the length of the input. A routing scheme that bounds the number of keys each query may read changes that growth from quadratic to linear, at the price of a scorer that has to decide which keys are worth reading. This paragraph stands in for the prose of a real submission: it is long enough to fill a column with ordinary text, and it says nothing a reviewer of layout would need to read closely.

Long-context sequence models spend most of their compute on attention, and the share grows with the length of the input. A routing scheme that bounds the number of keys each query may read changes that growth from quadratic to linear, at the price of a scorer that has to decide which keys are worth reading. This paragraph stands in for the prose of a real submission: it is long enough to fill a column with ordinary text, and it says nothing a reviewer of layout would need to read closely.

Long-context sequence models spend most of their compute on attention, and the share grows with the length of the input. A routing scheme that bounds the number of keys each query may read changes that growth from quadratic to linear, at the price of a scorer that has to decide which keys are worth reading. This paragraph stands in for the prose of a real submission: it is long enough to fill a column with ordinary text, and it says nothing a reviewer of layout would need to read closely.

Long-context sequence models spend most of their compute on attention, and the share grows with the length of the input. A routing scheme that bounds the number of keys each query may read changes that growth from quadratic to linear, at the price of a scorer that has to decide which keys are worth reading. This paragraph stands in for the prose of a real submission: it is long enough to fill a column with ordinary text, and it says nothing a reviewer of layout would need to read closely.

Long-context sequence models spend most of their compute on attention, and the share grows with the length of the input. A

routing scheme that bounds the number of keys each query may read changes that growth from quadratic to linear, at the price of a scorer that has to decide which keys are worth reading. This paragraph stands in for the prose of a real submission: it is long enough to fill a column with ordinary text, and it says nothing a reviewer of layout would need to read closely.

4 Conclusion

Long-context sequence models spend most of their compute on attention, and the share grows with the length of the input. A routing scheme that bounds the number of keys each query may read changes that growth from quadratic to linear, at the price of a scorer that has to decide which keys are worth reading. This paragraph stands in for the prose of a real submission: it is long enough to fill a column with ordinary text, and it says nothing a reviewer of layout would need to read closely. The conclusion ends here, on the second page.

References

[1] Rewon Child, Scott Gray, Alec Radford, and Ilya Sutskever. 2019. Generating Long Sequences with Sparse Transformers. *arXiv preprint arXiv:1904.10509* (2019).