

# Semantic Security

Rohit Musti

CUNY - Hunter College

February 9, 2022

# Overview

- Alice and Bob share a secret key  $k$ .

# Overview

- Alice and Bob share a secret key  $k$ .
- Alice wants to send a message  $m$  to Bob through an untrusted medium.

# Overview

- Alice and Bob share a secret key  $k$ .
- Alice wants to send a message  $m$  to Bob through an untrusted medium.
- Mechanism: Shannon Ciphers.

# Who is Claude Shannon?

- Father of Information Theory

# Who is Claude Shannon?

- Father of Information Theory
- Friends with Alan Turing (they actually compared notes on Turing's famous paper the Universal Turing machine)

# Who is Claude Shannon?

- Father of Information Theory
- Friends with Alan Turing (they actually compared notes on Turing's famous paper the Universal Turing machine)
- Estimated the complexity of chess

# Who is Claude Shannon?

- Father of Information Theory
- Friends with Alan Turing (they actually compared notes on Turing's famous paper the Universal Turing machine)
- Estimated the complexity of chess
- First to formalize the notion of security



# Shannon Cipher

- **Definition:** a Shannon Cipher is a pair of functions  $(E, D)$

# Shannon Cipher

- **Definition:** a Shannon Cipher is a pair of functions  $(E, D)$
- The  $E$  function takes in two arguments: a key  $k$  and a message  $m$ , and produces a ciphertext  $c$

$$c = E(k, m)$$

# Shannon Cipher

- **Definition:** a Shannon Cipher is a pair of functions  $(E, D)$
- The  $E$  function takes in two arguments: a key  $k$  and a message  $m$ , and produces a ciphertext  $c$

$$c = E(k, m)$$

- The  $D$  function takes in two arguments: a key  $k$  and a ciphertext  $c$ , and produces a plaintext  $m$

# Shannon Cipher

- **Definition:** a Shannon Cipher is a pair of functions  $(E, D)$
- The  $E$  function takes in two arguments: a key  $k$  and a message  $m$ , and produces a ciphertext  $c$

$$c = E(k, m)$$

- The  $D$  function takes in two arguments: a key  $k$  and a ciphertext  $c$ , and produces a plaintext  $m$
- While  $E$  maybe random,  $D$  must be deterministic

$$m = D(k, c)$$

# Shannon Cipher: Correctness

- Decryption must *undo* Encryption

# Shannon Cipher: Correctness

- Decryption must *undo* Encryption

$$m = D(k, E(k, m))$$

- More formally: let  $K$  be the key space,  $M$  be the message space, and  $C$  be the ciphertext space.

# Shannon Cipher: Correctness

- Decryption must *undo* Encryption

$$m = D(k, E(k, m))$$

- More formally: let  $K$  be the key space,  $M$  be the message space, and  $C$  be the ciphertext space.

$$E : K \times M \rightarrow C$$

# Shannon Cipher: Correctness

- Decryption must *undo* Encryption

$$m = D(k, E(k, m))$$

- More formally: let  $K$  be the key space,  $M$  be the message space, and  $C$  be the ciphertext space.

$$E : K \times M \rightarrow C$$

$$D : K \times C \rightarrow M$$



# Shannon Cipher: Correctness

- Decryption must *undo* Encryption

$$m = D(k, E(k, m))$$

- More formally: let  $K$  be the key space,  $M$  be the message space, and  $C$  be the ciphertext space.

$$E : K \times M \rightarrow C$$

$$D : K \times C \rightarrow M$$

- $\varepsilon$  is defined over  $(K, M, C)$

# Revisit: The One Time Pad

- A one time pad is a Shannon Cipher s.t.

$$K := M := C := \{0, 1\}^L$$

# Revisit: The One Time Pad

- A one time pad is a Shannon Cipher s.t.

$$K := M := C := \{0, 1\}^L$$

- Encryption for a key  $k \in \{0, 1\}^L$  and a message  $m \in \{0, 1\}^L$ :

$$E(k, m) := k \oplus m$$

# Revisit: The One Time Pad

- A one time pad is a Shannon Cipher s.t.

$$K := M := C := \{0, 1\}^L$$

- Encryption for a key  $k \in \{0, 1\}^L$  and a message  $m \in \{0, 1\}^L$ :

$$E(k, m) := k \oplus m$$

- Decryption for a key  $k \in \{0, 1\}^L$  and a ciphertext  $c \in \{0, 1\}^L$ :

$$D(k, c) := k \oplus c$$

# Revisit: The One Time Pad

- A one time pad is a Shannon Cipher s.t.

$$K := M := C := \{0, 1\}^L$$

- Encryption for a key  $k \in \{0, 1\}^L$  and a message  $m \in \{0, 1\}^L$ :

$$E(k, m) := k \oplus m$$

- Decryption for a key  $k \in \{0, 1\}^L$  and a ciphertext  $c \in \{0, 1\}^L$ :

$$D(k, c) := k \oplus c$$

- Future HW: Write out a mathematical justification that the one time pad meets the earlier correctness requirement (Decryption *undoes* Encryption)

# Security Requirements 1

- key assumption: adversaries know the encryption mechanism and distribution of  $K$

# Security Requirements 1

- key assumption: adversaries know the encryption mechanism and distribution of  $K$
- If Alice encrypts a message  $m$  with a key  $k$  and an adversary obtains the ciphertext  $c$ , the key  $k$  needs to be hard to guess

# Security Requirements 1

- key assumption: adversaries know the encryption mechanism and distribution of  $K$
- If Alice encrypts a message  $m$  with a key  $k$  and an adversary obtains the ciphertext  $c$ , the key  $k$  needs to be hard to guess (if  $k$  is easy to guess, then the adversary will just guess until they discover  $k$ ).



# Security Requirements 1

- key assumption: adversaries know the encryption mechanism and distribution of  $K$
- If Alice encrypts a message  $m$  with a key  $k$  and an adversary obtains the ciphertext  $c$ , the key  $k$  needs to be hard to guess (if  $k$  is easy to guess, then the adversary will just guess until they discover  $k$ ).
- Thus,  $k$  must be chosen uniformly & random from a large keyspace  $K$

## Security Requirements 2

- key assumption: adversaries may have some knowledge of the message being encrypted.

## Security Requirements 2

- key assumption: adversaries may have some knowledge of the message being encrypted.
- Supposed  $m_0 = \textit{meet\_at\_lunch\_time}$  and  $m_1 = \textit{meet\_at\_snack\_time}$ ,

## Security Requirements 2

- key assumption: adversaries may have some knowledge of the message being encrypted.
- Supposed  $m_0 = \text{meet\_at\_lunch\_time}$  and  $m_1 = \text{meet\_at\_snack\_time}$ , our adversary has a 50% chance of guessing correctly.

## Security Requirements 2

- key assumption: adversaries may have some knowledge of the message being encrypted.
- Supposed  $m_0 = \text{meet\_at\_lunch\_time}$  and  $m_1 = \text{meet\_at\_snack\_time}$ , our adversary has a 50% chance of guessing correctly.
- A secure cipher text should not increase this probability of guessing correctly.

## Security Requirements 2

- key assumption: adversaries may have some knowledge of the message being encrypted.
- Supposed  $m_0 = \text{meet\_at\_lunch\_time}$  and  $m_1 = \text{meet\_at\_snack\_time}$ , our adversary has a 50% chance of guessing correctly.
- A secure cipher text should not increase this probability of guessing correctly.
- Suppose there are 90 keys  $k_0$  s.t.  $E(k_0, m_0) = c$  and 10 keys  $k_1$  s.t.  $E(k_1, m_1) = c$ ,

## Security Requirements 2

- key assumption: adversaries may have some knowledge of the message being encrypted.
- Supposed  $m_0 = \text{meet\_at\_lunch\_time}$  and  $m_1 = \text{meet\_at\_snack\_time}$ , our adversary has a 50% chance of guessing correctly.
- A secure cipher text should not increase this probability of guessing correctly.
- Suppose there are 90 keys  $k_0$  s.t.  $E(k_0, m_0) = c$  and 10 keys  $k_1$  s.t.  $E(k_1, m_1) = c$ , the probability that a given message  $c$  is  $m_0$  is  $90/(90 + 10) = 90\%$ , increasing our adversaries odds of guessing correctly.

# Perfect Security

- Assumption: a key is drawn uniformly and randomly from a large key space:  $k$ .



# Perfect Security

- Assumption: a key is drawn uniformly and randomly from a large key space:  $\mathbf{k}$ .
- Let  $(E, D)$  be a Shannon Cipher defined over  $(K, M, C)$

# Perfect Security

- Assumption: a key is drawn uniformly and randomly from a large key space:  $\mathbf{k}$ .
- Let  $(E, D)$  be a Shannon Cipher defined over  $(K, M, C)$
- If for all  $m_0, m_1 \in M$ , for all  $c \in C$ , and  $\mathbf{k} \xleftarrow{R} K$  we have

$$\Pr[E(\mathbf{k}, m_0) = c] = \Pr[E(\mathbf{k}, m_1) = c]$$

# One Time Pad: Perfectly Security

- A result of our definition of perfect security is

$$|\{k \xleftarrow{R} K : E(k, m) = c\}| = N_c$$

# One Time Pad: Perfectly Security

- A result of our definition of perfect security is

$$|\{k \xleftarrow{R} K : E(k, m) = c\}| = N_c$$

- For any message  $m \in \{0, 1\}^l$  and cipher text  $c \in \{0, 1\}^l$ ,

$$k \oplus m = c$$

# One Time Pad: Perfectly Security

- A result of our definition of perfect security is

$$|\{k \xleftarrow{R} K : E(k, m) = c\}| = N_c$$

- For any message  $m \in \{0, 1\}^l$  and cipher text  $c \in \{0, 1\}^l$ ,

$$k \oplus m = c$$

thus,  $N_c = 1$ , satisfying the above result.

# Problems with Perfect Security

- Let  $(E, D)$  be a Shannon Cipher defined over  $(K, M, C)$ , if this cipher is perfectly secure, then  $|K| \geq |M|$

# Problems with Perfect Security

- Let  $(E, D)$  be a Shannon Cipher defined over  $(K, M, C)$ , if this cipher is perfectly secure, then  $|K| \geq |M|$
- It is impractical to have keys that are at least as large as the size of the message we are transmitting .

# Problems with Perfect Security

- Let  $(E, D)$  be a Shannon Cipher defined over  $(K, M, C)$ , if this cipher is perfectly secure, then  $|K| \geq |M|$
- It is impractical to have keys that are at least as large as the size of the message we are transmitting .
- Really, what we are concerned about are real world, computationally bounded adversaries.



# Problems with Perfect Security

- Let  $(E, D)$  be a Shannon Cipher defined over  $(K, M, C)$ , if this cipher is perfectly secure, then  $|K| \geq |M|$
- It is impractical to have keys that are at least as large as the size of the message we are transmitting .
- Really, what we are concerned about are real world, computationally bounded adversaries.
- We are also interested in efficient algorithms for encrypting and decrypting. By efficient, we mean polynomial functions.

# Semantic Security

Intuition: the probability that a computationally bounded adversary can learn anything about a message  $m$  given its cipher text  $c$  is negligible.

# Semantic Security

Intuition: the probability that a computationally bounded adversary can learn anything about a message  $m$  given its cipher text  $c$  is negligible.

Experiment  $b$

- Let  $\mathcal{E} = (E, D)$  be a Cipher defined over  $(\mathcal{K}, \mathcal{M}, \mathcal{C})$  and let our adversary  $\mathcal{A}$  be computationally bounded

# Semantic Security

Intuition: the probability that a computationally bounded adversary can learn anything about a message  $m$  given its cipher text  $c$  is negligible.

Experiment  $b$

- Let  $\mathcal{E} = (E, D)$  be a Cipher defined over  $(\mathcal{K}, \mathcal{M}, \mathcal{C})$  and let our adversary  $\mathcal{A}$  be computationally bounded
- $\mathcal{A}$  picks  $m_0, m_1 \in \mathcal{M}$  and sends to challenger

# Semantic Security

Intuition: the probability that a computationally bounded adversary can learn anything about a message  $m$  given its cipher text  $c$  is negligible.

Experiment  $b$

- Let  $\mathcal{E} = (E, D)$  be a Cipher defined over  $(\mathcal{K}, \mathcal{M}, \mathcal{C})$  and let our adversary  $\mathcal{A}$  be computationally bounded
- $\mathcal{A}$  picks  $m_0, m_1 \in \mathcal{M}$  and sends to challenger
- Challenger selects  $k \xleftarrow{R} \mathcal{K}$

# Semantic Security

Intuition: the probability that a computationally bounded adversary can learn anything about a message  $m$  given its cipher text  $c$  is negligible.

Experiment  $b$

- Let  $\mathcal{E} = (E, D)$  be a Cipher defined over  $(\mathcal{K}, \mathcal{M}, \mathcal{C})$  and let our adversary  $\mathcal{A}$  be computationally bounded
- $\mathcal{A}$  picks  $m_0, m_1 \in \mathcal{M}$  and sends to challenger
- Challenger selects  $k \xleftarrow{R} \mathcal{K}$
- Challenger computes  $E(k, m_b) := c$  and sends  $c$  to adversary

# Semantic Security

Intuition: the probability that a computationally bounded adversary can learn anything about a message  $m$  given its cipher text  $c$  is negligible.

Experiment  $b$

- Let  $\mathcal{E} = (E, D)$  be a Cipher defined over  $(\mathcal{K}, \mathcal{M}, \mathcal{C})$  and let our adversary  $\mathcal{A}$  be computationally bounded
- $\mathcal{A}$  picks  $m_0, m_1 \in \mathcal{M}$  and sends to challenger
- Challenger selects  $k \xleftarrow{R} \mathcal{K}$
- Challenger computes  $E(k, m_b) := c$  and sends  $c$  to adversary
- $\mathcal{A}$  outputs  $b^*$ , guessing which experiment was selected by the Challenger

# Semantic Security Advantage

- The *Semantic Security Advantage (SSA)* of the adversary  $\mathcal{A}$ , is



# Semantic Security Advantage

- The *Semantic Security Advantage (SSA)* of the adversary  $\mathcal{A}$ , is

$$SSA[\mathcal{A}, \mathcal{E}] := |Pr[W_0] - Pr[W_1]|$$

where  $W_b$  is the probability that  $\mathcal{A}$  outputs 1 in experiment  $b$

# Semantic Security Advantage

- The *Semantic Security Advantage (SSA)* of the adversary  $\mathcal{A}$ , is

$$SSA[\mathcal{A}, \mathcal{E}] := |Pr[W_0] - Pr[W_1]|$$

where  $W_b$  is the probability that  $\mathcal{A}$  outputs 1 in experiment  $b$

- At random,  $\mathcal{A}$  has a 50% probability of outputting the correct bit, yielding

$$SSA[\mathcal{A}, \mathcal{E}] := |Pr[W_0] - Pr[W_1]| = 0$$

# Semantic Security Advantage

- The *Semantic Security Advantage* (SSA) of the adversary  $\mathcal{A}$ , is

$$SSA[\mathcal{A}, \mathcal{E}] := |Pr[W_0] - Pr[W_1]|$$

where  $W_b$  is the probability that  $\mathcal{A}$  outputs 1 in experiment  $b$

- At random,  $\mathcal{A}$  has a 50% probability of outputting the correct bit, yielding

$$SSA[\mathcal{A}, \mathcal{E}] := |Pr[W_0] - Pr[W_1]| = 0$$

- In order to be semantically secure, the advantage has to be negligible. We can think of negligible as  $1 + \lambda \approx 1, \lambda = 2^{-100}$

# Semantic Security to Message Recovery

Semantic Security guarantees that an adversary cannot recover a message from a cipher text.

# Semantic Security to Message Recovery

Semantic Security guarantees that an adversary cannot recover a message from a cipher text. Here is our security game for message recovery.

# Semantic Security to Message Recovery

Semantic Security guarantees that an adversary cannot recover a message from a cipher text. Here is our security game for message recovery.

- Let  $\mathcal{E} = (E, D)$  be a semantically secure cipher defined over  $(\mathcal{K}, \mathcal{M}, \mathcal{C})$  and let our adversary  $\mathcal{A}$  be computationally bounded

# Semantic Security to Message Recovery

Semantic Security guarantees that an adversary cannot recover a message from a cipher text. Here is our security game for message recovery.

- Let  $\mathcal{E} = (E, D)$  be a semantically secure cipher defined over  $(\mathcal{K}, \mathcal{M}, \mathcal{C})$  and let our adversary  $\mathcal{A}$  be computationally bounded
- Challenger generates  $k \xleftarrow{R} \mathcal{K}$ ,  $m \xleftarrow{R} \mathcal{M}$  and computes  $E(k, m) = c$  and send  $c$  to the adversary  $\mathcal{A}$

# Semantic Security to Message Recovery

Semantic Security guarantees that an adversary cannot recover a message from a cipher text. Here is our security game for message recovery.

- Let  $\mathcal{E} = (E, D)$  be a semantically secure cipher defined over  $(\mathcal{K}, \mathcal{M}, \mathcal{C})$  and let our adversary  $\mathcal{A}$  be computationally bounded
- Challenger generates  $k \xleftarrow{R} \mathcal{K}$ ,  $m \xleftarrow{R} \mathcal{M}$  and computes  $E(k, m) = c$  and send  $c$  to the adversary  $\mathcal{A}$
- $\mathcal{A}$  outputs message  $m^*$



# Semantic Security to Message Recovery

Semantic Security guarantees that an adversary cannot recover a message from a cipher text. Here is our security game for message recovery.

- Let  $\mathcal{E} = (E, D)$  be a semantically secure cipher defined over  $(\mathcal{K}, \mathcal{M}, \mathcal{C})$  and let our adversary  $\mathcal{A}$  be computationally bounded
- Challenger generates  $k \xleftarrow{R} \mathcal{K}$ ,  $m \xleftarrow{R} \mathcal{M}$  and computes  $E(k, m) = c$  and send  $c$  to the adversary  $\mathcal{A}$
- $\mathcal{A}$  outputs message  $m^*$

## Semantic Security to Message Recovery: cont

Now let's use our adversary  $\mathcal{A}$  to break semantic security, violating our original assumption.

- Let  $\mathcal{E} = (E, D)$  be a semantically secure cipher defined over  $(\mathcal{K}, \mathcal{M}, \mathcal{C})$  and let our adversary  $\mathcal{B}$  be computationally bounded

## Semantic Security to Message Recovery: cont

Now let's use our adversary  $\mathcal{A}$  to break semantic security, violating our original assumption.

- Let  $\mathcal{E} = (E, D)$  be a semantically secure cipher defined over  $(\mathcal{K}, \mathcal{M}, \mathcal{C})$  and let our adversary  $\mathcal{B}$  be computationally bounded
- $\mathcal{B}$  picks  $m_0, m_1 \in \mathcal{M}$  and sends to challenger

## Semantic Security to Message Recovery: cont

Now let's use our adversary  $\mathcal{A}$  to break semantic security, violating our original assumption.

- Let  $\mathcal{E} = (E, D)$  be a semantically secure cipher defined over  $(\mathcal{K}, \mathcal{M}, \mathcal{C})$  and let our adversary  $\mathcal{B}$  be computationally bounded
- $\mathcal{B}$  picks  $m_0, m_1 \in \mathcal{M}$  and sends to challenger
- Challenger selects  $k \xleftarrow{R} \mathcal{K}$

## Semantic Security to Message Recovery: cont

Now let's use our adversary  $\mathcal{A}$  to break semantic security, violating our original assumption.

- Let  $\mathcal{E} = (E, D)$  be a semantically secure cipher defined over  $(\mathcal{K}, \mathcal{M}, \mathcal{C})$  and let our adversary  $\mathcal{B}$  be computationally bounded
- $\mathcal{B}$  picks  $m_0, m_1 \in \mathcal{M}$  and sends to challenger
- Challenger selects  $k \xleftarrow{R} \mathcal{K}$
- Challenger computes  $E(k, m_b) := c$  and sends  $c$  to  $\mathcal{B}$

## Semantic Security to Message Recovery: cont

Now let's use our adversary  $\mathcal{A}$  to break semantic security, violating our original assumption.

- Let  $\mathcal{E} = (E, D)$  be a semantically secure cipher defined over  $(\mathcal{K}, \mathcal{M}, \mathcal{C})$  and let our adversary  $\mathcal{B}$  be computationally bounded
- $\mathcal{B}$  picks  $m_0, m_1 \in \mathcal{M}$  and sends to challenger
- Challenger selects  $k \xleftarrow{R} \mathcal{K}$
- Challenger computes  $E(k, m_b) := c$  and sends  $c$  to  $\mathcal{B}$
- $\mathcal{B}$  sends  $c$  to  $\mathcal{A}$ , simulating the message recovery game.

## Semantic Security to Message Recovery: cont

Now let's use our adversary  $\mathcal{A}$  to break semantic security, violating our original assumption.

- Let  $\mathcal{E} = (E, D)$  be a semantically secure cipher defined over  $(\mathcal{K}, \mathcal{M}, \mathcal{C})$  and let our adversary  $\mathcal{B}$  be computationally bounded
- $\mathcal{B}$  picks  $m_0, m_1 \in \mathcal{M}$  and sends to challenger
- Challenger selects  $k \xleftarrow{R} \mathcal{K}$
- Challenger computes  $E(k, m_b) := c$  and sends  $c$  to  $\mathcal{B}$
- $\mathcal{B}$  sends  $c$  to  $\mathcal{A}$ , simulating the message recovery game.
- $\mathcal{A}$  returns  $m^*$ . If  $m^* = m_1$ ,  $\mathcal{B}$  returns 1, else it returns 0.

## Semantic Security to Message Recovery: cont

Now let's use our adversary  $\mathcal{A}$  to break semantic security, violating our original assumption.

- Let  $\mathcal{E} = (E, D)$  be a semantically secure cipher defined over  $(\mathcal{K}, \mathcal{M}, \mathcal{C})$  and let our adversary  $\mathcal{B}$  be computationally bounded
- $\mathcal{B}$  picks  $m_0, m_1 \in \mathcal{M}$  and sends to challenger
- Challenger selects  $k \xleftarrow{R} \mathcal{K}$
- Challenger computes  $E(k, m_b) := c$  and sends  $c$  to  $\mathcal{B}$
- $\mathcal{B}$  sends  $c$  to  $\mathcal{A}$ , simulating the message recovery game.
- $\mathcal{A}$  returns  $m^*$ . If  $m^* = m_1$ ,  $\mathcal{B}$  returns 1, else it returns 0.

Thus, if we can recover the message, we have broken semantic security.



# Derive Anonymous Routing from Semantic Security

- Let  $\mathcal{E} = (E, D)$  be a semantically secure cipher defined over  $(\mathcal{K}, \mathcal{M}, \mathcal{C})$

# Derive Anonymous Routing from Semantic Security

- Let  $\mathcal{E} = (E, D)$  be a semantically secure cipher defined over  $(\mathcal{K}, \mathcal{M}, \mathcal{C})$
- Suppose Alice wants to send information to Bob, but doesn't want Bob to know that the message came from her.

# Derive Anonymous Routing from Semantic Security

- Let  $\mathcal{E} = (E, D)$  be a semantically secure cipher defined over  $(\mathcal{K}, \mathcal{M}, \mathcal{C})$
- Suppose Alice wants to send information to Bob, but doesn't want Bob to know that the message came from her. (example: you want a radiologist to review a patient's scans without revealing the patients identity)

# Derive Anonymous Routing from Semantic Security

- Let  $\mathcal{E} = (E, D)$  be a semantically secure cipher defined over  $(\mathcal{K}, \mathcal{M}, \mathcal{C})$
- Suppose Alice wants to send information to Bob, but doesn't want Bob to know that the message came from her. (example: you want a radiologist to review a patient's scans without revealing the patients identity)
- Alice must first share  $k_0$  with  $router_0$  and  $k_1$  with  $router_1$ .

# Derive Anonymous Routing from Semantic Security

- Let  $\mathcal{E} = (E, D)$  be a semantically secure cipher defined over  $(\mathcal{K}, \mathcal{M}, \mathcal{C})$
- Suppose Alice wants to send information to Bob, but doesn't want Bob to know that the message came from her. (example: you want a radiologist to review a patient's scans without revealing the patients identity)
- Alice must first share  $k_0$  with  $router_0$  and  $k_1$  with  $router_1$ .
- Then Alice sends  $E(k_0, E(k_1, m))$  to router 1.

# Derive Anonymous Routing from Semantic Security

- Let  $\mathcal{E} = (E, D)$  be a semantically secure cipher defined over  $(\mathcal{K}, \mathcal{M}, \mathcal{C})$
- Suppose Alice wants to send information to Bob, but doesn't want Bob to know that the message came from her. (example: you want a radiologist to review a patient's scans without revealing the patients identity)
- Alice must first share  $k_0$  with  $router_0$  and  $k_1$  with  $router_1$ .
- Then Alice sends  $E(k_0, E(k_1, m))$  to router 1.
- $router_1$  decrypts and sends the message  $E(k_1, m)$  to  $router_2$  in random order.

# Derive Anonymous Routing from Semantic Security

- Let  $\mathcal{E} = (E, D)$  be a semantically secure cipher defined over  $(\mathcal{K}, \mathcal{M}, \mathcal{C})$
- Suppose Alice wants to send information to Bob, but doesn't want Bob to know that the message came from her. (example: you want a radiologist to review a patient's scans without revealing the patients identity)
- Alice must first share  $k_0$  with  $router_0$  and  $k_1$  with  $router_1$ .
- Then Alice sends  $E(k_0, E(k_1, m))$  to router 1.
- $router_1$  decrypts and sends the message  $E(k_1, m)$  to  $router_2$  in random order.
- $router_2$  decrypts and sends the message  $m$  to Bob in random order.

# Derive Anonymous Routing from Semantic Security

- Let  $\mathcal{E} = (E, D)$  be a semantically secure cipher defined over  $(\mathcal{K}, \mathcal{M}, \mathcal{C})$
- Suppose Alice wants to send information to Bob, but doesn't want Bob to know that the message came from her. (example: you want a radiologist to review a patient's scans without revealing the patients identity)
- Alice must first share  $k_0$  with  $router_0$  and  $k_1$  with  $router_1$ .
- Then Alice sends  $E(k_0, E(k_1, m))$  to router 1.
- $router_1$  decrypts and sends the message  $E(k_1, m)$  to  $router_2$  in random order.
- $router_2$  decrypts and sends the message  $m$  to Bob in random order.

Alice's security is  $1/n$  where  $n$  is the number of messages sent along the network.