

OpenVAS Executive Summary

Severity	Count
Critical	2
High	2
Medium	3
Low	3

CPE Inventory

Field	Value
Severity	Low
CVSS Score	0.0
CVE	N/A
Host	192.168.56.101
Port	general/CPE-T
Family	Service detection
Description	This routine uses information collected by other routines about CPE identities of operating systems, services and applications detected during the scan.
Impact	No impact information.
Solution	No solution available.

SSH Brute Force Logins With Default Credentials Reporting

Field	Value
Severity	High
CVSS Score	7.5
CVE	N/A
Host	192.168.56.101
Port	22/tcp
Family	Default Accounts
Description	It was possible to login into the remote SSH server using default credentials. As the NVT 'SSH Brute Force Logins with default Credentials' (OID: 1.3.6.1.4.1.25623.1.0.108013) might run into a timeout the actual reporting of this vulnerability takes place in this NVT instead. The script preference 'Report timeout' allows you to configure if such an timeout is reported.
Impact	No impact information.
Solution	Change the password as soon as possible.

Nikto (NASL wrapper)

Field	Value
Severity	Low
CVSS Score	0.0
CVE	N/A
Host	192.168.56.101
Port	80/tcp
Family	Web application abuses
Description	This plugin uses nikto to find weak CGI scripts and other known issues regarding web server security. See the preferences section for configuration options. Note: The plugin needs the 'nikto' or 'nikto.pl' binary found within the PATH of the user running the scanner and needs to be executable for this user. The existence of this binary is checked and reported separately within 'Availability of scanner helper tools' (OID: 1.3.6.1.4.1.25623.1.0.810000).
Impact	No impact information.
Solution	No solution available.

wapiti (NASL wrapper)

Field	Value
Severity	Low
CVSS Score	0.0
CVE	N/A
Host	192.168.56.101
Port	80/tcp
Family	Web application abuses
Description	This plugin uses wapiti to find web security issues. Make sure to have wapiti 2.x as wapiti 1.x is not supported. See the preferences section for wapiti options. Note that the scanner is using limited set of wapiti options. Therefore, for more complete web assessment, you should use standalone wapiti tool for deeper/customized checks. Note: The plugin needs the 'wapiti' binary found within the PATH of the user running the scanner and needs to be executable for this user. The existence of this binary is checked and reported separately within 'Availability of scanner helper tools' (OID: 1.3.6.1.4.1.25623.1.0.810000).
Impact	No impact information.
Solution	No solution available.

VNC Brute Force Login

Field	Value
Severity	Critical
CVSS Score	9.0
CVE	N/A
Host	192.168.56.101
Port	5900/tcp
Family	Brute force attacks
Description	Try to log in with given passwords via VNC protocol.
Impact	No impact information.
Solution	Change the password to something hard to guess or enable password protection at all.

SSL/TLS: OpenSSL CCS Man in the Middle Security Bypass Vulnerability

Field	Value
Severity	Medium
CVSS Score	6.8
CVE	CVE-2014-0224
Host	192.168.56.101
Port	5432/tcp
Family	SSL and TLS
Description	OpenSSL is prone to security-bypass vulnerability.
Impact	Successfully exploiting this issue may allow attackers to obtain sensitive information by conducting a man-in-the-middle attack. This may lead to other attacks.
Solution	Updates are available. Please see the references for more information.

Apache HTTP Server 'httpOnly' Cookie Information Disclosure Vulnerability

Field	Value
Severity	Medium
CVSS Score	4.3
CVE	CVE-2012-0053
Host	192.168.56.101
Port	80/tcp
Family	Web Servers
Description	This host is running Apache HTTP Server and is prone to cookie information disclosure vulnerability.
Impact	Successful exploitation will allow attackers to obtain sensitive information that may aid in further attacks.
Solution	Upgrade to Apache HTTP Server version 2.2.22 or later.

Multiple Vendors STARTTLS Implementation Plaintext Arbitrary Command Injection Vulnerability

Field	Value
Severity	Medium
CVSS Score	6.8
CVE	CVE-2011-0411, CVE-2011-1430, CVE-2011-1431, CVE-2011-1432, CVE-2011-1506, CVE-2011-1575, CVE-2011-1926, CVE-2011-2165
Host	192.168.56.101
Port	25/tcp
Family	SMTP problems
Description	Multiple vendors' implementations of 'STARTTLS' are prone to a vulnerability that lets attackers inject arbitrary commands.
Impact	An attacker can exploit this issue to execute arbitrary commands in the context of the user running the application. Successful exploits can allow attackers to obtain email usernames and passwords.
Solution	Updates are available. Please see the references for more information.

DistCC Remote Code Execution Vulnerability

Field	Value
Severity	Critical
CVSS Score	9.3
CVE	CVE-2004-2687
Host	192.168.56.101
Port	3632/tcp
Family	Gain a shell remotely
Description	DistCC 2.x, as used in XCode 1.5 and others, when not configured to restrict access to the server port, allows remote attackers to execute arbitrary commands via compilation jobs, which are executed by the server without authorization checks.
Impact	DistCC by default trusts its clients completely that in turn could allow a malicious client to execute arbitrary commands on the server.
Solution	Vendor updates are available. Please see the references for more information. For more information about DistCC's security see the references.

Test HTTP dangerous methods

Field	Value
Severity	High
CVSS Score	7.5
CVE	N/A
Host	192.168.56.101
Port	80/tcp
Family	Remote file access
Description	Misconfigured web servers allows remote clients to perform dangerous HTTP methods such as PUT and DELETE. This script checks if they are enabled and can be misused to upload or delete files.
Impact	- Enabled PUT method: This might allow an attacker to upload and run arbitrary code on this web server. - Enabled DELETE method: This might allow an attacker to delete additional files on this web server.
Solution	Use access restrictions to these dangerous HTTP methods or disable them completely.