

OpenVAS Executive Summary

Severity	Count
Critical	1
High	0
Medium	2
Low	2

OpenVAS / Greenbone Vulnerability Manager Default Credentials

Field	Value
Severity	Critical
CVSS Score	10.0
CVE	N/A
Host	127.0.0.1
Port	9390/tcp
Family	Default Accounts
Description	The remote OpenVAS / Greenbone Vulnerability Manager is installed/configured in a way that it has account(s) with default passwords enabled.
Impact	This issue may be exploited by a remote attacker to gain access to sensitive information or modify system configuration.
Solution	Change the password of the mentioned account(s).

Unknown Vulnerability

Field	Value
Severity	Low
CVSS Score	0.0
CVE	N/A
Host	unknown
Port	unknown
Family	Unknown
Description	No description available.
Impact	No impact information.
Solution	No solution available.

SSL/TLS: Certificate Expired

Field	Value
Severity	Medium
CVSS Score	5.0
CVE	N/A
Host	127.0.0.1
Port	443/tcp
Family	SSL and TLS
Description	The remote server's SSL/TLS certificate has already expired.
Impact	No impact information.
Solution	Replace the SSL/TLS certificate by a new one.

SSL/TLS: Certificate Expired

Field	Value
Severity	Medium
CVSS Score	5.0
CVE	N/A
Host	127.0.0.1
Port	9390/tcp
Family	SSL and TLS
Description	The remote server's SSL/TLS certificate has already expired.
Impact	No impact information.
Solution	Replace the SSL/TLS certificate by a new one.

TCP timestamps

Field	Value
Severity	Low
CVSS Score	2.6
CVE	N/A
Host	127.0.0.1
Port	general/tcp
Family	General
Description	The remote host implements TCP timestamps and therefore allows to compute the uptime.
Impact	A side effect of this feature is that the uptime of the remote host can sometimes be computed.
Solution	To disable TCP timestamps on linux add the line 'net.ipv4.tcp_timestamps = 0' to /etc/sysctl.conf. Execute 'sysctl -p' to apply the settings at runtime. To disable TCP timestamps on Windows execute 'netsh int tcp set global timestamps=disabled'. Starting with Windows Server 2008 and Vista, the timestamp can not be completely disabled. The default behavior of the TCP/IP stack on this Systems is to not use the Timestamp options when initiating TCP connections, but use them if the TCP peer that is initiating communication includes them in their synchronize (SYN) segment. See the references for more information.