

Specification of Red JonPRL Signatures

Jon Sterling

January 10, 2016

1 Grammar

The grammar of Red JonPRL signatures is presented in Figure 1. Note that an optional production of sort s is formatted $\langle s \rangle$ in the rules.

$sigexp$	$::=$	$\langle \cdot \rangle$	empty signature
		$sigexp. sigdec$	signature extension
$sigdec$	$::=$	Def $opid \langle [params] \rangle \langle (args) \rangle : sortid = [term]$	operator definition
		Tac $opid \langle [params] \rangle \langle (args) \rangle = [term]$	tactic definition
		Thm $opid \langle [params] \rangle \langle (args) \rangle : [term] \text{ by } [term]$	theorem declaration
$params$	$::=$	$\langle \cdot \rangle$	empty parameter list
		$params, symbind$	parameter list extension
$args$	$::=$	$\langle \cdot \rangle$	empty argument list
		$args, metabind$	argument list extension
$symbind$	$::=$	$symid : sortid$	symbol binding
$metabind$	$::=$	$metaid : valence$	metavariable binding
$valence$	$::=$	$\langle \langle \{ sortlist \} \rangle \langle [sortlist] \rangle . \rangle sortid$	valence
$sortlist$	$::=$	$\langle \cdot \rangle$	empty sort list
		$sortlist, sortid$	sort list extension

Figure 1: Grammar of signature expressions. The identifier sorts $opid$, $sortid$, $symid$ and $metaid$ can be assumed to be arbitrary strings; the sort $term$ is left uninterpreted.

2 Static Semantics

The static semantics for Red JonPRL signatures begins with a specification of the class of *semantic* objects that will serve as the meanings for the *syntactic* objects defined in Section 1. We assume an ambient abstract binding tree signature such that at least the following facts hold:

$$\frac{\overline{tac \ sort} \quad \overline{thm \ sort} \quad \overline{exp \ sort} \quad \overline{opid \ sort}}{\Upsilon \Vdash \text{prove} : (. \text{exp}, . \text{tac}) \text{ thm}}$$

Then, our semantic objects are defined as in Figure 2.

a, b	\in	Sym	
\mathbf{m}, \mathbf{n}	\in	Metavar	
σ, τ	\in	Sort	$\triangleq \{ \tau \mid \tau \text{ sort} \}$
v	\in	Valence	$\triangleq \{ v \mid v \text{ valence} \}$
ϑ	\in	Opid	$\triangleq \text{Sym}$
Υ	\in	Params	$\triangleq \text{Sym} \rightarrow \text{Sort}$
Θ	\in	Args	$\triangleq \text{Metavar} \rightarrow \text{Valence}$
M, N	\in	$\text{Tm}(\Theta, \Upsilon, \tau)$	$\triangleq \{ M \mid \Theta \triangleright \Upsilon \parallel \cdot \vdash M : \tau \}$
D	\in	Decl	$\triangleq \coprod_{\Upsilon, \Theta, \tau} \text{Tm}(\Theta, \Upsilon, \tau)$
Σ	\in	Sig	$\triangleq \text{Opid} \rightarrow \text{Decl}$

Figure 2: Specification of the semantic objects.

A *natural semantics* hinges on the elaboration judgment $E \vdash A \Rightarrow A'$, which means that the syntactic object A elaborates to the semantic object A' in the environment E . Let the $\Upsilon_\Sigma \in \text{Params}$ be defined as follows:

$$\Upsilon_\Sigma(\vartheta) \triangleq \begin{cases} \text{opid} & \text{if } \vartheta \in \text{dom}(\Sigma) \\ \perp & \text{otherwise} \end{cases}$$

Symbol Bindings

$$\boxed{\Sigma \vdash \text{symbolbind} \Rightarrow (a, \tau)}$$

$$\frac{\Sigma \vdash \text{symid} \Rightarrow a \quad \Sigma \vdash \text{sortid} \Rightarrow \tau}{\Sigma \vdash \text{symid} : \text{sortid} \Rightarrow (a, \tau)} \quad (1)$$

Metavariable Bindings

$$\boxed{\Sigma \vdash \text{metabind} \Rightarrow (\mathbf{m}, v)}$$

$$\frac{\Sigma \vdash \text{metaid} \Rightarrow \mathbf{m} \quad \Sigma \vdash \text{metaid} \Rightarrow v}{\Sigma \vdash \text{metaid} : \text{metaid} \Rightarrow (\mathbf{m}, v)} \quad (2)$$

Parameters

$$\boxed{\Sigma \vdash \text{params} \Rightarrow \Upsilon}$$

$$\overline{\Sigma \vdash \langle \cdot \rangle \Rightarrow \{ \}} \quad (3)$$

$$\frac{\Sigma \vdash \text{params} \Rightarrow \Upsilon \quad \Sigma \vdash \text{symbolbind} \Rightarrow (a, \tau)}{\Sigma \vdash \text{params}, \text{symbolbind} \Rightarrow \Upsilon \cup a \mapsto \tau} \quad (4)$$

Arguments

$$\boxed{\Sigma \vdash \text{args} \Rightarrow \Theta}$$

$$\overline{\Sigma \vdash \langle \cdot \rangle \Rightarrow \{ \}} \quad (5)$$

$$\frac{\Sigma \vdash \text{args} \Rightarrow \Theta \quad \Sigma \vdash \text{metabind} \Rightarrow (\mathbf{m}, v)}{\Sigma \vdash \text{args}, \text{metabind} \Rightarrow \Theta \cup \mathbf{m} \mapsto v} \quad (6)$$

Operator Identifiers

$$\boxed{\Sigma \vdash \text{opid} \Rightarrow \vartheta}$$

$$\frac{\vartheta \notin \text{dom}(\Sigma)}{\Sigma \vdash \text{opid} \Rightarrow \vartheta} \quad (7)$$

Declarations

$$\boxed{\Sigma \vdash \text{sigdec} \Rightarrow (\vartheta, D)}$$

$$\frac{\begin{array}{lll} \Sigma \vdash \text{params} \Rightarrow \Upsilon & \Sigma \vdash \text{sortid} \Rightarrow \tau & \Sigma \vdash \text{opid} \Rightarrow \vartheta \\ \Sigma \vdash \text{args} \Rightarrow \Theta & \Sigma \vdash \text{term} \Rightarrow M & \Theta \triangleright \Upsilon_\Sigma \oplus \Upsilon \parallel \cdot \vdash M : \tau \end{array}}{\Sigma \vdash \text{Def opid} \langle [\text{params}] \rangle \langle (\text{args}) \rangle : \text{sortid} = [\text{term}] \Rightarrow (\vartheta, \langle \Upsilon, \Theta, \tau, M \rangle)} \quad (8)$$

$$\frac{\begin{array}{ll} \Sigma \vdash \text{params} \Rightarrow \Upsilon & \Sigma \vdash \text{opid} \Rightarrow \vartheta \\ \Sigma \vdash \text{args} \Rightarrow \Theta & \Theta \triangleright \Upsilon_\Sigma \oplus \Upsilon \parallel \cdot \vdash M : \text{tac} \\ \Sigma \vdash \text{term} \Rightarrow M & \end{array}}{\Sigma \vdash \text{Tac opid} \langle [\text{params}] \rangle \langle (\text{args}) \rangle = [\text{term}] \Rightarrow (\vartheta, \langle \Upsilon, \Theta, \text{tac}, M \rangle)} \quad (9)$$

$$\frac{\begin{array}{llll} \Sigma \vdash \text{params} \Rightarrow \Upsilon & \Sigma \vdash \text{term}_1 \Rightarrow P & \Theta \triangleright \Upsilon_\Sigma \oplus \Upsilon \parallel \cdot \vdash P : \text{exp} & \Sigma \vdash \text{opid} \Rightarrow \vartheta \\ \Sigma \vdash \text{args} \Rightarrow \Theta & \Sigma \vdash \text{term}_2 \Rightarrow M & \Theta \triangleright \Upsilon_\Sigma \oplus \Upsilon \parallel \cdot \vdash M : \text{tac} & \end{array}}{\Sigma \vdash \text{Thm opid} \langle [\text{params}] \rangle \langle (\text{args}) \rangle : [\text{term}_1] \text{ by } [\text{term}_2] \Rightarrow (\vartheta, \langle \Upsilon, \Theta, \text{thm}, \text{prove}(P; M) \rangle)} \quad (10)$$

Signatures

$$\boxed{\vdash \text{sigexp} \Rightarrow \Sigma}$$

$$\overline{\vdash \langle \cdot \rangle \Rightarrow \{ \}} \quad (11)$$

$$\frac{\vdash \text{sigexp} \Rightarrow \Sigma \quad \Sigma \vdash \text{sigdec} \Rightarrow (\vartheta, D)}{\vdash \text{sigexp. sigdec} \Rightarrow \Sigma \cup \vartheta \mapsto D} \quad (12)$$