

The Definition of **Red JonPRL**,
the people's refinement logic

The JonPRL Group

January 23, 2016

Contents

1	Signatures	2
1.1	Grammar	2
1.2	Static Semantics	2

Chapter 1

Signatures

*Decisively Smash The Formalist
Clique!*

Chairman Jon

A *signature* is a collection of definitions, including terms, tactics and theorems.

1.1 Grammar

The grammar of **Red JonPRL** signatures is presented in Figure 1.1. Note that an optional production of sort s is formatted $\langle s \rangle$ in the rules.

$sigexp$	$::=$	$\langle \cdot \rangle$ $sigexp \ sigdec.$	empty signature signature extension
$sigdec$	$::=$	$\text{Def } opid \langle [params] \rangle \langle (args) \rangle : sortid = [term]$ $\text{Tac } opid \langle [params] \rangle \langle (args) \rangle = [term]$ $\text{Thm } opid \langle [params] \rangle \langle (args) \rangle : [term] \text{ by } [term]$	operator definition tactic definition theorem declaration
$params$	$::=$	$\langle \cdot \rangle$ $params, symbind$	empty parameter list parameter list extension
$args$	$::=$	$\langle \cdot \rangle$ $args, metabind$	empty argument list argument list extension
$symbind$	$::=$	$symid : sortid$	symbol binding
$metabind$	$::=$	$metaid : valence$	metavariable binding
$valence$	$::=$	$\langle \{ [sortlist] \} \langle [sortlist] \rangle . \rangle sortid$	valence
$sortlist$	$::=$	$\langle \cdot \rangle$ $sortlist, sortid$	empty sort list sort list extension

Figure 1.1: Grammar of signature expressions. The identifier sorts $opid$, $sortid$, $symid$ and $metaid$ can be assumed to be arbitrary strings; the sort $term$ is left uninterpreted.

1.2 Static Semantics

The static semantics for **Red JonPRL** signatures begins with a specification of the class of *semantic* objects that will serve as the meanings for the *syntactic* objects defined in Section 1.1. We assume an ambient abstract binding tree signature such that at least the following facts hold:

$$\frac{\overline{\text{tac sort}} \quad \overline{\text{thm sort}} \quad \overline{\text{exp sort}} \quad \overline{\text{opid sort}}}{\Upsilon \Vdash \text{prove} : (\text{. exp}, \text{. tac}) \text{ thm}}$$

Then, our semantic objects are defined as in Figure 1.2.

$$\begin{array}{llll} a, b & \in & \text{Sym} \\ \mathbf{m}, \mathbf{n} & \in & \text{Metavar} \\ \sigma, \tau & \in & \text{Sort} & \triangleq \{ \tau \mid \tau \text{ sort} \} \\ v & \in & \text{ProdValence} & \triangleq \{ v \mid v \text{ valence} \} \\ \vartheta & \in & \text{Opid} & \triangleq \text{Sym} \\ \Upsilon & \in & \text{Params} & \triangleq \text{Sym} \rightarrow \text{Sort} \\ \Theta & \in & \text{Args} & \triangleq \text{Metavar} \rightarrow \text{ProdValence} \\ M, N & \in & \text{Tm}(\Theta, \Upsilon, \tau) & \triangleq \{ M \mid \Theta \triangleright \Upsilon \parallel \cdot \vdash M : \tau \} \\ D & \in & \text{Decl} & \triangleq \coprod_{\Upsilon, \Theta, \tau} \text{Tm}(\Theta, \Upsilon, \tau) \\ \Sigma & \in & \text{Sig} & \triangleq \text{Opid} \rightarrow \text{Decl} \end{array}$$

Figure 1.2: Specification of the semantic objects.

A *natural semantics* hinges on the elaboration judgment $E \vdash A \Rightarrow A'$, which means that the syntactic object A elaborates to the semantic object A' in the environment E . Let the $\Upsilon_\Sigma \in \text{Params}$ be defined as follows:

$$\Upsilon_\Sigma(\vartheta) \triangleq \begin{cases} \text{opid} & \text{if } \vartheta \in \text{dom}(\Sigma) \\ \perp & \text{otherwise} \end{cases}$$

Symbol Bindings

$$\boxed{\Sigma \vdash \text{sybind} \Rightarrow (a, \tau)}$$

$$\frac{\Sigma \vdash \text{symid} \Rightarrow a \quad \Sigma \vdash \text{sortid} \Rightarrow \tau}{\Sigma \vdash \text{symid} : \text{sortid} \Rightarrow (a, \tau)} \quad (1.1)$$

Metavariable Bindings

$$\boxed{\Sigma \vdash \text{metabind} \Rightarrow (\mathbf{m}, v)}$$

$$\frac{\Sigma \vdash \text{metaid} \Rightarrow \mathbf{m} \quad \Sigma \vdash \text{valence} \Rightarrow v}{\Sigma \vdash \text{metaid} : \text{valence} \Rightarrow (\mathbf{m}, v)} \quad (1.2)$$

Parameters

$$\boxed{\Sigma \vdash \text{params} \Rightarrow \Upsilon}$$

$$\overline{\Sigma \vdash \langle \cdot \rangle \Rightarrow \{ \}} \quad (1.3)$$

$$\frac{\Sigma \vdash \text{params} \Rightarrow \Upsilon \quad \Sigma \vdash \text{sybind} \Rightarrow (a, \tau)}{\Sigma \vdash \text{params}, \text{sybind} \Rightarrow \Upsilon \cup a \mapsto \tau} \quad (1.4)$$

Arguments

$$\boxed{\Sigma \vdash \text{args} \Rightarrow \Theta}$$

$$\overline{\Sigma \vdash \langle \cdot \rangle \Rightarrow \{ \}} \quad (1.5)$$

$$\frac{\Sigma \vdash \text{args} \Rightarrow \Theta \quad \Sigma \vdash \text{metabind} \Rightarrow (\mathbf{m}, v)}{\Sigma \vdash \text{args}, \text{metabind} \Rightarrow \Theta \cup \mathbf{m} \mapsto v} \quad (1.6)$$

Operator Identifiers

$$\boxed{\Sigma \vdash \textit{opid} \Longrightarrow \vartheta}$$

$$\frac{\vartheta \notin \mathbf{dom}(\Sigma)}{\Sigma \vdash \textit{opid} \Longrightarrow \vartheta} \quad (1.7)$$

Declarations

$$\boxed{\Sigma \vdash \textit{sigdec} \Longrightarrow (\vartheta, D)}$$

$$\frac{\begin{array}{lll} \Sigma \vdash \textit{params} \Longrightarrow \Upsilon & \Sigma \vdash \textit{sortid} \Longrightarrow \tau & \Sigma \vdash \textit{opid} \Longrightarrow \vartheta \\ \Sigma \vdash \textit{args} \Longrightarrow \Theta & \Sigma \vdash \textit{term} \Longrightarrow M & \Theta \triangleright \Upsilon_{\Sigma} \oplus \Upsilon \parallel \cdot \vdash M : \tau \end{array}}{\Sigma \vdash \mathbf{Def} \textit{ opid} \langle [\textit{params}] \rangle \langle (\textit{args}) \rangle : \textit{sortid} = [\textit{term}] \Longrightarrow (\vartheta, \langle \Upsilon, \Theta, \tau, M \rangle)} \quad (1.8)$$

$$\frac{\begin{array}{ll} \Sigma \vdash \textit{params} \Longrightarrow \Upsilon & \Sigma \vdash \textit{opid} \Longrightarrow \vartheta \\ \Sigma \vdash \textit{args} \Longrightarrow \Theta & \Theta \triangleright \Upsilon_{\Sigma} \oplus \Upsilon \parallel \cdot \vdash M : \mathbf{tac} \\ \Sigma \vdash \textit{term} \Longrightarrow M & \end{array}}{\Sigma \vdash \mathbf{Tac} \textit{ opid} \langle [\textit{params}] \rangle \langle (\textit{args}) \rangle = [\textit{term}] \Longrightarrow (\vartheta, \langle \Upsilon, \Theta, \mathbf{tac}, M \rangle)} \quad (1.9)$$

$$\frac{\begin{array}{llll} \Sigma \vdash \textit{params} \Longrightarrow \Upsilon & \Sigma \vdash \textit{term}_1 \Longrightarrow P & \Theta \triangleright \Upsilon_{\Sigma} \oplus \Upsilon \parallel \cdot \vdash P : \mathbf{exp} & \Sigma \vdash \textit{opid} \Longrightarrow \vartheta \\ \Sigma \vdash \textit{args} \Longrightarrow \Theta & \Sigma \vdash \textit{term}_2 \Longrightarrow M & \Theta \triangleright \Upsilon_{\Sigma} \oplus \Upsilon \parallel \cdot \vdash M : \mathbf{tac} & \end{array}}{\Sigma \vdash \mathbf{Thm} \textit{ opid} \langle [\textit{params}] \rangle \langle (\textit{args}) \rangle : [\textit{term}_1] \text{ by } [\textit{term}_2] \Longrightarrow (\vartheta, \langle \Upsilon, \Theta, \mathbf{thm}, \mathbf{prove}(P; M) \rangle)} \quad (1.10)$$

Signatures

$$\boxed{\vdash \textit{sigexp} \Longrightarrow \Sigma}$$

$$\overline{\vdash \langle \cdot \rangle \Longrightarrow \{ \}} \quad (1.11)$$

$$\frac{\vdash \textit{sigexp} \Longrightarrow \Sigma \quad \Sigma \vdash \textit{sigdec} \Longrightarrow (\vartheta, D)}{\vdash \textit{sigexp sigdec.} \Longrightarrow \Sigma \cup \vartheta \mapsto D} \quad (1.12)$$