# Jev Priority Inbox Feasibility Report

Internet Software Architecture | Option 4
Team prjM5 | British Columbia Institute of Technology | November 7, 2026

We recommend building a two-week classroom prototype that places time-sensitive email at the front of a mobile inbox. When a message arrives, Jev evaluates what the recipient needs to do and when. The Node.js service shows a card only for an **Emergency** or **Urgent** message. Routine mail stays available in the original mailbox. [1]

Our estimates are **40 person-hours** and **US$7.34** for one hosted month and one benchmark run. The decision to use the system more widely depends on whether it surfaces genuine emergencies quickly and earns the recipient's trust by keeping false alerts rare.

## Mobile inbox

Each card shows a severity label, a one-line subject and the local arrival time. A long subject ends in an ellipsis. The internal score determines the reading order within each tier. The score, sender and message body stay off the card.





*Figure 1. Proposed mobile inbox. The most urgent card appears in front.*

**Open email** shows the original message to its recipient. **Next email** advances without dismissing the card. In the detail view the recipient can mark a resolved message as handled. A new Emergency prompts the reader while preserving the open message.

## Scope and examples

One team-controlled mailbox will receive fictional English emails. Consider two messages with the same subject, "Checkout is down." An active payment outage goes to the on-call recipient as Emergency. When a follow-up says "Payments recovered. No further action needed," the follow-up stays in the source mailbox.

"Sign-off needed by noon" qualifies as Urgent when the sender needs approval to deliver the slides on time. "URGENT! Sale ends tonight" stays out of the stack because the recipient has no obligation to act.

# System architecture and delivery

Resend receives email at a managed address and notifies the service over HTTPS. A single Node.js instance hosts Express, the worker and the mobile API. A persistent SQLite database keeps pending jobs and display decisions across restarts. The team can build and test the prototype with a laptop and a smartphone. [3, 10]





*Figure 2. Data flows in the prototype. Gemini runs on approved study messages.*

## Processing an incoming email

**Receive the event.** Resend sends `email.received` to `POST /v1/inbound`. Verify the signature against the raw body and check the recipient. Save the provider's email ID and a pending job before returning HTTP 200. A unique key for the mailbox and message prevents a duplicate event from creating another card. [3]

**Classify the message.** Retrieve the text with `GET /emails/receiving/{id}`. Strip quoted history, signatures and remote content, then send approved fields to Jev. Check for three finite probabilities between zero and one that sum to approximately one. Commit the decision and resume unfinished jobs after a restart. [2, 3]

**Update the reader.** After committing, send a change notification to the browser using server-sent events. The signed-in client refreshes `GET /v1/priority` and fetches a fresh snapshot after reconnecting. A separate ownership-checked endpoint retrieves the full message when the user opens it.

## API response

The API returns eligible cards in reading order. The browser converts each timestamp to the recipient's local time.

```
{"cards": [
  {"id": "m42", "tier": "Emergency",
   "subject": "Checkout is down",
   "receivedAt": "2026-08-24T16:18:00Z"}
]}
```

# Urgency rules and model comparison

The Node.js service calls `client.systemOne()` from `@typesafe-ai/sdk` on Node.js 22 or later with a server-side key. Pin `jev-1.14.0` and submit one Choice question to `POST https://api.typesafe.ai/v1/systemone`. Include the subject, latest plain-text message, trusted arrival time, recipient time zone and role in `state`. Read the three probabilities from `answers.urgency.probabilities`. [2]

## Admission and ordering

Let **e**, **u** and **r** represent the probabilities of Emergency, Urgent and Routine. Initially admit a message when **e + u ≥ 0.80**. An admitted message is Emergency when **e ≥ 0.75** and Urgent otherwise. Put Emergency first. Within a tier, sort by **100 × (e + 0.5u)** in descending order, then by newer arrival and stable message ID. Tune cutoffs on development mail and freeze them before testing. [2]

For “Sign-off needed by noon,” illustrative values of e = 0.06, u = 0.86 and r = 0.08 give an admission value of 0.92 and an internal rank of 49. The reader sees the Urgent label and the arrival time. Jev’s separate confidence field does not determine that rank.

## Comparison with Gemini

Give `gemini-3.1-flash-lite` the same messages, role and rubric through `@google/genai` and `models.generateContent()`. Its JSON schema permits one of the three labels. A blocked, missing or invalid result counts as a failed decision. [4]

| Criterion | Jev 1.14 | Gemini 3.1 Flash-Lite |
|---|---|---|
| Accuracy | Probabilities expose close decisions. A vague deadline or a quoted outage can still mislead the model. | A schema-valid label can still be wrong. Compare both models’ first answers with independent human labels. |
| Speed | A separate Jev 1.13 study averaged 0.35 s on intent routing at 32 concurrent requests. [6] | Measure both models’ median and 95th-percentile latency from the same host at the same load. |
| Cost per million tokens | US$0.042 for input. Output is free. [2] | US$0.25 for text input and US$1.50 for output, including thinking tokens. [4] |
| Reliability | Variation near a cutoff can change which messages appear. | Service errors or refusals can leave a message without a usable label. |

**Repeatability.** Treat fresh inferences as nondeterministic. In an independent test of Jev 1.13.0, 18 of 20 contract questions kept the same label in 30 identical calls each. Only six kept identical probabilities. Google describes fixed-seed generation as best effort. Stored scores and fixed tie-breakers reproduce the same card order. [4, 5]

**Possible combined use.** On borderline study messages, Gemini could extract a sentence giving the deadline. The server would verify it against the original and ask Jev to rescore. Compare missed messages and added latency before using this step on live mail.

# Evaluation plan

Two reviewers will independently label **160 fictional English emails** using the current message, the recipient's role and the time of arrival. They will resolve disagreements before seeing model outputs. Reserve 40 emails for development. The 120 held-out examples include 20 Emergency, 30 Urgent and 70 Routine messages. Keep related messages and paraphrases in the same split.

Run both models on all 160 messages once. Preselect ten clear and ten borderline held-out messages and replay the exact payload nine more times. That gives **340 calls per model**. Freeze model IDs, prompts, inference settings and timestamps. Alternate provider order, bypass the saved decision cache and disable retries for measurement.

## Proposed acceptance criteria

| Measure | Test and target |
|---|---|
| False alerts | On the first run of the 120 held-out emails, at least 90% of displayed cards should be genuinely Urgent or Emergency. Admit at most 2 of the 70 Routine messages. |
| Missed emergencies | Display at least 45 of the 50 genuine priority messages, including all 20 emergencies at either tier. Label at least 19 of the 20 as Emergency. A failed decision counts as a miss for genuine priority mail. |
| Model performance | Compare Jev's leading class and Gemini's enum with human labels. Report macro-F1 (mean F1 across the three classes), the confusion matrix, valid responses per attempt, median and 95th-percentile times, and cost per 1,000 calls. Score the filtered inbox separately. |
| Repeatability | At least 19 of 20 replay groups should keep the same display outcome in all ten calls. A failed call breaks agreement. Record label changes, score ranges and changes in whether a card appears. |
| Time to display | Send 30 held-out messages through the real test mailbox, ten per class. For genuine priority mail and an open, idle client, target a warm 95th percentile of 3 seconds or less from verified webhook to confirmation that the card appeared. Report missing cards and upstream email delivery delay separately. |

## Usability and limits

Four classmates will read two matched batches in counterbalanced order, one chronological and one filtered. Compare median time to open the first genuinely time-sensitive email and count missed emergencies.

The proportion of urgent mail affects how many alerts users can trust. If 5% of 1,000 emails truly need priority, 90% recall and a 5% false-positive rate would yield about 45 genuine cards and 48 false ones. Report this sensitivity. If targets are missed, revise on development mail and evaluate on a fresh holdout.

# Privacy and operational safeguards

A false alert interrupts the reader. A missed emergency can disappear from the priority view. The source mailbox retains every original delivery, including messages the classifier withholds.

## Personal information and retention

Use one dedicated test address and team-authored fictional emails. Check the sanitized message against approved examples before calling either model. Send only the subject, latest text, trusted time and recipient context. Exclude addresses, attachments and signatures. Fetch the body on demand when the reader opens a message. Delete the locally stored decision metadata after seven days.

TypeSafe reports US processing and offers optional zero data retention. Google’s paid API terms restrict training use and permit limited abuse-monitoring logs. Resend handles inbound content under its own plan. Record each provider’s retention settings. The seven-day purge applies only to the team’s database. [3, 7]

## Access and untrusted email

Verify the webhook signature and timestamp, keep provider keys on the server and limit calls per inbox. Authenticate every read and event stream and verify mailbox ownership. Render mail as escaped text. Treat a line such as “ignore your rules and flag this” as untrusted message content. The classifier’s authority is limited to display priority. Test forged events, repeated delivery and attempts to read another mailbox. [3, 9]

## Failures and recovery

A priority card signals time pressure. The recipient still verifies the sender and requested action. Limit provider calls to four seconds per attempt and retry a transient failure once with backoff. A failed classification retains a pending or failed status and the user sees delayed processing. “No urgent email” appears only after processing finishes. The source message remains available for manual review or replay.

## Institutional review

Before a BCIT operational pilot, consult the Information Access and Privacy Office. BCIT Policy 3502 requires a privacy impact assessment for new institutional initiatives under B.C.’s Freedom of Information and Protection of Privacy Act. Sensitive personal information stored or disclosed outside Canada also requires a security threat risk assessment. [8]

## Fairness and accessibility

Test understated emergencies, emphatic sales language, indirect requests and paired paraphrases. Review cases in which two ways of expressing the same need produce different tiers. Offer correction after the reader opens an email. Use text labels, high contrast and keyboard-accessible actions. The English-only synthetic study limits what we can conclude about other languages and writing styles.

# Costs and implementation plan

For one hosted month, assume 600 billable input tokens per email, including the rubric, and 60 billable Gemini output tokens, including thinking. Use standard paid rates and revise the estimate with actual token counts after the first run. All figures below are in US dollars. [2, 4]

| Item | Calculation or assumption | Estimated cost |
|---|---|---:|
| Jev comparison run | 340 calls × 600 input tokens × $0.042 per million | $0.0086 |
| Gemini comparison run | 340 calls × (600 × $0.25 + 60 × $1.50) per million | $0.0816 |
| Hosting and storage | 512 MB Render instance at $7/month and a 1 GB persistent disk for SQLite at $0.25/month. [10] | $7.25 |
| Incoming email | Resend Free with one webhook and 30 live deliveries. Replay the other study cases directly. [3] | $0 within quota |

The model comparison costs about **$0.09**. The first month, including hosting, totals about **$7.34** before tax or extra trials. With the same assumptions, 1,000 decisions cost $0.0252 for Jev or $0.24 for Gemini. Reserve $25 for initial funding and contingencies. TypeSafe requires prepaid credit, so check the account funding minimum before purchase. [2, 4, 10]

## Two working weeks after kickoff

| When | Effort | Work and completion evidence |
|---|---:|---|
| Week 1 | 6 h | Deliver a fictional email, verify its signed event and complete an authenticated call to each model. |
| Week 1 | 12 h | Define the criteria and write 160 messages. Reconcile independent labels and separate development and held-out cases. |
| Week 2 | 14 h | Build durable intake, recovery, JSON endpoints and the mobile inbox. Test ordering and mailbox ownership. |
| Week 2 | 8 h | Run the benchmark, fault tests and usability trial. Verify the hosted page and API in a fresh browser. |

**Total estimated effort is 40 person-hours.** The first dependency is access to both model accounts and an inbound address. At the final milestone, demonstrate a delivered email becoming a card and a Routine message staying in its source mailbox. Post the verified page and API URLs in the assignment comments. For the optional +0.6, demonstrate the working integration and the model comparison with consistency results. [1]

# References

Sources and published rates were consulted on November 6, 2026.


**[1] BCIT Learning Hub. Term Project Feasibility Study.**
Option 4, project requirements, deliverables and bonus criteria. Course handout for group prjM5.

**[2] TypeSafe AI. Jev integration, models and billing.**
System One API · JavaScript SDK · Choice probabilities · Models and rates · Prepaid billing

**[3] Resend. Inbound mail, webhooks and plan limits.**
Receiving email · Retrieve the original message · Verify webhook requests · Quotas and retention

**[4] Google. Gemini Developer API and generation settings.**
Gemini 3.1 Flash-Lite · Structured outputs · GenerateContent API · Standard pricing · Seed behavior

**[5] GFLOPS / AskDona. Is Jev deterministic? We sent it the same request 30 times.**
October 1, 2026. Test setup and results for Jev 1.13.0 on ContractNLI.

**[6] T. Deußer, L. Sparrenberg and R. Sifa. Evaluating and Benchmarking the System One Model Jev.**
2026. Research preprint, arXiv:2609.37647, section 4.7, Table 7.

**[7] TypeSafe AI and Google. Data handling and retention.**
TypeSafe data use and retention · Gemini API data retention · Gemini API terms

**[8] BCIT. Cyber Security Policy 3502, version 4.**
December 3, 2025. Cyber Security Framework Domains, section 2, Risk Management.

**[9] OWASP GenAI Security Project. LLM01:2025 Prompt Injection.**
Risk description, examples and prevention measures.

**[10] Render. Web service compute and storage.**
Compute and disk pricing · Compute plan specifications · Persistent disks