






# **L1/L2 Trigger Test Framework**








# Not only for testing:

Offline reprocessing with new trigger conditions is easily possible



## Thanks to Angela:

### MC and burst files can be read out

- MC and offline data can be processed
- Trigger efficiency analysis
- Reprocessing data with new trigger settings


### To be done by detectors

- Provide detector specific configurations
- Ask Angela how to produce input data
- Read docs and ask Angela/me to get started
- Implement L1/L2 algorithms



**Not only for testing:**

Offline reprocessing with new trigger conditions is easily possible



## Configuration of

- enabled cuts
- downscalings
- L1/L2 bypassing
- trigger parameters



Configuration is stored automatically in city



## Configuration of

- enabled cuts
- downscalings
- L1/L2 bypassing
- trigger parameters



**Config may be stored automatically in git:**

**Get config by date:**

```
git checkout 'master@{2015-06-15 18:31:43}'
```

**Get config by runID:**

```
git checkout -b run1234 1234
```



## Trigger decision and downscaling:

- every detector generates an 8 bit trigger word
- every possible value has its own downscaling factor
- based on all 8 bit words a global L1/L2 word (8 bit) is generated

## Information is lost!

- detector specific trigger word should be stored
- reconstructed data should also be stored and reused offline

A special detector ID may be used to store data in output data

11

If you have questions, please contact

**angela.romano@cern.ch**  
or **kunzej@cern.ch**

and please keep in mind....



I'm going to leave  
NA62 end of  
march!

