The summary tables

The annotation the whole session rests on: one row per sample, one block per level, downloadable as it is stored.

AT A GLANCE

Where	Summary → Tables
Shows	Two blocks — **Protein Metadata** and **Phospho Metadata**. Nothing else.
Data levels	Protein and phosphosite. Phosphoprotein, peptide and precursor have no block here.
Needs	An uploaded dataset and a generated annotation for that level. Without the annotation the block says Metadata not available yet.
Source	The stored annotation metadata — the sample table, not the measurement matrix. No filtering, imputation or data source enters this page.
Download	One CSV per block.
In viewer mode	This is the only Summary → tab that exists.

1 What is collected here

Every plot in the session labels its samples condition_n and colours them by condition, and every statistical test picks its columns by condition. All of that comes from one table per level, built on the annotation page and stored with the dataset. This page is that table, printed as it stands.

There are two blocks, in this order:

- **Protein Metadata** — the annotation of the protein dataset.
- **Phospho Metadata** — the annotation of the phosphosite dataset.

Each block carries a count line above the table, reading Rows: r | Columns: c. The rows are

samples, not features: Rows is the number of annotated sample columns at that level, and Columns is the width of the metadata table, which grows when a metadata file with extra grouping columns was uploaded.

> **EASY TO GET WRONG**
>
> This page is not the session's collected results. The coverage, boxplot, coefficient-of-variation and completeness tables each stay below the plot that produces them, and each downloads from there; the volcano and ANOVA result tables stay on Statistics →. What is gathered here is the annotation, because that is the one table every other page depends on and the one a reader of a finished analysis has to be able to check.

What a row holds

Columns of the metadata table

Column	What it holds
sample	The original sample name — the header of that column in the uploaded data file, exactly as it was spelled there.
condition	The condition the sample was assigned to. This is what the plots group and colour by, and what the condition selectors on every other page offer.
pair_id	Present when supplied in metadata or saved through a pairing panel. Two samples that share a pair_id represent the intended matched experimental unit in two conditions, and a paired test matches them by it.

Any further column of an uploaded metadata file is kept and shown as well, under a name made unique if the file repeated one. A metadata file with no column literally named condition has its first non-sample column copied into condition, so the original column and the condition column can both appear, holding the same values.

When a block is empty

- No dataset of that level is loaded, or its annotation has not been generated: the block reads Metadata not available yet.
- The annotation exists but its metadata table is empty: the same message. An empty metadata table means no sample was assigned, so no plot at that level will draw either.
- The table exists but has no columns the browser can render: No table rows available.
- Phosphoprotein, peptide and precursor never get a block, however many of them are loaded. A phosphoprotein dataset produced by a collapse inherits the phosphosite annotation, which is the block above it.

Both blocks are read once, when the page is opened. Re-annotating, re-uploading or collapsing while the page is on screen does not refresh them; leaving the tab and coming back does.

2 Controls

Controls on this page

Control	What it does	Default	Where
Download Protein Metadata	Writes the protein annotation metadata to protein_metadata_full.csv. Shown only when the block has a table.	action	page
Download Phospho Metadata	Writes the phosphosite annotation metadata to phospho_metadata_full.csv. Shown only when the block has a table.	action	page

While one download is running both buttons are disabled and the one in progress reads Downloading…, so two requests cannot overlap.

> NOTE
>
> The page draws no figure, so the plot appearance panel is not shown on it, and neither are the width, height, resolution and format controls that belong to the download of an image.

3 Downloading

The download is a comma-separated UTF-8 file with a header row and no index column: one line per sample, the columns in the order the table shows them. It is the stored metadata frame written out directly, so what arrives on disk is what every plot and every test in the session read.

Two differences from the screen are worth knowing, because both make the file the better copy:

- On screen a value that is not a whole number is printed to four decimals, and a true/false value as true or false. The CSV holds the stored value, unrounded.
- On screen a missing value is drawn as an empty cell. In the CSV it is an empty field, which reads back as NA rather than as the text nan.

A block whose table is scrolled on screen still downloads whole: the fixed-height window is a property of the box the table sits in, not of the data behind it.

Behind this page

Function	What it produces
summary_tables	Both blocks of this page: availability, row and column counts, column names and the table itself
download_current_metadata_annotation	The CSV behind either download button
get_annotation	The stored annotation a block is read from