

Cable ID	Summary	Test Limit	Length	Headroom	Date / Time
2.3-KLEIN	FAIL	TIA Cat 5e Channel	31 ft	-29.8 dB (NEXT)	06/20/2023 04:00 PM

Total Length:	31 ft
Number of Reports:	1
Number of Passing Reports:	0
Number of Failing Reports:	1
Number of Warning Reports:	0
Documentation Only:	0

Cable ID: 2.3-KLEIN

Test Limit: TIA Cat 5e Channel

Limits Version: 1.9300

Date / Time: 06/20/2023 04:00:02 PM

Operator: A

Headroom -29.8 dB (NEXT 3,6-4,5)

Cable Type: Cat 5 FTP

NVP: 69.0%

Main: DTX CableAnalyzer

S/N: 8727070

Software Version: 2.7400

Calibration Date: 05/10/2006

Adapter: DTX-CHA001

S/N: MBGSJDF

Test Summary: FAIL

Remote: DTX CableAnalyzer

S/N: 8727069


Software Version: 2.7400

Calibration Date: 05/10/2006


Adapter: DTX-CHA001

S/N: MBG1SUS

Length (ft), Limit 328	[Pair 3,6]	31
Prop. Delay (ns), Limit 555	[Pair 1,2]	94
Delay Skew (ns), Limit 50	[Pair 1,2]	48
Resistance (ohms)	[Pair 3,6]	Open
Insertion Loss Margin (dB)	[Pair 4,5]	-8.2 F
Frequency (MHz)	[Pair 4,5]	1.9
Limit (dB)	[Pair 4,5]	3.0





Wire Map (T568A)
FAIL





Worst Case Margin Worst Case Value



FAIL	MAIN	SR	MAIN	SR
Worst Pair	3,6-4,5	3,6-4,5	3,6-4,5	3,6-4,5
NEXT (dB)	-29.3 F	-29.8 F	-27.5	-19.1
Freq. (MHz)	1.8	1.8	3.8	13.1
Limit (dB)	59.4	59.4	54.0	45.0
Worst Pair	3,6	3,6	3,6	3,6
PS NEXT (dB)	-26.3 F	-26.8 F	-24.5	-16.2
Freq. (MHz)	1.8	1.8	3.8	13.1
Limit (dB)	56.4	56.4	51.0	42.0



FAIL	MAIN	SR	MAIN	SR
Worst Pair	3,6-4,5	3,6-4,5	3,6-4,5	3,6-4,5
ACR-F (dB)	-33.5 F	-33.7 F	-11.3	-10.4
Freq. (MHz)	1.5	1.5	85.8	97.3
Limit (dB)	53.9	53.9	18.7	17.6
Worst Pair	4,5	3,6	4,5	3,6
PS ACR-F (dB)	-30.5 F	-30.5 F	-8.6	-8.3
Freq. (MHz)	1.5	1.5	85.8	85.8
Limit (dB)	50.9	50.9	15.7	15.7



N/A	MAIN	SR	MAIN	SR
Worst Pair	3,6-4,5	3,6-4,5	3,6-4,5	3,6-4,5
ACR-N (dB)	-37.5	-38.0	-21.1	-23.2
Freq. (MHz)	1.8	1.8	14.0	13.1
Limit (dB)	56.4	56.4	36.1	36.9
Worst Pair	4,5	4,5	4,5	4,5
PS ACR-N (dB)	-34.5	-35.0	-18.1	-20.2
Freq. (MHz)	1.8	1.8	14.0	13.1
Limit (dB)	53.4	53.4	33.1	33.9



FAIL	MAIN	SR	MAIN	SR
Worst Pair	4,5	4,5	4,5	4,5
RL (dB)	-14.0 F	-14.0 F	-14.0	-14.0
Freq. (MHz)	1.0	1.0	1.0	1.0
Limit (dB)	17.0	17.0	17.0	17.0

