

Motivation



Overview

1. Introduction
2. Background: PDR on Hardware
3. PDR on Software
4. Implementation in Ultimate
5. Evaluation
6. Related Work
7. Future Work
8. Conclusion

Overview

1. Introduction
2. Background: PDR on Hardware
3. PDR on Software
4. Implementation in Ultimate
5. Evaluation
6. Related Work
7. Future Work
8. Conclusion

1. Introduction

Overview

1. Introduction
2. Background: PDR on Hardware
3. PDR on Software
4. Implementation in Ultimate
5. Evaluation
6. Related Work
7. Future Work
8. Conclusion

2.1 Preliminaries: Boolean Transition System

- A **Boolean Transition System** $S = (X, I, T)$ consists of
 - Set of **boolean variables** X
 - A conjunction representing the **initial state** I
 - A propositional formula T over variables in X and $X' = \{x' \in X \mid x' \in X'\}$, called **Transition Relation**
- **States** in S are cubes containing each variable from X with a boolean valuation of it
 - ➔ Finite number of states: $2^{|X|}$
- Transitions @Todo

2.1 Preliminaries: Formulas

- Given a formula φ over X , we get a **primed formula** φ' by replacing each variable with its corresponding variable in X'
- A **literal** is a variable or its negation
- A **cube** is a conjunction of literals
- A **clause** is a disjunction of literals
 - ➔ **Negation** of a **cube** is a **clause** and vice versa
- A **Safety Property** P is a formula over X that should be satisfiable by every state reachable from I
 - ➔ \bar{P} being a set of **bad states**

2.2 Algorithm: Overview

- PDR on hardware checks if states in \bar{P} are reachable from I
- For that it uses cubes of clauses, called Frames
 - Frame F_i represents an over-approximation of reachable states in at most i transitions from I
- PDR maintains sequence of frames $[F_0, F_1, \dots, F_k]$, called trace

2.2 Algorithm: Pseudo-Code

```
1: procedure PDR-PROVE( $I, T, P$ )
2:   check for 0-counter-example
3:   trace.push(new frame(I))

4:   loop
5:     while  $\exists$  cube  $c$ , s.t. trace.last()  $\wedge T \wedge c'$  is SAT and  $c \Rightarrow \bar{P}$  do
6:       recursively block proof-obligation( $c$ , trace.size() - 1)
7:       and strengthen the frames of the trace.
8:       if a proof-obligation( $p$ , 0) is generated then
9:         return false

10:     $F_{k+1} = \text{new frame}(P)$ 
11:    for all clause  $c \in \text{trace.last()}$  do
12:      if trace.last()  $\wedge T \wedge \bar{c}'$  is UNSAT then
13:         $F_{k+1} = F_{k+1} \wedge c$ 
14:      if trace.last()  $== F_{k+1}$  then
15:        return true
16:    trace.push( $F_{k+1}$ )
```

2.2 Algorithm: Pseudo-Code

```
1: procedure PDR-PROVE( $I, T, P$ )
2:   check for 0-counter-example
3:    $trace.push(new\ frame(I))$ 

4:   loop
5:     while  $\exists$  cube  $c$ , s.t.  $trace.last() \wedge T \wedge c'$  is SAT and  $c \Rightarrow \bar{P}$  do
6:       recursively block proof-obligation( $c$ ,  $trace.size() - 1$ )
7:       and strengthen the frames of the trace.
8:       if a proof-obligation( $p$ , 0) is generated then
9:         return false

10:     $F_{k+1} = new\ frame(P)$ 
11:    for all clause  $c \in trace.last()$  do
12:      if  $trace.last() \wedge T \wedge \bar{c}'$  is UNSAT then
13:         $F_{k+1} = F_{k+1} \wedge c$ 
14:      if  $trace.last() == F_{k+1}$  then
15:        return true
16:     $trace.push(F_{k+1})$ 
```

2.2 Algorithm: Checking for 0-Counter-Example

➤ Is $I \wedge \bar{P}$ satisfiable?

➔ If satisfiable:

- Algorithm terminates and returns that a bad state is reachable

➔ If unsatisfiable:

- Algorithm initializes the first frame in the trace: $F_0 = I$ and continues

2.2 Algorithm: Pseudo-Code

```
1: procedure PDR-PROVE( $I, T, P$ )
2:   check for 0-counter-example
3:   trace.push(new frame(I))

4:   loop                                     Next Transition Phase
5:     while  $\exists$  cube  $c$ , s.t.  $\text{trace.last()} \wedge T \wedge c'$  is SAT and  $c \Rightarrow \bar{P}$  do
6:       recursively block proof-obligation( $c$ ,  $\text{trace.size()} - 1$ )
7:       and strengthen the frames of the trace.
8:       if a proof-obligation( $p$ , 0) is generated then
9:         return false

10:     $F_{k+1} = \text{new frame}(P)$ 
11:    for all clause  $c \in \text{trace.last()}$  do
12:      if  $\text{trace.last()} \wedge T \wedge \bar{c}'$  is UNSAT then
13:         $F_{k+1} = F_{k+1} \wedge c$ 
14:      if  $\text{trace.last()} == F_{k+1}$  then
15:        return true
16:    trace.push( $F_{k+1}$ )
```

2.2 Algorithm: Next Transition Phase

- Checking if the next state is a good state

➤ Let $[F_0, F_1, \dots, F_k]$ be the current trace

➤ Is $F_k \wedge T \wedge \overline{P'}$ satisfiable?

➔ If **satisfiable**:

- Take **satisfying** assignment $\vec{x} = \{x_1, x_2, \dots, x_{|X|}, x'_1, x'_2, \dots, x'_{|X'|}\}$
- The algorithm gets **new bad state**: $b = x_1 \wedge x_2 \wedge \dots \wedge x_{|X|}$
- Construct the tuple $t = (b, k)$, called **proof-obligation**

2.2 Algorithm: Next Transition Phase

- Checking if the **next state** is a **good state**:
 - Let $[F_0, F_1, \dots, F_k]$ be the current trace
 - Is $F_k \wedge T \wedge \overline{P'}$ satisfiable?
 - ➔ If **unsatisfiable**:
 - **Continue** with the next phase

2.2 Algorithm: Pseudo-Code

```
1: procedure PDR-PROVE( $I, T, P$ )
2:   check for 0-counter-example
3:   trace.push(new frame(I))

4:   loop
5:     while  $\exists$  cube  $c$ , s.t. trace.last()  $\wedge T \wedge c'$  is SAT and  $c \Rightarrow \bar{P}$  do
6:       recursively block proof-obligation( $c$ , trace.size() - 1)
7:       and strengthen the frames of the trace.
8:       if a proof-obligation( $p$ , 0) is generated then
9:         return false

10:     $F_{k+1} = \text{new frame}(P)$ 
11:    for all clause  $c \in \text{trace.last()}$  do
12:      if trace.last()  $\wedge T \wedge \bar{c}'$  is UNSAT then
13:         $F_{k+1} = F_{k+1} \wedge c$ 
14:      if trace.last()  $== F_{k+1}$  then
15:        return true
16:    trace.push( $F_{k+1}$ )
```

Blocking-Phase


```

4:   loop
5:   while  $\exists$  cube  $c$ , s.t.  $trace.last() \wedge T \wedge c'$  is SAT and  $c \Rightarrow \bar{P}$  do
6:       recursively block proof-obligation( $c$ ,  $trace.size() - 1$ )
7:       and strengthen the frames of the trace.
8:       if a proof-obligation( $p$ , 0) is generated then
9:           return false

```

2.2 Algorithm: Blocking-Phase

- Proving that new **bad states** are **not reachable**

Note: useful to have
Piece of pseudo-code?

➤ If there are proof-obligations:

- Algorithm takes proof-obligation (b , i)
- Tries to **block bad state** b by checking $F_{i-1} \wedge T \wedge b'$ for **satisfiability**

➔ If **satisfiable**:

- Frame F_{i-1} is **not strong enough** to **block** b
- Take **satisfying** assignment $\vec{x} = \{x_1, x_2, \dots, x_{|X|}, x'_1, x'_2, \dots, x'_{|X'|}\}$
- The algorithm gets **another new bad state**: $c = x_1 \wedge x_2 \wedge \dots \wedge x_{|X|}$
- Construct **new proof-obligation** $u = (c, i - 1)$

2.2 Algorithm: Blocking-Phase

- Proving that new bad states are not reachable
 - If there are proof-obligations:
 - Algorithm takes proof-obligation (b, i)
 - Tries to block bad state b by checking $F_{i-1} \wedge T \wedge b'$ for satisfiability
 - ➔ If unsatisfiable:
 - Algorithm strengthens F_i with \bar{b}
 - ➔ $F_i = F_i \wedge \bar{b}$
 - Blocking bad state b at F_i

2.2 Algorithm: Blocking-Phase

➤ This continues recursively until:

- There are **no proof-obligations** left
 - ➔ Algorithm **continues** with the next phase
- A proof-obligation $(d, 0)$ is created
 - ➔ Proving that a **bad state** can be **reached**, terminating the algorithm

2.2 Algorithm: Pseudo-Code

```
1: procedure PDR-PROVE( $I, T, P$ )
2:   check for 0-counter-example
3:   trace.push(new frame(I))

4:   loop
5:     while  $\exists$  cube  $c$ , s.t.  $\text{trace.last()} \wedge T \wedge c'$  is SAT and  $c \Rightarrow \bar{P}$  do
6:       recursively block proof-obligation( $c$ ,  $\text{trace.size()} - 1$ )
7:       and strengthen the frames of the trace.
8:       if a proof-obligation( $p$ , 0) is generated then
9:         return false

10:     $F_{k+1} = \text{new frame}(P)$ 
11:    for all clause  $c \in \text{trace.last()}$  do
12:      if  $\text{trace.last()} \wedge T \wedge \bar{c}'$  is UNSAT then
13:         $F_{k+1} = F_{k+1} \wedge c$ 
14:      if  $\text{trace.last()} == F_{k+1}$  then
15:        return true
16:    trace.push( $F_{k+1}$ )
```

Propagation-Phase

2.2 Algorithm: Propagation-Phase

- Propagating **learned information**:

- After no proof-obligations are left, the algorithm initializes new frame $F_{k+1} = P$

- Algorithm passes on learned informations, e.g, which states are blocked:

- For each clause c in F_k check: $F_k \wedge T \wedge \bar{c}'$ for satisfiability

- ➔ If **satisfiable**:

- Do nothing, continue with next clause

2.2 Algorithm: Propagation-Phase

- Propagating **learned information**:

- After no proof-obligations are left, the algorithm initializes new frame $F_{k+1} = P$

- Algorithm passes on learned informations, e.g, which states are blocked:

- For each clause c in F_k check: $F_k \wedge T \wedge \bar{c}'$ for satisfiability

- ➔ If **unsatisfiable**:

- Algorithm strengthens F_{k+1} with c

- ➔ $F_{k+1} = F_{k+1} \wedge c$

2.2 Algorithm: Propagation-Phase

- Check for termination:
 - After all clauses have been tested, algorithm checks if $F_k \equiv F_{k+1}$
 - If so, the algorithm has found a fixpoint and terminates
 - ➔ No states of \bar{P} are reachable
 - If not, the algorithm continues with a new Next Transition Phase

2.2 Algorithm: Propagation-Phase

- Check for termination
 - After all clauses have been tested, algorithm checks if $F_k \equiv F_{k+1}$
 - If so, the algorithm has found a fixpoint and terminates
 - ➔ No states of \bar{P} are reachable
 - If not, the algorithm continues with a new Next Transition Phase
- Algorithm repeats the three phases until a fixpoint is found, or a proof-obligation $(d, 0)$ is created

2.2 Algorithm: Pseudo-Code TEMPLATE

```
1: procedure PDR-PROVE( $I, T, P$ )  
2:   check for 0-counter-example  
3:    $trace.push(new\ frame(I))$   
  
4:   loop  
5:     while  $\exists$  cube  $c$ , s.t.  $trace.last() \wedge T \wedge c'$  is SAT and  $c \Rightarrow \bar{P}$  do  
6:       recursively block proof-obligation( $c$ ,  $trace.size() - 1$ )  
7:       and strengthen the frames of the trace.  
8:       if a proof-obligation( $p$ , 0) is generated then  
9:         return false  
  
10:     $F_{k+1} = new\ frame(P)$   
11:    for all clause  $c \in trace.last()$  do  
12:      if  $trace.last() \wedge T \wedge \bar{c}'$  is UNSAT then  
13:         $F_{k+1} = F_{k+1} \wedge c$   
14:    if  $trace.last() == F_{k+1}$  then  
15:      return true  
16:     $trace.push(F_{k+1})$ 
```

2.3 Example

2.4 Possible Improvements

- Blocking **one state** at a time is **ineffective**:
 - Generalize blocked states
 - ➔ Eliminate insignificant cubes from states, that are not used by UNSAT-cores

- **Ternary Simulation** to reduce proof-obligations:
 - Extend binary variables with a **new value: unknown**
 - Check state variables of proof-obligations for importance
 - ➔ Eliminate unimportant state variables

Overview

1. Introduction
2. Background: PDR on Hardware
3. PDR on Software
4. Implementation in Ultimate
5. Evaluation
6. Related Work
7. Future Work
8. Conclusion

3.1 Preliminaries

- To use PDR on software, we need to lift the algorithm from propositional-logic based systems to first-order logic based systems

3.1 Preliminaries

- To use PDR on software, we need to lift the algorithm from propositional-logic based systems to first-order logic based systems
- For that we first need new definitions

3.1 Preliminaries: Control Flow Graph

- A control flow graph (CFG) $A = (X, L, G, \ell_0, \ell_E)$ is a graph consisting of
- A finite set of variables X
 - A finite set of locations L
 - A finite set of transitions $G \subseteq L \times FO \times L$
 - ➔ FO being a quantifier free first-order logic formula over variables in X and $X' = \{x \in X \mid x' \in X'\}$
 - An initial location $\ell_0 \in L$
 - An error location $\ell_E \in L$

3.1 Preliminaries: Control Flow Graph

➤ The transition formula $T_{\ell_1 \rightarrow \ell_2}$ from location ℓ_1 to location ℓ_2 is defined as:

- $$T_{\ell_1 \rightarrow \ell_2} = \begin{cases} (\ell_1, t, \ell_2), & (\ell_1, t, \ell_2) \in G \\ \text{false}, & \text{otherwise} \end{cases}$$

3.1 Preliminaries: Control Flow Graph

➤ The transition formula $T_{\ell_1 \rightarrow \ell_2}$ from location ℓ_1 to location ℓ_2 is defined as:

- $$T_{\ell_1 \rightarrow \ell_2} = \begin{cases} (\ell_1, t, \ell_2), & (\ell_1, t, \ell_2) \in G \\ \text{false}, & \text{otherwise} \end{cases}$$

➔ Global Transition Formula $T = \bigvee_{(\ell_1, t, \ell_2) \in G} T_{\ell_1 \rightarrow \ell_2}$

3.2 Lifted Algorithm: Pseudo-Code

```
1: procedure PDR-PROVE( $I, T, P$ )
2:   check for 0-counter-example
3:   trace.push(new frame(I))

4:   loop
5:     while  $\exists$  cube  $c$ , s.t. trace.last()  $\wedge T \wedge c'$  is SAT and  $c \Rightarrow \bar{P}$  do
6:       recursively block proof-obligation( $c$ , trace.size() - 1)
7:       and strengthen the frames of the trace.
8:       if a proof-obligation( $p$ , 0) is generated then
9:         return false

10:     $F_{k+1} = \text{new frame}(P)$ 
11:    for all clause  $c \in \text{trace.last()}$  do
12:      if trace.last()  $\wedge T \wedge \bar{c}'$  is UNSAT then
13:         $F_{k+1} = F_{k+1} \wedge c$ 
14:      if trace.last()  $== F_{k+1}$  then
15:        return true
16:    trace.push(F_{k+1})
```

```
1: procedure LIFTED-PDR-PROVE( $L, G$ )
2:   check for 0-counter-example
3:    $\ell_0.\text{trace.push}(\text{new frame}(\text{true}))$ 
4:   for all  $\ell \in L \setminus \{\ell_0, \ell_E\}$  do
5:      $\ell.\text{trace.push}(\text{new frame}(\text{false}))$ 
6:    $\text{level} := 0$ 

7:   loop
8:     for all  $\ell \in L \setminus \{\ell_E\}$  do
9:        $\ell.\text{trace.push}(\text{new frame}(\text{true}))$ 
10:     $\text{level} := \text{level} + 1$ 
11:    get initial proof-obligations

12:    while  $\exists$  proof-obligation  $(t, \ell, i)$ , do
13:      Recursively block proof-obligation
14:      if a proof-obligation( $p, \ell, 0$ ) is generated then
15:        return false

16:    for  $i = 0; i \leq \text{level}; i := i + 1$  do
17:      for  $\ell \in L \setminus \{\ell_E\}$  do
18:        if  $\ell.\text{trace}[i] \neq \ell.\text{trace}[i - 1]$  then
19:          break
20:    return true
```

3.2 Lifted Algorithm: Pseudo-Code

```
1: procedure PDR-PROVE( $I, T, P$ )
2:   check for 0-counter-example
3:    $trace.push(new\ frame(I))$ 

4:   loop
5:     while  $\exists$  cube  $c$ , s.t.  $trace.last() \wedge T \wedge c'$  is SAT and  $c \Rightarrow \bar{P}$  do
6:       recursively block proof-obligation( $c$ ,  $trace.size() - 1$ )
7:       and strengthen the frames of the trace.
8:       if a proof-obligation( $p$ , 0) is generated then
9:         return false

10:     $F_{k+1} = new\ frame(P)$ 
11:    for all clause  $c \in trace.last()$  do
12:      if  $trace.last() \wedge T \wedge \bar{c}'$  is UNSAT then
13:         $F_{k+1} = F_{k+1} \wedge c$ 
14:      if  $trace.last() == F_{k+1}$  then
15:        return true
16:     $trace.push(F_{k+1})$ 
```

```
1: procedure LIFTED-PDR-PROVE( $L, G$ )
2:   check for 0-counter-example
3:    $\ell_0.trace.push(new\ frame(true))$ 
4:   for all  $\ell \in L \setminus \{\ell_0, \ell_E\}$  do
5:      $\ell.trace.push(new\ frame(false))$ 
6:    $level := 0$ 

7:   loop
8:     for all  $\ell \in L \setminus \{\ell_E\}$  do
9:        $\ell.trace.push(new\ frame(true))$ 
10:     $level := level + 1$ 
11:    get initial proof-obligations

12:    while  $\exists$  proof-obligation  $(t, \ell, i)$ , do
13:      Recursively block proof-obligation
14:      if a proof-obligation( $p, \ell, 0$ ) is generated then
15:        return false

16:    for  $i = 0; i \leq level; i := i + 1$  do
17:      for  $\ell \in L \setminus \{\ell_E\}$  do
18:        if  $\ell.trace[i] \neq \ell.trace[i - 1]$  then
19:          break
20:    return true
```

3.2 Lifted Algorithm: Checking for 0-Counter-Example

➤ Is $\ell_0 = \ell_E$?

➔ Yes:

- Algorithm terminates, returning that ℓ_E is reachable

➔ No:

- Algorithm continues

3.2 Lifted Algorithm: Pseudo-Code

```
1: procedure PDR-PROVE( $I, T, P$ )
2:   check for 0-counter-example
3:    $trace.push(new\ frame(I))$ 
4:   loop
5:     while  $\exists$  cube  $c$ , s.t.  $trace.last() \wedge T \wedge c'$  is SAT and  $c \Rightarrow \bar{P}$  do
6:       recursively block proof-obligation( $c$ ,  $trace.size() - 1$ )
7:       and strengthen the frames of the trace.
8:       if a proof-obligation( $p$ , 0) is generated then
9:         return false
10:     $F_{k+1} = new\ frame(P)$ 
11:    for all clause  $c \in trace.last()$  do
12:      if  $trace.last() \wedge T \wedge \bar{c}'$  is UNSAT then
13:         $F_{k+1} = F_{k+1} \wedge c$ 
14:      if  $trace.last() == F_{k+1}$  then
15:        return true
16:     $trace.push(F_{k+1})$ 
```

```
1: procedure LIFTED-PDR-PROVE( $L, G$ )
2:   check for 0-counter-example
3:    $\ell_0.trace.push(new\ frame(true))$ 
4:   for all  $\ell \in L \setminus \{\ell_0, \ell_E\}$  do
5:      $\ell.trace.push(new\ frame(false))$ 
6:    $level := 0$ 
7:   loop
8:     for all  $\ell \in L \setminus \{\ell_E\}$  do
9:        $\ell.trace.push(new\ frame(true))$ 
10:     $level := level + 1$ 
11:    get initial proof-obligations
12:    while  $\exists$  proof-obligation  $(t, \ell, i)$ , do
13:      Recursively block proof-obligation
14:      if a proof-obligation( $p, \ell, 0$ ) is generated then
15:        return false
16:    for  $i = 0; i \leq level; i := i + 1$  do
17:      for  $\ell \in L \setminus \{\ell_E\}$  do
18:        if  $\ell.trace[i] \neq \ell.trace[i - 1]$  then
19:          break
20:    return true
```

3.2 Lifted Algorithm: Pseudo-Code

```
1: procedure PDR-PROVE( $I, T, P$ )
2:   check for 0-counter-example
3:   trace.push(new frame(I))
4:   loop
5:     while  $\exists$  cube  $c$ , s.t.  $trace.last() \wedge T \wedge c'$  is SAT and  $c \Rightarrow \bar{P}$  do
6:       recursively block proof-obligation( $c$ ,  $trace.size() - 1$ )
7:       and strengthen the frames of the trace.
8:       if a proof-obligation( $p$ , 0) is generated then
9:         return false
10:     $F_{k+1} = new\ frame(P)$ 
11:    for all clause  $c \in trace.last()$  do
12:      if  $trace.last() \wedge T \wedge \bar{c}'$  is UNSAT then
13:         $F_{k+1} = F_{k+1} \wedge c$ 
14:      if  $trace.last() == F_{k+1}$  then
15:        return true
16:    trace.push( $F_{k+1}$ )
```

```
1: procedure LIFTED-PDR-PROVE( $L, G$ )
2:   check for 0-counter-example
3:    $\ell_0.trace.push(new\ frame(true))$ 
4:   for all  $\ell \in L \setminus \{\ell_0, \ell_E\}$  do
5:      $\ell.trace.push(new\ frame(false))$ 
6:    $level := 0$ 
7:   loop
8:     for all  $\ell \in L \setminus \{\ell_E\}$  do
9:        $\ell.trace.push(new\ frame(true))$ 
10:     $level := level + 1$ 
11:    get initial proof-obligations
12:    while  $\exists$  proof-obligation  $(t, \ell, i)$ , do
13:      Recursively block proof-obligation
14:      if a proof-obligation( $p, \ell, 0$ ) is generated then
15:        return false
16:    for  $i = 0; i \leq level; i := i + 1$  do
17:      for  $\ell \in L \setminus \{\ell_E\}$  do
18:        if  $\ell.trace[i] \neq \ell.trace[i - 1]$  then
19:          break
20:    return true
```

3.2 Lifted Algorithm: Local Traces

- There is no global trace $[F_0, F_1, \dots, F_k]$
 - ➔ Every location $\ell \in L \setminus \{\ell_E\}$ has its own local trace $[F_{0,\ell}, F_{1,\ell}, \dots, F_{k,\ell}]$
 - ➔ Lifted frames are cubes of first-order formulas
 - ➔ @ToDo, explain changes to proof obligations

3.2 Lifted Algorithm: Pseudo-Code

```
1: procedure PDR-PROVE( $I, T, P$ )
2:   check for 0-counter-example
3:   trace.push(new frame(I))
4:   loop
5:     while  $\exists$  cube  $c$ , s.t.  $\text{trace.last()} \wedge T \wedge c'$  is SAT and  $c \Rightarrow \bar{P}$  do
6:       recursively block proof-obligation( $c$ ,  $\text{trace.size}() - 1$ )
7:       and strengthen the frames of the trace.
8:       if a proof-obligation( $p$ , 0) is generated then
9:         return false
10:     $F_{k+1} = \text{new frame}(P)$ 
11:    for all clause  $c \in \text{trace.last()} \text{ do}$ 
12:      if  $\text{trace.last()} \wedge T \wedge \bar{c}'$  is UNSAT then
13:         $F_{k+1} = F_{k+1} \wedge c$ 
14:      if  $\text{trace.last()} == F_{k+1}$  then
15:        return true
16:    trace.push( $F_{k+1}$ )
```

```
1: procedure LIFTED-PDR-PROVE( $L, G$ )
2:   check for 0-counter-example
3:    $\ell_0.\text{trace.push}(\text{new frame}(\text{true}))$ 
4:   for all  $\ell \in L \setminus \{\ell_0, \ell_E\}$  do
5:      $\ell.\text{trace.push}(\text{new frame}(\text{false}))$ 
6:    $\text{level} := 0$ 
7:   loop
8:     for all  $\ell \in L \setminus \{\ell_E\}$  do
9:        $\ell.\text{trace.push}(\text{new frame}(\text{true}))$ 
10:     $\text{level} := \text{level} + 1$ 
11:    get initial proof-obligations
12:    while  $\exists$  proof-obligation  $(t, \ell, i)$ , do
13:      Recursively block proof-obligation
14:      if a proof-obligation( $p, \ell, 0$ ) is generated then
15:        return false
16:    for  $i = 0; i \leq \text{level}; i := i + 1$  do
17:      for  $\ell \in L \setminus \{\ell_E\}$  do
18:        if  $\ell.\text{trace}[i] \neq \ell.\text{trace}[i - 1]$  then
19:          break
20:    return true
```

3.2 Lifted Algorithm: Initialization

➤ Initialize each local frames:

- $F_{0,\ell} = \begin{cases} \text{true}, & \ell = \ell_0 \\ \text{false}, & \text{otherwise} \end{cases}$

3.2 Lifted Algorithm: Pseudo-Code

```
1: procedure PDR-PROVE( $I, T, P$ )
2:   check for 0-counter-example
3:    $trace.push(new\ frame(I))$ 
4:   loop
5:     while  $\exists$  cube  $c$ , s.t.  $trace.last() \wedge T \wedge c'$  is SAT and  $c \Rightarrow \bar{P}$  do
6:       recursively block proof-obligation( $c$ ,  $trace.size() - 1$ )
7:       and strengthen the frames of the trace.
8:       if a proof-obligation( $p$ , 0) is generated then
9:         return false
10:     $F_{k+1} = new\ frame(P)$ 
11:    for all clause  $c \in trace.last()$  do
12:      if  $trace.last() \wedge T \wedge \bar{c}'$  is UNSAT then
13:         $F_{k+1} = F_{k+1} \wedge c$ 
14:      if  $trace.last() == F_{k+1}$  then
15:        return true
16:     $trace.push(F_{k+1})$ 
```

```
1: procedure LIFTED-PDR-PROVE( $L, G$ )
2:   check for 0-counter-example
3:    $\ell_0.trace.push(new\ frame(true))$ 
4:   for all  $\ell \in L \setminus \{\ell_0, \ell_E\}$  do
5:      $\ell.trace.push(new\ frame(false))$ 
6:    $level := 0$ 
7:   loop
8:     for all  $\ell \in L \setminus \{\ell_E\}$  do
9:        $\ell.trace.push(new\ frame(true))$ 
10:       $level := level + 1$ 
11:      get initial proof-obligations
12:      while  $\exists$  proof-obligation  $(t, \ell, i)$ , do
13:        Recursively block proof-obligation
14:        if a proof-obligation( $p, \ell, 0$ ) is generated then
15:          return false
16:      for  $i = 0; i \leq level; i := i + 1$  do
17:        for  $\ell \in L \setminus \{\ell_E\}$  do
18:          if  $\ell.trace[i] \neq \ell.trace[i - 1]$  then
19:            break
20:      return true
```

3.2 Lifted Algorithm: Next Level Phase

- Initializing the next level:
 - Let k be the current level
 - ➔ Every location $\ell \in L \setminus \{\ell_E\}$ has trace $[F_{0,\ell}, \dots, F_{k,\ell}]$
 - Algorithm initializes new level $k+1$ for all locations $\ell \in L \setminus \{\ell_E\}$
 - ➔ Adding new frame $F_{k+1,\ell} = \text{true}$

3.2 Lifted Algorithm: Next Level Phase

- Initializing the next level:
 - Let k be the current level
 - ➔ Every location $\ell \in L \setminus \{\ell_E\}$ has trace $[F_{0,\ell}, \dots, F_{k,\ell}]$
 - Additionally, the algorithm computes initial proof-obligations:
 - Because of the structure of CFGs, we always know the transitions to ℓ_E
 - ➔ Check G for transitions of the form (ℓ, t, ℓ_E)
 - ➔ For each transition, get proof-obligation (t, ℓ, k)
 - ➔ @ToDo explain lifted proof-obligations

3.2 Lifted Algorithm: Pseudo-Code

```
1: procedure PDR-PROVE( $I, T, P$ )
2:   check for 0-counter-example
3:    $trace.push(new\ frame(I))$ 

4:   loop
5:     while  $\exists$  cube  $c$ , s.t.  $trace.last() \wedge T \wedge c'$  is SAT and  $c \Rightarrow \bar{P}$  do
6:       recursively block proof-obligation( $c$ ,  $trace.size() - 1$ )
7:       and strengthen the frames of the trace.
8:       if a proof-obligation( $p$ , 0) is generated then
9:         return false

10:     $F_{k+1} = new\ frame(P)$ 
11:    for all clause  $c \in trace.last()$  do
12:      if  $trace.last() \wedge T \wedge \bar{c}'$  is UNSAT then
13:         $F_{k+1} = F_{k+1} \wedge c$ 
14:      if  $trace.last() == F_{k+1}$  then
15:        return true
16:     $trace.push(F_{k+1})$ 
```

```
1: procedure LIFTED-PDR-PROVE( $L, G$ )
2:   check for 0-counter-example
3:    $\ell_0.trace.push(new\ frame(true))$ 
4:   for all  $\ell \in L \setminus \{\ell_0, \ell_E\}$  do
5:      $\ell.trace.push(new\ frame(false))$ 
6:    $level := 0$ 

7:   loop
8:     for all  $\ell \in L \setminus \{\ell_E\}$  do
9:        $\ell.trace.push(new\ frame(true))$ 
10:     $level := level + 1$ 
11:    get initial proof-obligations

12:    while  $\exists$  proof-obligation  $(t, \ell, i)$ , do
13:      Recursively block proof-obligation
14:      if a proof-obligation( $p, \ell, 0$ ) is generated then
15:        return false

16:    for  $i = 0; i \leq level; i := i + 1$  do
17:      for  $\ell \in L \setminus \{\ell_E\}$  do
18:        if  $\ell.trace[i] \neq \ell.trace[i - 1]$  then
19:          break
20:    return true
```

3.2 Lifted Algorithm: Blocking-Phase

- Blocking-Phase no longer nested in preceding-phase
 - ➔ No longer optional
 - ➔ In each iteration we have at least the initial proof-obligations

3.2 Lifted Algorithm: Blocking-Phase

- Checking if **bad transitions** are reachable:
 - Algorithm takes proof-obligation (t, ℓ, i) with the lowest i
 - For each predecessor location ℓ_{pre} of ℓ check if $F_{i-1, \ell_{pre}} \wedge T_{\ell_{pre} \rightarrow \ell} \wedge t'$ is satisfiable
- ➔ If satisfiable:
 - t could not be blocked at ℓ on level i
 - Get new proof-obligation $(p, \ell_{pre}, i - 1)$
 - ➔ p being the weakest precondition of t and $T_{\ell_{pre} \rightarrow \ell}$

3.2 Lifted Algorithm: Blocking-Phase

- Checking if **bad transitions** are reachable:
 - Algorithm takes proof-obligation (t, ℓ, i) with the lowest i
 - For each predecessor location ℓ_{pre} of ℓ check if $F_{i-1, \ell_{pre}} \wedge T_{\ell_{pre} \rightarrow \ell} \wedge t'$ is satisfiable
 - ➔ If unsatisfiable:
 - t is blocked at ℓ on level i
 - Strengthen each frame $F_{j, \ell}$, $j \leq i$ with \bar{t}
 - ➔ $F_{j, \ell} = F_{j, \ell} \wedge \bar{t}$

3.2 Lifted Algorithm: Blocking-Phase

- This continues recursively until:
 - There are no proof-obligations left
 - ➔ Algorithm continues with the next phase
 - A proof-obligation $(d, \ell, 0)$ is created
 - ➔ Proving that there exists a feasible path to ℓ_E

3.2 Lifted Algorithm: Pseudo-Code

```
1: procedure PDR-PROVE( $I, T, P$ )
2:   check for 0-counter-example
3:   trace.push(new frame(I))

4:   loop
5:     while  $\exists$  cube  $c$ , s.t. trace.last()  $\wedge T \wedge c'$  is SAT and  $c \Rightarrow \bar{P}$  do
6:       recursively block proof-obligation( $c$ , trace.size() - 1)
7:       and strengthen the frames of the trace.
8:       if a proof-obligation( $p$ , 0) is generated then
9:         return false

10:    $F_{k+1} = \text{new frame}(P)$ 
11:   for all clause  $c \in \text{trace.last()}$  do
12:     if trace.last()  $\wedge T \wedge \bar{c}'$  is UNSAT then
13:        $F_{k+1} = F_{k+1} \wedge c$ 
14:     if trace.last()  $== F_{k+1}$  then
15:       return true
16:   trace.push( $F_{k+1}$ )
```

```
1: procedure LIFTED-PDR-PROVE( $L, G$ )
2:   check for 0-counter-example
3:    $\ell_0.\text{trace.push}(\text{new frame}(\text{true}))$ 
4:   for all  $\ell \in L \setminus \{\ell_0, \ell_E\}$  do
5:      $\ell.\text{trace.push}(\text{new frame}(\text{false}))$ 
6:   level := 0

7:   loop
8:     for all  $\ell \in L \setminus \{\ell_E\}$  do
9:        $\ell.\text{trace.push}(\text{new frame}(\text{true}))$ 
10:    level := level + 1
11:    get initial proof-obligations

12:    while  $\exists$  proof-obligation  $(t, \ell, i)$ , do
13:      Recursively block proof-obligation
14:      if a proof-obligation( $p, \ell, 0$ ) is generated then
15:        return false

16:    for  $i = 0$ ;  $i \leq \text{level}$ ;  $i := i + 1$  do
17:      for  $\ell \in L \setminus \{\ell_E\}$  do
18:        if  $\ell.\text{trace}[i] \neq \ell.\text{trace}[i - 1]$  then
19:          break
20:    return true
```

3.2 Lifted Algorithm: Propagation-Phase

- No more propagation of learned information
- Only checking for termination
 - ➔ Trying to find a global fixpoint:
 - Is there an i where $F_{i-1,\ell} = F_{i,\ell}$ for every $\ell \in L \setminus \{\ell_E\}$?

3.2 Lifted Algorithm: Propagation-Phase

- No more propagation of learned information
- Only checking for termination
 - ➔ Trying to find a global fixpoint:
 - Is there an i where $F_{i-1,\ell} = F_{i,\ell}$ for every $\ell \in L \setminus \{\ell_E\}$?
 - ➔ Yes:
 - Algorithm terminates returning that there is no feasible path to ℓ_E

3.2 Lifted Algorithm: Propagation-Phase

- No more propagation of learned information
- Only checking for termination
 - ➔ Trying to find a global fixpoint:
 - Is there an i where $F_{i-1,\ell} = F_{i,\ell}$ for every $\ell \in L \setminus \{\ell_E\}$?
 - ➔ No:
 - Algorithm continues with the next level

3.3 Example

3.4 Possible Improvements

Overview

1. Introduction
2. Background: PDR on Hardware
3. PDR on Software
4. Implementation in Ultimate
5. Evaluation
6. Related Work
7. Future Work
8. Conclusion

4.1 Implementation

4.2 Implemented Improvements

Overview

1. Introduction
2. Background: PDR on Hardware
3. PDR on Software
4. Implementation in Ultimate
5. Evaluation
6. Related Work
7. Future Work
8. Conclusion

5.1 Data Comparison

5.2 Discussion

Overview

1. Introduction
2. Background: PDR on Hardware
3. PDR on Software
4. Implementation in Ultimate
5. Evaluation
6. Related Work
7. Future Work
8. Conclusion

6. Related Work

Overview

1. Introduction
2. Background: PDR on Hardware
3. PDR on Software
4. Implementation in Ultimate
5. Evaluation
6. Related Work
7. Future Work
8. Conclusion

7.1 Further Improvements

Overview

1. Introduction
2. Background: PDR on Hardware
3. PDR on Software
4. Implementation in Ultimate
5. Evaluation
6. Related Work
7. Future Work
8. Conclusion

8. Conclusion
