

Motivation



Overview

1. Introduction
2. Background: PDR on Hardware
3. PDR on Software
4. Implementation in Ultimate
5. Evaluation
6. Related Work
7. Future Work
8. Conclusion

Overview

1. Introduction
2. Background: PDR on Hardware
3. PDR on Software
4. Implementation in Ultimate
5. Evaluation
6. Related Work
7. Future Work
8. Conclusion

1. Introduction

Overview

1. Introduction
2. Background: PDR on Hardware
3. PDR on Software
4. Implementation in Ultimate
5. Evaluation
6. Related Work
7. Future Work
8. Conclusion

2.1 Preliminaries

➤ A **Boolean Transition System** $S = (X, I, T)$ consists of

- Set of **boolean variables** X
- A conjunction representing the **initial state** I
- A propositional formula T over variables in X and $X' = \{x' \in X \mid x' \in X'\}$, called **Transition Relation**

➤ **States** in S are cubes containing each variable from X with a boolean valuation of it

➔ Finite number of states: $2^{|X|}$

➤ Transitions @Todo

2.1 Preliminaries

- Given a formula φ over X , we get a primed formula φ' by replacing each variable with its corresponding variable in X'
- A literal is a variable or its negation
- A cube is a conjunction of literals
- A clause is a disjunction of literals
 - ➔ Negation of a cube is a clause and vice versa
- A Safety Property P is a formula over X that should be satisfiable by every state reachable from I
 - ➔ \bar{P} being a set of bad states

2.2 Algorithm

- PDR on hardware checks if states in \bar{P} are reachable from I
- For that it uses cubes of clauses, called Frames
 - Frame F_i represents an over-approximation of reachable states in at most i transitions from I
- PDR maintains sequence of frames $[F_0, F_1, \dots, F_k]$, called trace

2.2 Algorithm: Pseudo-Code

```
1: procedure PDR-PROVE( $I, T, P$ )
2:   check for 0-counter-example
3:   trace.push(new frame(I))

4:   loop
5:     while  $\exists$  cube  $c$ , s.t.  $\text{trace.last()} \wedge T \wedge c'$  is SAT and  $c \Rightarrow \bar{P}$  do
6:       recursively block proof-obligation( $c$ ,  $\text{trace.size()} - 1$ )
7:       and strengthen the frames of the trace.
8:       if a proof-obligation( $p$ , 0) is generated then
9:         return false

10:     $F_{k+1} = \text{new frame}(P)$ 
11:    for all clause  $c \in \text{trace.last()}$  do
12:      if  $\text{trace.last()} \wedge T \wedge \bar{c}'$  is UNSAT then
13:         $F_{k+1} = F_{k+1} \wedge c$ 
14:      if  $\text{trace.last()} == F_{k+1}$  then
15:        return true
16:    trace.push( $F_{k+1}$ )
```

2.2 Algorithm: Pseudo-Code

```
1: procedure PDR-PROVE( $I, T, P$ )
2:   check for 0-counter-example
3:    $trace.push(new\ frame(I))$ 

4:   loop
5:     while  $\exists$  cube  $c$ , s.t.  $trace.last() \wedge T \wedge c'$  is SAT and  $c \Rightarrow \bar{P}$  do
6:       recursively block proof-obligation( $c$ ,  $trace.size() - 1$ )
7:       and strengthen the frames of the trace.
8:       if a proof-obligation( $p$ , 0) is generated then
9:         return false

10:     $F_{k+1} = new\ frame(P)$ 
11:    for all clause  $c \in trace.last()$  do
12:      if  $trace.last() \wedge T \wedge \bar{c}'$  is UNSAT then
13:         $F_{k+1} = F_{k+1} \wedge c$ 
14:      if  $trace.last() == F_{k+1}$  then
15:        return true
16:     $trace.push(F_{k+1})$ 
```

2.2 Algorithm: Checking for 0-counter-example

➤ Is $I \wedge \bar{P}$ satisfiable?

➔ If satisfiable:

- Algorithm terminates and returns that a bad state is reachable

➔ If unsatisfiable:

- Algorithm initializes the first frame in the trace: $F_0 = I$ and continues

2.2 Algorithm: Pseudo-Code

```
1: procedure PDR-PROVE( $I, T, P$ )
2:   check for 0-counter-example
3:   trace.push(new frame(I))

4:   loop                                     Next Transition Phase
5:     while  $\exists$  cube  $c$ , s.t. trace.last()  $\wedge T \wedge c'$  is SAT and  $c \Rightarrow \bar{P}$  do
6:       recursively block proof-obligation( $c$ , trace.size() - 1)
7:       and strengthen the frames of the trace.
8:       if a proof-obligation( $p$ , 0) is generated then
9:         return false

10:     $F_{k+1} = \text{new frame}(P)$ 
11:    for all clause  $c \in \text{trace.last()}$  do
12:      if trace.last()  $\wedge T \wedge \bar{c}'$  is UNSAT then
13:         $F_{k+1} = F_{k+1} \wedge c$ 
14:      if trace.last()  $== F_{k+1}$  then
15:        return true
16:    trace.push( $F_{k+1}$ )
```

2.2 Algorithm: Next Transition Phase:

- Checking if the next state is a good state:
 - Let $[F_0, F_1, \dots, F_k]$ be the current trace
 - Is $F_k \wedge T \wedge \overline{P'}$ satisfiable?
 - ➔ If unsatisfiable:
 - Continue with the next phase

2.2 Algorithm: Next Transition Phase:

- Checking if the next state is a good state

➤ Let $[F_0, F_1, \dots, F_k]$ be the current trace

➤ Is $F_k \wedge T \wedge \overline{P'}$ satisfiable?

➔ If satisfiable:

- Take satisfying assignment $\vec{x} = \{x_1, x_2, \dots, x_{|X|}, x'_1, x'_2, \dots, x'_{|X'|}\}$
- The algorithm gets new bad state: $b = x_1 \wedge x_2 \wedge \dots \wedge x_{|X|}$
- Construct the tuple $t = (b, k)$, called proof-obligation

2.2 Algorithm: Pseudo-Code

```
1: procedure PDR-PROVE( $I, T, P$ )
2:   check for 0-counter-example
3:   trace.push(new frame(I))

4:   loop
5:     while  $\exists$  cube  $c$ , s.t. trace.last()  $\wedge T \wedge c'$  is SAT and  $c \Rightarrow \bar{P}$  do
6:       recursively block proof-obligation( $c$ , trace.size() - 1)
7:       and strengthen the frames of the trace.
8:       if a proof-obligation( $p$ , 0) is generated then
9:         return false

10:     $F_{k+1} = \text{new frame}(P)$ 
11:    for all clause  $c \in \text{trace.last()}$  do
12:      if trace.last()  $\wedge T \wedge \bar{c}'$  is UNSAT then
13:         $F_{k+1} = F_{k+1} \wedge c$ 
14:      if trace.last()  $== F_{k+1}$  then
15:        return true
16:    trace.push( $F_{k+1}$ )
```

Blocking-Phase


```

4:   loop
5:   while  $\exists$  cube  $c$ , s.t.  $trace.last() \wedge T \wedge c'$  is SAT and  $c \Rightarrow \bar{P}$  do
6:       recursively block proof-obligation( $c$ ,  $trace.size() - 1$ )
7:       and strengthen the frames of the trace.
8:       if a proof-obligation( $p$ , 0) is generated then
9:           return false

```

2.2 Algorithm: Blocking-Phase

- Proving that new bad states are not reachable
- If there are proof-obligations:
 - Algorithm takes proof-obligation (b , i)
 - Tries to block bad state b by checking $F_{i-1} \wedge T \wedge b'$ for satisfiability
 - ➔ If satisfiable:
 - Frame F_{i-1} is not strong enough to block b
 - Take satisfying assignment $\vec{x} = \{x_1, x_2, \dots, x_{|X|}, x'_1, x'_2, \dots, x'_{|X'|}\}$
 - The algorithm gets another new bad state: $c = x_1 \wedge x_2 \wedge \dots \wedge x_{|X|}$
 - Construct new proof-obligation $u = (c, i - 1)$

2.2 Algorithm: Blocking-Phase

- Proving that new bad states are not reachable
- If there are proof-obligations:
 - Algorithm takes proof-obligation (b, i)
 - Tries to block bad state b by checking $F_{i-1} \wedge T \wedge b'$ for satisfiability
- ➔ If unsatisfiable:
 - Algorithm strengthens F_i with \bar{b}
 - ➔ $F_i = F_i \wedge \bar{b}$
 - Blocking bad state b at F_i

2.2 Algorithm: Blocking-Phase

➤ This continues recursively until:

- There are no proof-obligations left
 - ➔ Algorithm continues with the next phase
- A proof-obligation $(d, 0)$ is created
 - ➔ Proving that a bad state can be reached, terminating the algorithm

2.2 Algorithm: Pseudo-Code

```
1: procedure PDR-PROVE( $I, T, P$ )
2:   check for 0-counter-example
3:   trace.push(new frame(I))

4:   loop
5:     while  $\exists$  cube  $c$ , s.t.  $\text{trace.last()} \wedge T \wedge c'$  is SAT and  $c \Rightarrow \bar{P}$  do
6:       recursively block proof-obligation( $c$ ,  $\text{trace.size()} - 1$ )
7:       and strengthen the frames of the trace.
8:       if a proof-obligation( $p$ , 0) is generated then
9:         return false

10:     $F_{k+1} = \text{new frame}(P)$ 
11:    for all clause  $c \in \text{trace.last()}$  do
12:      if  $\text{trace.last()} \wedge T \wedge \bar{c}'$  is UNSAT then
13:         $F_{k+1} = F_{k+1} \wedge c$ 
14:      if  $\text{trace.last()} == F_{k+1}$  then
15:        return true
16:    trace.push( $F_{k+1}$ )
```

Propagation-Phase

2.2 Algorithm: Propagation-Phase

- Propagating learned information
- After no proof-obligations are left, the algorithm initializes new frame $F_{k+1} = P$
- Algorithm passes on learned informations, e.g, which states are blocked:
 - For each clause c in F_k check: $F_k \wedge T \wedge \bar{c}'$ for satisfiability
 - ➔ If satisfiable:
 - Do nothing, continue with next clause

2.2 Algorithm: Propagation-Phase

- Propagating learned information
 - After no proof-obligations are left, the algorithm initializes new frame $F_{k+1} = P$
 - Algorithm passes on learned informations, e.g, which states are blocked:
 - For each clause c in F_k check: $F_k \wedge T \wedge \bar{c}'$ for satisfiability
 - ➔ If unsatisfiable:
 - Algorithm strengthens F_{k+1} with c
 - ➔ $F_{k+1} = F_{k+1} \wedge c$

2.2 Algorithm: Propagation-Phase

- Check for termination
- After all clauses have been tested, algorithm checks if $F_k \equiv F_{k+1}$
 - If so, the algorithm has found a fixpoint and terminates
 - ➔ No states of \bar{P} are reachable
 - If not, the algorithm continues with a new Next Transition Phase

2.2 Algorithm: Propagation-Phase

- Check for termination
- After all clauses have been tested, algorithm checks if $F_k \equiv F_{k+1}$
 - If so, the algorithm has found a fixpoint and terminates
 - ➔ No states of \bar{P} are reachable
 - If not, the algorithm continues with a new Next Transition Phase
- Algorithm repeats the three phases until a fixpoint is found, or a proof-obligation $(d, 0)$ is created

2.2 Algorithm: Pseudo-Code TEMPLATE

```
1: procedure PDR-PROVE( $I, T, P$ )
2:   check for 0-counter-example
3:    $trace.push(new\ frame(I))$ 

4:   loop
5:     while  $\exists$  cube  $c$ , s.t.  $trace.last() \wedge T \wedge c'$  is SAT and  $c \Rightarrow \bar{P}$  do
6:       recursively block proof-obligation( $c$ ,  $trace.size() - 1$ )
7:       and strengthen the frames of the trace.
8:       if a proof-obligation( $p$ , 0) is generated then
9:         return false

10:     $F_{k+1} = new\ frame(P)$ 
11:    for all clause  $c \in trace.last()$  do
12:      if  $trace.last() \wedge T \wedge \bar{c}'$  is UNSAT then
13:         $F_{k+1} = F_{k+1} \wedge c$ 
14:      if  $trace.last() == F_{k+1}$  then
15:        return true
16:     $trace.push(F_{k+1})$ 
```

2.3 Example

2.4 Possible Improvements

- Blocking one state at a time is ineffective:
 - Generalize blocked states
 - ➔ Eliminate insignificant cubes from states, that are not used by UNSAT-cores

- Ternary Simulation to reduce proof-obligations:
 - Extend binary variables with a new value: unknown
 - Check state variables of proof-obligations for importance
 - ➔ Eliminate unimportant state variables

Overview

1. Introduction
2. Background: PDR on Hardware
3. PDR on Software
4. Implementation in Ultimate
5. Evaluation
6. Related Work
7. Future Work
8. Conclusion

3.1 Preliminaries

3.2 Lifted Algorithm

- Algorithm Pseudocode here

3.3 Example

3.4 Possible Improvements

Overview

1. Introduction
2. Background: PDR on Hardware
3. PDR on Software
4. Implementation in Ultimate
5. Evaluation
6. Related Work
7. Future Work
8. Conclusion

4.1 Implementation

4.2 Implemented Improvements

Overview

1. Introduction
2. Background: PDR on Hardware
3. PDR on Software
4. Implementation in Ultimate
5. Evaluation
6. Related Work
7. Future Work
8. Conclusion

5.1 Data Comparison

5.2 Discussion

Overview

1. Introduction
2. Background: PDR on Hardware
3. PDR on Software
4. Implementation in Ultimate
5. Evaluation
6. Related Work
7. Future Work
8. Conclusion

6. Related Work

Overview

1. Introduction
2. Background: PDR on Hardware
3. PDR on Software
4. Implementation in Ultimate
5. Evaluation
6. Related Work
7. Future Work
8. Conclusion

7.1 Further Improvements

Overview

1. Introduction
2. Background: PDR on Hardware
3. PDR on Software
4. Implementation in Ultimate
5. Evaluation
6. Related Work
7. Future Work
8. Conclusion

8. Conclusion
