

▼ Natural Language Processing Basics in TensorFlow

“What tags should this article have?”

Wikipedia: Deep learning

Machine learning
Representation learning
Artificial intelligence
(multiple label options per sample)

Classification

Google Translate

Machine Translation

Shakespeare

Text Generation

These are also referred to as sequence problems

Hi, how can I help?

Voice Assistants

A handful of example natural language processing (NLP) and natural language understanding (NLU) problems. These are also often referred to as sequence problems (going from one sequence to another).

The main goal of natural language processing (NLP) is to derive information from natural language.

Natural language is a broad term but you can consider it to cover any of the following:

- Text (such as that contained in an email, blog post, book, Tweet)
- Speech (a conversation you have with a doctor, voice commands you give to a smart speaker)

Under the umbrellas of text and speech there are many different things you might want to do.


If you're building an email application, you might want to scan incoming emails to see if they're spam or not spam (classification).

If you're trying to analyse customer feedback complaints, you might want to discover which section of your business they're for.

Note: Both of these types of data are often referred to as *sequences* (a sentence is a sequence of words). So a common term you'll come across in NLP problems is called *seq2seq*, in other words, finding information in one sequence to produce another sequence (e.g. converting a speech command to a sequence of text-based steps).

To get hands-on with NLP in TensorFlow, we're going to practice the steps we've used previously but this time with text data:

Text -> turn into numbers -> build a model -> train the model to find patterns -> use patterns (ma

 **Resource:** For a great overview of NLP and the different problems within it, read the article [A Simple Introduction to Natural Language Processing](#).

What we're going to cover

Let's get specific hey?

- Downloading a text dataset
- Visualizing text data
- Converting text into numbers using tokenization
- Turning our tokenized text into an embedding
- Modelling a text dataset
 - Starting with a baseline (TF-IDF)
 - Building several deep learning text models
 - Dense, LSTM, GRU, Conv1D, Transfer learning
- Comparing the performance of each our models
- Combining our models into an ensemble
- Saving and loading a trained model
- Find the most wrong predictions

How you should approach this notebook


You can read through the descriptions and the code (it should all run, except for the cells which error on purpose), but there's a better option.

Write all of the code yourself.

Yes. I'm serious. Create a new notebook, and rewrite each line by yourself. Investigate it, see if you can break it, why does it break?

You don't have to write the text descriptions but writing the code yourself is a great way to get hands-on experience.

Don't worry if you make mistakes, we all do. The way to get better and make less mistakes is to write more code.

 **Resource:** See the full set of course materials on GitHub: <https://github.com/mrdbourke/tensorflow-deep-learning>

▼ Check for GPU

In order for our deep learning models to run as fast as possible, we'll need access to a GPU.

In Google Colab, you can set this up by going to Runtime -> Change runtime type -> Hardware accelerator -> GPU.

After selecting GPU, you may have to restart the runtime.

```
# Check for GPU
!nvidia-smi -L
```

```
GPU 0: Tesla T4 (UUID: GPU-83e5329d-cbf0-78c6-44a5-65173576eb46)
```

▼ Get helper functions

In past modules, we've created a bunch of helper functions to do small tasks required for our notebooks.

Rather than rewrite all of these, we can import a script and load them in from there.

The script containing our helper functions can be [found on GitHub](#).

```
# Download helper functions script
!wget https://raw.githubusercontent.com/mrdbourke/tensorflow-deep-learning/main/extras/helper_functions.py

--2021-04-01 00:32:34-- https://raw.githubusercontent.com/mrdbourke/tensorflow-deep-learning/main/extras/helper_functions.py
Resolving raw.githubusercontent.com (raw.githubusercontent.com)... 185.199.110.133, 185.199.111.133, 185.199.112.133, 185.199.113.133
Connecting to raw.githubusercontent.com (raw.githubusercontent.com)|185.199.110.133|:443: connected.
HTTP request sent, awaiting response... 200 OK
Length: 9304 (9.1K) [text/plain]
Saving to: 'helper_functions.py.1'

helper_functions.py.1 100%[=====] 9.09K --.-KB/s in 0s

2021-04-01 00:32:34 (116 MB/s) - 'helper_functions.py.1' saved [9304/9304]
```

```
# Import series of helper functions for the notebook
from helper_functions import unzip_data, create_tensorboard_callback, plot_loss_curves, co
```

▼ TK - Download a text dataset

Let's start by download a text dataset. We'll be using the [Real or Not?](#) dataset from Kaggle which contains text-based Tweets about natural disasters.


The Real Tweets are actually about diasters, for example:

Jetstar and Virgin forced to cancel Bali flights again because of ash from Mount Raung volcano

The Not Real Tweets are Tweets not about disasters (they can be on anything), for example:

'Education is the most powerful weapon which you can use to change the world.' Nelson #Mandela #qu

For convenience, the dataset has been [downloaded from Kaggle](#) (doing this requires a Kaggle account) and uploaded as a downloadable zip file.

 **Note:** The original downloaded data has not been altered to how you would download it from Kaggle.

```
# Download data (same as from Kaggle)
!wget "https://storage.googleapis.com/ztm_tf_course/nlp_getting_started.zip"

# Unzip data
unzip_data("nlp_getting_started.zip")

--2021-04-01 00:32:36-- https://storage.googleapis.com/ztm_tf_course/nlp_getting_st
Resolving storage.googleapis.com (storage.googleapis.com)... 74.125.197.128, 74.125.1
Connecting to storage.googleapis.com (storage.googleapis.com)|74.125.197.128|:443...
HTTP request sent, awaiting response... 200 OK
Length: 607343 (593K) [application/zip]
Saving to: 'nlp_getting_started.zip.1'

nlp_getting_started 100%[=====>] 593.11K --.-KB/s in 0.004s

2021-04-01 00:32:36 (159 MB/s) - 'nlp_getting_started.zip.1' saved [607343/607343]
```

Unzipping nlp_getting_started.zip gives the following 3 .csv files:

- sample_submission.csv - an example of the file you'd submit to the Kaggle competition of your model's predictions.
- train.csv - training samples of real and not real disaster Tweets.
- test.csv - testing samples of real and not real disaster Tweets.

▼ TK - Visualizing a text dataset


Once you've acquired a new dataset to work with, what should you do first?

Explore it? Inspect it? Verify it? Become one with it?

All correct.

Remember the motto: visualize, visualize, visualize.

Right now, our text data samples are in the form of `.csv` files. For an easy way to make them visual, let's turn them into pandas `DataFrame`'s.

 **Reading:** You might come across text datasets in many different formats. Aside from CSV files (what we're working with), you'll probably encounter `.txt` files and `.json` files too. For working with these type of files, I'd recommend reading the two following articles by RealPython:

- [How to Read and Write Files in Python](#)
- [Working with JSON Data in Python](#)

```
# Turn .csv files into pandas DataFrame's
import pandas as pd
train_df = pd.read_csv("train.csv")
test_df = pd.read_csv("test.csv")
train_df.head()
```

	id	keyword	location	text	target
0	1	NaN	NaN	Our Deeds are the Reason of this #earthquake M...	1
1	4	NaN	NaN	Forest fire near La Ronge Sask. Canada	1
2	5	NaN	NaN	All residents asked to 'shelter in place' are ...	1
3	6	NaN	NaN	13,000 people receive #wildfires evacuation or...	1
4	7	NaN	NaN	Just got sent this photo from Ruby #Alaska as ...	1

The training data we downloaded is probably shuffled already. But just to be sure, let's shuffle it again.

```
# Shuffle training dataframe
train_df_shuffled = train_df.sample(frac=1, random_state=42) # shuffle with random_state=42
train_df_shuffled.head()
```


	id	keyword	location	text	target
2644	3796	destruction	NaN	So you have a new weapon that can cause un-ima...	1
2227	3185	deluge	NaN	The f&#amp;@ing things I do for #GISHWHES Just...	0
5448	7769	police	UK	DT @georgegalloway: RT @Galloway4Mayor: ☐ÛThe...	1
400	404	feedback	NaN	Aftershock back to school kick off was	0

Notice how the training data has a "target" column.

We're going to be writing code to find patterns (e.g. different combinations of words) in the "text" column of the training dataset to predict the value of the "target" column.

The test dataset doesn't have a "target" column.

Inputs (text column) -> Machine Learning Algorithm -> Outputs (target column)



Example text classification inputs and outputs for the problem of classifying whether a Tweet is about a diaster or not.

```
# The test data doesn't have a target (that's what we'd try to predict)
test_df.head()
```

	id	keyword	location	text
0	0	NaN	NaN	Just happened a terrible car crash
1	2	NaN	NaN	Heard about #earthquake is different cities, s...
2	3	NaN	NaN	there is a forest fire at spot pond, geese are...
3	9	NaN	NaN	Apocalypse lighting. #Spokane #wildfires
4	11	NaN	NaN	Typhoon Soudelor kills 28 in China and Taiwan

Let's check how many examples of each target we have.

```
# How many examples of each class?
train_df.target.value_counts()

0    4342
1    3271
Name: target, dtype: int64
```

Since we have two target values, we're dealing with a **binary classification** problem.

It's fairly balanced too, about 60% negative class (target = 0) and 40% positive class (target = 1).

Where,

- 1 = a real disaster Tweet
- 0 = not a real disaster Tweet


And what about the total number of samples we have?

```
# How many samples total?
print(f"Total training samples: {len(train_df)}")
print(f"Total test samples: {len(test_df)}")
print(f"Total samples: {len(train_df) + len(test_df)}")
```

```
Total training samples: 7613
Total test samples: 3263
Total samples: 10876
```

Alright, seems like we've got a decent amount of training and test data. If anything, we've got an abundance of testing examples, usually a split of 90/10 (90% training, 10% testing) or 80/20 is suffice.

Okay, time to visualize, let's write some code to visualize random text samples.

 **Question:** Why visualize random samples? You could visualize samples in order but this could lead to only seeing a certain subset of data. Better to visualize a substantial quantity (100+) of random samples to get an idea of the different kinds of data you're working with. In machine learning, never underestimate the power of randomness.

```
# Let's visualize some random training examples
import random
random_index = random.randint(0, len(train_df)-5) # create random indexes not higher than
for row in train_df_shuffled[["text", "target"]][random_index:random_index+5].itertuples()
_, text, target = row
print(f"Target: {target}", "(real disaster)" if target > 0 else "(not real disaster)")
print(f"Text:\n{text}\n")
print("---\n")
```

```
Target: 1 (real disaster)
Text:
Latest : Trains derailment: 'It's the freakiest of freak accidents' - The Indian Expr
---
```

```
Target: 1 (real disaster)
Text:
Motorcyclist bicyclist injured in Denver collision on Broadway: http://t.co/241cN8yx
---
```

Target: 1 (real disaster)

Text:

gmtTy mhtw4fnet

Officials: Alabama home quarantined over possible Ebola case - Washington Times

Target: 0 (not real disaster)

Text:

Your Router is One of the Latest DDoS Attack Weapons <http://t.co/vXxMvgtzvg> #phone #{

Target: 1 (real disaster)

Text:

Ignition Knock (Detonation) Sensor-Senso Standard KS94 <http://t.co/IhphZCkm41> <http://t.co/IhphZCkm41>

▼ Split data into training and validation sets

Since the test set has no labels and we need a way to evaluate our trained models, we'll split off some of the training data and create a validation set.

When our model trains (tries patterns in the Tweet samples), it'll only see data from the training set and we can see how it performs on unseen data using the validation set.

We'll convert our splits from pandas Series datatypes to lists of strings (for the text) and lists of ints (for the labels) for ease of use later.

To split our training dataset and create a validation dataset, we'll use Scikit-Learn's [train_test_split\(\)](#) method and dedicate 10% of the training samples to the validation set.

```
from sklearn.model_selection import train_test_split

# Use train_test_split to split training data into training and validation sets
train_sentences, val_sentences, train_labels, val_labels = train_test_split(train_df_shuff
                                                                              train_df_shuff
                                                                              test_size=0.1,
                                                                              random_state=4

# Check the lengths
len(train_sentences), len(train_labels), len(val_sentences), len(val_labels)

(6851, 6851, 762, 762)

# View the first 10 training sentences and their labels
train_sentences[:10], train_labels[:10]

(array(['@mogacola @zamtriossu i screamed after hitting tweet',
```




```
'Imagine getting flattened by Kurt Zouma',
'@Gurmeetramrahim #MSGDoing111WelfareWorks Green S welfare force ke appx 6500',
"@shakjn @C7 @Magnums im shaking in fear he's gonna hack the planet",
'Somehow find you and I collide http://t.co/Ee8Rp0ahPk',
'@EvaHanderek @MarleyKnysh great times until the bus driver held us hostage i
'destroy the free fandom honestly',
'Weapons stolen from National Guard Armory in New Albany still missing #Gunse
'@wfaaweather Pete when will the heat wave pass? Is it really going to be mic
'Patient-reported outcomes in long-term survivors of metastatic colorectal ca
dtype=object), array([0, 0, 1, 0, 0, 1, 1, 0, 1, 1]))
```

▼ TK - Converting text into numbers

Wonderful! We've got a training set and a validation set containing Tweets and labels.

Our labels are in numerical form (0 and 1) but our Tweets are in string form.

 **Question:** What do you think we have to do before we can use a machine learning algorithm with our text data?


If you answered something along the lines of "turn it into numbers", you're correct. A machine learning algorithm requires its inputs to be in numerical form.

In NLP, there are two main concepts for turning text into numbers:

- **Tokenization** - A straight mapping from word or character or sub-word to a numerical value. There are three main levels of tokenization:
 1. Using **word-level tokenization** with the sentence "I love TensorFlow" might result in "I" being 0, "love" being 1 and "TensorFlow" being 2. In this case, every word in a sequence considered a single **token**.
 2. **Character-level tokenization**, such as converting the letters A-Z to values 1-26. In this case, every character in a sequence considered a single **token**.
 3. **Sub-word tokenization** is in between word-level and character-level tokenization. It involves breaking individual words into smaller parts and then converting those smaller parts into numbers. For example, "my favourite food is pineapple pizza" might become "my, fav, avour, rite, fo, oo, od, is, pin, ine, app, le, piz, za". After doing this, these sub-words would then be mapped to a numerical value. In this case, every word could be considered multiple **tokens**.
- **Embeddings** - An embedding is a representation of natural language which can be learned. Representation comes in the form of a **feature vector**. For example, the word "dance" could be represented by the 5-dimensional vector [-0.8547, 0.4559, -0.3332, 0.9877, 0.1112]. It's important to note here, the size of the feature vector is tuneable. There are two ways to use embeddings:
 1. **Create your own embedding** - Once your text has been turned into numbers (required for an embedding), you can put them through an embedding layer (such as

[tf.keras.layers.Embedding](#)) and an embedding representation will be learned during model training.

2. **Reuse a pre-learned embedding** - Many pre-trained embeddings exist online. These pre-trained embeddings have often been learned on large corpuses of text (such as all of Wikipedia) and thus have a good underlying representation of natural language. You can use a pre-trained embedding to initialize your model and fine-tune it to your own specific task.



Example of **tokenization** (straight mapping from word to number) and **embedding** (richer representation of relationships between tokens).

Question: What level of tokenization should I use? What embedding should I choose?

It depends on your problem. You could try character-level tokenization/embeddings and word-level tokenization/embeddings and see which perform best. You might even want to try stacking them (e.g. combining the outputs of your embedding layers using [tf.keras.layers.concatenate](#)).

If you're looking for pre-trained word embeddings, [Word2vec embeddings](#), [GloVe embeddings](#) and many of the options available on [TensorFlow Hub](#) are great places to start.

Note: Much like searching for a pre-trained computer vision model, you can search for pre-trained word embeddings to use for your problem. Try searching for something like "use pre-trained word embeddings in TensorFlow".

TK - Text vectorization (tokenization)

Enough talking about tokenization and embeddings, let's create some.

We'll practice tokenization (mapping our words to numbers) first.

To tokenize our words, we'll use the helpful preprocessing layer [`tf.keras.layers.experimental.preprocessing.TextVectorization`](#).

The `TextVectorization` layer takes the following parameters:

- `max_tokens` - The maximum number of words in your vocabulary (e.g. 20000 or the number of unique words in your text), includes a value for OOV (out of vocabulary) tokens.
- `standardize` - Method for standardizing text. Default is `"lower_and_strip_punctuation"` which lowers text and removes all punctuation marks.
- `split` - How to split text, default is `"whitespace"` which splits on spaces.
- `ngrams` - How many words to contain per token split, for example, `ngrams=2` splits tokens into continuous sequences of 2.
- `output_mode` - How to output tokens, can be `"int"` (integer mapping), `"binary"` (one-hot encoding), `"count"` or `"tf-idf"`. See documentation for more.
- `output_sequence_length` - Length of tokenized sequence to output. For example, if `output_sequence_length=150`, all tokenized sequences will be 150 tokens long.
- `pad_to_max_tokens` - If `True` (default), the output feature axis will be padded to `max_tokens` even if the number of unique tokens in the vocabulary is less than `max_tokens`.

Let's see it in action.

```
import tensorflow as tf
from tensorflow.keras.layers.experimental.preprocessing import TextVectorization

# Use the default TextVectorization
text_vectorizer = TextVectorization(max_tokens=None, # how many words in the vocabulary (a
                                     standardize="lower_and_strip_punctuation", # how to pr
                                     split="whitespace", # how to split tokens
                                     ngrams=None, # create groups of n-words?
                                     output_mode="int", # how to map tokens to numbers
                                     output_sequence_length=None, # how long should the out
                                     pad_to_max_tokens=True)
```

We've initialized a `TextVectorization` object with the default settings but let's customize it a little bit for our own use case.

In particular, let's set values for `max_tokens` and `output_sequence_length`.

For `max_tokens` (the number of words in the vocabulary), multiples of 10,000 (`10,000`, `20,000`, `30,000`) or the exact number of unique words in your text (e.g. `32,179`) are common values.

For our use case, we'll use `10,000`.

And for the `output_sequence_length` we'll use the average number of tokens per Tweet in the training set. But first, we'll need to find it.

```
# Find average number of tokens (words) in training Tweets
round(sum([len(i.split()) for i in train_sentences])/len(train_sentences))
```

Now let's create another `TextVectorization` object using our custom parameters.

```
# Setup text vectorization variables
max_vocab_length = 10000 # max number of words to have in our vocabulary
max_length = 15 # max length our sequences will be (e.g. how many words from a Tweet does

text_vectorizer = TextVectorization(max_tokens=max_vocab_length,
                                     output_mode="int",
                                     output_sequence_length=max_length)
```

Beautiful!

To map our `TextVectorization` instance `text_vectorizer` to our data, we can call the `adapt()` method on it whilst passing it our training text.

```
# Fit the text vectorizer to the training text
text_vectorizer.adapt(train_sentences)
```

Training data mapped! Let's try our `text_vectorizer` on a custom sentence (one similar to what you might see in the training data).

```
# Create sample sentence and tokenize it
sample_sentence = "There's a flood in my street!"
text_vectorizer([sample_sentence])

<tf.Tensor: shape=(1, 15), dtype=int64, numpy=
array([[264,  3, 232,  4, 13, 698,  0,  0,  0,  0,  0,  0,  0,  0,  0],
       [0,  0]])>
```

Wonderful, it seems we've got a way to turn our text into numbers (in this case, word-level tokenization). Notice the 0's at the end of the returned tensor, this is because we set `output_sequence_length=15`, meaning no matter the size of the sequence we pass to `text_vectorizer`, it always returns a sequence with a length of 15.

How about we try our `text_vectorizer` on a few random sentences?

```
# Choose a random sentence from the training dataset and tokenize it
random_sentence = random.choice(train_sentences)
print(f"Original text:\n{random_sentence}\n\nVectorized version:")
text_vectorizer([random_sentence])

Original text:
meek mill should join isis since he loves suicide-bombing his career for no good reason

Vectorized version:
```

```
<tf.Tensor: shape=(1, 15), dtype=int64, numpy=
array([[ 770, 1812,  168, 1198,  543,  216,   56, 2401, 4506,   79, 1221,
        10,   40,  136,  764]])>
```

Looking good!

Finally, we can check the unique tokens in our vocabulary using the `get_vocabulary()` method.

```
# Get the unique words in the vocabulary
words_in_vocab = text_vectorizer.get_vocabulary()
top_5_words = words_in_vocab[:5] # most common tokens (notice the [UNK] token for "unknown")
bottom_5_words = words_in_vocab[-5:] # least common tokens
print(f"Number of words in vocab: {len(words_in_vocab)}")
print(f"Top 5 most common words: {top_5_words}")
print(f"Bottom 5 least common words: {bottom_5_words}")

Number of words in vocab: 10000
Top 5 most common words: ['', '[UNK]', 'the', 'a', 'in']
Bottom 5 least common words: ['pages', 'paeds', 'pads', 'padres', 'paddytomlinson1']
```

▼ TK - Creating an Embedding using an Embedding Layer

We've got a way to map our text to numbers. How about we go a step further and turn those numbers into an embedding?

The powerful thing about an embedding is it can be learned during training. This means rather than just being static (e.g. 1 = I, 2 = love, 3 = TensorFlow), a word's numeric representation can be improved as a model goes through data samples.

We can see what an embedding of a word looks like by using the [tf.keras.layers.Embedding](#) layer.

The main parameters we're concerned about here are:

- `input_dim` - The size of the vocabulary (e.g. `len(text_vectorizer.get_vocabulary())`).
- `output_dim` - The size of the output embedding vector, for example, a value of 100 outputs a feature vector of size 100 for each word.
- `embeddings_initializer` - How to initialize the embeddings matrix, default is "uniform" which randomly initializes embedding matrix with uniform distribution. This can be changed for using pre-learned embeddings.
- `input_length` - Length of sequences being passed to embedding layer.

Knowing these, let's make an embedding layer.

```
from tensorflow.keras import layers

embedding = layers.Embedding(input_dim=max_vocab_length, # set input shape
                             output_dim=128, # set size of embedding vector
                             embeddings_initializer="uniform", # default, initialize random
                             input_length=max_length) # how long is each input
```

embedding

```
<tensorflow.python.keras.layers.embeddings.Embedding at 0x7f4ad023a9d0>
```

Excellent, notice how `embedding` is a TensorFlow layer? This is important because we can use it as part of a model, meaning its parameters (word representations) can be updated and improved as the model learns.

How about we try it out on a sample sentence?

```
# Get a random sentence from training set
random_sentence = random.choice(train_sentences)
print(f"Original text:\n{random_sentence}\n\nEmbedded version:")
```

```
# Embed the random sentence (turn it into numerical representation)
sample_embed = embedding(text_vectorizer([random_sentence]))
sample_embed
```

Original text:

Suicide bomber kills 15 in Saudi security site mosque <http://t.co/ETyZY8GB2A> #mercader

Embedded version:

```
<tf.Tensor: shape=(1, 15, 128), dtype=float32, numpy=
array([[[[ 4.9278285e-02, -5.6655295e-03, -1.9763172e-02, ...,
          6.6318363e-04, -2.7966166e-02,  1.4702011e-02],
 [ 2.8175700e-02, -1.4095794e-02, -4.4446290e-02, ...,
        -4.9537048e-03, -4.8994493e-02, -2.5464464e-02],
 [-2.0656181e-02,  4.9244549e-02, -9.2459917e-03, ...,
        -1.2107313e-02,  4.2156544e-02, -3.7812542e-02],
 ...,
 [-6.8385974e-03,  2.0084169e-02,  7.8517087e-03, ...,
        -1.6542017e-02,  5.9604645e-06,  4.9306940e-02],
 [-6.8385974e-03,  2.0084169e-02,  7.8517087e-03, ...,
        -1.6542017e-02,  5.9604645e-06,  4.9306940e-02],
 [-6.8385974e-03,  2.0084169e-02,  7.8517087e-03, ...,
        -1.6542017e-02,  5.9604645e-06,  4.9306940e-02]]]], dtype=float32)>
```

Each token in the sentence gets turned into a length 128 feature vector.

```
# Check out a single token's embedding
sample_embed[0][0]
```


```
<tf.Tensor: shape=(128,), dtype=float32, numpy=
array([ 0.04927829, -0.00566553, -0.01976317,  0.00607758, -0.01136936,
        0.00663985,  0.01927099,  0.00754492, -0.00175365,  0.00606846,
        0.00106351,  0.02133454,  0.01348605,  0.03834771, -0.03279131,
        0.00950802,  0.01237954,  0.02429913,  0.04919076, -0.04646122,
       -0.02301148, -0.01166619, -0.02169355,  0.03843554, -0.02540166,
       -0.00597151, -0.00371651, -0.01586529, -0.00062561,  0.00592213,
        0.02834553, -0.02201325, -0.01236179, -0.01406534,  0.01560866,
        0.01037127,  0.00759111, -0.03521353, -0.02563059,  0.02682033,
```

```
-0.01251125, 0.04311582, -0.02334487, -0.02310722, -0.01918397,
0.01827598, -0.00871124, 0.02792168, 0.04474885, 0.03961029,
-0.02476542, 0.0185704 , -0.01366825, -0.04936813, -0.01160566,
0.03004562, 0.03262958, -0.00985865, 0.01954924, 0.03228349,
-0.02490274, 0.04636187, 0.01836151, -0.01517779, -0.00965267,
0.00933499, 0.01553644, 0.00710044, 0.03565482, -0.0443485 ,
-0.03455622, 0.01242312, -0.01468116, 0.00548655, -0.01005224,
0.01782237, 0.0250723 , 0.0087181 , -0.03399094, 0.02342396,
0.00094306, -0.01848843, -0.01380843, 0.04175049, -0.03824323,
-0.01821299, 0.02198598, -0.029931 , -0.01922448, -0.04107044,
0.03463114, 0.03064755, 0.00568541, -0.0377785 , 0.03850855,
-0.00409942, -0.04393035, 0.00671531, -0.00157862, -0.00951899,
-0.01166131, -0.04041838, 0.01213758, 0.04855827, 0.00055845,
0.0452286 , -0.0083486 , 0.03054622, 0.00249606, -0.02056009,
-0.03234287, -0.03716807, -0.0324836 , 0.00463159, 0.01566924,
0.00261984, 0.0064441 , -0.00483591, -0.03326859, 0.01926137,
0.04509808, 0.04702048, -0.04059768, -0.003556 , -0.00045647,
0.00066318, -0.02796617, 0.01470201], dtype=float32)>
```

These values might not mean much to us but they're what our computer sees each word as. When our model looks for patterns in different samples, these values will be updated as necessary.

Note: The previous two concepts (tokenization and embeddings) are the foundation for many NLP tasks. So if you're not sure about anything, be sure to research and conduct your own experiments to further help your understanding.

TK - Modelling a text dataset



Once you've got your inputs and outputs prepared, it's a matter of figuring out which machine learning model to build in between them to bridge the gap.

Now that we've got a way to turn our text data into numbers, we can start to build machine learning models to model it.

To get plenty of practice, we're going to build a series of different models, each as its own experiment. We'll then compare the results of each model and see which one performed best.

More specifically, we'll be building the following:

- **Model 0:** Naive Bayes (baseline)
- **Model 1:** Feed-forward neural network (dense model)
- **Model 2:** LSTM model
- **Model 3:** GRU model
- **Model 4:** Bidirectional-LSTM model
- **Model 5:** 1D Convolutional Neural Network
- **Model 6:** TensorFlow Hub Pretrained Feature Extractor
- **Model 7:** Same as model 6 with 10% of training data

Model 0 is the simplest to acquire a baseline which we'll expect each other of the other deeper models to beat.

Each experiment will go through the following steps:


- Construct the model
- Train the model
- Make predictions with the model
- Track prediction evaluation metrics for later comparison

Let's get started.

▼ TK - Model 0: Getting a baseline

As with all machine learning modelling experiments, it's important to create a baseline model so you've got a benchmark for future experiments to build upon.

To create our baseline, we'll create a Scikit-Learn Pipeline using the TF-IDF (term frequency-inverse document frequency) formula to convert our words to numbers and then model them with the [Multinomial Naive Bayes algorithm](#). This was chosen via referring to the [Scikit-Learn machine learning map](#).

 **Reading:** The ins and outs of TF-IDF algorithm is beyond the scope of this notebook, however, the curious reader is encouraged to check out the [Scikit-Learn documentation for more](#).

```
from sklearn.feature_extraction.text import TfidfVectorizer
from sklearn.naive_bayes import MultinomialNB
from sklearn.pipeline import Pipeline

# Create tokenization and modelling pipeline
model 0 = Pipeline([
```



```

        ("tfidf", TfidfVectorizer()), # convert words to numbers using tfidf
        ("clf", MultinomialNB()) # model the text
    ])

# Fit the pipeline to the training data
model_0.fit(train_sentences, train_labels)

Pipeline(memory=None,
         steps=[('tfidf',
                 TfidfVectorizer(analyzer='word', binary=False,
                                decode_error='strict',
                                dtype=<class 'numpy.float64'>,
                                encoding='utf-8', input='content',
                                lowercase=True, max_df=1.0, max_features=None,
                                min_df=1, ngram_range=(1, 1), norm='l2',
                                preprocessor=None, smooth_idf=True,
                                stop_words=None, strip_accents=None,
                                sublinear_tf=False,
                                token_pattern='(?u)\\b\\w\\w+\\b',
                                tokenizer=None, use_idf=True,
                                vocabulary=None)),
                ('clf',
                 MultinomialNB(alpha=1.0, class_prior=None, fit_prior=True))],
         verbose=False)

```

The benefit of using a shallow model like Multinomial Naive Bayes is that training is very fast.

Let's evaluate our model and find our baseline metric.

```

baseline_score = model_0.score(val_sentences, val_labels)
print(f"Our baseline model achieves an accuracy of: {baseline_score*100:.2f}%")

```

Our baseline model achieves an accuracy of: 79.27%

How about we make some predictions with our baseline model?

```


# Make predictions
baseline_preds = model_0.predict(val_sentences)
baseline_preds[:20]

array([1, 1, 1, 0, 0, 1, 1, 1, 1, 0, 0, 1, 0, 0, 0, 0, 0, 0, 1])

```

We could evaluate these as they are but since we're going to be evaluating several models in the same way going forward, let's create a helper function which takes an array of predictions and ground truth labels and computes the following:

- Accuracy
- Precision
- Recall
- F1-score

 **Note:** Since we're dealing with a classification problem, the above metrics are the most appropriate. If we were working with a regression problem, other metrics such as MAE (mean absolute error) would be a better choice.

```
# Function to evaluate: accuracy, precision, recall, f1-score
from sklearn.metrics import accuracy_score, precision_recall_fscore_support

def calculate_results(y_true, y_pred):
    """
    Calculates model accuracy, precision, recall and f1 score of a binary classification mod

    Args:
    -----
    y_true = true labels in the form of a 1D array
    y_pred = predicted labels in the form of a 1D array

    Returns a dictionary of accuracy, precision, recall, f1-score.
    """
    # Calculate model accuracy
    model_accuracy = accuracy_score(y_true, y_pred) * 100
    # Calculate model precision, recall and f1 score using "weighted" average
    model_precision, model_recall, model_f1, _ = precision_recall_fscore_support(y_true, y_p
    model_results = {"accuracy": model_accuracy,
                     "precision": model_precision,
                     "recall": model_recall,
                     "f1": model_f1}
    return model_results

# Get baseline results
baseline_results = calculate_results(y_true=val_labels,
                                     y_pred=baseline_preds)

baseline_results

{'accuracy': 79.26509186351706,
 'f1': 0.7862189758049549,
 'precision': 0.8111390004213173,
 'recall': 0.7926509186351706}
```

▼ TK - Model 1: A simple dense model

The first "deep" model we're going to build is a single layer dense model. In fact, it's barely going to have a single layer.

It'll take our text and labels as input, tokenize the text, create an embedding, find the average of the embedding (using Global Average Pooling) and then pass the average through a fully connected layer with one output unit and a sigmoid activation function.

If the previous sentence sounds like a mouthful, it'll make sense when we code it out (remember, if in doubt, code it out).

And since we're going to be building a number of TensorFlow deep learning models, we'll import our `create_tensorboard_callback()` function from `helper_functions.py` to keep track of the results of each.

```
# Create tensorboard callback (need to create a new one for each model)
from helper_functions import create_tensorboard_callback

# Create directory to save TensorBoard logs
SAVE_DIR = "model_logs"
```

Now we've got a TensorBoard callback function ready to go, let's build our first deep model.

```
# Build model with the Functional API
from tensorflow.keras import layers
inputs = layers.Input(shape=(1,), dtype="string") # inputs are 1-dimensional strings
x = text_vectorizer(inputs) # turn the input text into numbers
x = embedding(x) # create an embedding of the numerized numbers
x = layers.GlobalAveragePooling1D()(x) # lower the dimensionality of the embedding (try ru
outputs = layers.Dense(1, activation="sigmoid")(x) # create the output layer, want binary
model_1 = tf.keras.Model(inputs, outputs, name="model_1_dense") # construct the model
```

Looking good. Our model takes a 1-dimensional string as input (in our case, a Tweet), it then tokenizes the string using `text_vectorizer` and creates an embedding using `embedding`.

We then (optionally) pool the outputs of the embedding layer to reduce the dimensionality of the tensor we pass to the output layer.

✂ **Exercise:** Try building `model_1` with and without a `GlobalAveragePooling1D()` layer after the `embedding` layer. What happens? Why do you think this is?

Finally, we pass the output of the pooling layer to a dense layer with sigmoid activation (we use sigmoid since our problem is binary classification).

Before we can fit our model to the data, we've got to compile it. Since we're working with binary classification, we'll use `"binary_crossentropy"` as our loss function and the Adam optimizer.

```
# Compile model
model_1.compile(loss="binary_crossentropy",
                optimizer=tf.keras.optimizers.Adam(),
                metrics=["accuracy"])
```

Model compiled. Let's get a summary.

```
# Get a summary of the model
model_1.summary()
```

Model: "model_1_dense"

Layer (type)	Output Shape	Param #
--------------	--------------	---------

input_1 (InputLayer)	[(None, 1)]	0
text_vectorization_1 (TextVectorization)	(None, 15)	0
embedding (Embedding)	(None, 15, 128)	1280000
global_average_pooling1d (GlobalAveragePooling1D)	(None, 128)	0
dense (Dense)	(None, 1)	129
Total params: 1,280,129		
Trainable params: 1,280,129		
Non-trainable params: 0		

Most of the trainable parameters are contained within the embedding layer. Recall we created an embedding of size 128 (output_dim=128) for a vocabulary of size 10,000 (input_dim=10000), hence the 1,280,000 trainable parameters.

Alright, our model is compiled, let's fit it to our training data for 5 epochs. We'll also pass our TensorBoard callback function to make sure our model's training metrics are logged.

```
# Fit the model
model_1_history = model_1.fit(train_sentences, # input sentences can be a list of strings
                              train_labels,
                              epochs=5,
                              validation_data=(val_sentences, val_labels),
                              callbacks=[create_tensorboard_callback(dir_name=SAVE_DIR,
                                                                      experiment_name="simple_model")])

Saving TensorBoard log files to: model_logs/simple_dense_model/20210401-003242
Epoch 1/5
215/215 [=====] - 7s 17ms/step - loss: 0.6527 - accuracy: 0
Epoch 2/5
215/215 [=====] - 3s 13ms/step - loss: 0.4662 - accuracy: 0
Epoch 3/5
215/215 [=====] - 3s 13ms/step - loss: 0.3514 - accuracy: 0
Epoch 4/5
215/215 [=====] - 3s 13ms/step - loss: 0.2894 - accuracy: 0
Epoch 5/5
215/215 [=====] - 3s 13ms/step - loss: 0.2370 - accuracy: 0
```


Nice! Since we're using such a simple model, each epoch processes very quickly.

Let's check our model's performance on the validation set.

```
# Check the results
model_1.evaluate(val_sentences, val_labels)

24/24 [=====] - 0s 3ms/step - loss: 0.4768 - accuracy: 0.775
[0.4767865240573883, 0.7795275449752808]
```

And since we tracked our model's training logs with TensorBoard, how about we visualize them? We can do so by uploading our TensorBoard log files (contained in the `model_logs` directory) to [TensorBoard.dev](https://tensorboard.dev).

 **Note:** Remember, whatever you upload to TensorBoard.dev becomes public. If there are training logs you don't want to share, don't upload them.

```
# # View tensorboard logs of transfer learning modelling experiments (should be 4 models)
# # Upload TensorBoard dev records
# !tensorboard dev upload --logdir ./model_logs \
#   --name "First deep model on text data" \
#   --description "Trying a dense model with an embedding layer" \
#   --one_shot # exits the uploader when upload has finished

# If you need to remove previous experiments, you can do so using the following command
# !tensorboard dev delete --experiment_id EXPERIMENT_ID_TO_DELETE
```

The TensorBoard.dev experiment for our first deep model can be viewed here:

<https://tensorboard.dev/experiment/5d1Xm10aT6m6MgyW3HAGfw/>

TK (tensorboard training curves image)

Beautiful! Those are some colorful training curves. Would you say the model is overfitting or underfitting?


We've built and trained our first deep model, the next step is to make some predictions with it.

```
# Make predictions (these come back in the form of probabilities)
model_1_pred_probs[:20] # only print out the first 20 prediction probabilities

array([[0.44774365],
       [0.8252901 ],
       [0.99755377],
       [0.1550406 ],
       [0.10757869],
       [0.94020915],
       [0.9173237 ],
       [0.9930761 ],
       [0.9686743 ],
       [0.33699468],
       [0.13983482],
       [0.7352934 ],
       [0.06336693],
       [0.27171883],
       [0.00549738],
       [0.17941923],
       [0.03713888],
       [0.09032688],
       [0.29457733],
       [0.6167461 ]], dtype=float32)
```

Since our final layer uses a sigmoid activation function, we get our predictions back in the form of probabilities.

To convert them to prediction classes, we'll use `tf.round()`, meaning prediction probabilities below 0.5 will be rounded to 0 and those above 0.5 will be rounded to 1.

 **Note:** In practice, the output threshold of a sigmoid prediction probability doesn't necessarily have to be 0.5. For example, through testing, you may find that a cut off of 0.25 is better for your chosen evaluation metrics. A common example of this threshold cutoff is the [precision-recall tradeoff](#).

```
# Turn prediction probabilities into single-dimension tensor of floats
model_1_preds = tf.squeeze(tf.round(model_1_pred_probs)) # squeeze removes single dimension
model_1_preds[:20]

<tf.Tensor: shape=(20,), dtype=float32, numpy=
array([0., 1., 1., 0., 0., 1., 1., 1., 1., 0., 0., 1., 0., 0., 0., 0., 0.,
       0., 0., 1.], dtype=float32)>
```

Now we've got our model's predictions in the form of classes, we can use our `calculate_results()` function to compare them to the ground truth validation labels.

```
# Calculate model_1 metrics
model_1_results = calculate_results(y_true=val_labels,
                                   y_pred=model_1_preds)

model_1_results

{'accuracy': 77.95275590551181,
 'f1': 0.7776506830100394,
 'precision': 0.7811151206076258,
 'recall': 0.7795275590551181}
```

How about we compare our first deep model to our baseline model?

```
# Is our simple Keras model better than our baseline model?
import numpy as np
np.array(list(model_1_results.values())) > np.array(list(baseline_results.values()))

array([False, False, False, False])
```

Since we'll be doing this kind of comparison (baseline compared to new model) quite a few times, let's create a function to help us out.

```
# Create a helper function to compare our baseline results to new model results
def compare_baseline_to_new_results(baseline_results, new_model_results):
```

```

for key, value in baseline_results.items():
    print(f"Baseline {key}: {value:.2f}, New {key}: {new_model_results[key]:.2f}, Differen

compare_baseline_to_new_results(baseline_results=baseline_results,
                                new_model_results=model_1_results)

Baseline accuracy: 79.27, New accuracy: 77.95, Difference: -1.31
Baseline precision: 0.81, New precision: 0.78, Difference: -0.03
Baseline recall: 0.79, New recall: 0.78, Difference: -0.01
Baseline f1: 0.79, New f1: 0.78, Difference: -0.01

```

▼ Visualizing learned embeddings

Our first model (`model_1`) contained an embedding layer (`embedding`) which learned a way of representing words as feature vectors by passing over the training data.

Hearing this for the first few times may sound confusing.

So to further help understand what a text embedding is, let's visualize the embedding our model learned.

To do so, let's remind ourselves of the words in our vocabulary.

```

# Get the vocabulary from the text vectorization layer
words_in_vocab = text_vectorizer.get_vocabulary()
len(words_in_vocab), words_in_vocab[:10]

(10000, ['', '[UNK]', 'the', 'a', 'in', 'to', 'of', 'and', 'i', 'is'])

```

And now let's get our embedding layer's weights (these are the numerical representations of each word).

```
model_1.summary()
```

```
Model: "model_1_dense"
```

Layer (type)	Output Shape	Param #
input_1 (InputLayer)	[(None, 1)]	0
text_vectorization_1 (TextVe	(None, 15)	0
embedding (Embedding)	(None, 15, 128)	1280000
global_average_pooling1d (Gl	(None, 128)	0
dense (Dense)	(None, 1)	129
Total params: 1,280,129		
Trainable params: 1,280,129		
Non-trainable params: 0		

```
# Get the weight matrix of embedding layer
# (these are the numerical patterns between the text in the training dataset the model has
embed_weights = model_1.get_layer("embedding").get_weights()[0]
print(embed_weights.shape) # same size as vocab size and embedding_dim (each word is a emb

(10000, 128)
```

Now we've got these two objects, we can use the [Embedding Projector tool](#) to visualize our embedding.

To use the Embedding Projector tool, we need two files:

- The embedding vectors (same as embedding weights).
- The meta data of the embedding vectors (the words they represent - our vocabulary).

Right now, we've got of these files as Python objects. To download them to file, we're going to [use the code example available on the TensorFlow word embeddings tutorial page](#).

```
# # Code below is adapted from: https://www.tensorflow.org/tutorials/text/word\_embeddings#
# import io

# # Create output writers
# out_v = io.open("embedding_vectors.tsv", "w", encoding="utf-8")
# out_m = io.open("embedding_metadata.tsv", "w", encoding="utf-8")

# # Write embedding vectors and words to file
# for num, word in enumerate(words_in_vocab):
#     if num == 0: continue # skip padding token
#     vec = embed_weights[num]
#     out_m.write(word + "\n") # write words to file
#     out_v.write("\t".join([str(x) for x in vec]) + "\n") # write corresponding word vector
# out_v.close()
# out_m.close()

# # Download files locally to upload to Embedding Projector
# try:
#     from google.colab import files
# except ImportError:
#     pass
# else:
#     files.download("embedding_vectors.tsv")
#     files.download("embedding_metadata.tsv")
```

Once you've downloaded the embedding vectors and metadata, you can visualize them using Embedding Vector tool:

1. Go to <http://projector.tensorflow.org/>
2. Click on "Load data"
3. Upload the two files you downloaded (embedding_vectors.tsv and embedding_metadata.tsv)
4. Explore

5. Optional: You can share the data you've created by clicking "Publish"

What do you find?

Are words with similar meanings close together?

Remember, they might not be. The embeddings we downloaded are how our model interprets words, not necessarily how we interpret them.

Also, since the embedding has been learned purely from Tweets, it may contain some strange values as Tweets are a very unique style of natural language.

 **Question:** Do you have to visualize embeddings every time?

No. Although helpful for gaining an intuition of what natural language embeddings are, it's not completely necessary. Especially as the dimensions of your vocabulary and embeddings grow, trying to comprehend them would become an increasingly difficult task.

▼ Recurrent Neural Networks (RNN's)

For our next series of modelling experiments we're going to be using a special kind of neural network called a **Recurrent Neural Network (RNN)**.

The premise of an RNN is simple: use information from the past to help you with the future (this is where the term recurrent comes from). In other words, take an input (x) and compute an output (y) based on all previous inputs.

This concept is especially helpful when dealing with sequences such as passages of natural language text (such as our Tweets).

For example, when you read this sentence, you take into context the previous words when deciphering the meaning of the current word dog.

See what happened there?

I put the word "dog" at the end which is a valid word but it doesn't make sense in the context of the rest of the sentence.

When an RNN looks at a sequence of text (already in numerical form), the patterns it learns are continually updated based on the order of the sequence.

For a simple example, take two sentences:

1. Massive earthquake last week, no?
2. No massive earthquake last week.

Both contain exactly the same words but have different meaning. The order of the words determines the meaning (one could argue punctuation marks also dictate the meaning but for simplicity sake, let's stay focused on the words).

Recurrent neural networks can be used for a number of sequence-based problems:

- **One to one:** one input, one output, such as image classification.
- **One to many:** one input, many outputs, such as image captioning (image input, a sequence of text as caption output).
- **Many to one:** many inputs, one outputs, such as text classification (classifying a Tweet as real diaster or not real diaster).
- **Many to many:** many inputs, many outputs, such as machine translation (translating English to Spanish) or speech to text (audio wave as input, text as output).

When you come across RNN's in the wild, you'll most likely come across variants of the following:

- Long short-term memory cells (LSTMs).
- Gated recurrent units (GRUs).
- Bidirectional RNN's (passes forward and backward along a sequence, left to right and right to left).

Going into the details of each these is beyond the scope of this notebook (we're going to focus on using them instead), the main thing you should know for now is that they've proven very effective at modelling sequences.

For a deeper understanding of what's happening behind the scenes of the code we're about to write, I'd recommend the following resources:

Resources:


- [MIT Deep Learning Lecture on Recurrent Neural Networks](#) - explains the background of recurrent neural networks and introduces LSTMs.
- [The Unreasonable Effectiveness of Recurrent Neural Networks](#) by Andrej Karpathy - demonstrates the power of RNN's with examples generating various sequences.
- [Understanding LSTMs](#) by Chris Olah - an in-depth (and technical) look at the mechanics of the LSTM cell, possibly the most popular RNN building block.

▼ Model 2: LSTM

With all this talk of what RNN's are and what they're good for, I'm sure you're eager to build one.

We're going to start with an LSTM-powered RNN.

To harness the power of the LSTM cell (LSTM cell and LSTM layer are often used interchangeably) in TensorFlow, we'll use [tensorflow.keras.layers.LSTM\(\)](#).



Coloured block example of the structure of an recurrent neural network.

Our model is going to take on a very similar structure to `model_1`:

```
Input (text) -> Tokenize -> Embedding -> Layers -> Output (label probability)

# Create LSTM model
from tensorflow.keras import layers
inputs = layers.Input(shape=(1,), dtype="string")
x = text_vectorizer(inputs)
x = embedding(x)
print(x.shape)
# x = layers.LSTM(64, return_sequences=True)(x) # return vector for each word in the Tweet
x = layers.LSTM(64)(x) # return vector for whole sequence
print(x.shape)
# x = layers.Dense(64, activation="relu")(x) # optional dense layer on top of output of LS
outputs = layers.Dense(1, activation="sigmoid")(x)
model_2 = tf.keras.Model(inputs, outputs, name="model_2_LSTM")

(None, 15, 128)
(None, 64)
```

Note: Reading the documentation for the [TensorFlow LSTM layer](#), you'll find a plethora of parameters. Many of these have been tuned to make sure they compute as fast as possible. The main ones you'll be looking to adjust are `units` (number of hidden units) and `return_sequences` (set this to `True` when stacking LSTM or other recurrent layers).

Now we've got our LSTM model built, let's compile it using `"binary_crossentropy"` loss and the Adam optimizer.

```
# Compile model
model_2.compile(loss="binary_crossentropy",
                optimizer=tf.keras.optimizers.Adam(),
                metrics=["accuracy"])
```

And before we fit our model to the data, let's get a summary.

```
model_2.summary()
```

```
Model: "model_2_LSTM"
```

Layer (type)	Output Shape	Param #
=====		

input_2 (InputLayer)	[(None, 1)]	0
text_vectorization_1 (TextVectorization)	(None, 15)	0
embedding (Embedding)	(None, 15, 128)	1280000
lstm (LSTM)	(None, 64)	49408
dense_1 (Dense)	(None, 1)	65
=====		
Total params: 1,329,473		
Trainable params: 1,329,473		
Non-trainable params: 0		

Looking good! You'll notice a fair few more trainable parameters within our LSTM layer than `model_1`.

If you'd like to know where this number comes from, I recommend going through the above resources as well the following on calculating the number of parameters in an LSTM cell:

- [Stack Overflow answer to calculate the number of parameters in an LSTM cell](#) by Marcin Możejko
- [Calculating number of parameters in a LSTM unit and layer](#) by Shridhar Priyadarshi

Now our first RNN model's compiled let's fit it to our training data, validating it on the validation data and tracking its training parameters using our TensorBoard callback.

```
# Fit model
model_2_history = model_2.fit(train_sentences,
                              train_labels,
                              epochs=5,
                              validation_data=(val_sentences, val_labels),
                              callbacks=[create_tensorboard_callback(SAVE_DIR,
                                                                      "LSTM")])

Saving TensorBoard log files to: model_logs/LSTM/20210401-003301
Epoch 1/5
215/215 [=====] - 34s 21ms/step - loss: 0.2990 - accuracy: 0.0000
Epoch 2/5
215/215 [=====] - 3s 15ms/step - loss: 0.1537 - accuracy: 0.0000
Epoch 3/5
215/215 [=====] - 3s 15ms/step - loss: 0.1266 - accuracy: 0.0000
Epoch 4/5
215/215 [=====] - 3s 15ms/step - loss: 0.0931 - accuracy: 0.0000
Epoch 5/5
215/215 [=====] - 3s 15ms/step - loss: 0.0825 - accuracy: 0.0000
```

Nice! We've got our first trained RNN model using LSTM cells. Let's make some predictions with it.

The same thing will happen as before, due to the sigmoid activation function in the final layer, when we call the `predict()` method on our model, it'll return prediction probabilities rather than

classes.

```
# Make predictions on the validation dataset
model_2_pred_probs = model_2.predict(val_sentences)
model_2_pred_probs.shape, model_2_pred_probs[:10] # view the first 10

((762, 1), array([[8.5709346e-03],
                  [7.4427909e-01],
                  [9.9939656e-01],
                  [2.0226166e-02],
                  [4.3769312e-04],
                  [9.8749244e-01],
                  [2.9165131e-01],
                  [9.9961972e-01],
                  [9.9931455e-01],
                  [4.8511603e-01]], dtype=float32))
```

We can turn these prediction probabilities into prediction classes by rounding to the nearest integer (by default, prediction probabilities under 0.5 will go to 0 and those over 0.5 will go to 1).

```
# Round out predictions and reduce to 1-dimensional array
model_2_preds = tf.squeeze(tf.round(model_2_pred_probs))
model_2_preds[:10]

<tf.Tensor: shape=(10,), dtype=float32, numpy=array([0., 1., 1., 0., 0., 1., 0., 1.,
```

Beautiful, now let's use our `calculate_results()` function to evaluate our LSTM model and our `compare_baseline_to_new_results()` function to compare it to our baseline model.

```
# Calculate LSTM model results
model_2_results = calculate_results(y_true=val_labels,
                                   y_pred=model_2_preds)
model_2_results

{'accuracy': 77.16535433070865,
 'f1': 0.7681214344851189,
 'precision': 0.7767213938683196,
 'recall': 0.7716535433070866}


# Compare model 2 to baseline
compare_baseline_to_new_results(baseline_results, model_2_results)

Baseline accuracy: 79.27, New accuracy: 77.17, Difference: -2.10
Baseline precision: 0.81, New precision: 0.78, Difference: -0.03
Baseline recall: 0.79, New recall: 0.77, Difference: -0.02
Baseline f1: 0.79, New f1: 0.77, Difference: -0.02
```

▼ Model 3: GRU

Another popular and effective RNN component is the GRU or gated recurrent unit.

The GRU cell has similar features to an LSTM cell but has less parameters.

 **Resource:** A full explanation of the GRU cell is beyond the scope of this notepad but I'd suggest the following resources to learn more:

- [Gated Recurrent Unit](#) Wikipedia page
- [Understanding GRU networks](#) by Simeon Kostadinov

To use the GRU cell in TensorFlow, we can call the `tensorflow.keras.layers.GRU()` class.

The architecture of the GRU-powered model will follow the same structure we've been using:

Input (text) -> Tokenize -> Embedding -> Layers -> Output (label probability)

Again, the only difference will be the layer(s) we use between the embedding and the output.

```
# Build an RNN using the GRU cell
from tensorflow.keras import layers
inputs = layers.Input(shape=(1,), dtype="string")
x = text_vectorizer(inputs)
x = embedding(x)
# x = layers.GRU(64, return_sequences=True)(x) # stacking recurrent cells requires return_seq
x = layers.GRU(64)(x)
# x = layers.Dense(64, activation="relu")(x) # optional dense layer after GRU cell
outputs = layers.Dense(1, activation="sigmoid")(x)
model_3 = tf.keras.Model(inputs, outputs, name="model_3_GRU")
```

TensorFlow makes it easy to use powerful components such as the GRU cell in our models. And now our third model is built, let's compile it, just as before.

```
# Compile GRU model
model_3.compile(loss="binary_crossentropy",
                optimizer=tf.keras.optimizers.Adam(),
                metrics=["accuracy"])
```

What does a summary of our model look like?

```
# Get a summary of the GRU model
model_3.summary()
```

Model: "model_3_GRU"

Layer (type)	Output Shape	Param #
=====		
input_3 (InputLayer)	[(None, 1)]	0

text_vectorization_1 (TextVe	(None, 15)	0

embedding (Embedding)	(None, 15, 128)	1280000

gru (GRU)	(None, 64)	37248
dense_2 (Dense)	(None, 1)	65
=====		
Total params: 1,317,313		
Trainable params: 1,317,313		
Non-trainable params: 0		

Notice the difference in number of trainable parameters between `model_2` (LSTM) and `model_3` (GRU). The difference comes from the LSTM cell having more trainable parameters than the GRU cell.

We'll fit our model just as we've been doing previously. We'll also track our models results using our `create_tensorboard_callback()` function.

```
# Fit model
model_3_history = model_3.fit(train_sentences,
                              train_labels,
                              epochs=5,
                              validation_data=(val_sentences, val_labels),
                              callbacks=[create_tensorboard_callback(SAVE_DIR, "GRU")])

Saving TensorBoard log files to: model_logs/GRU/20210401-003349
Epoch 1/5
215/215 [=====] - 6s 20ms/step - loss: 0.2777 - accuracy: 0
Epoch 2/5
215/215 [=====] - 3s 15ms/step - loss: 0.0776 - accuracy: 0
Epoch 3/5
215/215 [=====] - 3s 15ms/step - loss: 0.0712 - accuracy: 0
Epoch 4/5
215/215 [=====] - 3s 15ms/step - loss: 0.0581 - accuracy: 0
Epoch 5/5
215/215 [=====] - 3s 14ms/step - loss: 0.0437 - accuracy: 0
```

Due to the optimized default settings of the GRU cell in TensorFlow, training doesn't take long at all.

Time to make some predictions on the validation samples.

```
# Make predictions on the validation data
model_3_pred_probs = model_3.predict(val_sentences)
model_3_pred_probs.shape, model_3_pred_probs[:10]

((762, 1), array([[1.1965477e-02],
                   [7.8170043e-01],
                   [9.9986637e-01],
                   [8.6641684e-02],
                   [7.6353412e-05],
                   [9.9975520e-01],
                   [6.9296145e-01],
                   [9.9995410e-01],
```

```
[9.9992466e-01],  
[9.4577050e-01]], dtype=float32))
```

Again we get an array of prediction probabilities back which we can convert to prediction classes by rounding them.

```
# Convert prediction probabilities to prediction classes  
model_3_preds = tf.squeeze(tf.round(model_3_pred_probs))  
model_3_preds[:10]  
  
<tf.Tensor: shape=(10,), dtype=float32, numpy=array([0., 1., 1., 0., 0., 1., 1., 1.,
```

Now we've got predicted classes, let's evaluate them against the ground truth labels.

```
# Calculate model_3 results  
model_3_results = calculate_results(y_true=val_labels,  
                                   y_pred=model_3_preds)  
  
model_3_results  
  
{'accuracy': 77.69028871391076,  
  'f1': 0.7751243211017478,  
  'precision': 0.7781874595396938,  
  'recall': 0.7769028871391076}
```

Finally we can compare our GRU model's results to our baseline.

```
# Compare to baseline  
compare_baseline_to_new_results(baseline_results, model_3_results)  
  
Baseline accuracy: 79.27, New accuracy: 77.69, Difference: -1.57  
Baseline precision: 0.81, New precision: 0.78, Difference: -0.03  
Baseline recall: 0.79, New recall: 0.78, Difference: -0.02  
Baseline f1: 0.79, New f1: 0.78, Difference: -0.01
```

▼ Model 4: Bidirectional RNN model

Look at us go! We've already built two RNN's with GRU and LSTM cells. Now we're going to look into another kind of RNN, the bidirectional RNN.

A standard RNN will process a sequence from left to right, where as a bidirectional RNN will process the sequence from left to right and then again from right to left.

Intuitively, this can be thought of as if you were reading a sentence for the first time in the normal fashion (left to right) but for some reason it didn't make sense so you traverse back through the words and go back over them again (right to left).


In practice, many sequence models often see an improvement in performance when using bidirectional RNN's.

However, this improvement in performance often comes at the cost of longer training times and increased model parameters (since the model goes left to right and right to left, the number of trainable parameters doubles).

Okay enough talk, let's build a bidirectional RNN.

Once again, TensorFlow helps us out by providing the [tensorflow.keras.layers.Bidirectional](#) class. We can use the `Bidirectional` class to wrap our existing RNNs, instantly making them bidirectional.

```
# Build a Bidirectional RNN in TensorFlow
from tensorflow.keras import layers
inputs = layers.Input(shape=(1,), dtype="string")
x = text_vectorizer(inputs)
x = embedding(x)
# x = layers.Bidirectional(layers.LSTM(64, return_sequences=True))(x) # stacking RNN layer
x = layers.Bidirectional(layers.LSTM(64))(x) # bidirectional goes both ways so has double
outputs = layers.Dense(1, activation="sigmoid")(x)
model_4 = tf.keras.Model(inputs, outputs, name="model_4_Bidirectional")
```

 **Note:** You can use the `Bidirectional` wrapper on any RNN cell in TensorFlow. For example, `layers.Bidirectional(layers.GRU(64))` creates a bidirectional GRU cell.

Our bidirectional model is built, let's compile it.

```
# Compile
model_4.compile(loss="binary_crossentropy",
                 optimizer=tf.keras.optimizers.Adam(),
                 metrics=["accuracy"])
```

And of course, we'll check out a summary.

```
# Get a summary of our bidirectional model
model_4.summary()
```

Model: "model_4_Bidirectional"

Layer (type)	Output Shape	Param #
=====		
input_4 (InputLayer)	[(None, 1)]	0

text_vectorization_1 (TextVe	(None, 15)	0

embedding (Embedding)	(None, 15, 128)	1280000

bidirectional (Bidirectional	(None, 128)	98816

dense_3 (Dense)	(None, 1)	129
=====		

```
Total params: 1,378,945
Trainable params: 1,378,945
Non-trainable params: 0
```

Notice the increased number of trainable parameters in `model_4` (bidirectional LSTM) compared to `model_2` (regular LSTM). This is due to the bidirectionality we added to our RNN.

Time to fit our bidirectional model and track its performance.

```
# Fit the model (takes longer because of the bidirectional layers)
model_4_history = model_4.fit(train_sentences,
                              train_labels,
                              epochs=5,
                              validation_data=(val_sentences, val_labels),
                              callbacks=[create_tensorboard_callback(SAVE_DIR, "bidirection")])

Saving TensorBoard log files to: model_logs/bidirectional_RNN/20210401-003410
Epoch 1/5
215/215 [=====] - 7s 23ms/step - loss: 0.1850 - accuracy: 0
Epoch 2/5
215/215 [=====] - 4s 16ms/step - loss: 0.0531 - accuracy: 0
Epoch 3/5
215/215 [=====] - 3s 16ms/step - loss: 0.0469 - accuracy: 0
Epoch 4/5
215/215 [=====] - 4s 16ms/step - loss: 0.0398 - accuracy: 0
Epoch 5/5
215/215 [=====] - 4s 17ms/step - loss: 0.0360 - accuracy: 0
```

Due to the bidirectionality of our model we see a slight increase in training time.

Not to worry, it's not too dramatic of an increase.

Let's make some predictions with it.

```
# Make predictions with bidirectional RNN on the validation data
model_4_pred_probs = model_4.predict(val_sentences)
model_4_pred_probs[:10]

array([[4.3160453e-02],
       [6.3816196e-01],
       [9.9997735e-01],
       [2.0801796e-01],
       [1.8262153e-04],
       [9.9970919e-01],
       [7.3967320e-01],
       [9.9999332e-01],
       [9.9998629e-01],
       [5.9087348e-01]], dtype=float32)
```

And we'll convert them to prediction classes and evaluate them against the ground truth labels and baseline model.

```
# Convert prediction probabilities to labels
model_4_preds = tf.squeeze(tf.round(model_4_pred_probs))
model_4_preds[:10]

<tf.Tensor: shape=(10,), dtype=float32, numpy=array([0., 1., 1., 0., 0., 1., 1., 1.,
...

# Calculate bidirectional RNN model results
model_4_results = calculate_results(val_labels, model_4_preds)
model_4_results

{'accuracy': 76.77165354330708,
 'f1': 0.766597011860758,
 'precision': 0.7677367335034279,
 'recall': 0.7677165354330708}

# Check to see how the bidirectional model performs against the baseline
compare_baseline_to_new_results(baseline_results, model_4_results)

Baseline accuracy: 79.27, New accuracy: 76.77, Difference: -2.49
Baseline precision: 0.81, New precision: 0.77, Difference: -0.04
Baseline recall: 0.79, New recall: 0.77, Difference: -0.02
Baseline f1: 0.79, New f1: 0.77, Difference: -0.02
```

▼ Convolutional Neural Networks for Text

You might've used convolutional neural networks (CNNs) for images before but they can also be used for sequences.

The main difference between using CNNs for images and sequences is the shape of the data. Images come in 2-dimensions (height x width) where as sequences are often 1-dimensional (a string of text).

So to use CNNs with sequences, we use a 1-dimensional convolution instead of a 2-dimensional convolution.

A typical CNN architecture for sequences will look like the following:

```
Inputs (text) -> Tokenization -> Embedding -> Layers -> Outputs (class probabilities)
```

You might be thinking "that just looks like the architecture layout we've been using for the other models..."

And you'd be right.

The difference again is in the layers component. Instead of using an LSTM or GRU cell, we're going to use a [tensorflow.keras.layers.Conv1D\(.\)](#) layer followed by a [tensorflow.keras.layers.GlobalMaxPool1D\(.\)](#) layer.

📖 **Resource:** The intuition here is explained succinctly in the paper [Understanding Convolutional Neural Networks for Text Classification](#), where they state that CNNs classify text through the following steps:

1. 1-dimensional convolving filters are used as ngram detectors, each filter specializing in a closely-related family of ngrams (an ngram is a collection of n-words, for example, an ngram of 5 might result in "hello, my name is Daniel").
2. Max-pooling over time extracts the relevant ngrams for making a decision.
3. The rest of the network classifies the text based on this information.

▼ TK - Model 5: Conv1D

Before we build a full 1-dimensional CNN model, let's see a 1-dimensional convolutional layer (also called a **temporal convolution**) in action.

We'll first create an embedding of a sample of text and experiment passing it through a `Conv1D()` layer and `GlobalMaxPool1D()` layer.

```
# Test out the embedding, 1D convolutional and max pooling
embedding_test = embedding(text_vectorizer(["this is a test sentence"])) # turn target sen
conv_1d = layers.Conv1D(filters=32, kernel_size=5, activation="relu") # convolve over targ
conv_1d_output = conv_1d(embedding_test) # pass embedding through 1D convolutional layer
max_pool = layers.GlobalMaxPool1D()
max_pool_output = max_pool(conv_1d_output) # get the most important features
embedding_test.shape, conv_1d_output.shape, max_pool_output.shape

(TensorShape([1, 15, 128]), TensorShape([1, 11, 32]), TensorShape([1, 32]))
```

Notice the output shapes of each layer.

The embedding has an output shape dimension of the parameters we set it to (`input_length=15` and `output_dim=128`).

The 1-dimensional convolutional layer has an output which has been compressed inline with its parameters. And the same goes for the max pooling layer output.

Our text starts out as a string but gets converted to a feature vector of length 64 through various transformation steps (from tokenization to embedding to 1-dimensional convolution to max pool).

Let's take a peak at what each of these transformations looks like.

```
# See the outputs of each layer
embedding_test[:1], conv_1d_output[:1], max_pool_output[:1]

(<tf.Tensor: shape=(1, 15, 128), dtype=float32, numpy=
  array([[[ 0.02096221, -0.00409704,  0.02650973, ..., -0.04754214,
```


get a summary.

```
# Create 1-dimensional convolutional layer to model sequences
from tensorflow.keras import layers
inputs = layers.Input(shape=(1,), dtype="string")
x = text_vectorizer(inputs)
x = embedding(x)
x = layers.Conv1D(filters=32, kernel_size=5, activation="relu")(x)
x = layers.GlobalMaxPool1D()(x)
# x = layers.Dense(64, activation="relu")(x) # optional dense layer
outputs = layers.Dense(1, activation="sigmoid")(x)
model_5 = tf.keras.Model(inputs, outputs, name="model_5_Conv1D")

# Compile Conv1D model
model_5.compile(loss="binary_crossentropy",
                 optimizer=tf.keras.optimizers.Adam(),
                 metrics=["accuracy"])

# Get a summary of our 1D convolution model
model_5.summary()
```

```
Model: "model_5_Conv1D"
```

Layer (type)	Output Shape	Param #
input_5 (InputLayer)	[(None, 1)]	0
text_vectorization_1 (TextVectorization)	(None, 15)	0
embedding (Embedding)	(None, 15, 128)	1280000
conv1d_1 (Conv1D)	(None, 11, 32)	20512
global_max_pooling1d_1 (GlobalMaxPooling1D)	(None, 32)	0
dense_4 (Dense)	(None, 1)	33
Total params: 1,300,545		
Trainable params: 1,300,545		
Non-trainable params: 0		

Woohoo! Looking great! Notice how the number of trainable parameters for the 1-dimensional convolutional layer is similar to that of the LSTM layer in `model_2`.

Let's fit our 1D CNN model to our text data. In line with previous experiments, we'll save its results using our `create_tensorboard_callback()` function.

[illegible]

```

Saving TensorBoard log files to: model_logs/Conv1D/20210401-003433
Epoch 1/5
215/215 [=====] - 5s 19ms/step - loss: 0.2178 - accuracy: 0
Epoch 2/5
215/215 [=====] - 3s 14ms/step - loss: 0.0734 - accuracy: 0
Epoch 3/5
215/215 [=====] - 3s 14ms/step - loss: 0.0573 - accuracy: 0
Epoch 4/5
215/215 [=====] - 3s 14ms/step - loss: 0.0494 - accuracy: 0
Epoch 5/5
215/215 [=====] - 3s 14ms/step - loss: 0.0480 - accuracy: 0

```

Nice! Thanks to GPU acceleration, our 1D convolutional model trains nice and fast. Let's make some predictions with it and evaluate them just as before.

```

# Make predictions with model_5
model_5_pred_probs = model_5.predict(val_sentences)
model_5_pred_probs[:10]

array([[1.8386783e-01],
       [9.3488133e-01],
       [9.9976474e-01],
       [6.3242055e-02],
       [7.8606331e-07],
       [9.9247026e-01],
       [8.7202114e-01],
       [9.9995613e-01],
       [9.999928e-01],
       [7.3194456e-01]], dtype=float32)

# Convert model_5 prediction probabilities to labels
model_5_preds = tf.squeeze(tf.round(model_5_pred_probs))
model_5_preds[:10]

<tf.Tensor: shape=(10,), dtype=float32, numpy=array([0., 1., 1., 0., 0., 1., 1., 1.,

```

```

# Calculate model_5 evaluation metrics
model_5_results = calculate_results(y_true=val_labels,
                                   y_pred=model_5_preds)
model_5_results

```

```

{'accuracy': 76.24671916010499,
 'f1': 0.7614244466786471,
 'precision': 0.762323768273959,
 'recall': 0.7624671916010499}

```

```

# Compare model_5 results to baseline
compare_baseline_to_new_results(baseline_results, model_5_results)

```

```

Baseline accuracy: 79.27, New accuracy: 76.25, Difference: -3.02
Baseline precision: 0.81, New precision: 0.76, Difference: -0.05

```

Baseline recall: 0.79, New recall: 0.76, Difference: -0.03
Baseline f1: 0.79, New f1: 0.76, Difference: -0.02

▼ Using Pretrained Embeddings (transfer learning for NLP)

For all of the previous deep learning models we've built and trained, we've created and used our own embeddings from scratch each time.

However, a common practice is to leverage pretrained embeddings through **transfer learning**. This is one of the main benefits of using deep models: being able to take what one (often larger) model has learned (often on a large amount of data) and adjust it for our own use case.

For our next model, instead of using our own embedding layer, we're going to replace it with a pretrained embedding layer.


More specifically, we're going to be using the [Universal Sentence Encoder](#) from [TensorFlow Hub](#) (a great resource containing a plethora of pretrained model resources for a variety of tasks).

🔑 **Note:** There are many different pretrained text embedding options on TensorFlow Hub, however, some require different levels of text preprocessing than others. Best to experiment with a few and see which best suits your use case.

▼ TK - Model 6: TensorFlow Hub Pretrained Sentence Encoder

The main difference between the embedding layer we created and the Universal Sentence Encoder is that rather than create a word-level embedding, the Universal Sentence Encoder, as you might've guessed, creates a whole sentence-level embedding.

Our embedding layer also outputs an a 128 dimensional vector for each word, where as, the Universal Sentence Encoder outputs a 512 dimensional vector for each sentence.



*The feature extractor model we're building through the eyes of an **encoder/decoder** model.*

🔑 **Note:** An **encoder** is the name for a model which converts raw data such as text into a numerical representation (feature vector), a **decoder** converts the numerical representation to a desired output.

As usual, this is best demonstrated with an example.

We can load in a TensorFlow Hub module using the [hub.load\(.\)](#) method and passing it the target URL of the module we'd like to use, in our case, it's "<https://tfhub.dev/google/universal-sentence-encoder/4>".

```
# Example of pretrained embedding with universal sentence encoder - https://tfhub.dev/goog
import tensorflow_hub as hub
embed = hub.load("https://tfhub.dev/google/universal-sentence-encoder/4") # load Universal
embed_samples = embed([sample_sentence,
                        "When you call the universal sentence encoder on a sentence, it turn

print(embed_samples[0][:50])
```

```
tf.Tensor(
[ -0.01157027  0.02485911  0.02878048 -0.012715    0.03971538  0.08827761
  0.02680985  0.05589839 -0.01068729 -0.00597292  0.00639323 -0.0181952
  0.00030814  0.09105889  0.05874645 -0.03180628  0.01512474 -0.05162929
  0.00991367 -0.06865346 -0.04209306  0.02678981  0.03011008  0.00321069
 -0.00337971 -0.04787357  0.02266719 -0.00985925 -0.04063613 -0.01292093
 -0.04666385  0.056303   -0.03949255  0.00517688  0.02495828 -0.07014441
  0.02871509  0.04947684 -0.00633978 -0.08960193  0.02807117 -0.00808362
 -0.01360601  0.0599865  -0.10361787 -0.05195374  0.00232955 -0.0233253
 -0.03758106  0.0332773 ], shape=(50,), dtype=float32)
```


```
# Each sentence has been encoded into a 512 dimension vector
embed_samples[0].shape
```

```
TensorShape([512])
```

Passing our sentences to the Universal Sentence Encoder (USE) encodes them from strings to 512 dimensional vectors, which make no sense to us but hopefully make sense to our machine learning models.

Speaking of models, let's build one with the USE as our embedding layer.

We can convert the TensorFlow Hub USE module into a Keras layer using the [hub.KerasLayer](#) class.

 **Note:** Due to the size of the USE TensorFlow Hub module, it may take a little while to download. Once it's downloaded though, it'll be cached and ready to use. And as with many TensorFlow Hub modules, there is a ["lite" version of the USE](#) which takes up less space but sacrifices some performance and requires more preprocessing steps. However, depending on your available compute power, the lite version may be better for your application use case.

```
# We can use this encoding layer in place of our text_vectorizer and embedding layer
sentence_encoder_layer = hub.KerasLayer("https://tfhub.dev/google/universal-sentence-encod
input_shape=[], # shape of inputs coming to our mo
dtype=tf.string, # data type of inputs coming to t
trainable=False, # keep the pretrained weights (we
name="USE")
```

Beautiful! Now we've got the USE as a Keras layer, we can use it in a Keras Sequential model.

```
# Create model using the Sequential API
model_6 = tf.keras.Sequential([
    sentence_encoder_layer, # take in sentences and then encode them into an embedding
    layers.Dense(64, activation="relu"),
    layers.Dense(1, activation="sigmoid")
], name="model_6_USE")
```

```
# Compile model
model_6.compile(loss="binary_crossentropy",
                 optimizer=tf.keras.optimizers.Adam(),
                 metrics=["accuracy"])
```

```
model_6.summary()
```

Model: "model_6_USE"

Layer (type)	Output Shape	Param #
=====		
USE (KerasLayer)	(None, 512)	256797824
dense_5 (Dense)	(None, 64)	32832
dense_6 (Dense)	(None, 1)	65
=====		
Total params: 256,830,721		
Trainable params: 32,897		
Non-trainable params: 256,797,824		
=====		

Notice the number of paramters in the USE layer, these are the pretrained weights its learned on various text sources (Wikipedia, web news, web question-answer forums, etc, see the [Universal Sentence Encoder paper](#) for more).

The trainable parameters are only in our output layers, in other words, we're keeping the USE weights frozen and using it as a feature-extractor. We could fine-tune these weights by setting `trainable=True` when creating the `hub.KerasLayer` instance.

Now we've got a feature extractor model ready, let's train it and track its results to TensorBoard using our `create_tensorboard_callback()` function.

```
# Train a classifier on top of pretrained embeddings
model_6_history = model_6.fit(train_sentences,
                              train_labels,
                              epochs=5,
                              validation_data=(val_sentences, val_labels),
                              callbacks=[create_tensorboard_callback(SAVE_DIR,
                                                                      "tf_hub_sentence_enco
```

Saving TensorBoard log files to: `model_logs/tf_hub_sentence_encoder/20210401-003512`

```

Epoch 1/5
215/215 [=====] - 7s 23ms/step - loss: 0.5850 - accuracy: 0.8
Epoch 2/5
215/215 [=====] - 2s 10ms/step - loss: 0.4226 - accuracy: 0.8
Epoch 3/5
215/215 [=====] - 2s 9ms/step - loss: 0.4040 - accuracy: 0.8
Epoch 4/5
215/215 [=====] - 2s 9ms/step - loss: 0.3907 - accuracy: 0.8
Epoch 5/5
215/215 [=====] - 2s 10ms/step - loss: 0.3905 - accuracy: 0.8

```

USE model trained! Let's make some predictions with it and evaluate them as we've done with our other models.

```

# Make predictions with USE TF Hub model
model_6_pred_probs = model_6.predict(val_sentences)
model_6_pred_probs[:10]

array([[0.2231317 ],
       [0.82815576],
       [0.98684573],
       [0.2156143 ],
       [0.7279634 ],
       [0.74375427],
       [0.97867924],
       [0.98012793],
       [0.9410219 ],
       [0.09511462]], dtype=float32)

# Convert prediction probabilities to labels
model_6_preds = tf.squeeze(tf.round(model_6_pred_probs))
model_6_preds[:10]

<tf.Tensor: shape=(10,), dtype=float32, numpy=array([0., 1., 1., 0., 1., 1., 1., 1.,

```



```

# Calculate model 6 performance metrics
model_6_results = calculate_results(val_labels, model_6_preds)
model_6_results

{'accuracy': 81.62729658792651,
 'f1': 0.8146067773916925,
 'precision': 0.8190827553840537,
 'recall': 0.8162729658792651}

# Compare TF Hub model to baseline
compare_baseline_to_new_results(baseline_results, model_6_results)

Baseline accuracy: 79.27, New accuracy: 81.63, Difference: 2.36
Baseline precision: 0.81, New precision: 0.82, Difference: 0.01
Baseline recall: 0.79, New recall: 0.82, Difference: 0.02
Baseline f1: 0.79, New f1: 0.81, Difference: 0.03

```

TK - Model 7: TensorFlow Hub Pretrained Sentence Encoder 10% of the training data

One of the benefits of using transfer learning methods, such as, the pretrained embeddings within the USE is the ability to get great results on a small amount of data (the USE paper even mentions this in the abstract).

To put this to the test, we're going to make a small subset of the training data (10%), train a model and evaluate it.

```
# Create subsets of 10% of the training data
train_10_percent = train_df_shuffled[["text", "target"]].sample(frac=0.1, random_state=42)
train_sentences_10_percent = train_10_percent["text"].to_list()
train_labels_10_percent = train_10_percent["target"].to_list()
len(train_sentences_10_percent), len(train_labels_10_percent)

(761, 761)
```

Because we've selected a random subset of the training samples, the classes should be roughly balanced (as they are in the full training dataset).

```
# Check the number of targets in our subset of data
train_10_percent["target"].value_counts()

0      413
1      348
Name: target, dtype: int64
```

To make sure we're making an appropriate comparison between our model's ability to learn from the full training set and 10% subset, we'll clone our USE model (`model_6`) using the [tf.keras.models.clone_model\(\)](#) method.

Doing this will create the same architecture but reset the learned weights of the clone target (pretrained weights from the USE will remain but all others will be reset).

```
# Clone model_6 but reset weights
model_7 = tf.keras.models.clone_model(model_6)

# Compile model
model_7.compile(loss="binary_crossentropy",
                optimizer=tf.keras.optimizers.Adam(),
                metrics=["accuracy"])

# Get a summary (will be same as model_6)
model_7.summary()
```

Model: "model_6_USE"

Layer (type)	Output Shape	Param #
USE (KerasLayer)	(None, 512)	256797824
dense_5 (Dense)	(None, 64)	32832
dense_6 (Dense)	(None, 1)	65
Total params: 256,830,721		
Trainable params: 32,897		
Non-trainable params: 256,797,824		

Notice the layout of `model_7` is the same as `model_6`. Now let's train the newly created model on our 10% training data subset.

```
# Fit the model to 10% of the training data
model_7_history = model_7.fit(x=train_sentences_10_percent,
                             y=train_labels_10_percent,
                             epochs=5,
                             validation_data=(val_sentences, val_labels),
                             callbacks=[create_tensorboard_callback(SAVE_DIR, "10_percent")])

Saving TensorBoard log files to: model_logs/10_percent_tf_hub_sentence_encoder/202104
Epoch 1/5
24/24 [=====] - 4s 106ms/step - loss: 0.6799 - accuracy: 0.6
Epoch 2/5
24/24 [=====] - 0s 17ms/step - loss: 0.6113 - accuracy: 0.79
Epoch 3/5
24/24 [=====] - 0s 17ms/step - loss: 0.5342 - accuracy: 0.86
Epoch 4/5
24/24 [=====] - 0s 18ms/step - loss: 0.4708 - accuracy: 0.86
Epoch 5/5
24/24 [=====] - 0s 17ms/step - loss: 0.4264 - accuracy: 0.82
```

Due to the smaller amount of training data, training happens even quicker than before.

Let's evaluate our model's performance after learning on 10% of the training data.

```
# Make predictions with the model trained on 10% of the data
model_7_pred_probs = model_7.predict(val_sentences)
model_7_pred_probs[:10]

array([[0.26274958],
       [0.8357978 ],
       [0.89284956],
       [0.34513992],
       [0.8134618 ],
       [0.8373141 ],
       [0.8959533 ],
       [0.9405368 ],
```

```

        [0.83913857],
        [0.0651088 ]], dtype=float32)

# Convert prediction probabilities to labels
model_7_preds = tf.squeeze(tf.round(model_7_pred_probs))
model_7_preds[:10]

<tf.Tensor: shape=(10,), dtype=float32, numpy=array([0., 1., 1., 0., 1., 1., 1., 1.,
# Calculate model results
model_7_results = calculate_results(val_labels, model_7_preds)
model_7_results

{'accuracy': 83.33333333333334,
 'f1': 0.8330353427819841,
 'precision': 0.8332273060924884,
 'recall': 0.8333333333333334}

# Compare to baseline
compare_baseline_to_new_results(baseline_results, model_7_results)

Baseline accuracy: 79.27, New accuracy: 83.33, Difference: 4.07
Baseline precision: 0.81, New precision: 0.83, Difference: 0.02
Baseline recall: 0.79, New recall: 0.83, Difference: 0.04
Baseline f1: 0.79, New f1: 0.83, Difference: 0.05

```

▼ TK - Comparing the performance of each of our models

Woah. We've come a long way! From training a baseline to several deep models.

Now it's time to compare our model's results.

But just before we do, it's worthwhile mentioning, this type of practice is a standard deep learning workflow. Training various different models, then comparing them to see which one performed best and continuing to train it if necessary.

The important thing to note is that for all of our modelling experiments we used the same training data (except for `model_7` where we used 10% of the training data).

To visualize our model's performances, let's create a pandas DataFrame with our results dictionaries and then plot it.

```

# Combine model results into a DataFrame
all_model_results = pd.DataFrame({"baseline": baseline_results,
                                  "simple_dense": model_1_results,
                                  "lstm": model_2_results,
                                  "gru": model_3_results,
                                  "bidirectional": model_4_results,
                                  "conv1d": model_5_results,
                                  "tf_hub_sentence_encoder": model_6_results,
                                  "tf_hub_10_percent_data": model_7_results})

all_model_results = all_model_results.transpose()


```

```
all_model_results = all_model_results.transpose()
all_model_results
```

	accuracy	precision	recall	f1
baseline	79.265092	0.811139	0.792651	0.786219
simple_dense	77.952756	0.781115	0.779528	0.777651
lstm	77.165354	0.776721	0.771654	0.768121
gru	77.690289	0.778187	0.776903	0.775124
bidirectional	76.771654	0.767737	0.767717	0.766597
conv1d	76.246719	0.762324	0.762467	0.761424
tf_hub_sentence_encoder	81.627297	0.819083	0.816273	0.814607
tf_hub_10_percent_data	83.333333	0.833227	0.833333	0.833035

```
# Reduce the accuracy to same scale as other metrics
all_model_results["accuracy"] = all_model_results["accuracy"]/100
```


```
# Plot and compare all of the model results
all_model_results.plot(kind="bar", figsize=(10, 7)).legend(bbox_to_anchor=(1.0, 1.0));
```



Looks like our pretrained USE TensorFlow Hub models have the best performance, even the one with only 10% of the training data seems to outperform the other models. This goes to show the power of transfer learning.

How about we drill down and get the F1-score's of each model?

```
# Sort model results by f1-score
all_model_results.sort_values("f1", ascending=False)["f1"].plot(kind="bar", figsize=(10, 7
```



Drilling down into a single metric we see our USE TensorFlow Hub models performing better than all of the other models. Interestingly, the baseline's F1-score isn't too far off the rest of the deeper models.

We can also visualize all of our model's training logs using TensorBoard.dev.

```
# # View tensorboard logs of transfer learning modelling experiments (should be 4 models)
# # Upload TensorBoard dev records
# !tensorboard dev upload --logdir ./model_logs \
#   --name "NLP modelling experiments" \
#   --description "A series of different NLP modellings experiments with various models" \
#   --one_shot # exits the uploader when upload has finished
```


The TensorBoard logs of the different modelling experiments we ran can be viewed here:

<https://tensorboard.dev/experiment/LkoAakb7QIKBZ0RL97cXbw/>

```
# If you need to remove previous experiments, you can do so using the following command
# !tensorboard dev delete --experiment_id EXPERIMENT_ID_TO_DELETE
```

▼ TK - Combining our models (model ensembling/stacking)

Many production systems use an **ensemble** (multiple different models combined) of models to make a prediction.

The idea behind model stacking is that if several uncorrelated models agree on a prediction, then the prediction must be more robust than a prediction made by a singular model.

The keyword in the sentence above is **uncorrelated**, which is another way of saying, different types of models. For example, in our case, we might combine our baseline, our bidirectional model and our TensorFlow Hub USE model.


Although these models are all trained on the same data, they all have a different way of finding patterns.

If we were to use three similarly trained models, such as three LSTM models, the predictions they output will likely be very similar.

Think of it as trying to decide where to eat with your friends. If you all have similar tastes, you'll probably all pick the same restaurant. But if you've all got different tastes and still end up picking the same restaurant, the restaurant must be good.

Since we're working with a classification problem, there are a few of ways we can combine our models:

1. **Averaging** - Take the output prediction probabilities of each model for each sample, combine them and then average them.
2. **Majority vote (mode)** - Make class predictions with each of your models on all samples, the predicted class is the one in majority. For example, if three different models predict [1, 0, 1] respectively, the majority class is 1, therefore, that would be the predicted label.
3. **Model stacking** - Take the outputs of each of your chosen models and use them as inputs to another model.

 **Resource:** The above methods for model stacking/ensembling were adapted from Chapter 6 of the [Machine Learning Engineering Book](#) by Andriy Burkov. If you're looking to enter the field of machine learning engineering, not only building models but production-scale machine learning systems, I'd highly recommend reading it in its entirety.

Again, the concept of model stacking is best seen in action.

We're going to combine our baseline model (`model_0`), LSTM model (`model_2`) and our USE model trained on the full training data (`model_6`) by averaging the combined prediction probabilities of each.

```
# Get mean pred probs for 3 models
baseline_pred_probs = np.max(model_0.predict_proba(val_sentences), axis=1) # get the predi
combined_pred_probs = baseline_pred_probs + tf.squeeze(model_2_pred_probs, axis=1) + tf.sq
combined_preds = tf.round(combined_pred_probs/3) # average and round the prediction probab
combined_preds[:20]

<tf.Tensor: shape=(20,), dtype=float32, numpy=
array([0., 1., 1., 0., 0., 1., 1., 1., 0., 0., 1., 0., 1., 0., 0., 0.,
       0., 0., 1.], dtype=float32)>
```

Wonderful! We've got a combined predictions array of different classes, let's evaluate them against the true labels and add our stacked model's results to our `all_model_results` DataFrame.

```
# Calculate results from averaging the prediction probabilities
ensemble_results = calculate_results(val_labels, combined_preds)
ensemble_results

{'accuracy': 79.52755905511812,
 'f1': 0.7939572894297304,
 'precision': 0.7962689279224713,
 'recall': 0.7952755905511811}


# Add our combined model's results to the results DataFrame
all_model_results.loc["ensemble_results"] = ensemble_results

# Convert the accuracy to the same scale as the rest of the results
all_model_results.loc["ensemble_results"]["accuracy"] = all_model_results.loc["ensemble_re

all_model_results
```

	accuracy	precision	recall	f1
baseline	0.792651	0.811139	0.792651	0.786219

How did the stacked model go against the other models?

 **Note:** It seems many of our model's results are similar. This may mean there are some limitations to what can be learned from our data. When many of your modelling experiments return similar results, it's a good idea to revisit your data, we'll do this shortly.

tf_hub_sentence_encoder	0.816273	0.819083	0.816273	0.814607
-------------------------	----------	----------	----------	----------

▼ TK - Saving and loading a trained model

Although training time didn't take very long, it's good practice to save your trained models to avoid having to retrain them.

Saving your models also enables you to export them for use elsewhere outside of your notebooks, such as in a web application.

There are two main ways of [saving a model in TensorFlow](#):

1. The HDF5 format.
2. The SavedModel format (default).

Let's take a look at both.

```
# Save TF Hub Sentence Encoder model to HDF5 format
model_6.save("model_6.h5")
```

If you save a model as a HDF5, when loading it back in, you need to let [TensorFlow know about any custom objects you've used](#) (e.g. components which aren't built from pure TensorFlow, such as TensorFlow Hub components).

```
# Load model with custom Hub Layer (required with HDF5 format)
loaded_model_6 = tf.keras.models.load_model("model_6.h5",
                                             custom_objects={"KerasLayer": hub.KerasLayer})
```

```
WARNING:tensorflow:5 out of the last 5 calls to <function recreate_function.<locals>
WARNING:tensorflow:5 out of the last 5 calls to <function recreate_function.<locals>
```

```
# How does our loaded model perform?
loaded_model_6.evaluate(val_sentences, val_labels)
```

```
24/24 [=====] - 1s 8ms/step - loss: 0.4279 - accuracy: 0.816
[0.42786261439323425, 0.8162729740142822]
```

Calling the `save()` method on our target model and passing it a filepath allows us to save our model in the `SavedModel` format.

```
# Save TF Hub Sentence Encoder model to SavedModel format (default)
model_6.save("model_6_SavedModel_format")

INFO:tensorflow:Assets written to: model_6_SavedModel_format/assets
INFO:tensorflow:Assets written to: model_6_SavedModel_format/assets
```

If you use `SavedModel` format (default), you can reload your model without specifying custom objects using the [`tensorflow.keras.models.load_model\(\)`](#) function.

```
# Load TF Hub Sentence Encoder SavedModel
loaded_model_6_SavedModel = tf.keras.models.load_model("model_6_SavedModel_format")

WARNING:tensorflow:6 out of the last 6 calls to <function recreate_function.<locals>>
WARNING:tensorflow:6 out of the last 6 calls to <function recreate_function.<locals>>

# Evaluate loaded SavedModel format
loaded_model_6_SavedModel.evaluate(val_sentences, val_labels)

24/24 [=====] - 1s 8ms/step - loss: 0.4279 - accuracy: 0.816
[0.42786261439323425, 0.8162729740142822]
```

As you can see saving and loading our model with either format results in the same performance.

 **Question:** Should you use the `SavedModel` format or `HDF5` format?

For most use cases, the `SavedModel` format will suffice. However, this is a TensorFlow specific standard. If you need a more general-purpose data standard, `HDF5` might be better. For more, check out the [TensorFlow documentation on saving and loading models](#).

▼ TK - Finding the most wrong examples

We mentioned before that if many of our modelling experiments are returning similar results, despite using different kinds of models, it's a good idea to return to the data and inspect why this might be.

One of the best ways to inspect your data is to sort your model's predictions and find the samples it got *most* wrong, meaning, what predictions had a high prediction probability but turned out to be wrong.

Once again, visualization is your friend. Visualize, visualize, visualize.

To make things visual, let's take our best performing model's prediction probabilities and classes along with the validation samples (text and ground truth labels) and combine them in a pandas DataFrame.

- If our best model still isn't perfect, what examples is it getting wrong?
- Which ones are the *most* wrong?
- Are there some labels which are wrong? E.g. the model gets it right but the ground truth label doesn't reflect this

```
# Create dataframe with validation sentences and best performing model predictions
val_df = pd.DataFrame({"text": val_sentences,
                       "target": val_labels,
                       "pred": model_6_preds,
                       "pred_prob": tf.squeeze(model_6_pred_probs)})
val_df.head()
```

	text	target	pred	pred_prob
0	DFR EP016 Monthly Meltdown - On Dnbheaven 2015...	0	0.0	0.223132
1	FedEx no longer to transport bioterror germs i...	0	1.0	0.828156
2	Gunmen kill four in El Salvador bus attack: Su...	1	1.0	0.986846
3	@camilacabello97 Internally and externally scr...	1	0.0	0.215614
4	Radiation emergency #preparedness starts with ...	1	1.0	0.727963

Oh yeah! Now let's find our model's wrong predictions (where `target != pred`) and sort them by their prediction probability (the `pred_prob` column).

```
# Find the wrong predictions and sort by prediction probabilities
most_wrong = val_df[val_df["target"] != val_df["pred"]].sort_values("pred_prob", ascending
most_wrong[:10]
```

	text	target	pred	pred_prob
759	FedEx will no longer transport bioterror patho	0	1 0	0.917414

Finally, we can write some code to visualize the sample text, truth label, prediction class and prediction probability. Because we've sorted our samples by prediction probability, viewing samples from the head of our `most_wrong` DataFrame will show us false positives.

A reminder:

- 0 = Not a real disaster Tweet
- 1 = Real disaster Tweet

555	@SonicLiberty557 all illuminated by the bright...	0	1.0	0.820524
-----	---	---	-----	----------

```
# Check the false positives (model predicted 1 when should've been 0)
for row in most_wrong[:10].itertuples(): # loop through the top 10 rows (change the index
_, text, target, pred, prob = row
print(f"Target: {target}, Pred: {int(pred)}, Prob: {prob}")
print(f"Text:\n{text}\n")
print("----\n")
```

```
Target: 0, Pred: 1, Prob: 0.9174144864082336
Text:
FedEx will no longer transport bioterror pathogens in wake of anthrax lab mishaps .
----
```

```
Target: 0, Pred: 1, Prob: 0.9145500659942627
Text:
? High Skies - Burning Buildings ? http://t.co/uVq41i3Kx2 #nowplaying
----
```

```
Target: 0, Pred: 1, Prob: 0.8587406277656555
Text:
@madonnamking RSPCA site multiple 7 story high rise buildings next to low density
----
```

```
Target: 0, Pred: 1, Prob: 0.8567568063735962
Text:
@noah_anyname That's where the concentration camps and mass murder come in.

EVERY. FUCKING. TIME.
----
```

```
Target: 0, Pred: 1, Prob: 0.8404760956764221
Text:
Ashes 2015: Australia's collapse at Trent Bridge among worst in history: England
----
```

```
Target: 0, Pred: 1, Prob: 0.8281557559967041
Text:
FedEx no longer to transport bioterror germs in wake of anthrax lab mishaps http://
----
```

Target: 0, Pred: 1, Prob: 0.8263236284255981

Text:

@SonofLiberty357 all illuminated by the brightly burning buildings all around the

Target: 0, Pred: 1, Prob: 0.8176058530807495

Text:

[55436] 1950 LIONEL TRAINS SMOKE LOCOMOTIVES WITH MAGNE-TRACTION INSTRUCTIONS <http>

Target: 0, Pred: 1, Prob: 0.8024678230285645

Text:

@AshGhebranious civil rights continued in the 60s. And what about trans-generation

Target: 0, Pred: 1, Prob: 0.785668671131134

Text:

We can view the bottom end of our `most_wrong` DataFrame to inspect false negatives (model predicts 0, not a real disaster Tweet, when it should've predicted 1, real disaster Tweet).

```
# Check the most wrong false negatives (model predicted 0 when should've predict 1)
for row in most_wrong[-10:].itertuples():
```

```
    _, text, target, pred, prob = row
```

```
    print(f"Target: {target}, Pred: {int(pred)}, Prob: {prob}")
```

```
    print(f"Text:\n{text}\n")
```

```
    print("----\n")
```

Target: 1, Pred: 0, Prob: 0.06116531044244766

Text:

'The way you move is like a full on rainstorm and I'm a house of cards'

Target: 1, Pred: 0, Prob: 0.056979626417160034

Text:

Lucas Duda is Ghost Rider. Not the Nic Cage version but an actual 'engulfed in flame'

Target: 1, Pred: 0, Prob: 0.05697683244943619

Text:

@DavidVonderhaar At least you were sincere ??

Target: 1, Pred: 0, Prob: 0.05442988872528076

Text:

@willienelson We need help! Horses will die!Please RT & sign petition!Take a s

Target: 1, Pred: 0, Prob: 0.04985428601503372

Text:

You can never escape me. Bullets don't harm me. Nothing harms me. But I know pain.

Target: 1, Pred: 0, Prob: 0.0436292327940464

Text:

I get to smoke my shit in peace

Target: 1, Pred: 0, Prob: 0.04113191366195679

Text:

Ron & Fez - Dave's High School Crush <https://t.co/aN3W16c8F6> via @YouTube

Target: 1, Pred: 0, Prob: 0.04028240218758583

Text:

Why are you deluged with low self-image? Take the quiz: <http://t.co/XsPqdOrIqj>. <http://t.co/XsPqdOrIqj>

Target: 1, Pred: 0, Prob: 0.037921249866485596

Text:

Reddit Will Now Quarantine? <http://t.co/pkUAMXw6pm> #onlinecommunities #reddit #ai

Target: 1, Pred: 0, Prob: 0.03653673082590103

Text:

@SoonerMagic_ I mean I'm a fan but I don't need a girl sounding off like a damn si

Do you notice anything interesting about the most wrong samples?

Are the ground truth labels correct? What do you think would happen if we went back and corrected the labels which aren't?

▼ TK - Making predictions on the test dataset

Alright we've seen how our model's perform on the validation set.

But how about the test dataset?

We don't have labels for the test dataset so we're going to have to make some predictions and inspect them for ourselves.

Let's write some code to make predictions on random samples from the test dataset and visualize them.

```
# Making predictions on the test dataset
test_sentences = test_df["text"].to_list()
test_samples = random.sample(test_sentences, 10)
for test_sample in test_samples:
    pred_prob = tf.squeeze(model_6.predict([test_sample])) # has to be list
```



```
pred = tf.round(pred_prob)
print(f"Pred: {int(pred)}, Prob: {pred_prob}")
print(f"Text:\n{test_sample}\n")
print("----\n")
```

Pred: 0, Prob: 0.33723971247673035

Text:

02 03 04 05 AVALANCHE 1500 REAR AXLE ASSEMBLY 2055271 <http://t.co/VxZhZsAlra> <http://t.co/VxZhZsAlra>

Pred: 1, Prob: 0.8898343443870544

Text:

Here's a quick timelapse I made of the Finger Rock Fire last night from about 9PM

Pred: 0, Prob: 0.4341371953487396

Text:

Sun_OfGod: Breaking news! Unconfirmed! I just heard a loud bang nearby. in what ap

Pred: 0, Prob: 0.20915700495243073

Text:

They can only ban SAFE abortions- back alley tragedy will come back. USA is NOT a

Pred: 1, Prob: 0.5870816111564636

Text:

Texian Iliad: A Military History of the Texas Revolution by Hardin Stephen L. <http://www.texasrevolution.com/>

Pred: 0, Prob: 0.08807205408811569

Text:

I'd love to see a nigga try and diss the King haha he would OBLITERATE THEM. With

Pred: 0, Prob: 0.16543787717819214

Text:

@ChelseaVPeretti's bit on @meltdown_show was also gold.

Pred: 0, Prob: 0.2548377513885498

Text:

was that thunder?

Pred: 0, Prob: 0.3722120225429535

Text:

Is This Country Latin America's Next 'Argentina': One week ago we reported on the (

Pred: 0, Prob: 0.04841297119855881

Text:

@ERPESTAR i aint a bitch girl popobawa revolves around you the cyclone

How do our model's predictions look on the test dataset?

It's important to do these kind of visualization checks as often as possible to get a glance of how your model performs on unseen data and subsequently how it might perform on the real test: Tweets from the wild.

▼ Predicting on Tweets from the wild

How about we find some Tweets and use our model to predict whether or not they're about a disaster or not?

To start, let's take one of my own [Tweets on living life like an ensemble model](#).

```
# Turn Tweet into string
daniels_tweet = "Life like an ensemble: take the best choices from others and make your ow
```

Now we'll write a small function to take a model and an example sentence and return a prediction.

```
def predict_on_sentence(model, sentence):
    """
    Uses model to make a prediction on sentence.

    Returns the sentence, the predicted label and the prediction probability.
    """
    pred_prob = model.predict([sentence])
    pred_label = tf.squeeze(tf.round(pred_prob)).numpy()
    print(f"Pred: {pred_label}", "(real disaster)" if pred_label > 0 else "(not real disaste
    print(f"Text:\n{sentence}")
```

Great! Time to test our model out.

```
# Make a prediction on Tweet from the wild
predict_on_sentence(model=model_6, # use the USE model
                    sentence=daniels_tweet)

Pred: 0.0 (not real disaster) Prob: 0.06137441471219063
Text:
Life like an ensemble: take the best choices from others and make your own
```

Woohoo! Our model predicted correctly. My Tweet wasn't about a disaster.

How about we find a few Tweets about actual disasters?

Such as the following two Tweets about the 2020 Beirut explosions.

```
# Source - https://twitter.com/BeirutCityGuide/status/1290696551376007168
beirut_tweet_1 = "Reports that the smoke in Beirut sky contains nitric acid, which is toxic"

# Source - https://twitter.com/BeirutCityGuide/status/1290773498743476224
beirut_tweet_2 = "#Beirut declared a “devastated city”, two-week state of emergency officially declared"
```


```
# Predict on disaster Tweet 1
predict_on_sentence(model=model_6,
                    sentence=beirut_tweet_1)

Pred: 1.0 (real disaster) Prob: 0.9640411734580994
Text:
Reports that the smoke in Beirut sky contains nitric acid, which is toxic. Please share
```

```
# Predict on disaster Tweet 2
predict_on_sentence(model=model_6,
                    sentence=beirut_tweet_2)

Pred: 1.0 (real disaster) Prob: 0.9739863276481628
Text:
#Beirut declared a “devastated city”, two-week state of emergency officially declared
```

Looks like our model is performing as expected, predicting both of the disaster Tweets as actual disasters.

 **Note:** The above examples are cherry-picked and are cases where you'd expect a model to function at high performance. For actual production systems, you'll want to continually perform tests to see how your model is performing.

▼ TK - The speed/score tradeoff

One of the final tests we're going to do is to find the speed/score tradeoffs between our best model and baseline model.

Why is this important?

Although it can be tempting to just choose the best performing model you find through experimentation, this model might not actually work in a production setting.

Put it this way, imagine you're Twitter and receive 1 million Tweets per hour (this is a made up number, the actual number is much higher). And you're trying to build a disaster detection system to read Tweets and alert authorities with details about a disaster in close to real-time.

Compute power isn't free so you're limited to a single compute machine for the project. On that machine, one of your models makes 10,000 predictions per second at 80% accuracy where as

another one of your models (a larger model) makes 100 predictions per second at 85% accuracy.

Which model do you choose?

Is the second model's performance boost worth missing out on the extra capacity?

Of course, there are many options you could try here, such as sending as many Tweets as possible to the first model and then sending the ones which the model is least certain of to the second model.

The point here is to illustrate the best model you find through experimentation, might not be the model you end up using in production.

To make this more concrete, let's write a function to take a model and a number of samples and time how long the given model takes to make predictions on those samples.

```
# Calculate the time of predictions
import time
def pred_timer(model, samples):
    """
    Times how long a model takes to make predictions on samples.

    Args:
    ----
    model = a trained model
    sample = a list of samples

    Returns:
    ----
    total_time = total elapsed time for model to make predictions on samples
    time_per_pred = time in seconds per single sample
    """
    start_time = time.perf_counter() # get start time
    model.predict(samples) # make predictions
    end_time = time.perf_counter() # get finish time
    total_time = end_time-start_time # calculate how long predictions took to make
    time_per_pred = total_time/len(val_sentences) # find prediction time per sample
    return total_time, time_per_pred
```

Looking good!

Now let's use our `pred_timer()` function to evaluate the prediction times of our best performing model (`model_6`) and our baseline model (`model_0`).

```
# Calculate TF Hub Sentence Encoder prediction times
model_6_total_pred_time, model_6_time_per_pred = pred_timer(model_6, val_sentences)
model_6_total_pred_time, model_6_time_per_pred

(0.21601832200008175, 0.00028348861154866374)

# Calculate Naive Bayes prediction times
baseline_total_pred_time, baseline_time_per_pred = pred_timer(model_0, val_sentences)
```


```
baseline_total_pred_time, baseline_time_per_pred  
  
(0.018003535000048032, 2.362668635176907e-05)
```


It seems with our current hardware (in my case, I'm using a Google Colab notebook) our best performing model takes over 10x the time to make predictions as our baseline model.

Is that extra prediction time worth it?

Let's compare time per prediction versus our model's F1-scores.

```
import matplotlib.pyplot as plt  
  
plt.figure(figsize=(10, 7))  
plt.scatter(baseline_time_per_pred, baseline_results["f1"], label="baseline")  
plt.scatter(model_6_time_per_pred, model_6_results["f1"], label="tf_hub_sentence_encoder")  
plt.legend()  
plt.title("F1-score versus time per prediction")  
plt.xlabel("Time per prediction")  
plt.ylabel("F1-Score");
```





Ideal position for speed and performance tradeoff model (fast predictions with great results).

Of course, the ideal position for each of these dots is to be in the top left of the plot (low time per prediction, high F1-score).

In our case, there's a clear tradeoff for time per prediction and performance. Our best performing model takes an order of magnitude longer per prediction but only results in a few F1-score point increase.

This kind of tradeoff is something you'll need to keep in mind when incorporating machine learning models into your own applications.

✂ Exercises

1. Rebuild, compile and train `model_1`, `model_2` and `model_5` using the [Keras Sequential API](#) instead of the Functional API.
2. Retrain the baseline model with 10% of the training data. How does perform compared to the Universal Sentence Encoder model with 10% of the training data?
3. Try fine-tuning the TF Hub Universal Sentence Encoder model by setting `training=True` when instantiating it as a Keras layer.

```
# We can use this encoding layer in place of our text_vectorizer and embedding layer
sentence_encoder_layer = hub.KerasLayer("https://tfhub.dev/google/universal-sentence-encoder/4",
                                         input_shape=[],
                                         dtype=tf.string,
                                         trainable=True) # turn training on to fine-tune the Tensor
```

4. Retrain the best model you've got so far on the whole training set (no validation split). Then use this trained model to make predictions on the test dataset and format the predictions into the same format as the `sample_submission.csv` file from Kaggle (see the Files tab in Colab for what the `sample_submission.csv` file looks like). Once you've done this, [make a submission to the Kaggle competition](#), how did your model perform?
5. Combine the ensemble predictions using the majority vote (mode), how does this perform compare to averaging the prediction probabilities of each model?
6. Make a confusion matrix with the best performing model's predictions on the validation set and the validation ground truth labels.

▼ Extra-curriculum

To practice what you've learned, a good idea would be to spend an hour on 3 of the following (3-hours total, you could through them all if you want) and then write a blog post about what you've learned.

- For an overview of the different problems within NLP and how to solve them read through:
 - [A Simple Introduction to Natural Language Processing](#)
 - [How to solve 90% of NLP problems: a step-by-step guide](#)
- Go through [MIT's Recurrent Neural Networks lecture](#). This will be one of the greatest additions to what's happening behind the RNN model's you've been building.
- Read through the [word embeddings page on the TensorFlow website](#). Embeddings are such a large part of NLP. We've covered them throughout this notebook but extra practice would be well worth it. A good exercise would be to write out all the code in the guide in a new notebook.
- For more on RNN's in TensorFlow, read and reproduce [the TensorFlow RNN guide](#). We've covered many of the concepts in this guide, but it's worth writing the code again for yourself.
- Text data doesn't always come in a nice package like the data we've downloaded. So if you're after more on preparing different text sources for being with your TensorFlow deep learning models, it's worth checking out the following:
 - [TensorFlow text loading tutorial](#).
 - [Reading text files with Python](#) by Real Python.
- This notebook has focused on writing NLP code. For a mathematically rich overview of how NLP with Deep Learning happens, read [Stanford's Natural Language Processing with Deep Learning lecture notes Part 1](#).
 - For an even deeper dive, you could even do the whole [CS224n](#) (Natural Language Processing with Deep Learning) course.
- Great blog posts to read:

- Andrei Karpathy's [The Unreasonable Effectiveness of RNNs](#) dives into generating Shakespeare text with RNNs.
- [Text Classification with NLP: Tf-Idf vs Word2Vec vs BERT](#) by Mauro Di Pietro. An overview of different techniques for turning text into numbers and then classifying it.
- [What are word embeddings?](#) by Machine Learning Mastery.
- Other topics worth looking into:
 - [Attention mechanisms](#). These are a foundational component of the transformer architecture and also often add improvements to deep NLP models.
 - [Transformer architectures](#). This model architecture has recently taken the NLP world by storm, achieving state of the art on many benchmarks. However, it does take a little more processing to get off the ground, the [HuggingFace Transformers library](#) is probably your best quick start.

 **Resource:** See the full set of course materials on GitHub:

<https://github.com/mrdbourke/tensorflow-deep-learning>