Google BigQuery

Dataset: blockchain_analytics_ethereum_mainnet_us

Tabels: token_transfers & transactions

Field name	Description	Original Table
block_hash	Hash of the block this event was emitted from.	token_transfers & transactions
block_number	Number of the block this event was emitted from.	token_transfers & transactions
block_timestamp	Unix timestamp when the block was added to the blockchain	token_transfers & transactions
transaction_hash	Hash of the transaction this event was emitted from.	token_transfers & transactions
transaction_index	The transaction's index position in the block.	token_transfers & transactions
event_index	The event's index position in the block.	token_transfers
batch_index	The transfer's position in the batch transfer event.	token_transfers
address	Address from which this event originated.	token_transfers
event_type	Token standard that matches the event.	token_transfers
event_hash	Keccak hash of the event signature.	token_transfers
event_signature	Function signature of the event.	token_transfers
operator_address	Address of the transfer operator.	token_transfers
from_address	Address of the previous owner of the token(s).	token_transfers
to_address	Address of the new owner of the token(s).	token_transfers
token_id	Identifier of the token(s) being transferred.	token_transfers
quantity	Quantity of tokens being transferred.	token_transfers
removed	Whether or not the event was orphaned off the main chain.	token_transfers
nonce_tx	Number of transactions made by the sender prior to this one.	transactions
from_address_tx	Address of the sender of the transaction.	transactions
to_address_tx	Address of the receiver of the transaction.	transactions
value_tx	Value transferred in Wei. A decimal number represented as a BIGNUMERIC to preserve up to 128-bit numeric precision.	transactions
value_lossless_tx	Value transferred in Wei. A decimal number represented in STRING format to preserve full 256-bit numeric precision.	transactions

gas_tx	Quantity of gas units provided by the sender of the transaction.	transactions
gas_price_tx	Price per gas unit provided by the sender of the transaction in Wei.	transactions
input_tx	Data sent along with the transaction, with a maximum size of 32 bytes.	transactions
max_fee_per_gas_tx	Maximum fee per unit of gas for this transaction.	transactions
max_priority_fee_per_gas_tx	Maximum priority fee per unit of gas for this transaction.	transactions
type_tx	Type of the transaction.	transactions
chain_id_tx	Chain ID used in transaction signing.	transactions
access_list_tx	List of addresses and storage keys that the transaction plans to access and has pre-paid gas for.	transactions
r_tx	ECDSA signature r.	transactions
s_tx	ECDSA signature s.	transactions
v_tx	ECDSA signature v.	transactions
y_parity_tx	ECDSA signature y_parity.	transactions
is_token_transfer	Indicates whether the row represents a token transfer or a non-token transaction	