

HORN SPEAKERS

AL-20FR

20 W, 100 V line, fire resistant round horn speaker.
Suitable for VA installations, for indoor and outdoor using (IP66 protection degree).
Provided with a power selection switch allowing the most suitable power in each installation.
Finished in aluminium and FR ABS.
Universal U-shaped metal mounting bracket.



RMS power	20 W
Power selection	20 W, 15 W, 10 W & 5 W
Impedance	500 Ω , 670 Ω , 1 k Ω & 2 k Ω
Sensitivity	108,5 dB SPL at 1 W, 1 m & 1 kHz
Acoustic pressure	121,5 dB SPL at 20 W, 1 m & 1 kHz
Radiation angle	80°
Frequency response	250 ~ 10.000 Hz
Dimensions (mm)	Ø 269 x 310 (length)
Power selector	Rotating switch
Protection degree	IP 66 (IEC-529)
Weight	2,2 kg
Finishing	Horn: aluminium Horn & rear cover: FR ABS
Colour	Horn: white Horn & rear cover: light grey
Accessories	Orientable U-shaped mounting bracketed Plastic parts: FR ABS (fire resistant)
FR features	100 V line cable and internal cabling: fire resistant material 100 V transformer equipped with a thermal protection switch. Activation at 110° C