



PARALLEL COMPUTING WITH DASK

Using Dask DataFrames

Dhavide Aruliah

Director of Training, Anaconda

Reading CSV

```
In [1]: import dask.dataframe as dd
```

- `dd.read_csv()` function
 - Accepts single filename or *glob* pattern (using wildcard `*`)
 - Does not read file immediately (*lazy evaluation*)
 - File(s) need not fit in memory

Reading Multiple CSV Files

```
In [2]: %ls
quarter1.csv  quarter2.csv  quarter3.csv  quarter4.csv
```

```
In [3]: transactions = dd.read_csv('*.csv')
```

```
In [4]: transactions.head()
```

```
Out[4]:
```

	id	names	amount	date
0	131	Norbert	-1159	2016-01-01
1	342	Jerry	1149	2016-01-01
2	485	Dan	1380	2016-01-01
3	513	Xavier	1555	2016-01-02
4	849	Michael	363	2016-01-02

```
In [5]: transactions.tail()
```

```
Out[5]:
```

	id	names	amount	date
195	838	Wendy	87	2016-12-28
196	915	Bob	852	2016-12-30
197	749	Patricia	1741	2016-12-31
198	743	Michael	1191	2016-12-31
199	889	Wendy	336	2016-12-31

Building Delayed Pipelines

```
In [6]: is_wendy = (transactions['names'] == 'Wendy')


In [7]: wendy_amounts = transactions.loc[is_wendy, 'amount']

In [8]: wendy_amounts
Out[8]:
Dask Series Structure:
npartitions=4
None      int64
None      ...
None      ...
None      ...
None      ...
Name: amount, dtype: int64
Dask Name: loc-series, 24 tasks

In [9]: wendy_diff = wendy_amounts.sum()

In [10]: wendy_diff
Out[10]: dd.Scalar<series-..., dtype=int64>

In [11]: wendy_diff.visualize(rankdir='LR')
```



Compatibility with Pandas API

Unavailable in `dask.dataframe`:

- some unsupported file formats (e.g., `.xls`, `.zip`, `.gz`)
- sorting

Available in `dask.dataframe`:

- indexing, selection, & reindexing
- aggregations: `.sum()`, `.mean()`, `.std()`, `.min()`, `.max()` **etc.**
- grouping with `.groupby()`
- datetime conversion with `dd.to_datetime()`



PARALLEL COMPUTING WITH DASK

Let's practice!



PARALLEL COMPUTING WITH DASK

Timing DataFrame Operations

Dhavid Aruliah

Director of Training, Anaconda

How Big is Big Data?

Data size M	Required hardware
$M < 8 \text{ GB}$	RAM (single machine)
$8 \text{ GB} < M < 10 \text{ TB}$	hard disk (single machine)
$M > 10 \text{ TB}$:	<i>specialized hardware</i>

Two key questions:

- Data fits in RAM (random access memory)?
- Data fits on hard disk?



Taxi CSV Files

```
In [1]: %ll -h yellow_tripdata_2015-*.csv
-rw-r--r-- 1 user staff 1.8G 31 Jul 16:43 yellow_tripdata_2015-01.csv
-rw-r--r-- 1 user staff 1.8G 31 Jul 16:43 yellow_tripdata_2015-02.csv
-rw-r--r-- 1 user staff 1.9G 31 Jul 16:43 yellow_tripdata_2015-03.csv
-rw-r--r-- 1 user staff 1.9G 31 Jul 16:43 yellow_tripdata_2015-04.csv
-rw-r--r-- 1 user staff 1.9G 31 Jul 16:43 yellow_tripdata_2015-05.csv
-rw-r--r-- 1 user staff 1.8G 31 Jul 16:43 yellow_tripdata_2015-06.csv
-rw-r--r-- 1 user staff 1.7G 31 Jul 16:43 yellow_tripdata_2015-07.csv
-rw-r--r-- 1 user staff 1.6G 31 Jul 16:43 yellow_tripdata_2015-08.csv
-rw-r--r-- 1 user staff 1.6G 31 Jul 16:43 yellow_tripdata_2015-09.csv
-rw-r--r-- 1 user staff 1.8G 31 Jul 16:43 yellow_tripdata_2015-10.csv
-rw-r--r-- 1 user staff 1.7G 31 Jul 16:43 yellow_tripdata_2015-11.csv
-rw-r--r-- 1 user staff 1.7G 31 Jul 16:43 yellow_tripdata_2015-12.csv
```

Timing I/O & Computation: Pandas

```
In [2]: import time, pandas as pd
```

```
In [3]: t_start = time.time(); \
...: df = pd.read_csv('yellow_tripdata_2015-01.csv'); \
...: t_end = time.time(); \
...: print('pd.read_csv(): {} s'.format(t_end-t_start)) # time [s]
```

```
Out[3]:
pd.read_csv: 43.820565938949585 s
```

```
In [4]: t_start = time.time(); \
...: m = df['trip_distance'].mean(); \
...: t_end = time.time(); \
...: print('.mean(): {} ms'.format((t_end-t_start)*1000)) # time [ms]
```

```
Out[4]:
.mean(): 17.752885818481445 ms
```

Timing I/O & Computation: Dask

```
In [5]: import dask.dataframe as dd, time
```

```
In [6]: t_start = time.time();\  
....: df = dd.read_csv('yellow_tripdata_2015-*.csv');\  
....: t_end = time.time();\  
....: print('dd.read_csv: {} ms'.format((t_end-t_start)*1000)) # time [ms]
```

```
Out[6]:  
dd.read_csv: 404.7999382019043 ms
```

```
In [7]: t_start = time.time();\  
....: m = df['trip_distance'].mean();\  
....: t_end = time.time();\  
....: print('.mean(): {} ms'.format((t_end-t_start)*1000)) # time [ms]
```

```
Out[7]:  
.mean(): 2.289295196533203 ms
```

```
In [8]: t_start = time.time(); \  
....: result = m.compute(); \  
....: t_end = time.time(); \  
....: print('.compute(): {} min'.format((t_end-t_start)/60)) # time [min]
```

```
Out[8]:  
.compute(): 3.4004417498906454 min
```



Timing in the IPython Shell

```
In [9]: m = df['trip_distance'].mean()
```

```
In [10]: %time result = m.compute()
```

```
CPU times: user 9min 50s, sys: 1min 16s, total: 11min 7s
```

```
Wall time: 3min 1s
```



Is Dask or Pandas Appropriate?

- How big is dataset?
- How much RAM available?
- How many threads/cores/CPU's available?
- Are Pandas computations/formats supported in Dask API?
- Is computation *I/O-bound* (disk-intensive) or *CPU-bound* (processor intensive)?

Best use case for Dask

- Computations from Pandas API available in Dask
- Problem size close to limits of RAM, fits on disk



PARALLEL COMPUTING WITH DASK

Let's practice!



PARALLEL COMPUTING WITH DASK

Analyzing NYC Taxi Rides

Dhavide Aruliah

Director of Training, Anaconda



The New York Taxi Dataset



Taxi CSV Files

```
In [1]: %ll -h yellow_tripdata_2015-*.csv
-rw-r--r-- 1 user staff 1.8G 31 Jul 16:43 yellow_tripdata_2015-01.csv
-rw-r--r-- 1 user staff 1.8G 31 Jul 16:43 yellow_tripdata_2015-02.csv
-rw-r--r-- 1 user staff 1.9G 31 Jul 16:43 yellow_tripdata_2015-03.csv
-rw-r--r-- 1 user staff 1.9G 31 Jul 16:43 yellow_tripdata_2015-04.csv
-rw-r--r-- 1 user staff 1.9G 31 Jul 16:43 yellow_tripdata_2015-05.csv
-rw-r--r-- 1 user staff 1.8G 31 Jul 16:43 yellow_tripdata_2015-06.csv
-rw-r--r-- 1 user staff 1.7G 31 Jul 16:43 yellow_tripdata_2015-07.csv
-rw-r--r-- 1 user staff 1.6G 31 Jul 16:43 yellow_tripdata_2015-08.csv
-rw-r--r-- 1 user staff 1.6G 31 Jul 16:43 yellow_tripdata_2015-09.csv
-rw-r--r-- 1 user staff 1.8G 31 Jul 16:43 yellow_tripdata_2015-10.csv
-rw-r--r-- 1 user staff 1.7G 31 Jul 16:43 yellow_tripdata_2015-11.csv
-rw-r--r-- 1 user staff 1.7G 31 Jul 16:43 yellow_tripdata_2015-12.csv
```

- Exercises use smaller files...

Taxi Data Features

```
In [2]: import pandas as pd
```

```
In [3]: df = pd.read_csv('yellow_tripdata_2015-01.csv')
```

```
In [4]: df.shape
```

```
Out[4]: (12748986, 19)
```

```
In [5]: df.columns
```

```
Out[5]:
```

```
Index(['VendorID', 'tpep_pickup_datetime', 'tpep_dropoff_datetime',  
      'passenger_count', 'trip_distance', 'pickup_longitude',  
      'pickup_latitude', 'RateCodeID', 'store_and_fwd_flag',  
      'dropoff_longitude', 'dropoff_latitude', 'payment_type', 'fare_amount',  
      'extra', 'mta_tax', 'tip_amount', 'tolls_amount',  
      'improvement_surcharge', 'total_amount'],  
      dtype='object')
```

Amount Paid

- How much was each ride?
 - `fare_amount`: cost of ride
 - `tolls_amount`: charges for toll roads
 - `extra`: additional charges
 - `tip_amount`: amount tipped (credit cards only)
 - `total_amount`: total amount paid by passenger





Payment type

```
In [6]: df['payment_type'].value_counts()
```

```
Out[6]:
```

```
1    7881388
```

```
2    4816992
```

```
3     38632
```

```
4     11972
```

```
5         2
```

```
Name: payment_type, dtype: int64
```



PARALLEL COMPUTING WITH DASK

Let's practice!