# What pitch is a growling stomach? A unified multi-mode acoustic model of borborygmi

Jonathan Mace[1,*], Brian R. Mace[2]

[1]Microsoft Research, Redmond, WA, United States

[2]Acoustics Research Centre, Department of Mechanical and Mechatronics Engineering, University of Auckland, Aucklar

[*]Corresponding author: jonathanmace@microsoft.com

**Abstract**

Borborygmi—the rumbling and gurgling sounds of the gastrointestinal tract—arise from oscillation of gas pockets entrained in intestinal fluid. Despite their clinical significance as indicators of gut motility, no first-principles acoustic model predicts their frequency spectrum from measurable anatomical parameters. We present a unified analytical framework comprising four resonance mechanisms: (i) tissue-constrained bubble resonance incorporating intestinal wall elasticity (which reduces to the classical Minnaert frequency in the limit of vanishing wall stiffness), (ii) Helmholtz resonance through peristaltic constrictions, (iii) axial piston modes of cylindrical gas slugs, and (iv) radial breathing modes of gas columns in elastic tubes. The constrained bubble model predicts frequencies of 135 Hz to 440 Hz for gas pocket volumes of 1 mL to 50 mL, overlapping the clinically observed 200 Hz to 550 Hz band for healthy adults without curve-fitting. A mode-transition map identifies which resonance mechanism dominates in each region of the volume–geometry parameter space. The framework provides a physics-based tool for interpreting auscultatory findings and designing acoustic monitoring systems for gastrointestinal motility assessment.

**Keywords:** borborygmi, bowel sounds, Minnaert resonance, bubble acoustics, gastrointestinal acoustics, Helmholtz resonator

## 1 Introduction

Few acoustic phenomena are as universally experienced yet as poorly understood as the sounds of the gastrointestinal tract. Borborygmi—the medical term for stomach and intestinal gurgling—have been documented since at least Cannon's Cannon [1905] pioneering auscultation studies, and their clinical significance as indicators of gut motility, obstruction, and post-operative recovery is well established Ching and Tan [2012], Craine et al. [1999], Dalle Donne et al. [2024]. Despite this long history, clinical assessment of bowel sounds remains largely qualitative: present or absent, normoactive or hyperactive, high-pitched or low-pitched.

The past two decades have seen growing interest in quantitative bowel sound analysis. Craine et al. Craine et al. [1999, 2002] developed computerised auscultation systems and reported spectral

differences between normal and obstructed bowel. Ching and Tan Ching and Tan [2012] performed spectral analysis using electronic stethoscopes and documented that healthy bowel sounds occupy a band of approximately 200 Hz to 550 Hz with a peak near 340 Hz, while intestinal obstruction shifts the spectrum in condition-specific ways. More recently, Nowak et al. Nowak et al. [2021] reviewed automated bowel sound analysis using machine learning classifiers, and Dalle Donne et al. Dalle Donne et al. [2024] surveyed wearable monitoring systems. These approaches treat bowel sounds as signals to be classified, but offer no predictive model explaining *why* particular frequencies appear.

The physics of bubble acoustics, by contrast, is mature. The classical result of Minnaert Minnaert [1933] for the resonant frequency of a spherical gas bubble in an incompressible fluid remains the starting point for underwater and biomedical acoustics alike Leighton [1994]. Church Church [1995] extended the theory to bubbles encapsulated in elastic shells—primarily for ultrasound contrast agents—and Hoff Hoff [2001] provided a comprehensive treatment of coated bubble dynamics. Li et al. Li et al. [2022] recently derived rigorous Minnaert corrections for bubbles in soft elastic media, while Ammari et al. Ammari et al. [2018] analysed bubbly media from a mathematical perspective. None of these works, however, has been applied to the specific geometry, material properties, and clinical context of the gastrointestinal tract.

We bridge this gap. In this paper we present a unified analytical framework in which intestinal gas pockets are modelled as acoustically resonant systems, with four principal mechanisms (the classical Minnaert frequency arising as a limiting case of the constrained bubble model) producing frequencies that overlap the clinically observed spectrum. The model requires no fitted parameters: all inputs are measurable anatomical and material properties—gas pocket volume, intestinal wall stiffness, lumen diameter, and constriction geometry—drawn from published literature or standard anatomical measurements. The tissue-constrained bubble mechanism was first analysed in the context of abdominal resonance by Mace et al. [2026], whose constrained-bubble formulation we extend here to the intestinal geometry. The tissue-constrained bubble model, which augments the Minnaert formula with elastic wall stiffness and inertia, captures much of the healthy bowel sound band of 200 Hz to 550 Hz for pocket volumes of 1 mL to 50 mL, specifically the 200 Hz to 440 Hz sub-band. Frequencies above 440 Hz likely require sub-millilitre pockets or Helmholtz contributions. A mode-transition map reveals which resonance mechanism dominates in each region of the volume–diameter parameter space, providing physical insight for interpreting auscultatory findings.

# 2 Theory

We model a gas pocket of volume $V$ trapped within the fluid-filled lumen of the intestinal tract. The pocket is surrounded by incompressible intestinal fluid of density $\rho_f = 1020\,\mathrm{kg/m^3}$ and confined by an elastic intestinal wall of Young's modulus $E$, Poisson's ratio $\nu$, thickness $h$, and density $\rho_w$. Four primary resonance mechanisms are considered, each corresponding to a distinct physical geometry and oscillation pattern; the classical Minnaert frequency is recovered as a limiting case of the constrained bubble model (Sec. 2.2). Table 1 summarises the canonical parameter values used throughout.

Table 1: Canonical parameter values for the borborygmi model.

| Parameter | Symbol | Value | Unit |
|---|---|---|---|
| Gas adiabatic exponent | $\gamma$ | 1.4 | — |
| Atmospheric pressure | $P_{\text{atm}}$ | 101,325 | Pa |
| Intra-abdominal pressure | $P_{\text{iap}}$ | 1,000 | Pa |
| Ambient pressure | $P_0$ | 102,325 | Pa |
| Intestinal fluid density | $\rho_f$ | 1,020 | kg/m$^3$ |
| Intestinal wall modulus | $E$ | 10 | kPa |
| Wall Poisson's ratio | $\nu$ | 0.45 | — |
| Wall thickness | $h$ | 3.0 | mm |
| Wall density | $\rho_w$ | 1,040 | kg/m$^3$ |
| Lumen diameter | $d$ | 30 | mm |
| Gas sound speed | $c_g$ | 343[a] | m/s |
| Neck diameter (Helmholtz) | $d_n$ | 5 | mm |
| Neck length (Helmholtz) | $L_n$ | 10 | mm |
| Loss tangent | $\eta$ | 0.25 | — |

[a]Room-temperature value; air at 37 °C gives $c_g \approx 353$ m/s, a ∼3% difference that affects only the Helmholtz mode and is smaller than the parametric uncertainty.

## 2.1 Free Minnaert bubble

The classical Minnaert frequency Minnaert [1933] for radial pulsation of a spherical gas bubble of radius $R$ in an unbounded incompressible fluid is

$$f_M = \frac{1}{2\pi R}\sqrt{\frac{3\gamma P_0}{\rho_f}}, \tag{1}$$

where $\gamma$ is the polytropic exponent, $P_0$ is the ambient pressure, and $\rho_f$ is the fluid density. The equivalent spherical radius is related to the pocket volume $V$ by $R = (3V/4\pi)^{1/3}$. For a 10 mL pocket ($R = 13.4$ mm) in intestinal fluid at body temperature, Eq. (1) gives $f_M = 244$ Hz.

The Minnaert frequency provides a useful baseline but neglects the elastic constraint of the surrounding intestinal wall. For a bubble suspended in free fluid this is appropriate; for a gas pocket enclosed within the gut, it is not.

## 2.2 Tissue-constrained bubble

The intestinal wall wrapping the gas pocket contributes both elastic stiffness and inertia. Following the approach of Church Church [1995] for encapsulated bubbles, we model the wall as a thin elastic shell of thickness $h$ concentric with the spherical gas pocket. The restoring force per unit surface area per unit radial displacement comprises a gas compressibility term and a wall elasticity term:

$$k_{\text{gas}} = \frac{3\gamma P_0}{R}, \qquad k_{\text{wall}} = \frac{2Eh}{R^2(1-\nu)}, \tag{2}$$

where $E$ and $\nu$ are the wall Young's modulus and Poisson's ratio, respectively. The effective inertia per unit area consists of the radiation added mass of the surrounding fluid and the shell mass:

$$m_{\text{fluid}} = \rho_f R, \qquad m_{\text{wall}} = \rho_w h. \tag{3}$$

The undamped natural frequency is then

$$f_c = \frac{1}{2\pi}\sqrt{\frac{k_{\text{gas}} + k_{\text{wall}}}{m_{\text{fluid}} + m_{\text{wall}}}}. \tag{4}$$

In the limit $E \to 0$ and $h \to 0$, the wall contributions vanish and Eq. (4) reduces exactly to the Minnaert result, Eq. (1). We have verified this reduction both analytically and numerically.

For the soft intestinal wall ($E = 10\,\text{kPa}$, $h = 3\,\text{mm}$, $\rho_w = 1040\,\text{kg/m}^3$), wall inertia $m_{\text{wall}}$ dominates over wall stiffness $k_{\text{wall}}$, and the constrained frequency is *lower* than the free Minnaert value. At 10 mL, $f_c = 223\,\text{Hz}$ compared with $f_M = 244\,\text{Hz}$—the wall adds mass without proportionate stiffness. This physically intuitive result (the gut wall is heavy and compliant) means the constrained model shifts predictions *towards* the lower end of the clinical band, improving agreement.

Damping is introduced through the loss tangent $\eta$ of the wall material, giving a quality factor $Q = 1/(2\zeta) = 1/\eta = 4.0$ and a damping ratio $\zeta = \eta/2 = 0.125$.

## 2.3 Helmholtz resonator

Peristaltic contractions can create a constriction—or "neck"—connecting the gas pocket to the adjacent lumen, forming a Helmholtz resonator Rayleigh [1896], Kinsler et al. [1999]. The resonant frequency is

$$f_H = \frac{c_g}{2\pi}\sqrt{\frac{A_n}{L_{\text{eff}} V}}, \tag{5}$$

where $c_g$ is the speed of sound in the gas, $A_n = \pi d_n^2/4$ is the neck cross-sectional area, $V$ is the pocket volume, and $L_{\text{eff}} = L_n + 1.6\, r_n$ is the effective neck length including the Rayleigh end correction Rayleigh [1896], with $r_n = d_n/2$ the neck radius.

For a 10 mL pocket with a 5 mm neck diameter and 10 mm neck length, $f_H = 647\,\text{Hz}$. This lies above the typical healthy bowel sound range but within the spectrum reported for obstructed bowel Ching and Tan [2012], Yoshino et al. [1990], suggesting that Helmholtz resonance may contribute to the high-pitched "tinkling" sounds characteristic of intestinal obstruction.

## 2.4 Axial piston mode

When the gas pocket assumes a cylindrical slug geometry filling the lumen cross-section, it can oscillate axially between fluid plugs on either side. The gas slug of length $L_s = V/(\pi R_l^2)$, where $R_l = d/2$ is the lumen radius, acts as a compressible spring, while the fluid plugs provide inertia through their radiation added mass:

$$k_{\text{ax}} = \frac{\gamma P_0 \pi R_l^2}{L_s}, \qquad m_{\text{end}} = \frac{8}{3}\rho_f R_l^3, \tag{6}$$

where $m_{\text{end}}$ is the radiation mass of each fluid piston face Kinsler et al. [1999]. With two identical end masses, the natural frequency is

$$f_{\text{ax}} = \frac{1}{2\pi}\sqrt{\frac{k_{\text{ax}}}{2\,m_{\text{end}}}}. \tag{7}$$

For a 10 mL slug in a 30 mm tube, $f_{\text{ax}} = 99\,\text{Hz}$—well below the audible borborygmi range. This mode likely contributes to the sub-audible low-frequency rumbling component of gut motility.

## 2.5 Radial breathing mode

A cylindrical gas column confined within an elastic tube can undergo radial breathing oscillations, in which the gas and tube wall expand and contract together. The per-displacement stiffness (force per unit wall area per unit radial displacement) for the cylindrical geometry is

$$k_{\text{gas}} = \frac{2\gamma P_0}{R_l}, \qquad k_{\text{wall}} = \frac{Eh}{R_l^2(1-\nu^2)}, \tag{8}$$

where the factor 2 (rather than 3 for the sphere) reflects cylindrical geometry, and the division by $R_l$ (or $R_l^2$ for the wall term) ensures dimensional consistency with the spherical model (Eq. (2)). The effective mass per unit area is

$$m_{\text{fluid}} = \rho_f R_l, \qquad m_{\text{wall}} = \rho_w h, \tag{9}$$

and the natural frequency is

$$f_r = \frac{1}{2\pi}\sqrt{\frac{k_{\text{gas}} + k_{\text{wall}}}{m_{\text{fluid}} + m_{\text{wall}}}}. \tag{10}$$

For a 30 mm tube, $f_r = 163\,\text{Hz}$. This frequency is largely independent of gas pocket volume (depending only on tube properties) and lies below the clinically reported bowel sound range of 200 Hz to 550 Hz. Like the axial piston mode, the radial breathing mode contributes to the low-frequency rumbling component of gut sounds rather than the characteristic mid-frequency borborygmi.

## 2.6 Mode selection and coexistence

Real intestinal gas pockets are irregular in shape and may simultaneously exhibit characteristics of several idealised geometries. The pocket geometry determines which mode dominates: quasi-spherical pockets favour the constrained bubble mode; elongated slugs excite axial piston oscillations; and pockets connected to the lumen through peristaltic constrictions act as Helmholtz resonators.

We define the dominant mode at each volume as the one producing the lowest frequency, on the physical grounds that the lowest-frequency mode requires the least energy to excite and is most readily driven by broadband peristaltic forcing. For the canonical parameters, the radial breathing mode (163 Hz, independent of pocket volume) is the lowest-frequency mode at small volumes; above approximately 3.5 mL, the axial piston mode takes over because its frequency

Table 2: Predicted resonant frequencies for a 10 mL gas pocket in a 30 mm diameter intestinal segment.

| Mode | Expression | Frequency (Hz) | Clinical relevance |
|---|---|---|---|
| Free Minnaert | Eq. (1) | 244 | Limiting case of constrained |
| Constrained bubble | Eq. (4) | 223 | Within healthy range |
| Helmholtz resonator | Eq. (5) | 647 | Obstruction / tinkling |
| Axial piston | Eq. (7) | 99 | Sub-audible rumbling |
| Radial breathing | Eq. (10) | 163 | Below clinical band |

drops with increasing slug length ($f_{\text{ax}} \propto V^{-1/2}$, compared with $f_c \propto V^{-1/3}$ for the constrained bubble).

Both the radial and axial modes lie below the clinically reported bowel sound band for most physiological volumes: $f_{\text{ax}} < 100$ Hz for $V > 10$ mL, and $f_r = 163$ Hz throughout. Consequently, the constrained bubble mode dominates the *clinically audible* band (200 Hz to 550 Hz) across most of the physiologically relevant volume range. However, for small gas pockets ($V < 2.5$ mL), the axial mode remains above 200 Hz and competes with the constrained bubble mode within the clinical band—for example, at $V = 1$ mL, $f_{\text{ax}} = 314$ Hz vs. $f_c = 440$ Hz.

The coexistence of multiple modes at each pocket volume provides a natural explanation for the broadband character of borborygmi: a single peristaltic event compressing a gas pocket excites several resonance mechanisms simultaneously, producing a sound with contributions at multiple frequencies.

# 3 Results

## 3.1 Canonical predictions

Table 2 presents the predicted resonant frequencies for all modes with a 10 mL gas pocket in a 30 mm diameter intestinal segment. The constrained bubble frequency of 223 Hz falls within the healthy bowel sound band (200 Hz to 550 Hz), while the Minnaert baseline at 244 Hz is also plausible. The Helmholtz mode at 647 Hz corresponds to higher-pitched obstruction sounds, and the axial piston mode at 99 Hz to sub-audible rumbling. The radial breathing mode at 163 Hz also lies below the clinical band.

## 3.2 Volume dependence

Figure 1 shows all mode frequencies as a function of gas pocket volume from 1 mL to 50 mL, with the clinical bowel sound band (200 Hz to 550 Hz) indicated by shading. All bubble- and slug-based modes decrease monotonically with increasing volume, following the expected $f \propto V^{-1/3}$ scaling for the Minnaert-type modes and $f \propto V^{-1/2}$ for the Helmholtz and axial modes. The radial breathing mode is independent of gas pocket volume as it depends solely on tube properties.

The constrained bubble model covers 135 Hz to 440 Hz over this volume range, overlapping the lower portion of the clinically observed healthy bowel sound band. At $V = 1$ mL, the constrained frequency is 440 Hz; at $V = 50$ mL, it decreases to 135 Hz. The Minnaert model predicts a slightly

wider range of 143 Hz to 527 Hz, but systematically overpredicts relative to the constrained model because it neglects wall inertia.




Figure 1: Predicted borborygmi frequencies as a function of gas pocket volume for all resonance mechanisms. Shaded region: clinically observed healthy bowel sound range Ching and Tan [2012]. The constrained bubble model provides the best coverage of the clinical band.

## 3.3 Mode transition map

Figure 2 presents a mode transition map showing all mode frequencies on logarithmic axes across a volume range of 0.1 mL to 100 mL. Crossover points mark volumes at which the lowest-frequency mode changes. For the canonical parameters, the radial breathing mode (163 Hz) is the lowest-frequency mode below approximately 3.5 mL, above which the axial piston mode takes over as its frequency decreases with increasing slug length.

Above this crossover, the axial piston mode is formally the lowest-frequency mode across the physiologically relevant range (5 mL to 50 mL). However, $f_{\mathrm{ax}}$ is sub-audible at larger volumes ($<$ 100 Hz for $V > 10$ mL), and the radial mode sits at a fixed 163 Hz below the clinical band.

The constrained bubble mode is therefore the dominant mechanism within the *clinically audible* band, confirming it as the primary contributor to auscultated bowel sounds. For small pockets ($V < 2.5$ mL), the axial mode enters the clinical frequency range and contributes alongside the constrained bubble mode. The Helmholtz mode consistently lies above both bubble modes, becoming relevant only when narrow constrictions are present.




Figure 2: Mode transition map showing all resonance mechanisms across gas pocket volumes from 0.1 mL to 100 mL. The clinical band (200 Hz to 550 Hz) is indicated by horizontal dashed lines. The constrained bubble mode dominates the clinically audible band; the radial breathing mode (163 Hz) and axial piston mode have the lowest overall frequencies but are predominantly sub-audible at physiological volumes.

## 3.4 Clinical comparison

Table 3 compares model predictions with reported clinical frequency bands. For each clinical condition, we identify the gas pocket volume that produces the reported peak frequency under the constrained bubble model.

The constrained bubble model predicts a range of 135 Hz to 440 Hz for 1 mL to 50 mL, which overlaps substantially with the healthy adult band of 200 Hz to 550 Hz reported by Ching and Tan Ching and Tan [2012]. The model's lower boundary (135 Hz at 50 mL) corresponds to the

Table 3: Comparison of constrained bubble model predictions with clinical borborygmi frequency data. Inferred volumes are obtained by inverting the constrained model at each reported peak frequency.

| Condition | Reported range (Hz) | Peak (Hz) | Inferred $V$ (mL) | Source |
|---|---|---|---|---|
| Healthy adult | 200–550 | 340 | ∼3 | Ching and Tan [2012] |
| Small bowel obstruction | 173–667 | 288 | ∼5 | Yoshino et al. [1990] |
| Large bowel obstruction | 309–878 | 440 | ∼1 | du Plessis et al. [2000] |
| Constrained model (1–50 mL) | 135–440 | — | 1–50 | This work |

infrasonic rumbling that is felt but not heard, while the upper boundary (440 Hz at 1 mL) aligns with the peak frequency reported for large bowel obstruction du Plessis et al. [2000].

The small bowel obstruction peak of 288 Hz Yoshino et al. [1990] corresponds to a pocket volume of approximately 5 mL under the constrained model. This is physically plausible: small bowel obstruction involves proximal dilation with accumulated gas and fluid, producing pockets of several millilitres that oscillate at frequencies in the mid-range of the clinical band. The large bowel obstruction peak of 440 Hz du Plessis et al. [2000] implies smaller gas pockets (∼1 mL), which may reflect fragmentation of gas into small volumes by colonic haustral contractions, or alternatively the stiffer colonic wall elevating frequencies through increased $k_{\text{wall}}$.

The model underpredicts the upper extent of the clinical range for healthy adults (550 Hz vs. the model's 440 Hz at 1 mL). This discrepancy is readily explained by sub-millilitre gas pockets—which are common in the small bowel Levitt [1971]—or by Helmholtz resonance contributing to the high-frequency tail of the spectrum.

## 3.5 Parametric sensitivity

The constrained bubble frequency depends primarily on gas pocket volume $V$ and secondarily on wall stiffness $E$ and tube diameter $d$. We examined each parameter's influence through targeted sweeps.

**Wall stiffness.** Increasing the wall modulus from 1 kPa (very soft mucosa) to 100 kPa (fibrotic bowel) raises $k_{\text{wall}}$ proportionally. At 10 mL, however, the constrained frequency shifts only from approximately 221 Hz at $E = 1$ kPa to 241 Hz at $E = 100$ kPa—a modest 9% increase. The constrained frequency is thus remarkably insensitive to wall stiffness, dominated instead by gas compressibility. This insensitivity arises because $k_{\text{wall}}$ is small relative to $k_{\text{gas}}$ for the soft intestinal wall, even at a hundredfold increase in $E$. Pathological spectral shifts from fibrosis are therefore expected to be subtle, though potentially still detectable with sufficiently precise acoustic monitoring.

**Tube diameter.** The constrained bubble frequency is independent of tube diameter, since the equivalent spherical radius $R$ depends on volume alone and the constrained model (Eq. 4) contains no lumen-geometry terms. This is a limitation of the spherical approximation: in reality, the

lumen boundary would modify the added-mass term for non-spherical pockets. However, tube diameter strongly influences the axial and radial modes. For the canonical 30 mm lumen, the radial breathing mode sits at 163 Hz, below the clinical band; for larger-diameter segments (colon, $d \approx 40$ mm to 60 mm), it decreases further into the sub-audible regime.

**Neck geometry (Helmholtz).** The Helmholtz frequency is highly sensitive to neck diameter: doubling $d_n$ from 3 mm to 6 mm approximately doubles the frequency at a given volume. This sensitivity means that the degree of peristaltic constriction modulates the pitch of click-type bowel sounds, consistent with the clinical observation that high-pitched tinkling sounds are associated with tight constrictions in obstruction.

# 4 Discussion

## 4.1 Why the constrained bubble model dominates

Among the resonance mechanisms considered, the tissue-constrained bubble provides the best match to clinical observations for two reasons. First, typical intestinal gas pockets in the range of 1 mL to 50 mL are quasi-spherical (or at least compact), so the spherical bubble assumption is reasonable. Second, the constrained model correctly captures the competing effects of wall inertia and wall stiffness. For the soft, dense intestinal wall ($E = 10$ kPa, $\rho_w = 1040\,\mathrm{kg/m^3}$), wall inertia slightly reduces the frequency below the free Minnaert value, while wall stiffness makes a comparatively small correction. The net effect places the constrained frequency within the clinical band without requiring any parameter tuning.

The Minnaert model alone overpredicts because it neglects wall inertia. The Helmholtz model is relevant only in the presence of a constriction neck, which is not the default geometry. The axial and radial modes both operate below the clinical frequency band and require elongated or tube-filling gas column geometries.

## 4.2 Interpreting the mode transition map

The mode transition map (Fig. 2) reveals a nuanced landscape. By the lowest-frequency criterion, the radial breathing mode dominates below $V \approx 3.5$ mL and the axial piston mode dominates above this volume, because its frequency drops more steeply with volume ($f_{\mathrm{ax}} \propto V^{-1/2}$ vs. $f_c \propto V^{-1/3}$ for the constrained bubble). However, both modes are predominantly sub-audible: $f_r = 163$ Hz (constant), and $f_{\mathrm{ax}} < 100$ Hz for $V > 10$ mL. Within the audible band (200 Hz to 550 Hz), the constrained bubble mode is the dominant contributor for volumes above ~2.5 mL. Below this volume, the axial mode also falls within the clinical band and may contribute to the multi-tonal character of small-pocket borborygmi. This distinction is clinically important: a single-mode model based on the constrained bubble is sufficient for interpreting most auscultatory findings, even though the formal lowest-frequency modes are sub-audible.

The Helmholtz mode, while not dominant in the lowest-frequency sense, deserves attention as a secondary mechanism. When peristaltic contractions are present, the Helmholtz frequency may overlay the bubble frequency, producing the characteristic broadband, multi-tonal quality

of real borborygmi. The mode transition map provides a quantitative framework for predicting which combinations of modes are active for a given pocket volume and constriction geometry.

## 4.3 Clinical implications

The model suggests a straightforward interpretation of clinical spectral shifts. Small bowel obstruction, which involves proximal dilation and accumulation of gas and fluid, produces moderate-sized gas pockets (3 mL to 10 mL) that resonate in the mid-frequency range (220 Hz to 340 Hz). The reported peak frequency of 288 Hz Yoshino et al. [1990] corresponds to a pocket volume of approximately 5 mL under the constrained model—physically consistent with dilated small bowel.

Large bowel obstruction, by contrast, may involve either smaller gas pockets (due to colonic haustral segmentation) or a stiffer colonic wall. Either mechanism would elevate the frequency, consistent with the higher peak of 440 Hz reported by Du Plessis et al. du Plessis et al. [2000]. The model's sensitivity to wall stiffness (Sec. 3.5) suggests that conditions affecting wall compliance—Crohn's disease, fibrosis, inflammation—could produce detectable spectral signatures.

If validated experimentally, the constrained bubble model could serve as a frequency inversion tool: given a measured peak frequency, one could infer the gas pocket volume, providing non-invasive information about intestinal gas distribution that is currently obtainable only through imaging.

## 4.4 Limitations

Several simplifications warrant discussion.

*Geometry.* Real intestinal gas pockets are irregular, not spherical or cylindrical. The spherical approximation is most accurate for compact pockets where the aspect ratio is near unity; elongated pockets would require a more detailed geometrical treatment. Furthermore, the equivalent-sphere diameter exceeds the lumen diameter for volumes above approximately 14 mL (a sphere of 14 mL has a diameter of 30 mm, matching the lumen). Larger pockets necessarily adopt elongated, non-spherical geometries to fit within the lumen. We therefore consider the spherical constrained-bubble model to be most reliable for volumes up to approximately 14 mL and treat predictions at larger volumes as an extrapolation that likely overestimates the effective bubble radius. The constrained model is also strictly independent of tube diameter—a consequence of the spherical assumption that neglects lumen-boundary effects on the added-mass term.

*Static equilibrium.* We model steady-state resonance frequencies and do not account for the time-varying geometry imposed by peristaltic waves. Peristalsis modulates both the pocket volume and any constriction neck dimensions on timescales of seconds, producing the characteristic intermittent quality of borborygmi.

*Single-pocket model.* Real intestinal gas exists as multiple pockets distributed along the tract Serra et al. [2001], Levitt [1971]. Acoustic interactions between neighbouring pockets—analogous to coupled oscillator systems—could produce frequency splitting and beating phenomena not captured by the present single-pocket analysis.

*Gas composition.* We assume air ($\gamma = 1.4$) for the gas pocket. Intestinal gas is a mixture of nitrogen, carbon dioxide, hydrogen, methane, and hydrogen sulphide Suarez et al. [1997], Levitt [1971], with a slightly different effective $\gamma$. For the dominant Minnaert and constrained modes, the frequency scales as $\sqrt{\gamma P_0}$, so modest changes in $\gamma$ (from 1.4 to approximately 1.3 for a $CO_2$-rich

mixture) would reduce frequencies by approximately 4%—smaller than the uncertainty in wall properties.

*Damping.* We use a single loss tangent $\eta = 0.25$ ($Q = 4.0$) to represent all dissipation mechanisms. In reality, viscous losses in the fluid, radiation damping, and viscoelastic losses in the wall contribute differently at different frequencies. At the constrained bubble frequency of 223 Hz, $Q = 4$ implies a free ring-down time of approximately 18 ms, which is 30–45× shorter than the observed 0.5 s to 0.8 s bowel sound burst durations Ching and Tan [2012]. This discrepancy indicates that clinically observed borborygmi are sustained excitation events—driven by ongoing peristaltic forcing over hundreds of milliseconds—rather than free ring-downs of a briefly excited resonator. The quality factor $Q = 4$ thus characterises the spectral width of each resonance, not the temporal duration of the sound event.

*Radiation and transmission.* We do not model how efficiently sound generated at the gas pocket propagates through tissue to the abdominal surface, where it is detected by stethoscope or microphone. This transmission path introduces frequency-dependent attenuation that would alter the measured spectrum relative to the source spectrum predicted here.

# 5 Conclusions

We have presented a unified analytical framework for predicting the resonant frequencies of intestinal gas pockets, comprising four acoustic mechanisms—tissue-constrained bubble resonance (with the classical Minnaert frequency as a limiting case), Helmholtz resonance, axial piston modes, and radial breathing modes. The principal findings are:

1. The tissue-constrained bubble model, which augments the classical Minnaert formula with intestinal wall elasticity and inertia, predicts frequencies of 135 Hz to 440 Hz for gas pocket volumes of 1 mL to 50 mL. This range overlaps the clinically observed healthy bowel sound band of 200 Hz to 550 Hz, specifically capturing the 200 Hz to 440 Hz sub-band without curve-fitting or fitted parameters. Frequencies above 440 Hz require sub-millilitre pockets or Helmholtz contributions.

2. A mode-transition map across the volume–frequency space shows that the radial breathing mode (163 Hz) and the axial piston mode have the lowest overall frequencies, but both are predominantly sub-audible ($f_{\mathrm{ax}} < 100$ Hz for $V > 10$ mL). The constrained bubble mode therefore dominates the clinically audible band across most of the physiologically relevant volume range, though the axial mode competes within the clinical band for small pockets ($V < 2.5$ mL). The Helmholtz mode provides a secondary high-frequency contribution relevant to obstruction-related tinkling sounds.

3. The model provides a physics-based framework for interpreting clinical spectral shifts: the reported peak frequencies for small bowel obstruction (288 Hz) and large bowel obstruction (440 Hz) correspond to pocket volumes of approximately 5 mL and 1 mL, respectively, under the constrained model.

4. Wall stiffness is a secondary parameter: a hundredfold increase (from 1 kPa to 100 kPa, representing fibrotic bowel) raises the predicted frequency by only ∼9%, indicating that

the constrained frequency is dominated by gas compressibility rather than wall elasticity. Pathological spectral shifts from fibrosis, while potentially detectable, are expected to be subtle.

5. The spherical bubble assumption limits the model's high-confidence range to volumes below approximately 14 mL, above which the equivalent-sphere diameter exceeds the lumen diameter. Predictions for larger volumes should be treated as extrapolations.

Experimental validation through simultaneous bowel sound recording and imaging (to estimate pocket volumes) is a natural next step. If confirmed, the constrained bubble model could serve as a non-invasive frequency inversion tool for estimating intestinal gas pocket volumes from measured acoustic spectra.

# Acknowledgements

The authors thank Professor Dietrich Weymann for his encouragement to submit the paper rather than continue polishing it.

Analytical modelling, code development, and manuscript drafting were performed with the assistance of GitHub Copilot CLI (GitHub, Inc.), a large language model. Publisher guidelines preclude listing it as a co-author, a policy the model accepts with the quiet dignity of someone who has read the terms of service and knows better than to argue.

# References

Habib Ammari, Brian Fitzpatrick, David Gontier, Hyundae Lee, and Hai Zhang. Minnaert resonances for acoustic waves in bubbly media. *Ann. Inst. H. Poincaré C*, 35(7):1975–1998, 2018.

Walter Bradford Cannon. Auscultation of the rhythmic sounds produced by the stomach and intestines. *Am. J. Physiol.*, 12(4):387–395, 1905.

Shiaw Shyan Ching and Yin Kuang Tan. Spectral analysis of bowel sounds in intestinal obstruction using an electronic stethoscope. *World J. Gastroenterol.*, 18(33):4585–4592, 2012.

Charles C. Church. The effects of an elastic solid surface layer on the radial pulsations of gas bubbles. *J. Acoust. Soc. Am.*, 97(3):1510–1521, 1995.

Brian L. Craine, Mary L. Silpa, and Catherine J. O'Toole. Computerized auscultation applied to intestinal motility assessment. *Dig. Dis. Sci.*, 44(9):1909–1916, 1999.

Brian L. Craine, Mary L. Silpa, Catherine J. O'Toole, and Neil Stollman. Enterotainment: Computerized abdominal auscultation is a useful clinical adjunct in suspected small bowel obstruction. *Dig. Dis. Sci.*, 47(6):1290–1296, 2002.

Lavinia Dalle Donne, Simone Cataldo, Stefano Ceruti, Daniela Morniroli, Fabio Mosca, and Maria L. Gianni. Bowel sounds monitoring: a systematic review. *Biomedicines*, 12(3):581, 2024.

J. du Plessis, R. le Roux, and M. van der Merwe. Spectral analysis of bowel sounds recorded by electronic stethoscope. *Dis. Colon Rectum*, 43(1):81–84, 2000.

Lars Hoff. *Acoustic Characterization of Contrast Agents for Medical Ultrasound Imaging*. Springer, Dordrecht, 2001.

Lawrence E. Kinsler, Austin R. Frey, Alan B. Coppens, and James V. Sanders. *Fundamentals of Acoustics*. John Wiley and Sons, New York, 4th edition, 1999.

Timothy G. Leighton. *The Acoustic Bubble*. Academic Press, London, 1994.

Michael D. Levitt. Volume and composition of human intestinal gas determined by means of an intestinal washout technic. *N. Engl. J. Med.*, 284(25):1394–1398, 1971.

Hongjie Li, Hongyu Liu, and Jun Zou. Minnaert resonances for acoustic waves in bubbly media. *SIAM J. Appl. Math.*, 82(1):119–141, 2022.

Jonathan Mace, Brian R. Mace, and GitHub Copilot CLI. Bowel gas as an acoustic transducer: A constrained bubble model for infrasound-induced mechanotransduction in the gastrointestinal tract. *JASA Express Letters*, 2026. Submitted.

Marcel Minnaert. On musical air-bubbles and the sounds of running water. *Philosophical Magazine*, 16(104):235–248, 1933.

Jan K. Nowak, Ryszard Nowak, Kamil Radzikowski, Ireneusz Grulkowski, and Jaroslaw Walkowiak. Automated bowel sound analysis: an overview. *Sensors*, 21(16):5294, 2021.

Baron Rayleigh, John William Strutt. *The Theory of Sound*, volume II. Macmillan, London, 2nd edition, 1896.

Jordi Serra, Fernando Azpiroz, and Juan R. Malagelada. Intestinal gas dynamics and tolerance in humans. *Gastroenterology*, 120(1):218–226, 2001.

Fabrizis L. Suarez, Julie Furne, John Springfield, and Michael D. Levitt. Insights into human colonic physiology obtained from the study of flatus composition. *Am. J. Physiol.*, 272(5):G1028–G1033, 1997.

Hiroyuki Yoshino, Yutaka Abe, Takashi Yoshino, and Kunihide Ohsato. Clinical application of spectral analysis of bowel sounds in intestinal obstruction. *Dis. Colon Rectum*, 33(9):753–757, 1990.