מבנה מסד הנתונים: פלטפורמת הקייטרינג

דיאגרמת ישויות וקשרים (ERD), גרסת SQLite, מבוססת על docs/DATABASE_SCHEMA.md (טיוטה v0.1)

15 tables · 13 relationships
2026-11-02

customers — MVP

PK	id	TEXT
U	auth_user_id	TEXT?
	full_name	TEXT
	email	TEXT?
	phone	TEXT?
	created_at	TEXT
	updated_at	TEXT

auth_user_id רק אם יוחלט על חשבונות משתמש (OPEN #1)

orders — MVP

PK	id	TEXT
FK	customer_id	TEXT
FK U	event_id	TEXT
	status	TEXT
	version	INTEGER
	fulfillment_type	TEXT
	requested_at	TEXT
	delivery_address	TEXT?
FK	delivery_zone_id	TEXT?
	subtotal_agorot	INTEGER?
	delivery_fee_agorot	INTEGER?
	total_agorot	INTEGER?
	submitted_at	TEXT?
	decided_at	TEXT?
	decision_note	TEXT?
	created_at	TEXT
	updated_at	TEXT

status: draft → pending_approval → approved / rejected
delivery_address חובה (delivery) במשלוח

order_items — MVP

PK	id	TEXT
FK	order_id	TEXT
FK	dish_id	TEXT
	quantity	REAL
	snapshot_name	TEXT?
	snapshot_pricing_unit	TEXT?
	snapshot_unit_price_ago…	INTEGER?
	snapshot_line_total_ago…	INTEGER?

quantity > 0 ,UNIQUE (order_id, dish_id)
snapshot נשמר בהגשה ומקבע את המחיר

dishes — MVP

PK	id	TEXT
FK	category_id	TEXT
	name	TEXT
	description	TEXT?
	image_path	TEXT?
	pricing_unit	TEXT
	unit_price_agorot	INTEGER
	unit_label	TEXT?
	currency	TEXT
	min_quantity	REAL?
	is_available	INTEGER
	kashrut_class	TEXT?
	is_vegetarian	INTEGER?
	is_vegan	INTEGER?
	dietary_verified_at	TEXT?
	created_at	TEXT
	updated_at	TEXT

pricing_unit: per_guest / per_tray / per_weight / per_item
kashrut_class: meat / dairy / pareve
ערך NULL בשדות התזונה פירושו לא ידוע

dish_allergens — MVP

PK FK	dish_id	TEXT
PK FK	allergen_id	INTEGER
	status	TEXT

status: contains / free / unknown
שורה חסרה = לא ידוע (לא "נקי")

allergens — MVP

PK	id	INTEGER
U	name	TEXT

events — MVP

PK	id	TEXT
FK	customer_id	TEXT
	event_type	TEXT
	event_date	TEXT
	adults	INTEGER
	children	INTEGER
	vegetarian_guests	INTEGER
	vegan_guests	INTEGER
	restricted_guests	INTEGER
	dietary_notes	TEXT?

CHECK (adults + children > 0)
כל הספירות ≥ 0

ai_change_proposals — בהמשך

PK	id	TEXT
FK	order_id	TEXT
FK	conversation_id	TEXT?
	base_order_version	INTEGER
	changes	TEXT (JSON)
	price_before_agorot	INTEGER
	price_after_agorot	INTEGER
	status	TEXT
	created_at	TEXT
	decided_at	TEXT?
	executed_at	TEXT?

מבוצע רק אם base_order_version = orders.version
הצעה אחת במצב pending לכל הזמנה

time_slots — בהמשך

PK	id	TEXT
	fulfillment_type	TEXT
	weekday	INTEGER?
	start_time	TEXT
	end_time	TEXT
	capacity	INTEGER?
	is_active	INTEGER

CHECK (end_time > start_time)
ללא קשרים

dish_categories — MVP

PK	id	TEXT
U	name	TEXT
	sort_order	INTEGER
	is_active	INTEGER

ai_conversations — בהמשך

PK	id	TEXT
FK	order_id	TEXT
	created_at	TEXT

blocked_dates — בהמשך

PK	id	TEXT
U	date	TEXT
	reason	TEXT?

ללא קשרים

delivery_zones — בהמשך

PK	id	TEXT
	name	TEXT
	fee_agorot	INTEGER
	definition	TEXT (JSON)
	is_active	INTEGER

ai_messages — בהמשך

PK	id	TEXT
FK	conversation_id	TEXT
	role	TEXT
	content	TEXT (JSON)
	created_at	TEXT

role: user / assistant / tool

MVP: לבנות עכשיו · שלב מאוחר יותר · PK מפתח ראשי · FK מפתח זר · U ייחודי · ? ניתן ל-NULL · רבים · בדיוק אחד · אופציונלי (FK שיכול להיות NULL)

כסף: INTEGER באגורות · תאריכים: TEXT ISO-8601 UTC · enum: TEXT + CHECK
בכל חיבור: PRAGMA foreign_keys = ON;