

1 Method

Simple methods that do not require explanation in `summary_examples_multichannel.mlx`

- 0.2 ISI
-

1.1 spike detection (0.2. in `summary_examples_multichannel.mlx`)

In order to detect neural spikes and build spike trains, we utilize a previously reported MATLAB spike-sorting algorithm [Le Floch et al., 2022]. The signal is first filtered bandpass filtered (300 – 6000 Hz or 100 – 6000 Hz) using the MATLAB function `bandpass`. Then any timepoint where the signal amplitude is lower than $-5 \times$ standard deviation of the filtered signal is considered as the peak of a spike. We slice 2 milliseconds back and forth from the peak to make a spike waveform.

1.2 burst detection

For burst detection in spike trains, we follow [Fair et al., 2020] to adopt MaxInterval method. It defines bursts using five pre-defined threshold parameters—max ISI at start of burst, max ISI in burst, min burst duration, min interburst interval, and min number of spikes in burst. Any series of spikes that satisfies all of these thresholds is considered as a burst. We set the threshold as 300, 301, 10, 50, 200, respectively.

1.3 spike sorting through PCA and k-means (0.4, 0.5 in `summary_examples_multichannel.mlx`)

In order to sort the detected spike waveforms that originates from different neurons, we apply dimension reduction and clustering algorithms. We first use principal component analysis (MATLAB function `pca` to reduce each spike waveform into a two-dimensional vector. Then we cluster these reduced vectors using k-means clustering algorithm (MATLAB function `kmeans`), which clusters the vectors into the pre-specified number of groups. We set the number of groups as 3.

1.4 Spike sorting quality metrics

1.5 3d network graph

In order to measure the connectivity between electrodes, we follow the synchronized score approach of [Lam et al., 2019]. To calculate the synchronized score between two spike trains, we first measure SPIKE-distance [Kreuz et al., 2013] using Python environment (version 3.9.2) and Python package PYSPIKE (version 0.7.0) [Mulansky and Kreuz, 2016]. **The SPIKE-distance is normalized to average of 1000 randomly generated baseline values; each baseline value is the SPIKE-distance between two uniformly randomly generated spike trains.** Then, synchronized scores are defined as SPIKE-distance values subtracted from 1. These sync scores range from 0 to 1, where a higher score indicates a high degree of synchrony.

Community structure on the electrodes is examined by graph-theoretic Louvain algorithm [Newman and Girvan, 2004, Blondel et al., 2008] which is based on modularity optimization. In the analysis, we model the electrodes as nodes (e.g., circles in the network map), whose 3d positions represent the position of the actual electrode. We set synchronized scores between every pair of active electrodes as edge (e.g., lines in the network map) weights between the corresponding nodes. The edges with synchronized scores less than 0.5 were filtered out. The result of the Louvain algorithm is visualized through color and size, using the Python package `plotly` (version 5.9.0). Nodes with the same color (i.e., electrodes) belong to the same community network. Synchronization scores are color-mapped, ranged from 0 (blue) to 1 (red). In addition, the larger the number of connected electrodes becomes, the larger the size of the node becomes.

1.6 Figures from

References

- [Blondel et al., 2008] Blondel, V. D., Guillaume, J.-L., Lambiotte, R., and Lefebvre, E. (2008). Fast unfolding of communities in large networks. *Journal of Statistical Mechanics: Theory and Experiment*, 2008(10):P10008.
- [Fair et al., 2020] Fair, S. R., Julian, D., Hartlaub, A. M., Pusuluri, S. T., Malik, G., Summerfield, T. L., Zhao, G., Hester, A. B., Ackerman, W. E., Hollingsworth, E. W., Ali, M., McElroy, C. A., Buhimschi, I. A., Imitola, J., Maitre, N. L., Bedrosian, T. A., and Hester, M. E. (2020). Electro-

- physiological Maturation of Cerebral Organoids Correlates with Dynamic Morphological and Cellular Development. *Stem Cell Reports*, 15(4):855–868. Publisher: Elsevier.
- [Kreuz et al., 2013] Kreuz, T., Chicharro, D., Houghton, C., Andrzejak, R. G., and Mormann, F. (2013). Monitoring spike train synchrony. *Journal of Neurophysiology*, 109(5):1457–1472.
- [Lam et al., 2019] Lam, D., Enright, H. A., Cadena, J., Peters, S. K. G., Sales, A. P., Osburn, J. J., Soscia, D. A., Kulp, K. S., Wheeler, E. K., and Fischer, N. O. (2019). Tissue-specific extracellular matrix accelerates the formation of neural networks and communities in a neuron-glia co-culture on a multi-electrode array. *Scientific Reports*, 9(1):4159. Number: 1 Publisher: Nature Publishing Group.
- [Le Floch et al., 2022] Le Floch, P., Li, Q., Lin, Z., Zhao, S., Liu, R., Tanim, K., Jiang, H., and Liu, J. (2022). Stretchable Mesh Nanoelectronics for Three-Dimensional Single-Cell Chronic Electrophysiology from Developing Brain Organoids. *Advanced materials (Deerfield Beach, Fla.)*, 34(11):e2106829.
- [Mulansky and Kreuz, 2016] Mulansky, M. and Kreuz, T. (2016). PySpikeA Python library for analyzing spike train synchrony. *SoftwareX*, 5:183–189.
- [Newman and Girvan, 2004] Newman, M. E. J. and Girvan, M. (2004). Finding and evaluating community structure in networks. *Phys. Rev. E*, 69:026113.