

JAC444 - Lecture 2

Generics

Segment 4

Generics

In this segment you will be learning about:

- Generics in Java – Abstraction over Types
- Generic Methods and Bounded Type Parameters
- Wildcards and Subtyping
- Type Erasure

Simple Box Class

```
/** Box class. */
```

```
public class Box {
```

```
    private Object o;
```

```
    public void add(Object o) {  
        this.o = o;  
    }
```

```
    public Object get() {  
        return o;  
    }
```

```
}
```

```
Box myBox = new Box();
```

```
myBox.add(new Integer(10));
```

```
Integer val = (Integer) myBox.get();
```

```
String str = (String) myBox.get();
```

```
java.Lang.ClassCastException;
```

Defining Simple Generics

```
/** Generic Box class. */
```

```
public class Box<T> {
```



generic type declaration

```
    private T t;
```



formal type parameter

```
    public void add(T t) {  
        this.t = t;  
    }
```

```
    public T get() {  
        return t;  
    }  
}
```

```
Box<Integer> integerBox = new Box<Integer>();  
Box<Integer> integerBox = new Box<>();
```

Type Parameter and Type Argument

- The generics can be used in: classes, interfaces, methods, constructors:

```
public interface List<E> {  
    void add(E x);  
    Iterator<E> iterator();  
}
```

```
public interface Iterator<E> {  
    E next();  
    boolean hasNext();  
}
```

- Generic type declaration `List<E>` is called *parameterized type*
`E` in `List<E>` is called type parameter
- `List<Integer>` the formal type parameter `E` is replaced by the *actual type argument* `Integer`
`Integer` in `List<Integer>` is called type argument

Multiple Type Parameters

```
public interface Pair<K, V> {
    public K getKey();
    public V getValue();
}

public class OrderedPair<K, V> implements Pair<K, V> {
    private K key;
    private V value;

    public OrderedPair(K key, V value) {
        this.key = key;
        this.value = value;
    }

    public K getKey()    { return key; }
    public V getValue() { return value; }
}

Pair<String, Integer> p1 = new OrderedPair<String, Integer>("Odd", 7);

OrderedPair<String, Box<Integer>> p =
    new OrderedPair<>("primes", new Box<Integer>(3));
```

Source: <http://docs.oracle.com/javase/tutorial/java/generics/types.html>

More Types

- Generic class can have multiple type parameters
- Type argument can be any user defined type

```
HashMap<String, Dog> map = new HashMap<String, Dog>();
```

```
map.put("bliss" new Dog("myDog"));
```

```
Dog d = map.get("bliss");
```

Generic method

- Type parameters can also be declared within method and constructor signatures to create *generic method*
- Type parameter's scope is limited to the method in which it is declared.

```
Public static <U> void inspect(U type) {  
  
    System.out.println("Type parameter U is of Class: "  
        + type.getClass().getName());  
  
}
```


Bounded Type Parameters

- Restriction on the type parameter
T is upper bounded by **Integer**

```
public class NaturalNumber<T extends Integer> {  
    private T n;  
    public NaturalNumber(T n) { this.n = n; }  
    public boolean isEven() {  
        return n.intValue() % 2 == 0;  
    }  
}
```

intValue() is the method from class **Integer**

Wildcards

- Consider the problem of writing a routine that shows out all the elements from a Box

```
void showAll ( Box<Object> b ) {  
    for (Object o : b)  
        System.out.println(o);  
}
```

How could we invoke the method with `Box<String>` if `Box<String>` is not a subtype of a `Box<Object>`

We define `wildcard type` as `?` and a `Box<?>` as a Box of unknown types

```
void showAll ( Box<?> b ) {  
    for (Object o : b)  
        System.out.println(o);  
}
```

Type Erasure

- When a generic type is instantiated, the compiler translates those types by a technique called *type erasure*
- `Box<String>` is translated to type `Box`, which is called the *raw type*
- When mixing legacy code with generic code, you may encounter warning messages similar to the following:

Note: `YourClass.java` uses unchecked or unsafe operations.

Note: Recompile with `-Xlint:unchecked` for details.

Generic and Raw Types

```
public class MixedClass {  
    public static void main(String[] args){  
        Box<Integer> bi;  
        bi = createBox();  
    }  
    /* Pretend that this method is part of an old library, written  
    before generics. It returns Box instead of Box<T>. */  
    static Box createBox() {  
        return new Box();  
    }  
}
```

```
MixedClass.java:4: warning: [unchecked] unchecked conversion  
found   : Box  
required: Box<java.lang.Integer>  
    bi = createBox();  
           ^
```

```
1 warning
```

Upper/Lower Bounded Wildcards

- Upper/Lower-bounded wildcard is `?` character

Upper-bounded: `<? extends Number>`

means any type that is at least a `Number` type

Lower-bounded: `<? super Integer>`

means any type that is a super type of an `Integer` type

Source:

<http://docs.oracle.com/javase/tutorial/java/generics/types.html>