




Chapter 2


Mathematical modelling of (small) arteries by 1D models







Structure of the vascular system







Structure of the vascular system




$d \approx \text{mm}$





**Target of the 1D model
we will derive**







Domain decomposition






Domain decomposition







Domain decomposition



Modelling each vessel segment?





Cylindrical geometry


curved vessel

Assumption: circular cross section

z axis coincides with main axis of vessel
(can be achieved by transformation)


$S(z,t)$ denotes cross section at position z and time t , $R(z,t)$ denotes the radius, accordingly


l : length of vessel



Transformation


\approx Identity for small Dean numbers






Navier-Stokes equations (3D)

$$\Omega(t) = \{ (r, \theta, z) \in \mathbb{R}^3 \mid 0 < z < l, 0 \leq r < R(z, t), 0 \leq \theta < 2\pi \} \subset \mathbb{R}^3$$





Navier-Stokes equations (3D)


Momentum and continuity equations:

$$\rho \frac{\partial \mathbf{u}}{\partial t} + \rho (\mathbf{u} \cdot \nabla) \mathbf{u} + \nabla P - \mathbf{div} (2\mu \mathbf{D}) = \mathbf{f}, \text{ in } \Omega(t), t > 0,$$

$$\mathbf{div} (\mathbf{u}) = 0, \text{ in } \Omega(t), t > 0.$$

ρ : density, blood is assumed to be incompressible





Navier-Stokes equations (3D)

Momentum and continuity equations:


$$\rho \frac{\partial \mathbf{u}}{\partial t} + \rho (\mathbf{u} \cdot \nabla) \mathbf{u} + \nabla P - \mathbf{div} (2\mu \mathbf{D}) = \mathbf{f}, \text{ in } \Omega(t), t > 0,$$

$$\mathbf{div} (\mathbf{u}) = 0, \text{ in } \Omega(t), t > 0.$$

ρ : density, blood is assumed to be incompressible

$\mathbf{f} \equiv \mathbf{0}$: no external forces, as for example gravity





Navier-Stokes equations (3D)

Momentum and continuity equations:

$$\rho \frac{\partial \mathbf{u}}{\partial t} + \rho (\mathbf{u} \cdot \nabla) \mathbf{u} + \nabla P - \mathbf{div} (2\mu \mathbf{D}) = \mathbf{f}, \text{ in } \Omega(t), t > 0,$$

$$\mathbf{div} (\mathbf{u}) = 0, \text{ in } \Omega(t), t > 0.$$

ρ : density, blood is assumed to be incompressible


$\mathbf{f} \equiv \mathbf{0}$: no external forces, as for example gravity

$$\mathbf{D} (\mathbf{u}) = \frac{1}{2} (\nabla \mathbf{u} + \nabla \mathbf{u}^T), \quad \nabla \mathbf{u} = \begin{pmatrix} \nabla u_1^T \\ \nabla u_2^T \\ \nabla u_3^T \end{pmatrix}$$

Remark:

$$\mathbf{div}(p\mathbf{I}) = \nabla p$$





Cylinder coordinates

Navier-Stokes equations (3D)

$$\begin{aligned}
 \frac{\partial v_r}{\partial t} + v_r \frac{\partial v_r}{\partial r} + \frac{v_\theta}{r} \frac{\partial v_r}{\partial \theta} + v_z \frac{\partial v_r}{\partial z} - \frac{v_\theta^2}{r} + \frac{1}{\rho} \frac{\partial p}{\partial r} - \frac{\mu}{\rho} \left(\frac{1}{r} \frac{\partial}{\partial r} \left(r \frac{\partial v_r}{\partial r} \right) + \frac{1}{r^2} \frac{\partial^2 v_r}{\partial \theta^2} + \frac{\partial^2 v_r}{\partial z^2} - \frac{v_r}{r^2} - \frac{2}{r^2} \frac{\partial v_\theta}{\partial \theta} \right) - b_r &= 0 \\
 \frac{\partial v_\theta}{\partial t} + v_r \frac{\partial v_\theta}{\partial r} + \frac{v_\theta}{r} \frac{\partial v_\theta}{\partial \theta} + v_z \frac{\partial v_\theta}{\partial z} - \frac{v_r v_\theta}{r} + \frac{1}{r \rho} \frac{\partial p}{\partial \theta} - \frac{\mu}{\rho} \left(\frac{1}{r} \frac{\partial}{\partial r} \left(r \frac{\partial v_\theta}{\partial r} \right) + \frac{1}{r^2} \frac{\partial^2 v_\theta}{\partial \theta^2} + \frac{\partial^2 v_\theta}{\partial z^2} - \frac{v_\theta}{r^2} + \frac{2}{r^2} \frac{\partial v_r}{\partial \theta} \right) - b_\theta &= 0 \\
 \frac{\partial v_z}{\partial t} + v_r \frac{\partial v_z}{\partial r} + \frac{v_\theta}{r} \frac{\partial v_z}{\partial \theta} + v_z \frac{\partial v_z}{\partial z} + \frac{1}{\rho} \frac{\partial p}{\partial z} - \frac{\mu}{\rho} \left(\frac{1}{r} \frac{\partial}{\partial r} \left(r \frac{\partial v_z}{\partial r} \right) + \frac{1}{r^2} \frac{\partial^2 v_z}{\partial \theta^2} + \frac{\partial^2 v_z}{\partial z^2} \right) - b_z &= 0 \\
 \frac{1}{r} \frac{\partial (r v_r)}{\partial r} + \frac{1}{r} \frac{\partial v_\theta}{\partial \theta} + \frac{\partial v_z}{\partial z} &= 0
 \end{aligned}$$

velocity
vector
field


$$\mathbf{v} = \begin{pmatrix} v_r \\ v_\theta \\ v_z \end{pmatrix}$$

radial component

circumferential component

axial component






Cylinder coordinates

Navier-Stokes equations (3D)

$$\begin{aligned}
 \frac{\partial v_r}{\partial t} + v_r \frac{\partial v_r}{\partial r} + \frac{v_\theta}{r} \frac{\partial v_r}{\partial \theta} + v_z \frac{\partial v_r}{\partial z} - \frac{v_\theta^2}{r} + \frac{1}{\rho} \frac{\partial p}{\partial r} - \frac{\mu}{\rho} \left(\frac{1}{r} \frac{\partial}{\partial r} \left(r \frac{\partial v_r}{\partial r} \right) + \frac{1}{r^2} \frac{\partial^2 v_r}{\partial \theta^2} + \frac{\partial^2 v_r}{\partial z^2} - \frac{v_r}{r^2} - \frac{2}{r^2} \frac{\partial v_\theta}{\partial \theta} \right) - b_r &= 0 \\
 \frac{\partial v_\theta}{\partial t} + v_r \frac{\partial v_\theta}{\partial r} + \frac{v_\theta}{r} \frac{\partial v_\theta}{\partial \theta} + v_z \frac{\partial v_\theta}{\partial z} - \frac{v_r v_\theta}{r} + \frac{1}{r \rho} \frac{\partial p}{\partial \theta} - \frac{\mu}{\rho} \left(\frac{1}{r} \frac{\partial}{\partial r} \left(r \frac{\partial v_\theta}{\partial r} \right) + \frac{1}{r^2} \frac{\partial^2 v_\theta}{\partial \theta^2} + \frac{\partial^2 v_\theta}{\partial z^2} - \frac{v_\theta}{r^2} + \frac{2}{r^2} \frac{\partial v_r}{\partial \theta} \right) - b_\theta &= 0 \\
 \frac{\partial v_z}{\partial t} + v_r \frac{\partial v_z}{\partial r} + \frac{v_\theta}{r} \frac{\partial v_z}{\partial \theta} + v_z \frac{\partial v_z}{\partial z} + \frac{1}{\rho} \frac{\partial p}{\partial z} - \frac{\mu}{\rho} \left(\frac{1}{r} \frac{\partial}{\partial r} \left(r \frac{\partial v_z}{\partial r} \right) + \frac{1}{r^2} \frac{\partial^2 v_z}{\partial \theta^2} + \frac{\partial^2 v_z}{\partial z^2} \right) - b_z &= 0 \\
 \frac{1}{r} \frac{\partial(r v_r)}{\partial r} + \frac{1}{r} \frac{\partial v_\theta}{\partial \theta} + \frac{\partial v_z}{\partial z} &= 0
 \end{aligned}$$

Neglect gravity / body forces: $\mathbf{b} = 0$





Cylinder coordinates


Navier-Stokes equations (3D)

$$\begin{aligned}
 \frac{\partial v_r}{\partial t} + v_r \frac{\partial v_r}{\partial r} + \frac{v_\theta}{r} \frac{\partial v_r}{\partial \theta} + v_z \frac{\partial v_r}{\partial z} - \frac{v_\theta^2}{r} + \frac{1}{\rho} \frac{\partial p}{\partial r} - \frac{\mu}{\rho} \left(\frac{1}{r} \frac{\partial}{\partial r} \left(r \frac{\partial v_r}{\partial r} \right) + \frac{1}{r^2} \frac{\partial^2 v_r}{\partial \theta^2} + \frac{\partial^2 v_r}{\partial z^2} - \frac{v_r}{r^2} - \frac{2}{r^2} \frac{\partial v_\theta}{\partial \theta} \right) - b_r &= 0 \\
 \frac{\partial v_\theta}{\partial t} + v_r \frac{\partial v_\theta}{\partial r} + \frac{v_\theta}{r} \frac{\partial v_\theta}{\partial \theta} + v_z \frac{\partial v_\theta}{\partial z} - \frac{v_r v_\theta}{r} + \frac{1}{r \rho} \frac{\partial p}{\partial \theta} - \frac{\mu}{\rho} \left(\frac{1}{r} \frac{\partial}{\partial r} \left(r \frac{\partial v_\theta}{\partial r} \right) + \frac{1}{r^2} \frac{\partial^2 v_\theta}{\partial \theta^2} + \frac{\partial^2 v_\theta}{\partial z^2} - \frac{v_\theta}{r^2} + \frac{2}{r^2} \frac{\partial v_r}{\partial \theta} \right) - b_\theta &= 0 \\
 \frac{\partial v_z}{\partial t} + v_r \frac{\partial v_z}{\partial r} + \frac{v_\theta}{r} \frac{\partial v_z}{\partial \theta} + v_z \frac{\partial v_z}{\partial z} + \frac{1}{\rho} \frac{\partial p}{\partial z} - \frac{\mu}{\rho} \left(\frac{1}{r} \frac{\partial}{\partial r} \left(r \frac{\partial v_z}{\partial r} \right) + \frac{1}{r^2} \frac{\partial^2 v_z}{\partial \theta^2} + \frac{\partial^2 v_z}{\partial z^2} \right) - b_z &= 0 \\
 \frac{1}{r} \frac{\partial(r v_r)}{\partial r} + \frac{1}{r} \frac{\partial v_\theta}{\partial \theta} + \frac{\partial v_z}{\partial z} &= 0
 \end{aligned}$$

Neglect gravity / body forces: $\mathbf{b} = 0$

Irrotational flow: $v_\theta = 0$ and $\frac{\partial}{\partial \theta} = 0$






Simplified (irrotational, no gravity) Navier-Stokes equations

$$\begin{aligned}\frac{\partial v_r}{\partial t} + v_r \frac{\partial v_r}{\partial r} + v_z \frac{\partial v_r}{\partial z} + \frac{1}{\rho} \frac{\partial p}{\partial r} - \frac{\mu}{\rho} \left(\frac{1}{r} \frac{\partial}{\partial r} \left(r \frac{\partial v_r}{\partial r} \right) + \frac{\partial^2 v_r}{\partial z^2} - \frac{v_r}{r^2} \right) &= 0 \\ \frac{\partial v_z}{\partial t} + v_r \frac{\partial v_z}{\partial r} + v_z \frac{\partial v_z}{\partial z} + \frac{1}{\rho} \frac{\partial p}{\partial z} - \frac{\mu}{\rho} \left(\frac{1}{r} \frac{\partial}{\partial r} \left(r \frac{\partial v_z}{\partial r} \right) + \frac{\partial^2 v_z}{\partial z^2} \right) &= 0 \\ \frac{1}{r} \frac{\partial(r v_r)}{\partial r} + \frac{\partial v_z}{\partial z} &= 0\end{aligned}$$


Neglect gravity / body forces: $\mathbf{b} = 0$


Irrotational flow: $v_\theta = 0$ and $\frac{\partial}{\partial \theta} = 0$






Main idea: Integration over cross-section





Circular cross-section

$$A(z, t) = |S(z, t)| = \pi R^2(z, t)$$




Mean (axial) velocity and velocity profile

$$v_z(r, z, t) = \bar{v}(z, t)s(r^*), \quad \bar{v} := \frac{1}{A} \int_S v_z dA \quad r^* = r/R(z, t)$$

Flow rate

$$Q(z, t) := \int_S v_z dA = A\bar{v}.$$







Simplified (irrotational, no gravity) Navier-Stokes equations

$$\frac{\partial v_r}{\partial t} + v_r \frac{\partial v_r}{\partial r} + v_z \frac{\partial v_r}{\partial z} + \frac{1}{\rho} \frac{\partial p}{\partial r} - \frac{\mu}{\rho} \left(\frac{1}{r} \frac{\partial}{\partial r} \left(r \frac{\partial v_r}{\partial r} \right) + \frac{\partial^2 v_r}{\partial z^2} - \frac{v_r}{r^2} \right) = 0$$

$$\frac{\partial v_z}{\partial t} + v_r \frac{\partial v_z}{\partial r} + v_z \frac{\partial v_z}{\partial z} + \frac{1}{\rho} \frac{\partial p}{\partial z} - \frac{\mu}{\rho} \left(\frac{1}{r} \frac{\partial}{\partial r} \left(r \frac{\partial v_z}{\partial r} \right) + \frac{\partial^2 v_z}{\partial z^2} \right) = 0$$

$$\frac{1}{r} \frac{\partial (r v_r)}{\partial r} + \frac{\partial v_z}{\partial z} = 0$$







Example: mass/volume balance equation

$$\frac{1}{r} \frac{\partial(rv_r)}{\partial r} + \frac{\partial v_z}{\partial z} = 0 \quad \longrightarrow \quad \int_S \frac{1}{r} \frac{\partial(rv_r)}{\partial r} dA + \int_S \frac{\partial v_z}{\partial z} dA = 0$$





Example: mass/volume balance equation



$$\frac{1}{r} \frac{\partial(rv_r)}{\partial r} + \frac{\partial v_z}{\partial z} = 0 \quad \longrightarrow \quad \boxed{\int_S \frac{1}{r} \frac{\partial(rv_r)}{\partial r} dA} + \int_S \frac{\partial v_z}{\partial z} dA = 0$$

$$\int_S \frac{1}{r} \frac{\partial(rv_r)}{\partial r} dA = \int_0^{2\pi} \int_0^R \frac{\partial(rv_r)}{\partial r} dr d\theta$$

area element

$$dA = r dr d\theta$$







Example: mass/volume balance equation

$$\frac{1}{r} \frac{\partial(rv_r)}{\partial r} + \frac{\partial v_z}{\partial z} = 0 \quad \longrightarrow \quad \boxed{\int_S \frac{1}{r} \frac{\partial(rv_r)}{\partial r} dA} + \int_S \frac{\partial v_z}{\partial z} dA = 0$$

$$\int_S \frac{1}{r} \frac{\partial(rv_r)}{\partial r} dA = \int_0^{2\pi} \int_0^R \frac{\partial(rv_r)}{\partial r} dr d\theta = 2\pi R v_r(R, t) \quad v_r \text{ independent of } \theta$$






Example: mass/volume balance equation


$$\frac{1}{r} \frac{\partial(rv_r)}{\partial r} + \frac{\partial v_z}{\partial z} = 0 \quad \longrightarrow \quad \boxed{\int_S \frac{1}{r} \frac{\partial(rv_r)}{\partial r} dA} + \int_S \frac{\partial v_z}{\partial z} dA = 0$$

$$\int_S \frac{1}{r} \frac{\partial(rv_r)}{\partial r} dA = \int_0^{2\pi} \int_0^R \frac{\partial(rv_r)}{\partial r} dr d\theta = 2\pi R v_r(R, t) = 2\pi R \frac{\partial R}{\partial t}$$



boundary condition:
 v_r at $r=R$ is wall velocity $\frac{\partial R}{\partial t}$







Example: mass/volume balance equation

$$\frac{1}{r} \frac{\partial(rv_r)}{\partial r} + \frac{\partial v_z}{\partial z} = 0 \quad \longrightarrow \quad \boxed{\int_S \frac{1}{r} \frac{\partial(rv_r)}{\partial r} dA} + \int_S \frac{\partial v_z}{\partial z} dA = 0$$

$$\int_S \frac{1}{r} \frac{\partial(rv_r)}{\partial r} dA = \int_0^{2\pi} \int_0^R \frac{\partial(rv_r)}{\partial r} dr d\theta = 2\pi R \underbrace{v_r(R, t)}_{=\partial R/\partial t} = 2\pi R \frac{\partial R}{\partial t} = \frac{\partial(\pi R^2)}{\partial t} \boxed{= \frac{\partial A}{\partial t}}$$

use chain rule or product rule







Example: mass/volume balance equation

$$\frac{1}{r} \frac{\partial(rv_r)}{\partial r} + \frac{\partial v_z}{\partial z} = 0 \quad \longrightarrow \quad \int_S \frac{1}{r} \frac{\partial(rv_r)}{\partial r} dA + \boxed{\int_S \frac{\partial v_z}{\partial z} dA} = 0$$





Example: mass/volume balance equation

$$\frac{1}{r} \frac{\partial(rv_r)}{\partial r} + \frac{\partial v_z}{\partial z} = 0 \quad \longrightarrow \quad \int_S \frac{1}{r} \frac{\partial(rv_r)}{\partial r} dA + \boxed{\int_S \frac{\partial v_z}{\partial z} dA} = 0$$



Leibniz' rule for parameter integral

$$\frac{d}{dz} \left(\int_{a(z)}^{b(z)} f(z, r, t) dr \right) = \underbrace{\int_{a(z)}^{b(z)} \frac{\partial}{\partial z} f(z, r, t) dr}_{\text{bounds constant}} + \underbrace{f(z, b(z), t) \frac{d}{dz} b(z) - f(z, a(z), t) \frac{d}{dz} a(z)}_{\text{change due to changes in bounds}}$$

bounds constant

change due to changes in bounds







Example: mass/volume balance equation

$$\frac{1}{r} \frac{\partial(rv_r)}{\partial r} + \frac{\partial v_z}{\partial z} = 0 \quad \longrightarrow \quad \int_S \frac{1}{r} \frac{\partial(rv_r)}{\partial r} dA + \boxed{\int_S \frac{\partial v_z}{\partial z} dA} = 0$$

$$\int_S \frac{\partial u_z}{\partial z} dA = \int_0^{R(z)} \int_0^{2\pi} \frac{\partial u_z}{\partial z} r d\theta dr = \int_0^{R(z)} \frac{\partial}{\partial z} \left(\int_0^{2\pi} u_z r d\theta \right) dr$$







Example: mass/volume balance equation

$$\frac{1}{r} \frac{\partial(rv_r)}{\partial r} + \frac{\partial v_z}{\partial z} = 0 \quad \longrightarrow \quad \int_S \frac{1}{r} \frac{\partial(rv_r)}{\partial r} dA + \boxed{\int_S \frac{\partial v_z}{\partial z} dA} = 0$$

$$\int_S \frac{\partial u_z}{\partial z} dA = \int_0^{R(z)} \int_0^{2\pi} \frac{\partial u_z}{\partial z} r d\theta dr = \int_0^{R(z)} \frac{\partial}{\partial z} \left(\int_0^{2\pi} u_z r d\theta \right) dr = \int_0^{R(z)} \frac{\partial g}{\partial z} dr$$

$$g(z, r, t) := \int_0^{2\pi} v_z r d\theta = 2\pi v_z r$$





Example: mass/volume balance equation

$$\frac{1}{r} \frac{\partial(rv_r)}{\partial r} + \frac{\partial v_z}{\partial z} = 0 \quad \longrightarrow \quad \int_S \frac{1}{r} \frac{\partial(rv_r)}{\partial r} dA + \boxed{\int_S \frac{\partial v_z}{\partial z} dA} = 0$$

$$\int_S \frac{\partial u_z}{\partial z} dA = \int_0^{R(z)} \int_0^{2\pi} \frac{\partial u_z}{\partial z} r d\theta dr = \int_0^{R(z)} \frac{\partial}{\partial z} \left(\int_0^{2\pi} u_z r d\theta \right) dr = \int_0^{R(z)} \frac{\partial g}{\partial z} dr$$



(Leibniz' rule)

$$= \frac{d}{dz} \left(\int_0^{R(z)} g dr \right) - g(z, R(z), t) \frac{dR(z)}{dz} + g(z, 0, t) \frac{d0}{dz}$$

$$g(z, r, t) := \int_0^{2\pi} v_z r d\theta = 2\pi v_z r$$

$$= \frac{d}{dz} \left(\int_S u_z dA \right) - 2\pi R u_z(t, R) \frac{\partial R}{\partial z}$$





Example: mass/volume balance equation

$$\frac{1}{r} \frac{\partial(rv_r)}{\partial r} + \frac{\partial v_z}{\partial z} = 0 \quad \longrightarrow \quad \int_S \frac{1}{r} \frac{\partial(rv_r)}{\partial r} dA + \boxed{\int_S \frac{\partial v_z}{\partial z} dA} = 0$$

$$\int_S \frac{\partial u_z}{\partial z} dA = \int_0^{R(z)} \int_0^{2\pi} \frac{\partial u_z}{\partial z} r d\theta dr = \int_0^{R(z)} \frac{\partial}{\partial z} \left(\int_0^{2\pi} u_z r d\theta \right) dr = \int_0^{R(z)} \frac{\partial g}{\partial z} dr$$



(Leibniz' rule)

$$= \frac{d}{dz} \left(\int_0^{R(z)} g dr \right) - g(z, R(z), t) \frac{dR(z)}{dz} + g(z, 0, t) \frac{d0}{dz}$$

$$g(z, r, t) := \int_0^{2\pi} v_z r d\theta = 2\pi v_z r$$

$$= \frac{d}{dz} \left(\int_S u_z dA \right) - 2\pi R u_z(t, R) \frac{\partial R}{\partial z}$$

what is $u_z(R, t)$? 



Example: mass/volume balance equation

$$\frac{1}{r} \frac{\partial(rv_r)}{\partial r} + \frac{\partial v_z}{\partial z} = 0 \quad \longrightarrow \quad \int_S \frac{1}{r} \frac{\partial(rv_r)}{\partial r} dA + \boxed{\int_S \frac{\partial v_z}{\partial z} dA} = 0$$

$$\int_S \frac{\partial u_z}{\partial z} dA = \int_0^{R(z)} \int_0^{2\pi} \frac{\partial u_z}{\partial z} r d\theta dr = \int_0^{R(z)} \frac{\partial}{\partial z} \left(\int_0^{2\pi} u_z r d\theta \right) dr = \int_0^{R(z)} \frac{\partial g}{\partial z} dr$$


(Leibniz' rule)



$$= \frac{d}{dz} \left(\int_0^{R(z)} g dr \right) - g(z, R(z), t) \frac{dR(z)}{dz} + g(z, 0, t) \frac{d0}{dz}$$

$$= \frac{d}{dz} \left(\int_S u_z dA \right) - 2\pi R u_z(t, R) \frac{\partial R}{\partial z}$$

$$g(z, r, t) := \int_0^{2\pi} v_z r d\theta = 2\pi v_z r$$

boundary condition:
 v_z at $r=R$ is 0 (no-slip)







Example: mass/volume balance equation

$$\frac{1}{r} \frac{\partial(rv_r)}{\partial r} + \frac{\partial v_z}{\partial z} = 0 \quad \longrightarrow \quad \int_S \frac{1}{r} \frac{\partial(rv_r)}{\partial r} dA + \boxed{\int_S \frac{\partial v_z}{\partial z} dA} = 0$$

$$\begin{aligned} \int_S \frac{\partial u_z}{\partial z} dA &= \frac{d}{dz} \left(\int_S u_z dA \right) - \underbrace{2\pi R u_z(t, R)}_{=0} \frac{\partial R}{\partial z} \\ &= \frac{\partial Q}{\partial z}, \end{aligned}$$

boundary condition:
 v_z at $r=R$ is 0 (no-slip)






Mass balance (summary)

$$\frac{1}{r} \frac{\partial(rv_r)}{\partial r} + \frac{\partial v_z}{\partial z} = 0 \quad \longrightarrow \quad \int_S \frac{1}{r} \frac{\partial(rv_r)}{\partial r} dA + \int_S \frac{\partial v_z}{\partial z} dA = 0$$

$$\longrightarrow \frac{\partial A}{\partial t} + \frac{\partial Q}{\partial z} = 0$$

1. boundary condition:
 v_r at $r=R$ is wall velocity $\frac{\partial R}{\partial t}$
2. boundary condition:
 v_z at $r=R$ is 0 (no-slip)





Momentum balance

$$\frac{\partial Q}{\partial t} + \frac{\partial}{\partial z} \left(\alpha \frac{Q^2}{A} \right) + \frac{A}{\rho} \frac{\partial p}{\partial z} + K_R \frac{Q}{A} = 0,$$

$$v_z(r, z, t) = \bar{v}(z, t) s(r^*)$$

$$\alpha := \frac{\int_S v_z^2 dA}{A \bar{v}^2} = \frac{1}{A} \int_S s^2 dA,$$


$$K_R = -2\pi \frac{\mu}{\rho} s'(1)$$


typical choice: power law profile

$$v_z(r, z, t) = \bar{v}(z, t) s(r^*) = \bar{v}(z, t) \frac{\gamma + 2}{\gamma} [1 - (r^*)^\gamma] = \bar{v}(z, t) \frac{\gamma + 2}{\gamma} \left[1 - \left(\frac{r}{R} \right)^\gamma \right]$$

$$K_R = -2\pi \frac{\mu}{\rho} s'(1) = 2\pi \frac{\mu}{\rho} (\gamma + 2), \quad \gamma = \frac{2 - \alpha}{\alpha - 1}$$

(no boundary layer effects, small Womersley numbers)





1D Equations (summary)


$$\frac{\partial A}{\partial t} + \frac{\partial Q}{\partial z} = 0, \quad \text{mass balance}$$

$$\frac{\partial Q}{\partial t} + \frac{\partial}{\partial z} \left(\alpha \frac{Q^2}{A} \right) + \frac{A}{\rho} \frac{\partial p}{\partial z} + K_R \frac{Q}{A} = 0, \quad \text{momentum balance}$$



3 unknowns (A, Q, p), 2 equations

**→ Find relationship between A and p
(closure model)**






Closure model





$$F_{p\theta} = 2R_0p = 2h_0\sigma_{\theta\theta} = F_{\sigma\theta}$$

$$\Rightarrow \sigma_{\theta\theta} = \frac{pR_0}{h_0}$$





Closure model




$$F_{pr} = \pi R_0 p = -\pi R_0 \sigma_{rr} = F_{\sigma r}$$


$$\Rightarrow \sigma_{rr} = -p$$

$$h_0 \ll R_0,$$





Closure model



$$F_{pr} = \pi R_0 p = -\pi R_0 \sigma_{rr} = F_{\sigma r}$$

$$\Rightarrow \sigma_{rr} = -p$$

$$F_{p\theta} = 2R_0 p = 2h_0 \sigma_{\theta\theta} = F_{\sigma\theta}$$


$$\Rightarrow \sigma_{\theta\theta} = \frac{pR_0}{h_0}$$

$$h_0 \ll R_0 \quad \longrightarrow \quad \sigma_{rr} \ll \sigma_{\theta\theta}$$

**assumption on
axial strain**


$$\epsilon_{zz} \approx 0$$





Closure model

Hooke's law



$$\epsilon_{ij} = \frac{1}{E} [(1 + \nu)\sigma_{ij} - \nu\delta_{ij}\sigma_{kk}]$$

$$\epsilon_{\theta\theta} = \frac{1}{E} [\sigma_{\theta\theta} - \nu(\sigma_{rr} + \sigma_{zz})] \approx \frac{1}{E} [\sigma_{\theta\theta} - \nu\sigma_{zz}],$$

$$\epsilon_{zz} = \frac{1}{E} [\sigma_{zz} - \nu(\sigma_{\theta\theta} + \sigma_{rr})] \approx \frac{1}{E} [\sigma_{zz} - \nu\sigma_{\theta\theta}] \approx 0.$$


$$\epsilon_{\theta\theta} \approx \frac{1}{E} [\sigma_{\theta\theta} - \nu^2\sigma_{\theta\theta}] = \frac{(1 - \nu^2)}{E} \sigma_{\theta\theta} = \frac{(1 - \nu^2)}{E} \frac{pR_0}{h_0}$$

$$\sigma_{rr} \ll \sigma_{\theta\theta} \quad \epsilon_{zz} \approx 0 \quad \sigma_{\theta\theta} = \frac{pR_0}{h_0}$$


$$\Delta p = p - P_{ext} = \frac{(1 - \nu^2)}{E} \frac{\Delta p R_0}{h_0}$$

relative pressure, generalize






Closure model



$$\epsilon_{\theta\theta} = \frac{R - R_0}{R_0} \frac{2\pi}{2\pi}$$

$$\epsilon_{\theta\theta} \approx \frac{(1 - \nu^2)}{E} \frac{p R_0}{h_0}$$

$$p = P_{ext} + \frac{E h_0}{(1 - \nu^2) R_0} \epsilon_{\theta\theta} = P_{ext} + \frac{E h_0}{(1 - \nu^2) R_0} \frac{R - R_0}{R_0} = P_{ext} + \frac{\sqrt{\pi} E h_0}{(1 - \nu^2) \sqrt{A_0}} \left(\sqrt{\frac{A}{A_0}} - 1 \right)$$



1D Equations (summary again)

$$\frac{\partial A}{\partial t} + \frac{\partial Q}{\partial z} = 0,$$

mass balance


$$\frac{\partial Q}{\partial t} + \frac{\partial}{\partial z} \left(\alpha \frac{Q^2}{A} \right) + \frac{A}{\rho} \frac{\partial p}{\partial z} + K_R \frac{Q}{A} = 0,$$

momentum balance

$$p = P_{\text{ext}} + G_0 \left(\sqrt{\frac{A}{A_0}} - 1 \right) \quad G_0 = \frac{\sqrt{\pi} E h_0}{(1 - \nu^2) \sqrt{A_0}}$$

closure model





1D Equations (transport form)

Transport system of equations with flux function \mathbf{F} and source term \mathbf{S} :


$$\frac{\partial \mathbf{U}}{\partial t} + \frac{\partial \mathbf{F}}{\partial z} (\mathbf{U}) = \mathbf{S} (\mathbf{U}), \quad z \in (0, l), \quad t > 0$$

$$\mathbf{U} = \begin{pmatrix} A \\ Q \end{pmatrix}, \quad \mathbf{F} (\mathbf{U}) = \begin{pmatrix} Q \\ \frac{Q^2}{A} + \frac{G_0 A^{3/2}}{3\rho A_0^{1/2}} \end{pmatrix}, \quad \mathbf{S} (\mathbf{U}) = \begin{pmatrix} 0 \\ -K_R \frac{Q}{A} \end{pmatrix}$$

$$G_0 = \frac{\sqrt{\pi} E h_0}{(1 - \nu^2) \sqrt{A_0}}$$

(simplified for constant parameters, for varying parameters see lecture notes)





Literature

John, L., P. Pustějovská, and O. Steinbach. "On the influence of the wall shear stress vector form on hemodynamic indicators." *Computing and Visualization in Science* 18.4-5 (2017): 113-122

D'Angelo, Carlo. "Multiscale modelling of metabolism and transport phenomena in living tissues." *Bibliothèque de l'EPFL, Lausanne* (2007)


Čanić, Sunčica, and Eun Heui Kim. "Mathematical analysis of the quasilinear effects in a hyperbolic model blood flow through compliant axi-symmetric vessels." *Mathematical Methods in the Applied Sciences* 26.14 (2003): 1161-1186

Westerhof, Nicolaas, et al. "Analog studies of the human systemic arterial tree." *Journal of biomechanics* 2.2 (1969): 121IN1135IN3137IN5139-134136138143

Olufsen, Mette S. "Structured tree outflow condition for blood flow in larger systemic arteries." *American journal of physiology-Heart and circulatory physiology* 276.1 (1999): H257-H268

Fernández, Miguel Ángel, Vuk Milisic, and Alfio Quarteroni. "Analysis of a geometrical multiscale blood flow model based on the coupling of ODEs and hyperbolic PDEs." *Multiscale Modeling & Simulation* 4.1 (2005): 215-236






Literature

Köppl, T., Schneider, M., Pohl, U., & Wohlmuth, B. (2014). The influence of an unilateral carotid artery stenosis on brain oxygenation. *Medical engineering & physics*, 36(7), 905-914

Galdi, G., Rannacher, R., Robertson, A., Turek, S.: *Hemodynamical Flows: Modeling, Analysis and Simulation*, vol. 37. Birkhäuser, Basel (2008)





University of Stuttgart

Institute for Modelling Hydraulic and Environmental Systems

Thank you!



<https://www.iws.uni-stuttgart.de/lh2/>

Timo Koch (Oslo)

e-mail timokoch@uio.no

University of Stuttgart
Pfaffenwaldring 61, 70569 Stuttgart

**Institute for Modelling Hydraulic
and Environmental Systems,**


**Department of Hydromechanics
and Modelling of Hydrosystems**



SFB 1313

sfb1313.uni-stuttgart.de

Interface-Driven Multi-Field
Processes in Porous Media



DuMu^x

dumux.org



<http://dune-project.org/>