
Assignment

Setup

Virtual machine

In the given [.zip](#)-File is an OVF template to create a virtual machine. You can import the given template either to VirtualBox or VMWare Player. No special setup is required.

The virtual machine is configured to log you in automatically. You'll find a link to Git repository on the desktop when the virtual machine is up and running.

Side note: It's recommended to pull the repository before starting the assignment as it might be the case that there are outstanding changes!

Docker

If you don't want to use the virtual machine, or if you just prefer to use Docker, you can use the image `knsit/yarn` to avoid the Installation of the whole toolchain (Node.js, Yarn). Just navigate to the `assignment` directory in the Git repository and run the container like this (Linux/Mac):

```
1 docker run --name yarn --rm -v "$PWD":/home/yarn knsit/yarn:1.3.2 run dev
```

or Windows:

```
1 docker run --name yarn -v "%((pwd).Path):/home/yarn" --rm -p 8080:8080 knsit/yarn:1.3.2 run dev
```

As editor/IDE we recommend to use Visual Studio Code with the following plugins:

- EditorConfig for VS Code
- TSLint Vue
- Vue TypeScript Snippets
- yarn

The plugins are not required but they would make it easier.

Dev-Server

To run the Dev-Server execute the following command:

```
1 yarn run dev
2 # or if you prefer npm
3 npm run dev
```

No matter if you're using *npm* or *yarn* the task runner should open a new browser tab/window. The tiny web application you're confronted with contains:

- the lecture notes rendered as HTML
- this document which will lead you through this assignment (also rendered as HTML)
- the API spec (OpenAPI) of a custom **Internet Chuck Norris Database** we'll use for one part of the assignment
- Links to the components you have to complete as part of this assignment
- Links to the solutions for all parts of this assignment

Part 1

The first part of the assignment covers the basic Vue.js concepts for databinding like `v-model`, template strings (`{{myVariable}}`), `v-for`, `v-if` and `v-else`.

Have a look at the folder `assignment/src/components/assignments/part1`.

It contains (more or less) a typical Vue.js TypeScript component:

- `index.ts` - controls the exports of the module
- `part1.html` - contains the template rendered with this component
- `part1.scss` - contains styles required **only** for this component (common styles are located in the file `main.scss`)
- `part1.ts` - contains the business logic of the component and imports the `.html` and the `.scss` files

The file `part1.html` contains a tab view with two tabs. One to register your favorite movie actors and one for displaying them as card view. Once you have “submitted” the actor registration form (actually you don't submit anything as we are in a single page application) the actor should show up in the second tab.

The required HTML code is already there but all databindings are missing. Start by binding the form to the properties of the `currentInputActor` in the component. If you are not sure if the binding is working correctly have a look at the browser console. The given model logs the new value of a property everytime a setter is called (of course just for debugging purposes! Don't do that in production!).

If you have no idea how to start have a look at the docs. Or just ask us!

Part 2

The second part deals with TypeScript in general and in combination with Vue.js in particular.

At first have a look at the API spec of the ICNDB integrated in the application. The most interesting endpoint is `/jokes` because we want to fetch from 1 to 500 Chuck Norris jokes and display them once more as card view.

Because writing TypeScript but handling the API responses as objects of type `any` is nonsense start by implementing the required interfaces. We recommend to implement one interface (e.g. `JokesArrayResponse`) as a wrapper for the outer response and one interface (e.g. `Joke`) as wrapper for the concrete inner object.

If you have completed these two interfaces you're ready to implement the HTTP calls to the API. The recommended way to do HTTP communication in Vue.js is to use axios (especially with TypeScript because axios provides typings). Of course you can use other libraries but axios is already installed so it's the fastest way to get started.

When you have logged your first successful responses you're good to go to display the retrieved data. The given template already contains the required markup but some bindings and directives are missing. The *TODO* entries should guide you through this relatively quickly.

Now that you're able to display one joke (the default page size) it's time to adopt the dropdown by adding a click-handler. The handler should pass the new page size to the component and trigger a reload of the items.

Hint: the doc page mentioned in the first part also explains how to register click handlers.

The last thing we want to achieve is that the input fields at the top of the page are used to change the first and last name displayed in the jokes (live of course).

Hint: you might need an extra `Joke` implementation to accomplish this behaviour.

A word about asynchronous calls in TypeScript

Additionally to the classic callback style to handle asynchronous calls (callback hell - yeah!) TypeScript provides a nice feature to await the response and handle it in a (pseudo) synchronous way. The following snippet shows how to use *axios* with TypeScript's `async` and `await`:

```
1 private async doCall() {
2     let url = 'https://icndb.kns-it.de/api/v1/jokes/random';
3     let response: AxiosResponse<JokesArrayResponse> = await this.axios.
        get(url);
4     // ...
```

```
5 }
```

Part 3

You're still here? You don't have any hobbies, do you?

Well, it's time to make your hands **really** dirty!

The last part of the assignment covers the underlying concepts of databinding in Vue.js. (Don't you want to go for a mulled wine after all?)

You have been warned!