

RFQ Number:62923 Rev 03



Power Cables

AL/XLPE/SWA/PVC

0.6/1 kV IEC 60502-1

TECHNICAL INFORMATION

Type of Cable	AL/XLPE/SWA/PVC
Standard Applied to Cable	IEC 60502-1
Rated Voltage	kV0.6/1

CONSTRUCTION

Conductor	
Conductor Type / Standard	Stranded Class 2 according IEC 60228 Sector Shape from sizes 25 mm ² and larger
Material of Conductor	Aluminium
Insulation	
Material of Insulation	XLPE
Insulation Operating Temperature	°C90
Bedding	
Material	PVC
Color	Black
Armouring	
Material Of Armour	Galvanized Steel Wire Armoured (SWA)
Outer Jacket	
Material	PVC
Color	Black

CABLE MARKING

BICC CABLES Size mm2 AL/XLPE/SWA/PVC 0.6/1 kV IEC 60502-1 Manufacturing Year Made for Coast Cables LTD.+ Meter Length.	
Print Type	Ink Jet

TESTS

Routine tests generally to IEC 60502-1
Electrical Resistance of the conductors according to IEC 60228.

CHARACTERISTICS

Thermal performance		Fire performance	
Maximum service temperature	°C90	Flame Retardant Part 1 according IEC 60332-1	
Maximum short-circuit temperature	°C250		
Mechanical performance		Packing	
Minimum bending radius	mm8 x D	>95mm2 ,1000 ± 5% Meter Wooden Drums	
		<95mm2 ,1000 ± 5% Meter Wooden Drums	

CABLE DIMENSIONS

Cable Code		Size (mm2)	Approx. Overall Diameter (mm)	Approx. Weight (Kg/Km)	max. Conductor DC Resistance at 20 °C (Ω/Km)	Current Carrying Capacity (Amp.)			Core Identification
						in Air @30° C	In Ground @20° c	In duct @ 20°c	
1	04C025AT0XC0PWP	4X25	25.7	1195	1.2000	98	119	92	Red, Yellow, Blue, Black
2	04C035CT0XC0PWP	4X35	28.3	1415	0.868	120	139	107	Red, Yellow, Blue, Black
3	04C050CT0XC0PWP	4X50	32	1740	0.641	145	170	131	Red, Yellow, Blue, Black
4	04C070CT0XC0PWP	4X70	36.9	2400	0.443	185	206	160	Red, Yellow, Blue, Black
5	04C120CT0XC0PWP	4X120	45.9	3800	0.253	264	284	224	Red, Yellow, Blue, Black
6	04C150CT0XC0PWP	4X150	50.2	4440	0.206	306	320	247	Red, Yellow, Blue, Black
7	04C240AT0XC0PWP	4X240	61.4	6436	0.1250	418	427	330	Red, Yellow, Blue, Black
8	04C300AT0XC0PWP	4X300	65.8	7220	0.1000	488	479	374	Red, Yellow, Blue, Black

RFQ Number:62923 Rev 03



Power Cables

AL/XLPE/AWA/PVC

0.6/1 kV IEC 60502-1

TECHNICAL INFORMATION

Type of Cable		AL/XLPE/AWA/PVC
Standard Applied to Cable		IEC 60502-1
Rated Voltage	kV	0.6/1

CONSTRUCTION

Conductor		
Conductor Type / Standard		Stranded Class 2 according IEC 60228 Circular Compacted
Material of Conductor		Aluminium
Insulation		
Material of Insulation		XLPE
Insulation Operating Temperature	°C	90
Bedding		
Material		PVC
Armouring		
Material Of Armour		Aluminium Wire Armoured (AWA)
Outer Jacket		
Material		PVC
Color		Black

CABLE MARKING

BICC CABLES Size mm2 AL/XLPE/AWA/PVC 0.6/1 kV IEC 60502-1 Manufacturing Year Made for Coast Cables LTD.+ Meter Length.	
Print Type	Ink Jet

TESTS

Routine tests generally to IEC 60502-1
Electrical Resistance of the conductors according to IEC 60228.

CHARACTERISTICS

Thermal performance			Fire performance	
Maximum service temperature	°C	90	Flame Retardant Part 1 according IEC 60332-1	
Maximum short-circuit temperature	°C	250		
Mechanical performance			Packing	
Minimum bending radius	mm	8 x D	>95mm2 ,1000 ± 5% Meter Wooden Drums <95mm2 ,1000 ± 5% Meter Wooden Drums	

CABLE DIMENSIONS

Cable Code		Size (mm2)	Approx. Overall Diameter (mm)	Approx. Weight (Kg/Km)	Max. Conductor DC Resistance at 20 °C (Ω/Km)	Current Carrying Capacity (Amp.) Trefoil Formation			Core Identification
						in Air @30° C	In Ground@20 °c	In duct @ 20°c	
1	01C300AT0XC0PJP	1X300	33.4	1550	0.1000	448	435	357	Red
2	01C400AT0XC0PJP	1X400	36.9	1960	0.0778	564	509	419	Red
3	01C630AT0XC0PJP	1X630	45.1	2950	0.0469	868	724	625	Red