



View Section: 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16

TURTLE WAX, INC

SUPER HARD SHELL PASTE, T-222(C), T-223(C)

SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MSDS Name: SUPER HARD SHELL PASTE, T-222(C), T-223(C)

Manufacturer Name: TURTLE WAX, INC

Address:

5655 WEST 73RD ST

City: CHICAGO

State:IL

Zip:60638-6211

Country:US

Business Phone: 708-563-3600

For information in North America, call: 708-563-3600 Health Phone: 800-424-9300,SPILL/800-332-3073

Manufacturer MSDS Creation Date:

09/20/1993

To Top of page

SECTION 2: COMPOSITION, INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Percent	
ALIPHATIC PETROLEUM	8008-20-6	6-9	
SOLVENT			

RTECS:

OA5500000

OSHA PEL TWA: NOT ESTABLISHED ACGIH TLV TWA: NOT ESTABLISHED

ACGIH STEL/Ceiling: N/P

Comments:

Other REC Limits: NONE RECOMMENDED; Ozone Depleting Chemical: N;

To Top of page

SECTION 3: HAZARDS IDENTIFICATION

ALIPHATIC PETROLEUM SOLVENT:

Route of Exposure:

Inhalation: YES Skin: YES Ingestion: NO

Potential Health Effects:

INHALATION- IRRITATION, CHEMICAL PNEUMONIA. INTENTIONAL MISUSE HARMFUL. SKIN- CAN CAUSE DEFATTING. EYES- CAUSES IRRITATION. INGESTION- CAUSES DIGESTIVE SYSTEM UPSETS. IF SUCKED INTO LUNGS, EFFECTS ARE SAME AS FOR INHALATION ABOVE. NO CHRONIC EFFECTS.

Carcinogenicity:

NOT APPLICABLE

OSHA Designation: NO NTP Designation: NO IARC Designation: NO

Signs/Symptoms:

INHALATION- DIZZINESS AND NAUSEA. SKIN- BLISTERS OR RASH. EYES-IRRITATION, INGESTION- DIZZINESS AND NAUSEA, MAY BE FATAL.

Aggravation of Pre-Existing Conditions:

NONE SPECIFIED BY MANUFACTURER.

LD 50 LC 50 Mixture UNKNOWN

To Top of page

SECTION 4: FIRST AID MEASURES

First Aid

INHALATION- REMOVE TO FRESH AIR. USE ARTIFICIAL RESPIRATION AND OXYGEN IF NEEDED. SKIN- REMOVE CONTAMINATED CLOTHING, AND AVOID IGNITION SOURCES. WASH EFFECTED AREAS THOROUGHLY WITH SOAP AND WATER. EYES-FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION IF EFFECTS PERSIST. INGESTION- RINSE MOUTH. DO NOT INDUCE VOMITING. GET PROMPT MEDICAL ATTENTION, ESPECIALLY IF SUCKED INTO LUNGS.

To Top of page

SECTION 5: FIRE FIGHTING MEASURES

Flash Point:

>150F,>66C

Flash Point Method:

CC

Upper Flammable or Explosive Limit: N/K Lower Flammable or Explosive Limit: N/K

Auto Ignition Temperature: N/A

Extinguishing Media:

WATER SPRAY, ALCOHOL FOAM, CARBON DIOXIDE, DRY CHEMICAL.

Fire Fighting Instructions:

TREAT AS COMBUSTIBLE LIQUID FIRE, ESPECIALLY WHEN MOLTEN. KEEP UNIGNITED CONTAINERS COOL WITH WATER.

Unusual Fire Hazards:

VAPORS ARE HEAVIER THAN AIR, MAY COLLECT IN LOW AREAS, AND MAY TRAVEL TO DISTANT SOURCES OF IGNITION AND FLASH BACK.

To Top of page

SECTION 6: ACCIDENTAL RELEASE MEASURES

Leak Response:

REMOVE ALL IGNITION SOURCES. PROVIDE GOOD VENTILATION. TAKE UP SPILLS AND PUT INTO CLOSED CONTAINERS. AVOID FLOW TO SEWERS. FLOORS MAY BE SLIPPERY.

Other Precautions:

NONE

Neutralizing Agent

N/R

To Top of page

SECTION 7: HANDLING and STORAGE

Handling:

KEEP AWAY FROM IGNITION OR HEAT SOURCE. STORE IN COOL AND VENTILATED PLACES, BUT AVOID FREEZING. KEEP CONTAINERS CLOSED.

To Top of page

SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

Ventilation System:

PROVIDE GOOD VENTILATION.

Hand Protection Description:

WEAR SOLVENT RESISTANT GLOVES.

Eye/Face Protection:

WEAR GOGGLES.

Respiratory Protection:

USE NIOSH-APPROVED RESPIRATOR APPROPRIATE FOR CONCENTRATION OF VAPOR.

Other Protective:

EYE WASH STATIONS, PROTECTIVE CLOTHING AS NEEDED.

Other:

EMPTY CONTAINERS: RINSE THOROUGHLY BEFORE HANDLING, REUSE OR DISPOSAL.

Work Hygienic Practices

WASH HANDS AFTER HANDLING THIS MATERIAL.

To Top of page

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical State/Appearance:

GREEN CREAM PASTE, TYPICAL SOLVENT ODOR.

pH:

8.5

Decomposition Temperature:

N/K

Vapor Pressure:

N/K

Vapor Density:

N/K

Boiling Point:

N/K

Melting Point: 140-150F

Solubility In Water: DISPERSABLE

Specific Gravity: 1.009

Evaporation Point: N/K

Percent Volatile: 20-25

Viscosity: N/P

Other:

Corrosion Rate: N/K

HCC V4

To Top of page

SECTION 10: STABILITY AND REACTIVITY

Chemical Stability:

YES

Conditions to Avoid:

NONE

Incompatibilities with Other Materials: STRONG OXIDIZERS SUCH AS PEROXIDES.

Hazardous Polymerization:

NO

Hazardous Decomposition Products:

CARBON DIOXIDE, CARBON MONOXIDE, HYDROCARBONS.

Conditions To Avoid Polymerization NOT APPLICABLE

CECTION 44 - TOYTOOLOGICAL INCORMATION	To Top of page
SECTION 11: TOXICOLOGICAL INFORMATION	
Toxicological Paragraph: N/P	
SECTION 12 : ECOLOGICAL INFORMATION	To Top of page
Ecological Paragraph: N/P	
SECTION 13 : DISPOSAL CONSIDERATIONS	To Top of page
Waste Disposal: DISPOSE OF IN ACCORDANCE WITH APPLICABLE LOCAL, STATE AND FE REGULATIONS.	DERAL
SECTION 14: TRANSPORT INFORMATION	To Top of page
Transportation Information: N/P	
SECTION 15: REGULATORY INFORMATION	To Top of page
ALIPHATIC PETROLEUM SOLVENT:	
SARA: N/P	
US Federal: N/P	
State: N/P	
	To Top of page

SECTION 16: ADDITIONAL INFORMATION

MSDS Author:

N/P

Disclaimer:

Please note that although the information, opinions and recommendations contained in these Material Safety Data Sheets are compiled from sources believed to be reliable, we accept no responsibility for the accuracy, sufficiency, or reliability or for any loss or injury resulting from the use of the information. Newly discovered hazards are frequent and this information may not be completely up to date.

Other Information

N/P

Copyright@ 1996-2002 Actio Software Corporation. All Rights Reserved.