

340

MATERIAL SAFETY DATA SHEET

Issued to : WRS Group
624 Texas Central Parkway

Waco

TX 76712

Attention of :

Sales Number :
Sales Description Number One :
Sales Description Number Two :

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

CHEMICAL PRODUCT IDENTIFICATION:

PRODUCT ID : RV-53477
PRODUCT DESCRIPTION : OLIVE GREEN #10
TRADE NAME : COLORMATCH
FORMULA ID : RV-53477
FORMULA VERSION NUMBER : 1
PRINT DATE : 06/25/2008

MANUFACTURER IDENTIFICATION:

NAME : PLASTICOLORS, INC.
ADDRESS : 2600 MICHIGAN AVENUE
ASHTABULA OH 44004

TELEPHONE : 440-997-5137
EMERGENCY CONTACT : Chemtrec
EMERGENCY TELEPHONE : (800) 424-9300

HMIS INFORMATION:

Health - 1 Flammability - 1 Reactivity - 0

SECTION 2 - COMPOSITION, INFORMATION ON INGREDIENTS

1

CAS# PROPRIETARY

Polyester Resin

PCT BY WT: 5-10%

EXPOSURE LIMIT:

OSHA PEL

None established.

ACGIH TLV

None established.

PLASTICOLORS, INC.
MATERIAL SAFETY DATA SHEET

RV-53477

This product contains no reported carcinogens or suspected
carcinogens.

This product contains pigments which may become a dust nuisance when
removed by abrasive blasting, sanding, or grinding.

SECTION 3 - HAZARDS IDENTIFICATION

CAUTION! : May cause skin and eye irritation

POTENTIAL HEALTH EFFECTS:

ACUTE EFFECTS:

EYE:

Exposure can cause eye irritation. Symptoms may include stinging,
tearing, redness, and swelling.

SKIN:

Exposure may cause mild skin irritation. Symptoms may include redness
and burning.

INHALATION:

Breathing of vapor or mist is possible. Breathing aerosol and/or mist
is possible when material is sprayed. Aerosol and mist may present
a greater risk of injury because more material may be present in the
air than from vapor alone. Breathing small amounts of this material
during normal handling is not likely to cause harmful effects.
Breathing large amounts may be harmful. Symptoms usually occur at air
concentrations higher than the recommended exposure limits. May cause
temporary respiratory irritation.

INGESTION:

May cause central nervous system depression.

CHRONIC EFFECTS:

EYE:

No harmful effects by chronic exposure reported.

INGESTION:

No harmful effects by chronic exposure reported.

INHALATION:

PLASTICOLORS, INC.
MATERIAL SAFETY DATA SHEET

RV-53477

With repeated and prolonged exposure at high concentrations, these fumes and vapors could cause nausea, drowsiness and headache.

SKIN:

May be harmful if absorbed through the skin.

MEDICAL CONDITIONS AGGRAVATED

May aggravate pre-existing skin disorders.

Due to the presence of some component(s) (**)

Contains surfactant which, based on studies with rabbits involving the sustained occluded contact of the undiluted surfactant with skin, indicate that such conditions may result in the development of inflammatory changes in the lung.

Previous respiratory impairments.

CARCINOGENICITY:

SECTION 4 - FIRST AID MEASURES

NOTE TO PHYSICIAN:

Flush eyes immediately with large amounts of water for at least 15 minutes. Flush under both upper and lower lids. Seek medical aid. Wash from skin with soap and water. If irritation develops, seek medical aid. Wash contaminated clothing before reuse. If inhaled, remove person to fresh air and aid in breathing if necessary. Seek medical aid. If ingested, seek medical aid.

SECTION 5 - FIRE FIGHTING MEASURES

FIRE AND EXPLOSIVE PROPERTIES OF THE CHEMICAL: Emits toxic fumes under fire conditions

| | | | |
|---------------------------|---|-------|--------|
| Flashpoint | : | 225.0 | °F |
| Explosion Level | : | Low | - -N/A |
| | | High | - -N/A |

EXTINGUISHING MEDIA:

CO2, foam, dry chemical.

Water may be ineffective but can be used to cool containers exposed

PLASTICOLORS, INC.
MATERIAL SAFETY DATA SHEET

RV-53477

to heat or flame. Caution should be exercised when using water or foam as frothing may occur.

Water or foam may cause frothing which can be violent and possibly endanger the life of the firefighter. Water may be used to cool fire exposed containers. Wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS.

FIRE-FIGHTING PROCEDURES AND EQUIPMENTS:

Firefighters must wear NIOSH-approved self-contained breathing apparatus and full protective equipment.

Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Do not use water for spill clean-up. Sweep with natural bristle broom. Pick up material with non-sparkling shovel. Place in dry disposal containers.

Always dispose of in accordance with local, state and federal regulations.

SECTION 7 - HANDLING AND STORAGE

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed.

If used in dry form, use proper grounding techniques when emptying contents from package. Failure to use proper grounding techniques may result in build-up of hazardous electrostatic charges which could cause flash fire or explosion.

PLASTICOLORS, INC.
MATERIAL SAFETY DATA SHEET

RV-53477

Store in closed properly labeled containers away from heat, open flames and strong oxidizers.

Surfactants can cause foaming problems in biological wastewater treatment plants and other high shear operations.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION

EYE PROTECTION:

Chemical safety goggles and/or face shield.

RESPIRATORY PROTECTION:

Not required under normal conditions of use.

If the OSHA PEL, ACGIH TLV, or any other TLV for any component listed in Section II is exceeded, use NIOSH approved air-purifying respirator.

SKIN PROTECTION:

Chemically resistant, impervious shoes or boots. Other protective clothing to prevent skin contact.

ENGINEERING CONTROLS:

Use ventilation adequate to maintain safe levels.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

| | | |
|-------------------------------------|---|-----------------|
| Physical Appearance | : | PIGMENTED PASTE |
| Odor | : | SLIGHT TO NONE |
| Vapor Pressure | : | .35 |
| Specific Gravity | : | 1.787 |
| Formula Weight per Volume | : | 14.8754 LBS/GAL |

SECTION 10 - STABILITY AND REACTIVITY

INCOMPATIBILITIES:

Strong acids, strong alkali (bases), peroxides, and other oxidizers.

Strong oxidizers.

It is incompatible with hydrazine, calcium hypochlorite, performic

PLASTICOLORS, INC.
MATERIAL SAFETY DATA SHEET

RV-53477

acid, and bromine pentafluoride.

Avoid contact with strong acids, strong alkalies, strong oxidizing agents.

DECOMPOSITION:

Carbon monoxide, carbon dioxide, various hydrocarbons.

Oxides of nitrogen.

CONDITIONS TO AVOID:

Avoid contact with strong acids.

Excessive heat, flame and other possible ignition sources.

Accumulation of static charges.

POLYMERIZATION:

Product will not undergo hazardous polymerization.

STABILITY:

Stable

SECTION 11 - TOXICOLOGICAL INFORMATION

Not Evaluated at this time.

SECTION 12 - TRANSPORT INFORMATION

No Data

SECTION 13 - REGULATORY INFORMATION

DISPOSAL CONSIDERATIONS:

In a licensed, permitted facility, incinerate or landfill as a solid after cementation or encapsulation. Do not discharge into waterways or sewer systems. Spilled material, empty containers and unused contents must be disposed of in accordance with applicable local, state, and federal regulations.

OTHER REGULATIONS:

PLASTICOLORS, INC.
MATERIAL SAFETY DATA SHEET

RV-53477

Due to the presence of some component(s) (**)
This component is subject to Pennsylvania Right-to-Know disclosure requirements.

Due to the presence of some component(s) (**)
This component is subject to New Jersey Right-to-Know disclosure requirements.

TSCA Status:

TSCA (United States) The intentional ingredients of this product are listed.

Due to the presence of some component(s) (**)
This component is subject to Minnesota Right-to-Know disclosure requirements.

SARA 313 INFORMATION:

This product contains NONE of the substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

SECTION 14 - OTHER INFORMATION

Prepared by : K. EGLINTON
Last Revision Date : NONE
MSDS Prepared for : WRS Group
624 Texas Central Parkway

Waco

TX 76712

The information contained herein is presented in good faith and is based on data believed to be accurate. However, no warranty is expressed or implied regarding this information or the results obtained from the use of this Material Safety Data Sheet whether it originated with Plasticolors, Inc. or not. This Material Safety Data Sheet relates only to the specific material designated herein and does not relate to use with any other material or in any process. This information is supplied upon the condition that the user will make the appropriate determination as to its suitability for their purposes prior to use. Plasticolors, Inc. assumes no legal responsibility


PLASTICOLORS, INC.
MATERIAL SAFETY DATA SHEET

RV-53477

for use or reliance upon this information.

This information must be included in all MSDSs that are copied and distributed for this material.

PLASTICOLORS, INC.
P.O. BOX 816
ASHTABULA, OH 44005-0816
(440) 997-5137



US POSTAGE
\$ 00.59

Mailed From 44004
06/18/2008
031A 0002310171

MATERIAL SAFETY DATA SHEET

MS. TERRI DAWSON
WRS GROUP
624 TEXAS CENTRAL PARKWAY
WACO, TX 76712