



Paints

MATERIAL SAFETY DATA SHEET

prepared 12/03/01

LIQUID NAILS ADHESIVE FOR PROJECTS & CONSTRUCTION

ICI Paints North America

925 Euclid Avenue Cleveland, Ohio 44115

EMERGENCY TELEPHONE NO. (800) 545-2643

169

LN601

HAZARDS IDENTIFICATION (ANSI Section 3)

Primary route(s) of exposure : Inhalation, skin contact, eye contact, ingestion.

Effects of overexposure :

Inhalation : Irritation of respiratory tract. Prolonged inhalation may lead to loss of appetite, mucous membrane irritation, fatigue, drowsiness, dizziness and/or lightheadedness, headache, uncoordination, nausea, vomiting, coughing, central nervous system depression, intoxication, anesthetic effect or narcosis, difficulty of breathing, convulsions, loss of consciousness, death.

Skin contact : Irritation of skin. Prolonged or repeated contact can cause dermatitis, defatting.

Eye contact : Irritation of eyes. Prolonged or repeated contact can cause conjunctivitis, blurred vision, tearing of eyes, redness of eyes, severe eye irritation.

Ingestion : Ingestion may cause lung inflammation and damage due to aspiration of material into lungs, drowsiness, dizziness and/or lightheadedness, headache, uncoordination, nausea, vomiting, diarrhea, gastro-intestinal disturbances, abdominal pain, central nervous system depression, intoxication, difficulty of breathing, convulsions, paralysis, cardiac failure, death.

Medical conditions aggravated by exposure : Eye, skin, respiratory disorders lung disorders respiratory disorders

FIRST-AID MEASURES (ANSI Section 4)

Inhalation : Remove to fresh air. Restore and support continued breathing. Get emergency medical attention. Have trained person give oxygen if necessary. Get medical help for any breathing difficulty.

Skin contact : Flush from skin with water. Then wash thoroughly with soap and water. Remove contaminated clothing. Wash contaminated clothing before re-use.

Eye contact : Flush immediately with large amounts of water, especially under lids for at least 15 minutes. If irritation or other effects persist, obtain medical treatment.

Ingestion : If swallowed, obtain medical treatment immediately.

FIRE-FIGHTING MEASURES (ANSI Section 5)

Fire extinguishing media : Dry chemical or foam water fog. Carbon dioxide. Closed containers may explode when exposed to extreme heat or fire. Vapors may ignite explosively at ambient temperatures. Vapors are heavier than air and may travel long distances to a source of ignition and flash back. Vapors can form explosive mixtures in air at elevated temperatures. Closed containers may burst if exposed to extreme heat or fire. May decompose under fire conditions emitting irritant and/or toxic gases.

Fire fighting procedures : Water may be used to cool and protect exposed containers. Firefighters should use full protective clothing, eye protection, and self-contained breathing apparatus.

Hazardous decomposition or combustion products : Carbon monoxide, carbon dioxide, toxic gases. Oxides of calcium

ACCIDENTAL RELEASE MEASURES (ANSI Section 6)

Steps to be taken in case material is released or spilled : Comply with all applicable health and environmental regulations. Eliminate all sources of ignition. Ventilate area with explosion-proof equipment. Use non-sparking tools. Evacuate all unnecessary personnel. Place collected material in proper container. Complete personal protective equipment must be used during cleanup. Large spills - shut off leak if safe to do so. Dike and contain spill. Pump to storage or salvage vessels. Use absorbent to pick up excess residue. Keep salvageable material and rinse water out of sewers and water courses. Small spills - use absorbent to pick up residue and dispose of properly.

HANDLING AND STORAGE (ANSI Section 7)

Handling and storage : Store below 80°F. Keep away from heat, sparks and open flame.

Other precautions : Use only with adequate ventilation. Do not take internally. Keep out of reach of children. Avoid contact with skin and eyes, and breathing of vapors. Wash hands thoroughly after handling, especially before eating or smoking. Keep containers tightly closed and upright when not in use. Empty containers may contain hazardous residues. Ground equipment when transferring to prevent accumulation of static charge.

EXPOSURE CONTROLS/PERSONAL PROTECTION (ANSI Section 8)

Respiratory protection : Control environmental concentrations below applicable exposure standards when using this material. When respiratory protection is determined to be necessary, use a NIOSH/MSHA (Canadian 294.4) Approved elastomeric sealing-surface facepiece respirator outfitted with organic vapor cartridges and paint spray (dust/mist) prefilters. Determine the proper level of protection by conducting appropriate air monitoring. Consult 29CFR1910.134 For selection of respirators (Canadian 294.4).

Ventilation : Provide dilution ventilation or local exhaust to prevent build-up of vapors. Use explosion-proof equipment. Use non-sparking equipment.

Personal protective equipment : Eye wash, safety shower, safety glasses or goggles. Impervious gloves, impervious clothing.

STABILITY AND REACTIVITY (ANSI Section 10)

Under normal conditions : Stable see section 5 fire fighting measures

Materials to avoid : Oxidizers, acids, Styrene monomer

Conditions to avoid : Elevated temperatures, contact with oxidizing agent, sparks, open flame, ignition sources.

Hazardous polymerization : Will not occur

TOXICOLOGICAL INFORMATION (ANSI Section 11)

Supplemental health information : Contains a chemical that may be absorbed through skin. Notice - reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Other effects of overexposure may include toxicity to central nervous system.

Carcinogenicity : Contains crystalline silica which is considered a hazard by inhalation. IARC has classified crystalline silica as carcinogenic to humans (group 1). Crystalline silica is also a known cause of silicosis, a noncancerous lung disease. The national toxicology program (NTP) has classified crystalline silica as a known human carcinogen.

Reproductive effects : No reproductive effects are anticipated

Mutagenicity : No mutagenic effects are anticipated

Teratogenicity : No teratogenic effects are anticipated

ECOLOGICAL INFORMATION (ANSI Section 12)

No ecological testing has been done by ICI paints on this product as a whole.

DISPOSAL CONSIDERATIONS (ANSI Section 13)

Waste disposal : Dispose in accordance with all applicable regulations. Avoid discharge to natural waters.

The information contained herein is based on data available at the time of preparation of this data sheet which ICI Paints believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. ICI Paints shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and the users of this material. Complies with OSHA hazard communication standard 29CFR1910.1200.

REGULATORY INFORMATION

(ANSI Section 15)

As of the date of this MSDS, all of the components in this product are listed (or are otherwise exempt from listing) on the TSCA inventory. This product has been classified in accordance with the hazard criteria of the CPR (controlled products regulations) and the MSDS contains all the information required by the CPR.

Physical Data

(ANSI Sections 1, 9, and 14)

Product Code	Description	Wt. / Gal.	VOC gr. / ltr.	% Volatile by Volume	Flash Point	Boiling Range	HMIS	DOT, proper shipping name
AHE60101T NO	In-601, liquid nails adhesive for projects and construction	9.43	400.04	57.58	1 f	122-185	*240	adhesives,3,UN1133,PGIII
AHE60112T NO	In-601, liquid nails adhesive for projects and construction	9.43	400.04	57.58	1 f	122-185	*240	adhesives,3,UN1133,PGIII
AHE60124T NO	In-601, liquid nails adhesive for projects and construction	9.43	400.04	57.58	1 f	122-185	*240	adhesives,3,UN1133,PGIII

Ingredients

Product Codes with % by Weight (ANSI Section 2)

Chemical Name	Common Name	CAS. No.	AHE60101T NO	AHE60112T NO	AHE60124T NO
2-methylpentane	2-methylpentane	107-83-5	5-10	5-10	5-10
limestone	limestone	1317-85-3	20-30	20-30	20-30
kaolin	clay	1332-58-7	20-30	20-30	20-30
quartz	quartz	14808-60-7	1-10	1-10	1-10
benzene, 1,3-diethyl-, polymer with 1,3-butadiene and ethenylbenzene	styrene-butadiene polymer	26471-45-4	5-10	5-10	5-10
solvent naphtha (petroleum), light aliphatic	light aliphatic solvent naphtha (petroleum)	84742-89-8	10-20	10-20	10-20
distillates (petroleum), steam-cracked, polymers with light steam-cracked petroleum naphtha	aromatic hydrocarbon resin	88410-16-2	10-20	10-20	10-20
2,2-dimethylbutane	dimethylbutane	75-83-2	1-5	1-5	1-5
2,3-dimethylbutane	dimethylbutane	79-29-8	1-5	1-5	1-5
benzene, ethenyl-, polymer with 1,3-butadiene	styrene-butadiene polymer	9003-55-8	1-5	1-5	1-5
3-methylpentane	3-methyl pentane	98-14-0	1-5	1-5	1-5

Chemical Hazard Data

(ANSI Sections 2, 8, 11, and 15)

Common Name	CAS. No.	ACGIH-TLV			OSHA-PEL			S.R. Std.	S2, S3, CC			H, M, N, I, O		
		8-Hour TWA	STEL	C	8-Hour TWA	STEL	C		S2	S3	CC	H	M	N, I, O
2-methylpentane	107-83-5	500 ppm	not est.	1000 ppm	not est.	not est.	not est.	not est.	n	n	n	n	n	n
limestone	1317-85-3	10 mg/m3	not est.	not est.	5 mg/m3	not est.	not est.	not est.	n	n	n	n	n	n
clay	1332-58-7	2 mg/m3	not est.	not est.	5 mg/m3	not est.	not est.	not est.	n	n	n	n	n	n
quartz	14808-60-7	.05 mg/m3	not est.	not est.	0.1 mg/m3	not est.	not est.	not est.	n	n	n	n	y	n
styrene-butadiene polymer	26471-45-4	not est.	not est.	not est.	300 ppm	not est.	not est.	not est.	n	n	n	n	n	n
light aliphatic solvent naphtha (petroleum)	84742-89-8	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n	n	n
aromatic hydrocarbon resin	88410-16-2	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n	n	n
dimethylbutane	75-83-2	500 ppm	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n	n	n
dimethylbutane	79-29-8	500 ppm	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n	n	n
styrene-butadiene polymer	9003-55-8	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n	n	n
3-methyl pentane	98-14-0	500 ppm	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n	n	n

Footnotes:

C=Skin - Additional exposure, over and above airborn exposure, may result from skin absorption.

n=not applicable
not est=not established
CC=CERCLA Chemical

ppm=parts per million
mg/m3=milligrams per cubic meter
Sup Cont=Supplier Confidential

S2=Sara Section 302 EHS
S3=Sara Section 313 Chemical
S.R.Std.=Supplier Recommended Standard

H=Hazardous Air Pollutant, M=Marine Pollutant
P=Pollutant, S=Severe Pollutant
Carcinogenicity Listed By:
N=NT, I=IARC, O=OSHA, y=yes, n=no