

MATERIAL SAFETY 3M
 DATA SHEET 3M Center
 St. Paul, Minnesota
 55144-1000
 1-800-364-3577 or (651) 737-6501 (24 hours)

Copyright, 2001, Minnesota Mining and Manufacturing Company.
 All rights reserved. Copying and/or downloading of this
 information for the purpose of properly utilizing 3M products
 is allowed provided that:

- 1) the information is copied in full with no changes unless
 prior agreement is obtained from 3M, and
- 2) neither the copy nor the original is resold or otherwise
 distributed with the intention of earning a profit thereon.

DIVISION: ENGINEERED ADHESIVES

TRADE NAME:

3M(TM) Vac-U-Mount 6096

ID NUMBER/U.P.C.:

62-4689-4930-0 00-21200-30072-1 62-4689-4933-4 00-21200-49137-5

62-4689-4936-7 - - -

ISSUED: May 18, 2001

SUPERSEDES: January 19, 2001

DOCUMENT: 07-8162-5

1. INGREDIENT	C.A.S. NO.	PERCENT
PETROLEUM DISTILLATE.....	64742-49-0	35 - 45
PROPANE.....	74-98-6	25 - 35
NON-VOLATILE COMPONENTS - N.J. TRADE		
SECRET REGISTRY NO. 04499600-6167P++..	TradeSecret	10 - 20
ACETONE.....	67-64-1	10 - 20
ISOPROPYL ALCOHOL.....	67-63-0	.5 - 1.5

IN CASE OF EMERGENCY: THE NUMBERS AT THE TOP OF THIS PAGE PROVIDE 24
 HOUR RESPONSE FROM ANY PHONE FOR ALL EMERGENCIES WITH THIS PRODUCT.
 The components of this product are in compliance with the chemical
 notification requirements of TSCA. All applicable chemical
 ingredients in this material are listed on the European Inventory of
 Existing Chemical Substances (EINECS), or are exempt polymers whose
 monomers are listed on EINECS.

++Synthetic rubber, resin and stabilizers. Non-hazardous per WHMIS.

2. PHYSICAL DATA

BOILING POINT:..... Compressed gas
 VAPOR PRESSURE:..... Compressed gas
 VAPOR DENSITY:..... N/A
 EVAPORATION RATE:..... N/A
 SOLUBILITY IN WATER:..... Very slight
 SPECIFIC GRAVITY:..... 0.661 Water=1
 PERCENT VOLATILE:..... ca. 85 % by wt

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

2. PHYSICAL DATA (continued)

pH:..... N/A
VISCOSITY:..... N/A
MELTING POINT:..... N/D

APPEARANCE AND ODOR:
liquid in aerosol, CLEAR-TRANSLUCENT

3. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT:..... -50.00 F
FLAMMABLE LIMITS - LEL:..... N/A
FLAMMABLE LIMITS - UEL:..... Flam.Gas
AUTOIGNITION TEMPERATURE:..... N/D

EXTINGUISHING MEDIA:
Water spray, Carbon dioxide, Dry chemical, Foam

SPECIAL FIRE FIGHTING PROCEDURES:
Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head. Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. For leaks or spills which have not ignited, water spray can be used to disperse the flammable vapor and protect personnel attempting to stop the leak.

UNUSUAL FIRE AND EXPLOSION HAZARDS:
Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back.

NFPA HAZARD CODES: HEALTH: 2 FIRE: 4 REACTIVITY: 0 AEROSOL STORAGE: 3
UNUSUAL REACTION HAZARD: none

OSHA FIRE HAZARD CLASS: Class IB Flammable Liquid

4. REACTIVITY DATA

STABILITY: Stable

INCOMPATIBILITY - MATERIALS/CONDITIONS TO AVOID:
Heat.

HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur.

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

4. REACTIVITY DATA (continued)

HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon Monoxide and Carbon Dioxide, Hydrocarbons, Toxic Vapors, Gases
or Particulates.

5. ENVIRONMENTAL INFORMATION

SPILL RESPONSE:

Refer to other sections of this MSDS for information regarding
physical and health hazards, respiratory protection, ventilation, and
personal protective equipment. Ventilate area. Extinguish all
ignition sources. Contain spill. Cover with inorganic absorbent
material. Collect spilled material. Collect using non-sparking
tools. Clean up residue. Place in an approved metal container.

RECOMMENDED DISPOSAL:

Incinerate in an industrial or commercial facility. Facility must be
capable of handling aerosol cans. Dispose of completely absorbed
waste product in a hazardous waste facility. Reclaim if feasible.

RECYCLE EMPTY AEROSOL CONTAINERS WHERE AVAILABLE.

ENVIRONMENTAL DATA:

Not determined.

REGULATORY INFORMATION:

Volatile Organic Compounds: ca. 72 %.
VOC Less H2O & Exempt Solvents: N/D.

Since regulations vary, consult applicable regulations or authorities
before disposal. In the event of an uncontrolled release of this
material, the user should determine if the release qualifies as a
reportable quantity. U.S. EPA Hazardous Waste Number = D001
(Ignitable)

EPCRA HAZARD CLASS:

FIRE HAZARD: Yes PRESSURE: Yes REACTIVITY: No ACUTE: Yes CHRONIC: Yes

6. SUGGESTED FIRST AID

EYE CONTACT:

Immediately flush eyes with large amounts of water. Get immediate
medical attention.

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

6. SUGGESTED FIRST AID (continued)

SKIN CONTACT:

Flush skin with large amounts of water. If irritation persists, get medical attention.

INHALATION:

Remove person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, get immediate medical attention.

IF SWALLOWED:

If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person.

7. PRECAUTIONARY INFORMATION

EYE PROTECTION:

Avoid eye contact with vapor, spray, or mist. Wear safety glasses with side shields.

SKIN PROTECTION:

Avoid prolonged or repeated skin contact.

RECOMMENDED VENTILATION:

Do not use in a confined area or areas with little or no air movement. If exhaust ventilation is not adequate, use appropriate respiratory protection. Provide ventilation adequate to control vapor concentrations below recommended exposure limits and/or control spray or mist.

RESPIRATORY PROTECTION:

Avoid breathing of vapors, mists or spray. Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: half-mask organic vapor respirator.

PREVENTION OF ACCIDENTAL INGESTION:

Do not ingest.

RECOMMENDED STORAGE:

Store at temperature below 120 degrees F (49 degrees C). Store out of direct sunlight. Keep out of the reach of children.

FIRE AND EXPLOSION AVOIDANCE:

Aerosol container contains flammable gas under pressure. Keep away from heat, sparks, open flame, and other sources of ignition. Extremely flammable liquid and vapor. Do not pierce or burn container, even after use. No smoking while handling this material.

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

7. PRECAUTIONARY INFORMATION (continued)

Avoid static discharge.

EXPOSURE LIMITS

INGREDIENT	VALUE	UNIT	TYPE	AUTH	SKIN*
PETROLEUM DISTILLATE.....	50	PPM	TWA	CMRG	
PROPANE.....	1000	PPM	TWA	OSHA	
PROPANE.....	2500	PPM	TWA	ACGIH	
NON-VOLATILE COMPONENTS - N.J.					
TRADE SECRET REGISTRY NO. 04499600-					
6167P++.....	NONE	NONE	NONE	NONE	
ACETONE.....	500	PPM	TWA	ACGIH	
ACETONE.....	750	PPM	STEL	ACGIH	
ACETONE.....	750	PPM	TWA	OSHA	
			OSHA VACATED PEL		
ACETONE.....	1000	PPM	STEL	OSHA	
			OSHA VACATED PEL		
ACETONE.....	1000	PPM	TWA	OSHA	
ISOPROPYL ALCOHOL.....	400	PPM	TWA	ACGIH	
ISOPROPYL ALCOHOL.....	500	PPM	STEL	ACGIH	
ISOPROPYL ALCOHOL.....	400	PPM	TWA	OSHA	
ISOPROPYL ALCOHOL.....	500	PPM	STEL	OSHA	

* SKIN NOTATION: Listed substances indicated with 'Y' under SKIN refer to the potential contribution to the overall exposure by the cutaneous route including mucous membrane and eye, either by airborne or, more particularly, by direct contact with the substance. Vehicles can alter skin absorption.

SOURCE OF EXPOSURE LIMIT DATA:

- ACGIH: American Conference of Governmental Industrial Hygienists
- CMRG: Chemical Manufacturer Recommended Exposure Guidelines
- OSHA: Occupational Safety and Health Administration
- OSHAV: Occupational Safety and Health Administration Vacated PEL.
Vacated Permissible Exposure Limits (PEL) are enforced as the OSHA PEL in some states. Check with your local regulatory authority.
- NONE: None Established

8. HEALTH HAZARD DATA

EYE CONTACT:

Moderate Eye Irritation: signs/symptoms can include redness, swelling, pain, tearing, and hazy vision.

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

8. HEALTH HAZARD DATA (continued)

SKIN CONTACT:

Mild Skin Irritation (after prolonged or repeated contact):
signs/symptoms can include redness, swelling, and itching.

May be absorbed through the skin and produce effects similiar to
those caused by inhalation and/or ingestion.

INHALATION:

Intentional concentration and inhalation may be harmful or fatal.

Blood disorders: signs/symptoms can include prolonged weakness and
fatigue.

Liver Effects: signs/symptoms can include yellow skin(jaundice) and
tenderness of upper abdomen.

Central Nervous System Depression: signs/symptoms can include
headache, dizziness, drowsiness, incoordination, slowed reaction time,
slurred speech, giddiness and unconsciousness.

Irritation (upper respiratory): signs/symptoms can include soreness
of the nose and throat, coughing and sneezing.

IF SWALLOWED:

Ingestion is not a likely route of exposure to this product.

WHILE THE FOLLOWING EFFECTS ARE ASSOCIATED WITH ONE OR MORE OF THE
INDIVIDUAL INGREDIENTS IN THIS PRODUCT AND ARE REQUIRED TO BE
INCLUDED ON THE MSDS BY THE U.S. OSHA HAZARD COMMUNICATION STANDARD,
THEY ARE NOT EXPECTED EFFECTS DURING FORESEEABLE USE OF THIS PRODUCT.

Irritation of Gastrointestinal Tissues: signs/symptoms can include
pain, vomiting, abdominal tenderness, nausea, blood in vomitus, and
blood in feces.

SECTION CHANGE DATES

HEADING	SECTION CHANGED SINCE	January 19, 2001	ISSUE
---------	-----------------------	------------------	-------

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.